Generator

ENTERED RECEIVED

OCT 21 2014

NMED
Hazardous Waste Bureau

Los Alamos
NATIONAL LABORATORY
EST 1943

*Environment Safety & Health (ADESH)*
**PO Box 1663, MS K491**
Los Alamos, New Mexico 87545
Phone: (505) 667-4218/Fax: (5005) 665-3811

*National Nuclear Security Administration*
*Los Alamos Field Office, A316*
3747 West Jemez Road
Los Alamos, New Mexico, 87545
Phone: (505) 667-5105/Fax: (505) 667-5948

*Date*: OCT 21 2014
*Symbol*: ADESH-14-0109
*LAUR*: LA-UR-14-28034
*Locates Action No.*: N/A

Mr. Ryan Flynn, Secretary
New Mexico Environment Department
Harold Runnel Building
1190 Saint Francis Drive
P.O. Box 5469
Santa Fe, NM 87502

Dear Secretary Flynn:

**Subject: Second Addendum, Reporting Additional Instances of Noncompliance with Hazardous Waste Facility Permit and Generator Requirements, Los Alamos National Laboratory**

The purpose of this letter is to voluntarily report additional non-compliances with the Los Alamos National Laboratory (LANL) Hazardous Waste Permit and regulatory requirements applicable to generators under the New Mexico Hazardous Waste Act and Resource Recovery and Conservation Act (RCRA). This report is being made to the New Mexico Environment Department (NMED) by the U.S. Department of Energy National Nuclear Security Administration (NNSA), and the Los Alamos National Security, LLC (LANS) (collectively, NNSA/LANS or the Permittees). The Permittees previously self-identified and reported to NMED several non-compliances in the July 1, 2014 *Addendum to the Los Alamos National Laboratory Hazardous Waste Facility Permit Reporting on Instances of Noncompliance and Releases for Fiscal Years2012 and 2013*(ref: ADESH-14-030).

Permittees committed in the July 1, 2014 letter to update NMED should any additional noncompliance with Permit or other regulatory requirements be identified. Enclosure 1 to this letter provides details and documentation regarding additional non-compliances identified since the July 1, 2014 submittal.



36647

If you have comments or questions regarding this submittal, please contact Mark P. Haagenstad at (505) 665-2014 or Gene E. Turner at (505) 667-5794.

Sincerely,

Michael T. Brandt, DrPH, CIH
Associate Director
Environment, Safety & Health
Los Alamos National Laboratory

Sincerely,

for

Peter Maggiore
Assistant Manager
Environmental Projects Office
Los Alamos Field Office
DOE/NNSA

MTB/KBL/MPH/LRVH:kt

Enclosures: (1) Second Addendum, Reporting Instances of Noncompliance - Hazardous Waste Facility Permit, Los Alamos National Laboratory

Cy:

Tom Blaine, NMED, Santa Fe, NM, (E-File)
John Kieling, NMED, Santa Fe, NM (E-File)
Steve Pullen, NMED/HWB, Santa Fe, NM, (E-File)
Timothy Hall, NMED/HWB, Santa Fe, NM, (E-File)
Trais Kliphuis, NMED, Santa Fe, NM, (E-File)
J. R. Stroble, CBFO, Carlsbad, NM, (E-File)
Dana Bryson, CBFO, Carlsbad, NM, (E-File)
Mark Pearcy, CBFO, Carlsbad, NM, (E-File)
Jose Franco, CBFO, Carlsbad, NM, (E-File)
Kimberly Davis Lebak, NA-LA, (E-File)
Peter Maggiore, NA-LA, (E-File)
Lisa Cummings, NA-LA, (E-File)
Gene E. Turner, NA-LA, (E-File)
Kirsten M. Laskey, NA-LA, (E-File)
Carl A. Beard, PADOPS, (E-File aosburn@lanl.gov)
Michael T. Brandt, ADESH, (E-File)
Raeanna R. Sharp-Geiger, ADESH, (E-File)
Randy Erickson, ADEP, (E-file)
Enrique Torres, ADEP, (E-File)
Alison M. Dorries, ENV-DO, (E-File)
James S. Clemmons, LTP, (E-File)
Donald L. Allen, LTP, (E-File)
Scott Miller, LTP-SSS, (E-File)
Anthony R. Grieggs, ENV-CP, (E-File)
Kenneth M. Hargis, LTP-PTS, (E-File)
Mark P. Haagenstad, ENV-CP, (E-File)
Deborah K. Woitte, LC-ESH, (E-File)
Selena Z. Sauer, LC-ESH, (E-File)
Luciana Vigil-Holterman, ENV-CP, (E-File)
lasomailbox@nnsa.doe.gov, (E-File)
locatesteam@lanl.gov, (E-File)
env-correspondence@lanl.gov, (E-File)

**ENCLOSURE 1**

Second Addendum
Reporting Instances of Noncompliance
Los Alamos National Laboratory Hazardous Waste Facility Permit
and Hazardous Waste Generator Requirements

ADESH-14-0109

LAUR-14-28034

Date: OCT 2 1 2014

**Second Addendum**
**Reporting Instances of Noncompliance**
**LANL's Hazardous Waste Facility Permit**
**and Hazardous Waste Generator Requirements**

**October 17, 2014**

## Introduction

By letter dated July 1, 2014, the U.S. Department of Energy and Los Alamos National Security, LLC (DOE/LANS) (collectively, the Permittees) submitted to the New Mexico Environment Department (NMED) an addendum to add information to the *Hazardous Waste Facility Permit Instances of Noncompliance and Releases for Fiscal Years 2012 and 2013* to meet the reporting requirement of the Los Alamos National Laboratory (LANL) Hazardous Waste Facility Permit, EPA No. NM0890010515 (the LANL Permit). The July 1st addendum related to activities associated with the processing of the nitrate salt-bearing waste stream at the Waste Characterization, Reduction, and Repackaging Facility (WCRRF) during fiscal years 2012 and 2013. In the July 1, 2014 addendum, the Permittees noted that they were in the process of reevaluating the waste characterization information concerning the nitrate salt-bearing waste stream, and would update NMED with information including acceptable knowledge and/or sampling activities that occur as necessary.

The noncompliances addressed in this document were identified as a result of the reevaluation activities conducted to date on the remediated and unremediated nitrate salt-bearing waste. LANL Permit Section 1.9.14 requires reporting of all instances of noncompliance that do not pose a threat to human health and the environment to be submitted by December 1 of each year, and addresses noncompliance information from October 1st through September 30th of each fiscal year. The noncompliances discussed in this document relate to activities required under the LANL Permit, and extend to prior fiscal years, as well as generator requirements under NMED rules incorporating 40 CFR Part 262.

On October 14, 2014, DOE/NNSA and LANS representatives met with NMED officials to orally notify the Department of these instances of noncompliance. Except for the noncompliance related to pre-transportation requirements, the nitrate salt-bearing waste containers associated with these noncompliances are addressed under NMED's Administrative Order No. 5-19001 (May 19, 2014) and *LANL's Revised Nitrate Salt Bearing Waste Container Isolation Plan* submitted pursuant to that Order.

Facility Information

Owner and Operator:
United States Department of Energy
3747 West Jemez Road
Los Alamos, NM 87544

Co-Operator:
Los Alamos National Security, LLC
PO Box 1663
Los Alamos, NM 87545

Facility:
Los Alamos National Laboratory
PO Box 1663
Los Alamos, NM 87545

## I. Summary of Noncompliances

The Permittees are reporting the following instances of noncompliance as a result of reevaluating waste characterization information associated with the nitrate salt-bearing waste containers described in the Central Characterization Project (CCP) Acceptable Knowledge Summary Report CCP-AK-LANL-006. The 707 suspect nitrate salt-bearing waste containers identified by LANL are part of the following waste streams: LA-MHD01.001, LA-CIN01.001, LA-MIN02-V.001 and LA-MIN04-S.001. This document addresses noncompliances identified under the LANL Permit as well as NMED regulations applicable to hazardous waste generators. Section II addresses background facts regarding historical and current waste characterization and re-evaluation activities. Section III contains a detailed discussion of the noncompliances, and they are summarized below:

1. Failure to conduct an adequate hazardous waste determination (D001) (40 CFR §262.11)

The Permittees believe that they failed to conduct an adequate hazardous waste determination for the nitrate salt-bearing wastes with regard to EPA Hazardous Waste Number (HWN) D001 (ignitability characteristic). The Permittees' prior waste characterization activities for these legacy (pre-1991) wastes were based on the best available information at the time the wastes were managed, and included extensive reviews of available information; however, recent analytical testing has shown that these wastes carry HWN D001 as an oxidizer. As a consequence, the Permittees believe they failed to meet specific LANL Permit requirements identified below, as well as generator pre-transport requirements pursuant to 40 CFR §§262.30-31.

2. LANL Permit Requirements

   A. D001 (Oxidizers)
      i. Special requirements for managing ignitable hazardous wastes (LANL Permit Sections 2.8.1, 2.8.2 and Attachment C.5.1) (unremediated nitrate salt-bearing waste containers);
      ii. Labeling hazardous waste containers with the HWN D001 (LANL Permit 3.6(1)) (remediated and unremediated nitrate salt-bearing waste containers); and
      iii. Placement of incompatible wastes and materials in the same container (LANL Permit Section 2.8.2) (remediated nitrate salt-bearing waste containers).

   B. D007, D008, D009 (Characteristic metals)

      Labeling hazardous waste containers with the HWNs D007, D008, D009 (chromium, lead and mercury) (LANL Permit 3.6(1)) (unremediated nitrate salt-bearing waste containers).

   C. D002 (Corrosive wastes)

      Failure to properly label specific waste containers with the HWN D002 (LANL Permit 3.6(1)) (unremediated nitrate salt-bearing waste containers).

3. Pre-Transport Requirements (40 CFR §§262.30-31)

   A. Transportation of nitrate salt-bearing wastes to an off-site facility (WIPP, WCS) without properly packaging the wastes for the HWN D001.

   B. Transportation of nitrate salt-bearing wastes to an off-site facility (WIPP, WCS) without properly relabeling the wastes with the HWN D001.

## II. Background Facts

### 1. Historical Waste Characterization and Re-evaluation Activities

LANL generated "uncemented" nitrate salt waste from evaporator bottoms associated with the nitrate recovery process and plutonium operations at the Plutonium Processing Facility located at Technical Area (TA) 55 from 1979 to 1991. After 1991, wastes from the evaporator process were treated by cement fixation, and are referred to as "cemented" nitrate salt waste[1]. The "uncemented" nitrate salt-bearing waste is a legacy waste that is also sometimes referred to an "unconsolidated" waste. In the early 1990s, LANL began efforts to characterize its legacy transuranic (TRU) waste inventory in order to determine which waste streams had become subject to RCRA regulation as mixed TRU waste (MTRU). LANL initially assigned uncemented nitrate salts containers one or more of the following HWNs: D007, D008, and D009. Some nitrate-salt bearing wastes were not identified as hazardous wastes at the time and were not assigned an EPA HWN.

LANL characterization activities related to the uncemented nitrate salt-bearing wastes were also tied to the *Transuranic Waste Inspectable Storage Project* (TWISP), which involved the retrieval of waste containers under the Consent Agreement for Compliance Orders NMHWA 93-01, 93-02, 93-03, 93-04 approved by NMED on December 10, 1993. LANL compiled extensive waste characterization information for waste analysis plans prepared for TWISP and the permit applications submitted for the LANL Permit renewal. The TWISP project also coincided with two major initiatives to recharacterize LANL's MTRU inventory for purposes of eventual WIPP disposal, including the LANL TRU Waste Characterization Project (TWCP) in the late 1990s, and its successor, the Central Characterization Project (CCP) in the early 2000s. These two projects resulted in significant reevaluations of and enhancements to acceptable knowledge (AK) information for all LANL TRU waste streams, including the cemented and un-cemented TA-55 nitrate salts.

In 2009, CCP issued a Nonconformance Report (NCR) (NCR-LANL-0509-09) that placed a hold on approximately 48 nitrate salt-bearing waste drums. The NCR identified new information from the generator (LANL) that these drums were potentially non-cemented evaporator salts and would require re-assignment to a separate waste stream. As a result, LANL convened an AK team to reevaluate the nitrate salts waste characterization information compiled to date. The team reviewed the current information in the LANL waste databases, and obtained and reviewed copies of the original data packages (as available) for the containers. They interviewed several subject matter experts (SMEs) and technical personnel involved with the original generation of the waste, and SMEs with expertise on the chemical and physical properties of concern with uncemented nitrate salts. At the same time, a separate LANL effort was underway to verify which drums in the LANL legacy TRU waste population were, in fact, uncemented nitrate salts, because the nitrate salts had never been originally identified as a discrete waste stream in the historical LANL TRU databases.

With regard to ignitability (HWN D001), the LANL AK team determined that the uncemented nitrate salt-bearing drums did not meet the 40 CFR §261.21(a)(4) DOT oxidizer definition based on review of the available information, which established that prior to the time the wastes were managed (i.e., 2009-2012), they had never exhibited oxidizer properties or other parts of the ignitability characteristic.[2] With

---

[1] From the mid-1980s until 1991, both uncemented and cemented salt wastes were being generated at TA-55. By the end of 1991, 100% of the nitrate salt evaporator bottom waste streams were cemented.

[2] The LANL AK team believed that the uncemented salts were not likely to be ignitable based on interviews of TA-55 SMEs and waste technicians who packaged the wastes, and reviews of historical evidence and the original waste description documents. Further, generator interviews emphasized that the uncemented nitrate salts were packaged wet.

regard to corrosivity (D002), the LANL AK team stated that some uncemented nitrate salts drums might contain measurable free liquids, and recommended that any liquids identified be managed as D002 hazardous waste unless shown otherwise by pH testing. Any liquids would be remediated prior to shipment to WIPP.

With regard to the toxicity characteristic, the AK team reviewed 2007 analytical results based on limited metals data from testing modern (non-legacy) TA-55 evaporator solutions (i.e., nitrate salts processed by cementation), and confirmed that RCRA toxicity characteristic codes D007, D008, and D009 should apply to the historical nitrate salt wastes prior to certification for shipment to WIPP. However, the AK team's findings/conclusions were based only on the AK information available at that time (i.e., 2009-2012); no ignitability, reactivity, or pH data then existed for the 267 containers.

In July 2012, LANL's TRU Waste Program (LTP) program issued *Solution Package Definitions Report-72, Salt Waste,* Rev. 1 ("SP-72"), which established the waste disposition path for the nitrate salt-bearing wastes (see Attachment 1). SP 72 identified a population of 305 legacy TA-55 containers suspected to be uncemented nitrate salts as of May 14, 2012, and identified the appropriate HWNs to be assigned to the containers as HWNs D007, D008, and D009. The report stated that each container would be verified individually by CCP during container certification prior to shipment to WIPP, and would be re-assigned to another appropriate AK waste stream if found not to be uncemented nitrate salts. Under SP 72, the nitrate salts drums would be relabeled with HWNs D007, D008 and D009 during the CCP certification process, when re-packaging the remediated waste at TA-50 WCRRF for subsequent shipment to WIPP.

2. 2014 LANL Waste Re-characterization Activities

The following summarizes the Permittees' re-characterization and evaluation efforts undertaken for the nitrate salt-bearing waste stream since submitting the July 1, 2014 addendum regarding *Hazardous Waste Facility Permit Instances of Noncompliance and Releases for Fiscal Years 2012 and 2013.*

On July 30, 2014, the Permittees notified NMED that they had determined to conservatively apply the HWN D001 for characteristic of ignitability to 57 remediated nitrate salt-bearing waste containers and 29 unremediated nitrate salt-bearing waste containers stored at LANL (a copy of this letter is available at http://permalink.lanl.gov/object/tr?what=info:lanl-repo/eprr/ERID-259155)). The Permittees provided this notice under LANL Permit, Section 2.4.7, as part of their reevaluation efforts of the waste characterization information for the nitrate salt bearing waste streams including factual review, scientific analysis, and testing. On July 25, 2014, the Permittees placed HWN D001 on labels of unremediated and remediated nitrate salt-bearing waste containers stored at LANL (*see* Item 7 to LANL's September 30, 2014 *Response to the August 26,2014 Request for Information, Treatment of Waste without a Permit and Failure to Reevaluate Acceptable Knowledge, Los Alamos National Laboratory*, available at http://permalink.lanl.gov/object/tr?what=info:lanl-repo/eprr/ERID-261912). Additionally, the Permittees made timely notifications to NMED and off-site facilities (Waste Control Specialists (WCS), in Andrews, Texas and WIPP) regarding manifest discrepancies resulting from the application of the D001 HWNs as required under 40 CFR Part 262.

On September 5, 2014, upon NMED's request, the Permittees provided the "reasoning and analysis" for determining to assign HWN D001 to the remediated and unremediated nitrate salt-bearing waste containers (*see* Letter from Permittees to NMED Secretary Flynn dated September 5, 2014, referenced above). As described in that letter, the Permittees determined to apply the HWN D001 to the remediated and unremediated nitrate salt-bearing waste containers based on analytical results from two samples

taken from an empty unremediated nitrate salt-bearing parent drum stored at Area G, 231. The results showed the presence of nitrate compounds, including sodium and magnesium nitrates, which are identified by U.S. Department of Transportation (DOT) regulations as Division 5.1 DOT oxidizers under 49 CFR §172.101 and 49 CFR §173.127. Although the analytical results applied to samples from one unremediated drum, the Permittees determined to conservatively label all of the 29 unremediated nitrate-salt bearing drums and 57 remediated nitrate-salt bearing drums stored at LANL with the HWN D001.

*Remediated Nitrate Salt-Bearing Waste Drums*

As described above, the Permittees previously determined that the uncemented nitrate salt-bearing waste did not meet the definition of a D001 ignitable solid. However, to further support managing these specific nitrate salt wastes as "non-ignitable," the Permittees determined to remediate and repackage the nitrate salt-bearing waste with an inert material (e.g., zeolite/kitty litter) with a minimum absorbent material to nitrate salts mixture ratio of 1.5 to 1 (*see* CCP's *Acceptable Knowledge Summary Report for Los Alamos National Laboratory TA-55 Mixed Transuranic Waste* (CCP–AK-LANL-006, Rev. 13) at page 142) (Attachment 2). This ratio was based on results of oxidizing solids testing performed by the Energetic Materials Research and Testing Center (EMRTC) and a white paper authored by the LANL-Carlsbad Office Difficult Waste Team (DWT), *Amount of Zeolite Required to Meet the Constraints Established by the EMRTC Report RF 10-13: Application to LANL Evaporator Nitrate Salts*) (Attachment 3). The EMRTC testing established the concentration at which the most reactive mixture of sodium and potassium nitrate becomes a non-oxidizer when mixed with either zeolite or grout. Based on the EMRTC testing, the LANL DWT concluded that the results could be applied to LANL's uncemented nitrate salts.

As previously reported, LANL remediated and repackaged certain nitrate-salt bearing waste containers using an organic kitty litter, and not a zeolite-based kitty litter (see July 1, 2014 Letter from Permittees to NMED Secretary Flynn, *Addendum to the Los Alamos National Laboratory Hazardous Waste Facility Permit Reporting on Instances of Noncompliance and Releases for Fiscal Years 2012 and 2013*). The type of absorbent did not comport with the EMRTC testing or the LANL DWT recommendation.

*Analytical Test Results*

In August 2014, the Permittees conducted analytical testing using surrogate samples of the remediated nitrate salt-bearing waste containers. Samples were tested by Southwest Research Institute of San Antonio, Texas using the DOT oxidizing solids test method specified in 49 CFR §§173.127(a)(1) (i.e., the United Nations (UN) *Manual of Tests and Criteria*, Section 34, Method O.1). Samples were also analyzed using US EPA's *Test Methods for Evaluating Solid Waste, Physical/Chemical Methods* (SW-846) Method 1040, Test Method for Oxidizing Solids. The test results indicated the presence of DOT 5.1 oxidizers. Prior to receiving the most recent test results, surrogate samples of remediated nitrate salt-bearing waste had been analyzed using SW-846, Method 1040. The earlier test results using SW-846, Method 1040 generally supported the conclusion that the surrogate samples of the remediated nitrate salt-bearing waste could be classified as oxidizers. LANL provided NMED this information, along with testing results, by letter from the Permittees to NMED Secretary Flynn dated September 19, 2014, titled *Response to LANL Nitrate Salt-Bearing Waste Container Isolation Plan* (see Attachment 2 of Enclosure 3), available at http://permalink.lanl.gov/object/tr?what=info:lanl-repo/eprr/ERID-261850.

3. Numbers and Location of Nitrate Salt-Bearing Containers

LANL currently stores and manages eighty-six (86) suspect nitrate salt-bearing waste containers at TA-54, Area G, Dome 375 (contains 57 remediated drums) and Dome 231 (contains 29 unremediated

drums).[3] These containers are subject to *LANL's Nitrate Salt-Bearing Waste Container Isolation Plan* approved by NMED under the May 19, 2014 Administrative Order. Twenty-nine (29) unremediated suspect nitrate salt-bearing waste containers have been stored at LANL ever since they were generated. Generation dates vary between 1979 and 1991.

LANL processed the remediated nitrate salt-bearing waste containers at TA-50 WCRRF between 2011 and 2014. Fifty-seven (57) remediated daughter containers are currently stored at LANL; one-hundred and thirteen (113) remediated daughter containers were shipped to WCS between April and early June, 2014; and 503 remediated daughter containers were shipped to WIPP between August 8, 2013 and January 29, 2014. A comprehensive list of the individual containers shipped to WIPP and WCS, and those remaining at LANL, was provided in Attachment 2 to LANL's September 30, 2014 *Response to the August 26,2014 Request for Information, Treatment of Waste without a Permit and Failure to Reevaluate Acceptable Knowledge, Los Alamos National Laboratory* (available at http://permalink.lanl.gov/object/tr?what=info:lanl-repo/eprr/ERID-261912).

**III. Discussion of Specific Noncompliances**

1. Failure to conduct an adequate hazardous waste determination (D001)

Under EPA and NMED regulations at 40 CFR §262.10, upon generation of a solid waste, the generator (LANL) is required to undertake a hazardous waste determination in order to determine how the waste should be managed, and to re-evaluate this characterization as appropriate and necessary. For the reasons described above, as a result of reevaluating waste characterization information, the Permittees believe that the prior waste characterization determination regarding HWN D001 was inadequate. As detailed in our response to NMED dated September 5, 2014, recent analytical testing results has supported this determination. Oxidizer tests performed on surrogates of the remediated waste in July and August 2014 confirmed that the surrogates were oxidizers under both the UN O.1 test and SW-846 Method 1040. Based on this information, on July 30, 2014 the Permittees notified NMED that they would conservatively label the fifty-seven (57) remediated nitrate salt-bearing waste containers and twenty-nine (29) unremediated nitrate-salt bearing waste containers currently stored at LANL.

2. LANL Permit Requirements

A. D001 (Oxidizers)

i. Special requirements for managing ignitable hazardous wastes (LANL Permit Sections 2.8.1, 2.8.2 and Attachment C.5.1) (unremediated nitratesalt-bearing waste containers

After review of the LANL Permit's storage requirements and interim status regulations, the Permittees believe that the containers now identified as D001 hazardous wastes were stored in locations authorized to store D001 mixed radioactive wastes. However, the population of nitrate salt-bearing drums did not fully meet the "special requirements" for managing ignitable hazardous wastes under LANL Permit Sections 2.8.1, 2.8.2 and Attachment C.5.1. Although many of the requirements were met, there are specific requirements for ignitable D001 wastes that likely were not met, including the requirement to segregate and separate ignitable wastes and to use non-sparking tools when managing containers with ignitable wastes.

[3] The term "suspect" nitrate salt-bearing wastes refers to wastes that may contain either uncemented or cemented nitrate-salt bearing wastes; these containers may in fact hold cemented nitrate-salt wastes and are in the process of being evaluated.

ii. Labeling, HWN D001 (LANL Permit 3.6(1)) (remediated and unremediated nitrate salt-bearing waste containers).

As previously reported, the Permittees first added a HWN D001 label to the nitrate salt-bearing waste drums on July 25, 2014. Since the remediated and unremediated nitrate-salt waste drums are now identified as D001 hazardous wastes, the Permittees do not believe they complied with LANL Permit 3.6(1), which requires that drums contain "all applicable EPA Hazardous Waste Number(s)."

iii. Placement of incompatible wastes and materials in the same container (LANL Permit Section 2.8.2) (remediated nitrate salt-bearing waste containers).

The Permittees do not believe they complied with LANL Permit Section 2.8.2, which addresses placement of incompatible wastes and materials in the same container, and imposes special precautions. At WCRRF, operators placed an organic absorbent and neutralizer containing triethanolamine into drums with the nitrate salts-bearing wastes (D001) which, in turn, would constitute placement of incompatible wastes and materials in the same container based on the EPA Hazardous Waste Compatibility Chart (*A Method for Determining the Compatibility of Hazardous Wastes,* EPA-600/2-80-76, April 1980).

B. D007, D008, D009 (Labeling, LANL Permit 3.6(1)) (unremediated nitrate salt-bearing waste containers)

The Permittees do not believe they complied with LANL Permit Section 3.6(1), which requires labeling of HWNs D007, D008 and D009 on containers stored at TA-54 Area G prior to remediation at WCRFF. SP 72 did not require that HWNs D007, D008, or D009 be placed on container labels until the container itself was verified to be uncemented nitrate salt-bearing wastes, as part of the CCP certification process prior to shipment to WIPP. Based on 2014 reviews of the historical LANL databases, of the 267 original unremediated parent nitrate salt bearing waste containers, fifteen (15) were labeled D007, fifty (50) were labeled D008, and one-hundred and sixty-nine (169) were labeled with all three HWNs prior to the commencement of nitrate salt drum remediation efforts in WCRRF. Thirty-three (33) nitrate salt-bearing waste containers were not originally identified as hazardous waste and were not originally assigned an EPA HWN. (*See* Item 3 and Attachment 2 of the LANL September 30, 2014 Response to NMED's Information Request, available at http://permalink.lanl.gov/object/tr?what=info:lanl-repo/eprr/ERID-261912). Although not properly labeled prior to remediation, LANL stored and managed these waste containers in areas that met all applicable permit and regulatory requirements. TA-54 Area G and TA-50 WCRRF have been authorized for storage of the HWNs D007-D009 since LANL submitted its Hazardous Waste Part A Permit Application for Mixed Waste, on January 25, 1991, and under the renewed LANL Hazardous Waste Facility Permit, approved in December, 2010. Additionally, these designations do not represent ignitable, reactive, or incompatible wastes and are not subject to the additional storage provisions for those types of wastes at those permitted units.

C. D002 (Corrosive Wastes) (Labeling, LANL Permit 3.6(1)) (unremediated nitrate salt-bearing waste containers).

On June 5, 2014, the Permittees determined to add the HWN D002 label for the characteristic of corrosivity to the 26 unremediated nitrate salt-bearing waste containers with free liquids remaining on-site at LANL. NMED was notified of this decision on June 5, 2014

(http://permalink.lanl.gov/object/tr?what=info:lanl-repo/eprr/ERID-524866) during one of the technical calls held in accordance with the May 19, 2014 Administrative Order. RTR videos and the rationale for addition of the HWN D002 to 26 of the 29 remaining unremediated nitrate salt waste containers were included in the September 5, 2014 submittal by the Permittees. *See also*, Permittees' September 30, 2014 letter, *Response to the August 26, 2014 Request for Information, Treatment of Waste without a Permit and Failure to Reevaluate Acceptable Knowledge, Los Alamos National Laboratory*, available at http://permalink.lanl.gov/object/tr?what=info:lanl-repo/eprr/ERID-261912. Since these unremediated drums contained liquids and were not labeled, the Permittees do not believe they complied with LANL Permit 3.6(1), which requires that drums contain "all applicable EPA Hazardous Waste Number(s)."

With regard to the remediated nitrate salt-bearing waste containers, the Permittees remediated a total of fifteen (15) nitrate salt-bearing parent containers having liquids with a measured pH less than 2 (as documented in the table in Attachment 3 of the Permittees' September 30, 2014 letter). These parent containers likewise had not been labeled with the HWN D002.

3. Pre-Transport Requirements (40 CFR §§262.30-31)

Although not required by the LANL Permit, the Permittees are notifying NMED that they believe they did not comply with generator requirements under 40 CFR Part 262 by shipping nitrate salt-bearing waste containers to WIPP and WCS between August 2013 and June 2014. For the reasons discussed above, these containers should have been packaged and labelled appropriately for the D001 hazardous waste in the containers. As described in 40 CFR §§262.30 and 31, this required that the containers be packaged and labelled in compliance with the applicable Department of Transportation regulations in 49 CFR parts 172, 173, 178, and 179.

The DOT regulations apply in two instances that affect the 40 CFR part 262 regulations. The presence of an organic absorbent in some of the nitrate salt-bearing waste containers shipped to WIPP and WCS was not appropriate for the Type B package authorized for shipment and therefore not in compliance with 49 CFR §173.416. In addition, the determination to apply the HWN D001 retroactively to the waste stream for the shipped waste containers requires that the waste packages shipped should have been labelled for the additional hazard class by 49 CFR §172.402. By reference, these nonconformances with the DOT requirements were also not in compliance with 40 CFR §§262.30-31.

## IV. Steps Taken or Planned to Reduce, Eliminate, and Prevent Recurrence

As required by Permit Section 1.9.14, the Permittees continue to investigate and evaluate steps to reduce, eliminate, and prevent recurrence of these noncompliances. The Permittees are confident that the nitrate salt-bearing wastes are being safely stored and managed on-site at LANL, as required by NMED under the Administrative Order No. 5-19001 (May 19, 2014) and *LANL's Revised Nitrate Salt Bearing Waste Container Isolation Plan* submitted pursuant to that Order. The Permittees continue to reevaluate and expand the waste characterization information concerning these nitrate salt waste streams, including the recent sampling and analytical campaigns. Upon completion of these activities, the Permittees intend to update the waste characterization information, including acceptable knowledge and/or any sampling activities that occur as necessary.

The steps taken or planned to reduce, eliminate, and prevent recurrence are summarized below in relation to each of the categories of noncompliance identified below:

1. Failure to Conduct an Adequate Hazardous Waste Determination

As previously described, the Permittees believe that all HWNs applicable to the population of

remediated and unremediated nitrate salt-bearing waste containers have been assigned appropriately, and that AK documentation and labels have been updated accordingly. LANL has undertaken numerous reevaluation activities including sampling and analysis through testing of an unremediated empty parent drum and surrogate remediated wastes. These activities are critical to understanding the nature of the nitrate salt-bearing wastes. LANL has not been able to sample a nitrate salt-bearing waste remediated drum, and is currently seeking necessary approvals to engage in this process to develop a more comprehensive understanding of the waste constituents.

Since this waste stream is no longer being generated at LANL, extensive "remediation" efforts are being undertaken to ensure that these wastes can be safely transported and accepted at WIPP. LANL has created a "Remediation Team" under the Isolation Plan that will address steps to prevent recurrence through long-term remediation of the nitrate salt-bearing containers. The Remediation Team is evaluating the options for remediation, including treatment plans or proposals, to render the nitrate salt-wastes safe for transportation and disposal at WIPP. The Remediation Team is required to work closely with NMED and discuss any permit modifications or authorizations necessary for treatment, including sampling, neutralization steps, reagents used, the location for processing the wastes and any other key information. See *LANL 's Nitrate Salt Bearing Waste Isolation Plan,* Revision 2 (at http://permalink.lanl.gov/object/tr?what=info:lanl-repo/eprr/ERID-261850), and the Permittees' September 30, 2014 submittal to NMED (at http://permalink.lanl.gov/object/tr?what=info:lanl-repo/eprr/ERID-261912) for recent updates on the status and progress of Remediation Team efforts. The Permittees will work closely with NMED staff to ensure that they are informed of these activities, including through regularly scheduled technical calls that commenced June 4, 2014 and will continue as required under the Administrative Order. As emphasized previously, the Permittees will obtain all necessary permits and approvals from NMED prior to commencing treatment activities for the remediated and unremediated nitrate salt-bearing waste containers.

2. LANL Permit Requirements

Permittees have labeled all remediated and unremediated nitrate-salt bearing waste containers with the appropriate HWNs (D001, D002, D007, D008 and D009). Further, these containers are being managed in compliance with LANL Permit requirements for potentially ignitable and corrosive hazardous wastes (including compatibility, secondary containment of liquids, etc.). The steps to prevent recurrence are detailed in the Permittees' Isolation Plan, Revision 2. The revised plan, submitted to the NMED on September 19, 2014 (see http://permalink.lanl.gov/object/tr?what=info:lanl-repo/eprr/ERID-261850), incorporated all modifications required by NMED. It describes in detail how the Permittees are continuing to isolate, secure and/or treat all nitrate salt-bearing waste containers currently stored at LANL, and includes a schedule of immediate actions being undertaken in that regard. The status of these actions is regularly reported during twice-weekly technical calls between the NMED and the Permittees.

3. LANL Permit Pre-Transport Requirements

The basis for the nonconformances associated with DOT and RCRA packaging and labelling requirements are linked to the inadequate hazardous waste characterization regarding D001, as discussed above. Further transport of these waste containers will only occur in conjunction with the information developed through the reevaluation and further remediation of the waste stream as reported to the NMED.

## CERTIFICATION

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

10/21/14

Michael T. Brandt, DrPH, CIH
Associate Director
Environment, Safety, and Health
Los Alamos National Security, LLC
Los Alamos National Laboratory
Operator

Date Signed

For

10/21/14

Peter Maggiore
Assistant Manager, Los Alamos Field Office
National Nuclear Security Administration
U.S. Department of Energy
Owner/Operator

Date Signed

**List of Attachments to Enclosure 1, Second Addendum, Reporting Instances of Noncompliance, LANL's Hazardous Waste Facility Permit and Hazardous Waste Generator Requirements, October 17, 2014**

| | |
|---|---|
| Attachment 1 | Solution Package Definitions Report-72, Salt Waste, Rev. 1, July, 2012 (LA-UR-14-28056) |
| Attachment 2 | Central Characterization Project (CCP) Acceptable Knowledge Summary Report for Los Alamos National Laboratory TA-55 Mixed Transuranic Waste (CCP–AK-LANL-006), Revision 13, February 10, 2014 (LA-UR #: Not Applicable) |
| Attachment 3 | LANL-Carlsbad Office Difficult Waste Team (DWT), Amount of Zeolite Required to Meet the Constraints Established by the EMRTC Report RF 10-13: Application to LANL Evaporator Nitrate Salts, May 8, 2012 (LA-UR-14-26860) |

**Attachment 1**

Solution Package Definitions Report-72, Salt Waste, Rev. 1, July, 2012

LA-UR-14-28056

## Solution Package Scope Definition

# REPORT-72, Salt Waste (SP #72) Rev 1

| | | |
|---|---|---|
| **Developed By:** | Susan S. Ramsey | 7/3/12<br>Date |
| **CCP Review:** | Craig Simmons | 7/9/12<br>Date |
| **Approved By:**<br>Tech Solutions | Davis Christensen | 7/9/12<br>Date |
| Disposition Project Owner | Mark Shepard | 7/11/2012<br>Date |
| EH&Q | Gary Schramm | 7-16-12<br>Date |
| Shipping and Safe Storage | Scott Miller | 7/17/12<br>Date |
| FOD | Steve Henry | 7/11/12<br>Date |
| Projects/ Services | Dave Frederici | 07.11.2012<br>Date |
| WDP Program | Steve Clemmons | 7/12/12<br>Date |

## *Inventory Description*

The legacy TA-55 unconsolidated, nitrate salts are defined here as unconsolidated waste evaporator salts and evaporator bottoms that were generated at TA-55. Evaporator salts and evaporator bottoms were generated continuously from nitrate recovery operations at TA-55, PF-4 since the beginning of plutonium operations in 1979. Evaporators are used to re-concentrate plutonium, if possible, or to reduce the volume of liquid waste. The time frame for non-cemented nitrate salt is from the onset of plutonium operations (1978-1979) to late 1991. Since late 1991, all nitrate salts generated from the evaporator process are sent to cement fixation.

The table below shows the type and number of containers with unconsolidated nitrate salt wastes. A CCP Nonconformance Report (NCR-LANL-0509-09) was issued for drums with uncemented, evaporator nitrate salts to be re-evaluated for re-assignment by CCP. As of May 14, 2012, three hundred and five (305) containers are included in this solution package (SP) report. All 305 containers will be evaluated by CCP during container certification prior to shipment to WIPP and will be reassigned to the appropriate AK waste stream, as required. Two hundred and ninety-two (292) are in the Governor's Goal (GG). A revision to this report may be required if the scope of the remediation activities change sufficiently.

| Legacy/NG | Waste Stream | Container Type | Count of Container Type | Sum of PE-Ci | Sum of Volume |
|---|---|---|---|---|---|
| **Legacy** | | | **305** | **1669** | **71** |
| | **LA-CIN01.001-Cans** | | **31** | **149** | **8** |
| | | 55-GAL | 19 | 79 | 4 |
| | | 85-GAL | 12 | 70 | 4 |
| | **LA-MHD01.001** | | **269** | **1505** | **63** |
| | | 55-GAL | 103 | 715 | 21 |
| | | 85-GAL | 59 | 623 | 19 |
| | | POC | 107 | 167 | 22 |
| | **LA-MIN04-S.001** | | **5** | **15** | **1** |
| | | 55-GAL | 1 | 4 | 0 |
| | | POC | 4 | 11 | 1 |
| **Grand Total** | | | **305** | **1669** | **71** |

Note: Data is as of 14 May 2012

## *AK Waste Stream*

**Waste Stream LA-MHD01.001 (Heterogeneous Debris)**

**Waste Stream Description:**

Waste stream LA-MHD01.001 consists of mixed heterogeneous debris waste generated during plutonium recovery, fabrication, R&D and associated facility and equipment maintenance, decontamination and decommissioning (D&D), waste repackaging, and below-grade retrieval operations. The debris waste includes paper, rags, plastic, rubber, wood-based high-efficiency particulate air (HEPA) filters, other plastic-based and cellulose-based items, noncombustible items such as metal and glass, and lesser quantities of homogeneous solids (less than 50 percent by volume) contaminated with nuclear materials such as americium oxide. Plastic-based waste includes (but may not be limited to): tape, polyethylene and vinyl, gloves including leaded gloves, plastic vials, polystyrene, Tygon tubing, polyvinyl chloride plastic, Teflon products, Plexiglas, and dry-box gloves (unleaded neoprene base). Cellulose-based waste includes (but may not be limited to): rags, wood, paper, cardboard, laboratory coats, coveralls, booties, cotton gloves, and similar materials. Noncombustible debris waste includes (but may not be limited to): bottles, cans, composite HEPA filters, crucibles, equipment, fluorescent bulbs, glass, gloveboxes, glovebox windows, graphite, metal pipes, miscellaneous labware, motors, pumps, slag, small tools, and ventilation ductwork. Homogeneous solid waste includes: hydroxide cake/filter materials, salts, and ash residues. Hydroxide cake/filter materials are composed of precipitated materials such as americium (Am), cadmium, calcium, chromium, iron, lead, magnesium, mercury, neptunium, plutonium (Pu), potassium, silver, sodium hydroxide, thorium, and uranium (U). Salt waste can include varying mixtures of calcium chloride, cesium chloride, lithium chloride, magnesium chloride, potassium chloride, sodium chloride, zinc chloride, residual entrained calcium and zinc metal, and various plutonium and americium compounds. Ash residues originate from the thermal reduction of organic-based waste products that were contaminated with plutonium (e.g., plastics, rubber, wood, cellulosics, and oils) and may include incomplete combustion products such as small pieces of plastic and metal debris items. The waste stream also includes a small fraction of absorbent materials which may include Ascarite, diatomaceous earth, vermiculite, or zeolite with trace contamination (less than one weight percent [wt. %]) of absorbed materials such as waste oils and organics. Any payload container consisting of more than 50 percent by volume of homogeneous solids will be excluded from this waste stream.

The waste stream contains Resource Conservation and Recovery Act (RCRA)-regulated constituents and is assigned the following EPA Hazardous Waste Numbers (HWNs): F001, F002, F005, D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040. This waste stream may also include wastes containing or contaminated with polychlorinated biphenyls (PCBs).

Prohibited items are known to be present in the waste stream. Procedures allowed containers greater than four liters, sealed with tape, to be used for waste packaging until LANL WIPP-approved procedures were implemented. Small vials of liquids and unpunctured aerosol cans also have been observed. Lead shielding is often used to increase handling safety, and thick shielding can obscure RTR observations. Additionally, based on interviews with site personnel performing VE and prohibited item disposition repackaging, internal cans (both shielded and unshielded) have been measured for dose rate during repackaging and found to contain waste with radiation levels exceeding 200 millirem per hour (mrem/hr). Waste packages containing prohibited items identified during characterization activities will be segregated then dispositioned appropriately and/or repackaged to remove the items prior to certification and shipment.

**Waste Stream LA-CIN01.001 (Homogeneous Cemented)**
**Waste Stream Description:**

Waste Stream LA-CIN01.001 consists of solidified homogeneous solid waste (cemented TRU Waste) generated during plutonium recovery, fabrication, R&D and associated facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations. The waste includes cemented materials such as aqueous and organic liquids from analytical chemistry, americium oxide, ash, calcium chloride salts, chloride solutions, evaporator bottoms, filter aid, filter cakes, plutonium/uranium filings and fines, glove box sweepings, graphite powder, HEPA filter media, leached ash residues, leached particulate solids (e.g., ash, sand, slag, and crucible parts), oxides (e.g., americium, metal, and uranium), miscellaneous oils (e.g., pump oil), silica solids, solvents, spent ion exchange resins, trioctyl phosphineoxide and iodine in kerosene, and uranium solutions. Containers generated from October 2006 to present are mixed with cement in a rigid plastic mixing container, which is contained in a single, ~12-mil thick, plastic liner bag. A plastic bag skirt of the same material is attached to the mixing container on the inside of the drum-out bag for contamination control. The bag skirt is pushed down into the container once the mixing is complete to expose a clean drum-out bag. The drum-out bag is gathered into a tight bundle, sealed with tape and two plastic cable ties, and cut to remove the drum from the glove box.

Based on the review of container documentation and documented waste management practices, no prohibited items were specifically identified in the waste stream, except the potential for prohibited quantities of liquid due to dewatering. In addition, the results of available headspace gas sampling and analysis of 50 drums in this waste stream indicated that FVOCs are not present in significant amounts. The total FVOCs measured for each of the drums is well below 500 ppm. Based on the final waste form and sample data, containers in waste stream LA-CIN01.001 are not expected to exceed a total FVOC concentration of greater than or equal to 500 ppm. The two predominant isotopes by mass for waste stream LA-CIN01.001 are Pu-239 and U-238, and over 95 percent of the total activity is from Am-241, Pu-238, Pu-239, and Pu-241.

**Waste Stream LA-MIN04-S.001 (Salt Waste)**

## Waste Stream Description:

Waste stream LA-MIN04-S.001 consists of inorganic homogeneous solid waste generated during plutonium recovery, fabrication, R&D and associated facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations. The waste is largely comprised of salts which are a byproduct from a variety of plutonium metal purification operations including electrorefining, molten salt extraction, salt stripping, fluoride reduction, and direct oxide reduction. Salts serve as a transportation vehicle for plutonium ions and provide a trap for impurities that are driven or extracted out during the purification process. Salt waste can include varying mixtures of calcium chloride, cesium chloride, lithium chloride, magnesium chloride, potassium chloride, sodium chloride, zinc chloride, residual entrained calcium and zinc metal, and various plutonium and americium compounds. The waste may also be contaminated with solvent metals and reagent materials such as barium, bismuth, cadmium, calcium carbonate, gallium, lead, molybdenum, niobium, tantalum, titanium, tungsten, vanadium, yttrium (Y), and zirconium. Salts can be cemented and disposed of in waste stream LA-CIN01.001; however, the salts disposed of separately under this waste stream are uncemented. A small

fraction of debris waste (mainly plastic and metal packaging) and magnesium oxide crucible pieces may also be present. Any payload container consisting of more than 50 percent by volume of heterogeneous debris will be excluded from this waste stream.

The waste stream contains RCRA-regulated constituents and is assigned the following EPA HWNs: F001, F002, F005, D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040. This waste stream does not include wastes containing or contaminated with PCBs.

Based on the review of container documentation and documented waste management practices, no prohibited items are specifically identified in the waste stream. However, procedures allowed containers greater than four liters, sealed with tape, to be used for waste packaging until LANL WIPP-approved procedures were implemented. Lead shielding is often used to increase handling safety, and thick shielding can obscure RTR observations. Additionally, based on interviews with site personnel performing VE and prohibited item disposition repackaging, internal cans (both shielded and unshielded) have been measured for dose rate during repackaging and found to contain waste with radiation levels exceeding 200 mrem/hr. Waste packages containing prohibited items identified during confirmation activities will be segregated then dispositioned appropriately and/or repackaged to remove the items prior to certification and shipment.

## *Material Type*

All containers are expected to be the same Material Type (weapons grade). On a waste stream basis, the two predominant isotopes by mass for waste stream LA-MHD01.001 are Pu-239 and uranium (U)-238, and over 95 percent of the total activity is from Pu-238, Pu-239, and Pu-241. The two predominant isotopes by mass for waste stream LA-MIN04-S.001 are Pu-239 and Pu-240 while over 95 percent of the total activity is from Pu-238, Pu-239, Pu-240, and Pu-241.

## *Volume, MAR, FGE and Weight (Average and Max)*

| Waste Stream | Container Type | Count | Ave. PE-Ci | Max PE-Ci | Ave. EC PE-Ci | Max EC PE-Ci | Max Gross Weight | Max Dose |
|---|---|---|---|---|---|---|---|---|
| **LA-CIN01.001-Cans** | | **31** | **4.81** | **19.16** | | | **578** | **40.0** |
| **LA-MHD01.001** | | **269** | **5.59** | **25.65** | **2.45** | **6.41** | **812** | **190.0** |
| | 55-GAL | 103 | 6.94 | 18.36 | 2.29 | 4.59 | 556 | 120.0 |
| | 85-GAL | 59 | 10.55 | 25.65 | 2.64 | 6.41 | 812 | 190.0 |
| | POC | 107 | 1.56 | 5.44 | | | 439 | 55.0 |
| **LA-MIN04-S.001** | | **5** | **2.95** | **4.26** | | | **380** | **20.4** |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | 55-GAL | 1 | 4.26 | 4.26 | | | 266 | 20.4 |
| | POC | 4 | 2.63 | 3.42 | | | 380 | 1.8 |
| **Grand Total** | | **305** | **5.47** | **25.65** | **2.45** | **6.41** | **812** | **190.0** |

Note: Volume = cubic meters ($M^3$); weight = Lbs; Dose = total surface dose rate (mrem/hr)

None of the drums exceed WCRRF limits for PE-Ci, EC PE-Ci or weight. The weight of drum S870065 was recorded as 812 pound (lbs), it was re-weighed in May 2012 and the new weight is 440 pounds, which does not exceed 624 lbs. weight limit for WCRRF. The database will be updated to reflect the new weight for this drum.

## *Disposition Strategy*

The population of SP#72 now consists entirely of containers with known or suspected nitrate salts. A thorough review of generator records over the time period 1979 to 1991 was conducted to identify this population. Approximately one-third of the population consists of daughter containers that were remediated for high dose, impenetrable or prohibited items at WCRRF prior April 2012. In May 2012 the LANL Carlsbad Office Difficult Waste Team authored a white paper (*Amount of Zeolite Required to Meet the Constraints Established by the EMRTC Report RF 10-13: Application to LANL Evaporator Nitrate Salts*, May 08, 2012), agreed to by the DOE June 14, 2012, that established the requirement that a minimum of 1.2 volumes of kitty litter/zeolite must be mixed with 1.0 volume of nitrate salts (in existing parent and daughter containers) in order for the WIPP to affirm that the final mixture of LANL nitrate salts can be considered a non-oxidizing solid. The mixing recipe (1.2:1) techniques affect the entire population of three hundred and five (305) parent and daughter containers in SP#72.

There are approximately twenty-three (23) drums in this package that are unvented and will require venting and installation of HEPA filters prior to remediation. There are also approximately twenty-six (26) drums that have conflicting information as to whether the drums contain unconsolidated or cemented salt. The latter will be presented to HE-RTR to discriminate the waste configuration prior to submittal to WCRRF for remediation. The objective is to remediate the entire population of nitrate salt containers so that they meet the CCP certification requirements for shipment to WIPP.

## *Disposition Path*

The table below details the number and container types and expected pathways for unconsolidated nitrate salts, based on prior RTR screening results and other existing data in the container management database (as of May 14, 2012).

| Count | Container Type | Description | Path |
|---|---|---|---|
| 33 | 55-Gal | Daughter containers from previous repack campaign | • Submit for pre-screen thru RTR (to determine presence of homogeneous nitrate salt)<br>• Transfer failed drums (with identified nitrate salt) to WCRRF for remediation<br>• Mix nitrate salt waste with at least 1.2 volumes of kitty litter/zeolite<br>• Package in 55-gal drum, as needed |
| 111 | POC | Daughter containers from previous repack campaign | • Transfer to WCRRF for remediation<br>• Mix nitrate salt waste with at least 1.2 volumes of kitty litter/zeolite<br>• Package in 55-gal drum or POC, as needed |
| 41 | 85-Gal | 55-gal Parent (original) containers in overpacks | • Evaluate container integrity and certification for transfer<br>• Re-overpack drums as needed<br>• Transfer to WCRRF for remediation<br>• Mix nitrate salt waste with at least 1.2 volumes of kitty litter/zeolite<br>• Package in 55-gal drum or POC, as necessary |
| 71 | 55-Gal | Parent (original) containers | • Evaluate container for transfer integrity and certification, and re-overpack drums as needed<br>• Transfer to WCRRF for remediation<br>• Mix nitrate salt waste with at least 1.2 volumes of kitty litter/zeolite<br>• Package in 55-gal drum or POC, as necessary |
| 23 | 85-Gal | Unvented 55-gal parent (original) containers in overpacks | • Submit to HE RTR pre-screen to confirm that inner 55-gal drum is unvented<br>• Vent drums at Dome 33 (≥HC3), as required<br>• Evaluate container for integrity and certification, and re-overpack, as required<br>• Ensure inner, 55-gal drum has WCRRF approved filter |

| | | | |
|---|---|---|---|
| | | | • Transfer to WCRRF for remediation<br>• Mix nitrate salt waste with at least 1.2 volumes of kitty litter/zeolite<br>• Package in 55-gal drum or POC, as needed |
| 26 | 7 85-Gal<br>19 55-Gal | Suspect cement cans or nitrate salts | • Submit to HE-RTR pre-screen (to confirm vented inner container and cement cans)<br>• Submit unvented nitrate salt drums to Dome 33 (≥HC3), vent and install filters, as required<br>• Evaluate container integrity and certification for transfer<br>• Ensure inner, 55-gal drums have WCRRF approved filter<br>• Transfer nitrate salt waste drums to WCRRF for remediation<br>• Mix nitrate salt waste with at least 1.2 volumes of kitty litter/zeolite<br>• Package in 55-gal drum or POC, as needed<br>• Submit confirmed, vented cement cans to CCP for pre-certification<br>• Transfer unvented, cement cans to SP#57 for processing |
| **305** | **Total Containers** | | |

Note: Data is as of May 14, 2012

There are thirty-three (33) 55-gal daughter containers of nitrate salt wastes that were mixed with Waste Lock 770® during a previous repack campaign. The previous remediation campaign resulted in the generation of 55-gallon and POC containers. The 55-gal daughter drums are likely to contain the debris, consisting of plastic, lead liners and other miscellaneous debris wastes from the WCRRF glovebox activities. Although thought to be unlikely, some drums may contain bagged nitrate salt with the debris. These 55-gal drums are proposed to go through pre-screening using the RTR to determine the presence of homogeneous nitrate salts. Based on RTR pre-screen results, each container may either go to WCRRF for remediation if the drum contains debris wastes and nitrate salts, or may be submitted directly to CCP for pre-certification if the drums contain entirely debris wastes. If these drums are classified as debris wastes, re-assignment to another AK waste stream may not be required. For estimating purposes, all drums are assumed to go to WCRRF and two (2) 55-gal drums will be generated for each daughter remediated. All of the resulting 66 containers will then be submitted for certification.

There are one hundred and eleven (111) POC daughter containers of nitrate salt wastes that were mixed with Waste Lock 770® during a previous repack campaign. These containers are proposed to proceed directly to WCRFF to be remediated in accordance with a new or revised procedure to ensure the final mixture meets or exceeds Carlsbad's mixing requirements (each liter of composite nitrate salt waste is to be mixed with at least 1.2 liters of zeolite/kitty litter). The resulting mixture can be re-packaged into 55-gallon drums. The estimated two-fold volume increase is estimated to create two (2) 55-gal drums for each daughter remediated. All of the resulting 222 containers will then be submitted for certification.

There are one hundred and twelve (112) parent containers of nitrate salt drums that have not been previously repacked that are proposed to proceed directly to WCRRF for remediation. The forty-one (41) 85-gallon containers need to be evaluated to see if they can be transferred directly or require re-packaging for purposes of transfer. These parent containers are proposed to proceed directly to WCRFF to be remediated in accordance with a new or revised procedure to ensure the final mixture meets or exceeds Carlsbad's mixing requirements (each liter of composite nitrate salt waste is to be mixed with at least 1.2 liters of zeolite/kitty litter). The resulting mixture can be packaged into 55-gallon drums or POC as needed. It is estimated that three (3) 55-gal drums and three (3) POCs will be generated as daughters for each parent remediated. All of the 672 daughter containers will be submitted for certification.

There are twenty-three (23) 85-gal drums that are proposed to go through pre-screening using the HE-RTR to confirm that inner 55-gal drum is unvented, and install HEPA filters as necessary. Based on the HE-RTR results, the vented drums will be transferred to WCRFF for remediation and the unvented containers submitted to Dome 33 for venting prior to transfer to WCRRF for remediation. These 23 drums are all >0.52 PE-Ci (≥HC3), so venting at Dome 33 must be scheduled accordingly. Previous RTR results (from 2005 thru 2007) also indicated that the drums failed for the prohibited items, including sealed container >4-L, liquids in the container, and impenetrable object due to possible lead shielding. None of the containers exceed 624 pound weight limit for WCRRF, the heaviest drum in this group weighs 516 pounds. At WCRRF, the nitrate salt drums will be remediated in accordance with a new or revised procedure to ensure the final mixture meets or exceeds Carlsbad's mixing requirements (each liter of composite nitrate salt waste is to be mixed with at least 1.2 liters of zeolite/kitty litter). The resulting mixture can be re-packaged into 55-gallon drums or POC as needed. It is estimated that three (3) 55-gal drums and three (3) POCs will be generated as daughters for each parent remediated. All of the resulting 138 containers will then be submitted for certification.

There are seven (7) 85-gal and nineteen (19) 55-gal drums proposed to go through HE-RTR pre-screening to confirm the presence of unconsolidated nitrate salt or cements cans and to determine if the inner container is vented. These twenty-six (26) parent containers are assigned to cemented waste stream LA-CIN01.001 and were transferred fromSP57 to SP72 based on the recent data review of the generator's discardable waste log sheet that indicated that these drums are nitrate salts. Based on the HE-RTR pre-screen results, the containers will go to WCRRF for remediation if found to be nitrate salt drums, or will be submitted to CPP for pre-certification if cemented cans and inner container is vented

and has an approved filter, or will be transferred to SP#57 for disposition if cemented cans are identified as unvented or possess other prohibited items. At WCRRF, the nitrate salt drums will be remediated in accordance with a new or revised procedure to ensure the final mixture meets or exceeds Carlsbad's mixing requirements (each liter of composite nitrate salt waste is to be mixed with at least 1.2 liters of zeolite/kitty litter). The resulting mixture can be re-packaged into 55-gallon drums. It is estimated that three (3) 55-gal drums and three (3) POCs will be generated as daughters for each parent remediated. All of the resulting 156 containers will then be submitted for certification.

## *Certification Path*

All of the containers will go through the CCP certification cycle after remediation activities at WCRRF.

### *RTR*

***Description:*** All 1254 remediation daughters will be subject to RTR. Hence, it will require approximately 90 days to complete the RTR certification activities for these daughter drums.

**Rate:** 14/day

### *HENC*

***Description:*** All 1254 remediation daughters will be subject to analysis at HENC. Hence, it will require approximately 90 days to complete the NDA analysis for these daughter drums.

***Rate:*** 14/day

### *FGA*

***Description:*** All 1254 remediation daughters will be subject to analysis for flammable gases. Hence, it will require approximately 90 days to complete the flammable gas, head space analyses for these daughter drums.

***Rate:*** 14/day

## *SHIPPING*

### *RANT*

***Description:***

55-gal drums will be shipped with no special requirements. However, the payload must not exceed 6,000 pounds or dunnage drums will need to be used to make up the payload configuration of 14 55-gal drums or 2 SWBs per TRUPACT II.

***Rate:*** Based on the average weight of 350 lbs, 28 drums per TRUPACT II per shipment may be achieved, although this year the average shipment has been about 16 to 19 drums.

## *Work Required for Disposition (detailed descriptions of scope)*

### AK Documentation

***Description:*** All 1254 remediation daughter containers will be evaluated by CCP during container certification prior to shipment to WIPP and will be reassigned to the appropriate AK waste stream as required. All drums are currently in an approved AK waste stream; however, the assignment of the remediated nitrate salt to debris, homogenous or perhaps an absorbed waste stream is pending a CCP decision. The revised waste stream description is estimated to be completed in late FY2012. CCP must also revise the TRU Waste Content (TRUCON) code to include the physical and chemical form of the final kitty litter/nitrate salt mixture and the waste packaging configurations.

### Procedure Change

***Description:*** Detailed operating procedure WP-WCRR-DOP-0233 *WCRRF Waste Characterization Glovebox Operations* must be revised or replaced to the implement the recipe to mix kitty litter/zeolite and nitrate salts. The final mixture must meet or exceed 1.2:1 kitty litter/zeolite:nitrate salt as specified by the LANL Carlsbad white paper *(Amount of Zeolite Required to Meet the Constraints Established by the EMRTC Report RF 10-13: Application to LANL Evaporator Nitrate Salts, May 08, 2012).*

### Readiness

***Description:*** Any drums with MAR inventories ≥HC 3 (0.52 PE-Ci) that require venting will need to be scheduled after receipt of start-up authorization authority approval for ≥HC 3 operations which follows successful completion of both contractor and Federal readiness assessments.

## *Commodities needed for this Solution Package*

The commodities are estimate on the basis that all debris daughter drums require remediation at WCRRF; all 55-gal and 85-gal, unvented drums require installation of HEPA filters at Dome 33; and that all suspect cement drums are actually unconsolidated nitrate salts.

| Item | Number Needed |
|---|---|
| **Filters** | **1254** |
| **55-Gal** | **682** |
| **85-Gal** | **117** |
| **POCs** | **705** |

## *Critical Action Items required to Process Waste*

| Action | Responsible Manager | Due Date |
|---|---|---|
| **Modify Procedure EP-WCRR-DOP-0233** | Mark Shepard | 30 days prior to use |
| **Modify RWP** | NA | NA |
| **Equipments/Procurements** | NA | NA |

## *Schedule Assumptions:*

- There are three hundred and five (305) that are estimated to be processed at WCRRF. These are estimated to create twelve hundred and fifty-four (1254) daughter containers. It is estimated that 10 drums per week will be processed at WCRRF.
- Thirty-three (33) 55-gal drums will be submitted to RTR to determine if the drums contain only debris, and not homogeneous nitrate salts. It is assumed that they contain nitrate salts and all will go to WCRRF as part of the 305.
- Twenty-three (23) 85-gal drums will be submitted to Dome 33 Drum Venting System (DVS) to vent and install HEPA filters. All are ≥HC 3. Assume 6 drums/day will start after SP#03 and X05.
- Twenty-six (26) drums (7 85-gallon and 19 55-gallon) drums require pre-screening thru HE RTR after SP#57 to determine if the drums are indeed unvented and contain cemented cans. It is assumed that all are vented and contain nitrate salts and all will go to WCRRF as part of 305.

**Shipping:**

Based on the estimated generation of daughter drums resulting from the remediation activities, the resulting 1254 daughter drums will require 128 days to ship, assuming 16 containers/shipment.

## *Attachments*

- Lists of Containers by proposed path
- Schedule

## Daughter (Repack) 55-Gal Drums - Submit to RTR for pre-screening

| PKG_ID | Original ID | Legacy/NG | Waste Stream | GG MAR | PECi | EC PECi | Gross Weight (lbs) | FGE | Total Dose |
|---|---|---|---|---|---|---|---|---|---|
| 91013 | S851506 | Legacy | LA-MHD01.001 | | 2.11 | | 405.40 | 23.32 | 8.7 |
| 91006 | S881563 | Legacy | LA-MHD01.001 | | 2.63 | | 124.40 | 29.03 | 17.4 |
| 90999 | S881562 | Legacy | LA-MHD01.001 | | 1.40 | | 118.20 | 15.41 | 7.5 |
| 90993 | S851432 | Legacy | LA-MHD01.001 | | 2.44 | | 235.60 | 26.95 | 16.3 |
| 90986 | S881569 | Legacy | LA-MHD01.001 | | 3.60 | | 122.20 | 17.94 | 15.3 |
| 90971 | S881608 | Legacy | LA-MHD01.001 | | 1.70 | | 203.60 | 18.76 | 48.6 |
| 90965 | S883130 | Legacy | LA-MHD01.001 | | 1.13 | | 312.60 | 12.51 | 33 |
| 90953 | S863787 | Legacy | LA-MHD01.001 | | 0.77 | | 204.40 | 8.45 | 29.3 |
| 90939 | S863788 | Legacy | LA-MHD01.001 | | 1.34 | | 290.20 | 14.76 | 44 |
| 90936 | S871844 | Legacy | LA-MHD01.001 | | 1.83 | | 373.20 | 20.17 | 25.2 |
| 90931 | S863696 | Legacy | LA-MHD01.001 | | 3.01 | | 157.00 | 30.70 | 22.5 |
| 90927 | S860096 | Legacy | LA-MHD01.001 | | 1.51 | | 385.40 | 16.68 | 31 |
| 90925 | S862411 | Legacy | LA-MHD01.001 | | 6.74 | | 341.00 | 91.64 | 12.3 |
| 90899 | S823187 | Legacy | LA-MHD01.001 | | 1.83 | | 419.20 | 20.24 | 17.25 |
| 90895 | S832155 | Legacy | LA-MHD01.001 | | 2.44 | | 295.40 | 26.98 | 26 |
| 90892 | S845201 | Legacy | LA-MHD01.001 | | 5.44 | | 329.20 | 53.47 | 11.2 |
| 90888 | S823194 | Legacy | LA-MHD01.001 | | 1.98 | | 306.20 | 18.98 | 12 |
| 90883 | S833261 | Legacy | LA-MHD01.001 | | 1.39 | | 177.80 | 14.66 | 32 |
| 90880 | S843962 | Legacy | LA-MHD01.001 | | 3.24 | | 321.80 | 35.75 | 12.25 |
| 90872 | S844213 | Legacy | LA-MHD01.001 | | 2.69 | | 196.60 | 28.90 | 43.6 |
| 90865 | S832464 | Legacy | LA-MHD01.001 | | 1.46 | | 299.60 | 13.91 | 13.5 |
| 90855 | S834539 | Legacy | LA-MHD01.001 | | 0.85 | | 165.40 | 1.97 | 11.7 |
| 90845 | S832149 | Legacy | LA-MHD01.001 | | 0.50 | | 129.40 | 4.52 | 4 |
| 90840 | S832040 | Legacy | LA-MHD01.001 | | 4.02 | | 213.80 | 44.39 | 6.5 |
| 90835 | S832156 | Legacy | LA-MHD01.001 | | 0.41 | | 232.40 | 4.15 | 49 |
| 90814 | S832448 | Legacy | LA-MHD01.001 | | 0.71 | | 196.60 | 7.73 | 45 |
| 90801 | S822838 | Legacy | LA-MHD01.001 | | 1.28 | | 175.00 | 14.10 | 18 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| 90752 | S825639 | Legacy | LA-MHD01.001 | | 0.50 | | 157.00 | 5.62 | 0.85 |
| 90727 | S832147 | Legacy | LA-MHD01.001 | | 1.58 | | 355.40 | 17.42 | 15.3 |
| 90715 | S824551 | Legacy | LA-MHD01.001 | | 0.73 | | 175.40 | 8.05 | 14.7 |
| 90712 | S832340 | Legacy | LA-MHD01.001 | | 0.71 | | 227.80 | 7.85 | 7.6 |
| 90323 | S910172 | Legacy | LA-MHD01.001 | | 4.26 | | 266.00 | 26.08 | 20.4 |
| 90315 | S910171 | Legacy | LA-MHD01.001 | | 2.41 | | 199.00 | 16.04 | 25.3 |
| | | | | | | | | | |

## Daughter (Repack) POCs - Submit for Remediation at WCRRF

| PKG_ID | Original ID | Legacy/NG | Waste Stream | GG MAR | PECI | EC PECI | Gross Weight (lbs) | FGE | Total Dose |
|---|---|---|---|---|---|---|---|---|---|
| 91019 | S851506 | Legacy | LA-MHD01.001 | | 2.11 | | 349.60 | 23.32 | 0.55 |
| 91018 | S851506 | Legacy | LA-MHD01.001 | | 2.11 | | 376.80 | 23.32 | 0.75 |
| 91017 | S851506 | Legacy | LA-MHD01.001 | | 2.11 | | 411.40 | 23.32 | 1.1 |
| 91011 | S881563 | Legacy | LA-MHD01.001 | | 2.63 | | 413.60 | 29.03 | 1.3 |
| 91010 | S881563 | Legacy | LA-MHD01.001 | | 2.63 | | 401.20 | 29.03 | 0.75 |
| 91009 | S881563 | Legacy | LA-MHD01.001 | | 2.63 | | 408.80 | 29.03 | 1.3 |
| 91008 | S881563 | Legacy | LA-MHD01.001 | | 2.63 | | 398.20 | 29.03 | 1.4 |
| 91007 | S881563 | Legacy | LA-MHD01.001 | | 2.63 | | 412.00 | 29.03 | 1.1 |
| 91004 | S881562 | Legacy | LA-MHD01.001 | | 1.40 | | 390.20 | 15.41 | 1.8 |
| 91003 | S881562 | Legacy | LA-MHD01.001 | | 1.40 | | 426.20 | 15.41 | 2 |
| 91002 | S881562 | Legacy | LA-MHD01.001 | | 1.40 | | 394.00 | 15.41 | 1.3 |
| 91001 | S881562 | Legacy | LA-MHD01.001 | | 1.40 | | 389.00 | 15.41 | 1.5 |
| 91000 | S881562 | Legacy | LA-MHD01.001 | | 1.40 | | 437.80 | 15.41 | 1.5 |
| 90997 | S851432 | Legacy | LA-MHD01.001 | | 2.44 | | 365.80 | 26.95 | 0.9 |
| 90996 | S851432 | Legacy | LA-MHD01.001 | | 2.44 | | 428.40 | 26.95 | 2 |
| 90995 | S851432 | Legacy | LA-MHD01.001 | | 2.44 | | 415.60 | 26.95 | 2.1 |
| 90991 | S881569 | Legacy | LA-MHD01.001 | | 1.87 | | 386.60 | 19.32 | 0.8 |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 90990 | S881569 | Legacy | LA-MHD01.001 | 1.87 | | 426.00 | 19.32 | 1.8 |
| 90989 | S881569 | Legacy | LA-MHD01.001 | 1.87 | | 408.60 | 19.32 | 1.1 |
| 90988 | S881569 | Legacy | LA-MHD01.001 | 1.87 | | 400.20 | 19.32 | 1.4 |
| 90987 | S881569 | Legacy | LA-MHD01.001 | 1.87 | | 400.60 | 19.32 | 1.4 |
| 90974 | S881608 | Legacy | LA-MHD01.001 | 1.70 | | 438.60 | 18.76 | 1.1 |
| 90973 | S881608 | Legacy | LA-MHD01.001 | 1.70 | | 395.80 | 18.76 | 1.1 |
| 90972 | S881608 | Legacy | LA-MHD01.001 | 1.70 | | 382.60 | 18.76 | 1 |
| 90969 | S883130 | Legacy | LA-MHD01.001 | 1.13 | | 398.40 | 12.51 | 1.5 |
| 90968 | S883130 | Legacy | LA-MHD01.001 | 1.13 | | 415.80 | 12.51 | 1.5 |
| 90966 | S883130 | Legacy | LA-MHD01.001 | 1.13 | | 404.60 | 12.51 | 1.5 |
| 90957 | S863787 | Legacy | LA-MHD01.001 | 0.77 | | 417.40 | 8.45 | 0.65 |
| 90956 | S863787 | Legacy | LA-MHD01.001 | 0.77 | | 399.60 | 8.45 | 0.65 |
| 90955 | S863787 | Legacy | LA-MHD01.001 | 0.77 | | 374.20 | 8.45 | 0.75 |
| 90942 | S863788 | Legacy | LA-MHD01.001 | 1.34 | | 377.44 | 14.76 | 1 |
| 90941 | S863788 | Legacy | LA-MHD01.001 | 1.34 | | 390.00 | 14.76 | 1 |
| 90937 | S871844 | Legacy | LA-MHD01.001 | 1.83 | | 355.80 | 20.17 | 1 |
| 90934 | S863696 | Legacy | LA-MHD01.001 | 3.01 | | 420.60 | 30.70 | 0.75 |
| 90933 | S863696 | Legacy | LA-MHD01.001 | 3.01 | | 400.00 | 30.70 | 0.9 |
| 90932 | S863696 | Legacy | LA-MHD01.001 | 3.01 | | 418.80 | 30.70 | 0.8 |
| 90929 | S860096 | Legacy | LA-MHD01.001 | 1.51 | | 378.80 | 16.68 | 1.5 |
| 90900 | S823187 | Legacy | LA-MHD01.001 | 1.83 | | 371.20 | 20.24 | 1.5 |
| 90897 | S832155 | Legacy | LA-MHD01.001 | 2.44 | | 405.60 | 26.98 | 1.3 |
| 90896 | S832155 | Legacy | LA-MHD01.001 | 2.44 | | 375.20 | 26.98 | 2 |
| 90893 | S845201 | Legacy | LA-MHD01.001 | 5.44 | | 416.80 | 53.47 | 2.1 |
| 90890 | S823194 | Legacy | LA-MHD01.001 | 1.98 | | 405.80 | 18.98 | 1.25 |
| 90886 | S833261 | Legacy | LA-MHD01.001 | 1.39 | | 373.80 | 14.66 | 0.75 |
| 90885 | S833261 | Legacy | LA-MHD01.001 | 1.39 | | 419.00 | 14.66 | 1.5 |
| 90884 | S833261 | Legacy | LA-MHD01.001 | 1.39 | | 394.80 | 14.66 | 1.5 |
| 90881 | S843962 | Legacy | LA-MHD01.001 | 3.24 | | 375.00 | 35.75 | 0.75 |
| 90878 | S844213 | Legacy | LA-MHD01.001 | 2.69 | | 359.20 | 28.90 | 1.5 |
| 90877 | S844213 | Legacy | LA-MHD01.001 | 2.69 | | 391.00 | 28.90 | 7.5 |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 90876 | S844213 | Legacy | LA-MHD01.001 | 2.69 | | 378.40 | 28.90 | 1 |
| 90875 | S844213 | Legacy | LA-MHD01.001 | 2.69 | | 377.20 | 28.90 | 0.105 |
| 90870 | S832464 | Legacy | LA-MHD01.001 | 1.46 | | 380.20 | 13.91 | 55 |
| 90869 | S832464 | Legacy | LA-MHD01.001 | 1.46 | | 361.40 | 13.91 | 0.55 |
| 90868 | S832464 | Legacy | LA-MHD01.001 | 1.46 | | 385.80 | 13.91 | 0.65 |
| 90867 | S832464 | Legacy | LA-MHD01.001 | 1.46 | | 375.80 | 13.91 | 0.55 |
| 90866 | S832464 | Legacy | LA-MHD01.001 | 1.46 | | 389.00 | 13.91 | 0.8 |
| 90863 | S834539 | Legacy | LA-MHD01.001 | 2.02 | | 366.00 | 18.81 | 1.5 |
| 90862 | S834539 | Legacy | LA-MHD01.001 | 2.02 | | 374.40 | 18.81 | 1.25 |
| 90861 | S834539 | Legacy | LA-MHD01.001 | 2.02 | | 363.40 | 18.81 | 1.5 |
| 90860 | S834539 | Legacy | LA-MHD01.001 | 2.02 | | 347.80 | 18.81 | 2.3 |
| 90859 | S834539 | Legacy | LA-MHD01.001 | 2.02 | | 356.40 | 18.81 | 1.25 |
| 90858 | S834539 | Legacy | LA-MHD01.001 | 2.02 | | 351.60 | 18.81 | 1.5 |
| 90853 | S832149 | Legacy | LA-MHD01.001 | 0.50 | | 368.80 | 4.52 | 1.5 |
| 90852 | S832149 | Legacy | LA-MHD01.001 | 0.50 | | 372.40 | 4.52 | 2 |
| 90851 | S832149 | Legacy | LA-MHD01.001 | 0.50 | | 379.80 | 4.52 | 0.15 |
| 90850 | S832149 | Legacy | LA-MHD01.001 | 0.50 | | 397.60 | 4.52 | 1.3 |
| 90849 | S832149 | Legacy | LA-MHD01.001 | 0.50 | | 399.80 | 4.52 | 1.5 |
| 90848 | S832149 | Legacy | LA-MHD01.001 | 0.50 | | 409.40 | 4.52 | 2 |
| 90843 | S832040 | Legacy | LA-MHD01.001 | 4.02 | | 355.00 | 44.39 | 7 |
| 90842 | S832040 | Legacy | LA-MHD01.001 | 4.02 | | 361.40 | 44.39 | 9 |
| 90841 | S832040 | Legacy | LA-MHD01.001 | 4.02 | | 383.00 | 44.39 | 0.9 |
| 90838 | S832156 | Legacy | LA-MHD01.001 | 0.41 | | 368.60 | 4.15 | 0.75 |
| 90837 | S832156 | Legacy | LA-MHD01.001 | 0.41 | | 375.20 | 4.15 | 0.15 |
| 90836 | S832156 | Legacy | LA-MHD01.001 | 0.41 | | 390.20 | 4.15 | 0.12 |
| 90823 | S832448 | Legacy | LA-MHD01.001 | 0.71 | | 371.80 | 7.73 | 0.8 |
| 90822 | S832448 | Legacy | LA-MHD01.001 | 0.71 | | 368.00 | 7.73 | 0.5 |
| 90821 | S832448 | Legacy | LA-MHD01.001 | 0.71 | | 369.40 | 7.73 | 0.8 |
| 90820 | S832448 | Legacy | LA-MHD01.001 | 0.71 | | 381.00 | 7.73 | 0.9 |
| 90819 | S832448 | Legacy | LA-MHD01.001 | 0.71 | | 365.00 | 7.73 | 0.55 |
| 90818 | S832448 | Legacy | LA-MHD01.001 | 0.71 | | 386.00 | 7.73 | 1.3 |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 90817 | S832448 | Legacy | LA-MHD01.001 | 0.71 | | 380.80 | 7.73 | 0.85 |
| 90812 | S822838 | Legacy | LA-MHD01.001 | 1.28 | | 383.00 | 14.10 | 0.55 |
| 90811 | S822838 | Legacy | LA-MHD01.001 | 1.28 | | 361.00 | 14.10 | 0.1 |
| 90810 | S822838 | Legacy | LA-MHD01.001 | 1.28 | | 371.20 | 14.10 | 0.1 |
| 90809 | S822838 | Legacy | LA-MHD01.001 | 1.28 | | 383.40 | 14.10 | 0.55 |
| 90808 | S822838 | Legacy | LA-MHD01.001 | 1.28 | | 366.60 | 14.10 | 0.55 |
| 90807 | S822838 | Legacy | LA-MHD01.001 | 1.28 | | 357.40 | 14.10 | 0.55 |
| 90806 | S822838 | Legacy | LA-MHD01.001 | 1.28 | | 348.00 | 14.10 | 0.75 |
| 90805 | S822838 | Legacy | LA-MHD01.001 | 1.28 | | 349.40 | 14.10 | 0.85 |
| 90804 | S822838 | Legacy | LA-MHD01.001 | 1.28 | | 338.40 | 14.10 | 0.75 |
| 90803 | S822838 | Legacy | LA-MHD01.001 | 1.28 | | 347.20 | 14.10 | 0.55 |
| 90802 | S822838 | Legacy | LA-MHD01.001 | 1.28 | | 351.00 | 14.10 | 0.55 |
| 90760 | S825639 | Legacy | LA-MHD01.001 | 0.50 | | 378.40 | 5.62 | 0.55 |
| 90759 | S825639 | Legacy | LA-MHD01.001 | 0.50 | | 372.60 | 5.62 | 0.65 |
| 90758 | S825639 | Legacy | LA-MHD01.001 | 0.50 | | 373.00 | 5.62 | 0.75 |
| 90757 | S825639 | Legacy | LA-MHD01.001 | 0.50 | | 373.00 | 5.62 | 0.35 |
| 90756 | S825639 | Legacy | LA-MHD01.001 | 0.50 | | 359.80 | 5.62 | 0.35 |
| 90755 | S825639 | Legacy | LA-MHD01.001 | 0.50 | | 364.40 | 5.62 | 0.65 |
| 90728 | S832147 | Legacy | LA-MHD01.001 | 1.58 | | 340.40 | 17.42 | 0.35 |
| 90725 | S824551 | Legacy | LA-MHD01.001 | 0.73 | | 388.20 | 8.05 | 5.5 |
| 90724 | S824551 | Legacy | LA-MHD01.001 | 0.73 | | 372.00 | 8.05 | 1.2 |
| 90723 | S824551 | Legacy | LA-MHD01.001 | 0.73 | | 357.60 | 8.05 | 1 |
| 90722 | S824551 | Legacy | LA-MHD01.001 | 0.73 | | 343.30 | 8.05 | 1.4 |
| 90721 | S824551 | Legacy | LA-MHD01.001 | 0.73 | | 343.20 | 8.05 | 0.65 |
| 90720 | S824551 | Legacy | LA-MHD01.001 | 0.73 | | 352.00 | 8.05 | 1.3 |
| 90719 | S824551 | Legacy | LA-MHD01.001 | 0.73 | | 359.40 | 8.05 | 1.2 |
| 90718 | S824551 | Legacy | LA-MHD01.001 | 0.73 | | 349.80 | 8.05 | 1.4 |
| 90713 | S832340 | Legacy | LA-MHD01.001 | 0.71 | | 338.60 | 7.85 | 1.2 |
| 90324 | S910172 | Legacy | LA-MIN04-5.001 | 3.42 | | 373.20 | 10.37 | 0.75 |
| 90318 | S910171 | Legacy | LA-MIN04-5.001 | 2.36 | | 380.20 | 5.80 | 1.75 |
| 90317 | S910171 | Legacy | LA-MIN04-5.001 | 2.36 | | 372.20 | 5.80 | 0.95 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **90316** | S910171 | Legacy | LA-MIN04.S.001 | 2.36 | | | 364.60 | 5.80 | 0.75 |

## Original/Parent 85-Gal Drums - Submit for Remediation at WCRRF

| PKG_ID | Original ID | Legacy/NG | Waste Stream | GG MAR | PEG | EC PEG | Gross Weight (lbs) | FGE | Total Dose |
|---|---|---|---|---|---|---|---|---|---|
| **S891279** | S891279 | Legacy | LA-MHD01.001 | 14.75 | 14.75 | 3.69 | 378.38 | 162.86 | 4 |
| **S881607** | S881607 | Legacy | LA-MHD01.001 | 23.97 | 23.97 | 5.99 | 385.21 | 166.50 | 1 |
| **S881570** | S881570 | Legacy | LA-MHD01.001 | 25.65 | 25.65 | 6.41 | 407.26 | 159.87 | 2 |
| **S873554** | S873554 | Legacy | LA-MHD01.001 | 6.12 | 6.12 | 1.53 | 416.08 | 67.64 | 70 |
| **S870478** | S870478 | Legacy | LA-MHD01.001 | 4.45 | 4.45 | 1.11 | 410.13 | 49.18 | 3 |
| **S870381** | S870381 | Legacy | LA-MHD01.001 | 4.10 | 4.10 | 1.02 | 401.09 | 45.26 | 5 |
| **S870213** | S870213 | Legacy | LA-MHD01.001 | 3.73 | 3.73 | 0.93 | 403.29 | 41.24 | 0 |
| **S870065** | S870065 | Legacy | LA-MHD01.001 | 5.96 | 5.96 | 1.49 | 812.10 | 65.88 | 2 |
| **S864694** | S864694 | Legacy | LA-MHD01.001 | 8.80 | 8.80 | 2.20 | 409.03 | 97.15 | 2 |
| **S860014** | S860014 | Legacy | LA-MHD01.001 | 15.64 | 15.64 | 3.91 | 444.97 | 171.85 | 6 |
| **S855793** | S855793 | Legacy | LA-MHD01.001 | 3.44 | 3.44 | 0.86 | 513.04 | 36.20 | 3 |
| **S855566** | S855566 | Legacy | LA-MHD01.001 | 9.15 | 9.15 | 2.29 | 502.90 | 92.71 | 4 |
| **S855139** | S855139 | Legacy | LA-MHD01.001 | 5.93 | 5.93 | 1.48 | 478.04 | 64.26 | 10 |
| **S853006** | S853006 | Legacy | LA-MHD01.001 | 8.42 | 8.42 | 2.10 | 467.46 | 92.98 | 1 |
| **S852593** | S852593 | Legacy | LA-MHD01.001 | 11.80 | 11.80 | 2.95 | 383.01 | 126.54 | 2 |
| **S851772** | S851772 | Legacy | LA-MHD01.001 | 13.08 | 13.08 | 3.27 | 537.08 | 146.74 | 2 |
| **S851764** | S851764 | Legacy | LA-MHD01.001 | 9.65 | 9.65 | 2.41 | 418.95 | 103.48 | 2 |
| **S851739** | S851739 | Legacy | LA-MHD01.001 | 11.42 | 11.42 | 2.85 | 399.33 | 122.57 | 2 |
| **S851682** | S851682 | Legacy | LA-MHD01.001 | 17.03 | 17.03 | 4.26 | 481.79 | 184.61 | 2 |
| **S851426** | S851426 | Legacy | LA-MHD01.001 | 11.53 | 11.53 | 2.88 | 545.45 | 127.37 | 3 |
| **S846195** | S846195 | Legacy | LA-MHD01.001 | 11.23 | 11.23 | 2.81 | 476.94 | 124.08 | 3 |
| **S846172** | S846172 | Legacy | LA-MHD01.001 | 10.58 | 10.58 | 2.64 | 482.01 | 116.83 | 3 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **S846132** | S846132 | Legacy | LA-MHD01.001 | 8.67 | 8.67 | 2.17 | 510.62 | 97.15 | 12 |
| **S846107** | S846107 | Legacy | LA-MHD01.001 | 14.98 | 14.98 | 3.75 | 469.67 | 165.50 | 5 |
| **S846096** | S846096 | Legacy | LA-MHD01.001 | 8.81 | 8.81 | 2.20 | 479.59 | 97.34 | 2 |
| **S846088** | S846088 | Legacy | LA-MHD01.001 | 16.50 | 16.50 | 4.12 | 525.01 | 183.23 | 3 |
| **S846037** | S846037 | Legacy | LA-MHD01.001 | 13.21 | 13.21 | 3.30 | 435.05 | 145.92 | 2 |
| **S844684** | S844684 | Legacy | LA-MHD01.001 | 8.77 | 8.77 | 2.19 | 434.76 | 94.75 | 2 |
| **S842528** | S842528 | Legacy | LA-MHD01.001 | 16.87 | 16.87 | 4.22 | 259.53 | 186.30 | 3 |
| **S834406** | S834406 | Legacy | LA-MHD01.001 | 14.31 | 14.31 | 3.58 | 356.77 | 146.93 | 4 |
| **S832241** | S832241 | Legacy | LA-MHD01.001 | 6.61 | 6.61 | 1.65 | 553.21 | 60.60 | 2 |
| **S832148** | S832148 | Legacy | LA-MHD01.001 | 6.14 | 6.14 | 1.53 | 390.73 | 67.78 | 25 |
| **S832141** | S832141 | Legacy | LA-MHD01.001 | 3.06 | 3.06 | 0.77 | 437.69 | 31.45 | 10 |
| **S824967** | S824967 | Legacy | LA-MHD01.001 | 5.70 | 5.70 | 1.42 | 437.91 | 62.59 | 4 |
| **S824541** | S824541 | Legacy | LA-MHD01.001 | 16.13 | 16.13 | 4.03 | 396.90 | 38.44 | 6 |
| **S824508** | S824508 | Legacy | LA-MHD01.001 | 15.32 | 15.32 | 3.83 | 422.04 | 169.17 | 2 |
| **S824187** | S824187 | Legacy | LA-MHD01.001 | 5.42 | 5.42 | 1.36 | 399.99 | 59.90 | 190 |
| **S824184** | S824184 | Legacy | LA-MHD01.001 | 2.87 | 2.87 | 0.72 | 426.89 | 31.74 | 6 |
| **S823276** | S823276 | Legacy | LA-MHD01.001 | 9.46 | 9.46 | 2.37 | 439.02 | 104.50 | 20 |
| **S822876** | S822876 | Legacy | LA-MHD01.001 | 1.85 | 1.85 | 0.46 | 356.11 | 13.44 | 130 |
| **S821203** | S821203 | Legacy | LA-MHD01.001 | 13.04 | 13.04 | 3.26 | 455.99 | 144.04 | 2 |

## Original/Parent 55-Gal Drums - Submit for Remediation at WCRRF

| PKG_ID | Original ID | Legacy/NG | Waste Stream | GG MAR | PEGi | EC PEGi | Gross Weight (lbs) | FGE | Total Dose |
|---|---|---|---|---|---|---|---|---|---|
| **S910170** | S910170 | Legacy | LA-MHD01.001 | 7.60 | 7.60 | 1.90 | 417.63 | 83.93 | 1 |
| **S891513** | S891513 | Legacy | LA-MHD01.001 | 14.68 | 14.68 | 3.67 | 441.22 | 162.11 | 10 |
| **S870475** | S870475 | Legacy | LA-MHD01.001 | 6.49 | 6.49 | 1.62 | 384.77 | 71.73 | 3 |
| **S864663** | S864663 | Legacy | LA-MHD01.001 | 3.32 | 3.32 | 0.83 | 428.87 | 35.85 | 1 |
| **S864662** | S864662 | Legacy | LA-MHD01.001 | 2.99 | 2.99 | 0.75 | 414.54 | 32.78 | 8 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **S863789** | S863789 | Legacy | LA-MHD01.001 | 3.53 | 3.53 | 0.88 | 383.89 | 39.04 | 2 |
| **S862255** | S862255 | Legacy | LA-MHD01.001 | 3.62 | 3.62 | 0.90 | 324.14 | 39.93 | 1 |
| **S862241** | S862241 | Legacy | LA-MHD01.001 | 11.23 | 11.23 | 2.81 | 395.80 | 124.08 | 2 |
| **S861980** | S861980 | Legacy | LA-MHD01.001 | 4.00 | 4.00 | 1.00 | 465.03 | 44.19 | 2 |
| **S861976** | S861976 | Legacy | LA-MHD01.001 | 5.85 | 5.85 | 1.46 | 439.90 | 64.67 | 2 |
| **S861975** | S861975 | Legacy | LA-MHD01.001 | 4.36 | 4.36 | 1.09 | 332.73 | 48.16 | 2 |
| **S860095** | S860095 | Legacy | LA-MHD01.001 | 3.71 | 3.71 | 0.93 | 395.80 | 41.00 | 1 |
| **S860093** | S860093 | Legacy | LA-MHD01.001 | 2.69 | 2.69 | 0.67 | 439.02 | 29.72 | 1 |
| **S855290** | S855290 | Legacy | LA-MHD01.001 | 5.60 | 5.60 | 1.40 | 443.43 | 52.86 | 1 |
| **S855240** | S855240 | Legacy | LA-MHD01.001 | 11.90 | 11.90 | 2.97 | 439.02 | 129.08 | 2 |
| **S855126** | S855126 | Legacy | LA-MHD01.001 | 5.40 | 5.40 | 1.35 | 448.06 | 55.26 | 3 |
| **S854616** | S854616 | Legacy | LA-MHD01.001 | 5.85 | 5.85 | 1.46 | 471.87 | 64.33 | 3 |
| **S853899** | S853899 | Legacy | LA-MHD01.001 | 5.40 | 5.40 | 1.35 | 454.01 | 58.93 | 1 |
| **S853898** | S853898 | Legacy | LA-MHD01.001 | 6.53 | 6.53 | 1.63 | 556.32 | 71.40 | 8 |
| **S853771** | S853771 | Legacy | LA-MHD01.001 | 4.95 | 4.95 | 1.24 | 454.23 | 54.67 | 5 |
| **S853641** | S853641 | Legacy | LA-MHD01.001 | 14.48 | 14.48 | 3.62 | 475.18 | 148.24 | 2 |
| **S853492** | S853492 | Legacy | LA-MHD01.001 | 9.02 | 9.02 | 2.25 | 519.72 | 99.60 | 7 |
| **S853326** | S853326 | Legacy | LA-MHD01.001 | 11.29 | 11.29 | 2.82 | 498.11 | 124.74 | 1 |
| **S853279** | S853279 | Legacy | LA-MHD01.001 | 6.87 | 6.87 | 1.72 | 472.09 | 75.87 | 2 |
| **S852923** | S852923 | Legacy | LA-MHD01.001 | 10.54 | 10.54 | 2.63 | 327.66 | 116.36 | 4 |
| **S852895** | S852895 | Legacy | LA-MHD01.001 | 5.38 | 5.38 | 1.35 | 465.03 | 56.82 | 4 |
| **S852883** | S852883 | Legacy | LA-MHD01.001 | 6.64 | 6.64 | 1.66 | 398.00 | 73.37 | 8 |
| **S852590** | S852590 | Legacy | LA-MHD01.001 | 16.74 | 16.74 | 4.19 | 431.96 | 184.89 | 1 |
| **S852513** | S852513 | Legacy | LA-MHD01.001 | 16.77 | 16.77 | 4.19 | 418.95 | 185.27 | 2 |
| **S851752** | S851752 | Legacy | LA-MHD01.001 | 12.13 | 12.13 | 3.03 | 406.38 | 130.94 | 6 |
| **S846660** | S846660 | Legacy | LA-MHD01.001 | 12.48 | 12.48 | 3.12 | 433.06 | 137.82 | 2 |
| **S846168** | S846168 | Legacy | LA-MHD01.001 | 14.04 | 14.04 | 3.51 | 456.88 | 155.45 | 4 |
| **S845338** | S845338 | Legacy | LA-MHD01.001 | 9.45 | 9.45 | 2.36 | 441.00 | 99.26 | 2 |
| **S845104** | S845104 | Legacy | LA-MHD01.001 | 10.09 | 10.09 | 2.52 | 375.95 | 101.35 | 3 |
| **S845072** | S845072 | Legacy | LA-MHD01.001 | 11.49 | 11.49 | 2.87 | 408.81 | 110.23 | 3 |
| **S845031** | S845031 | Legacy | LA-MHD01.001 | 15.17 | 15.17 | 3.79 | 420.93 | 158.40 | 4 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **S844689** | S844689 | Legacy | LA-MHD01.001 | 12.27 | 12.27 | 3.07 | 415.86 | 130.14 | 3 |
| **S844573** | S844573 | Legacy | LA-MHD01.001 | 17.07 | 17.07 | 4.27 | 313.11 | 186.05 | 2 |
| **S843528** | S843528 | Legacy | LA-MHD01.001 | 8.52 | 8.52 | 2.13 | 492.16 | 94.14 | 1 |
| **S842463** | S842463 | Legacy | LA-MHD01.001 | 12.39 | 12.39 | 3.10 | 437.03 | 133.02 | 3 |
| **S842234** | S842234 | Legacy | LA-MHD01.001 | 8.52 | 8.52 | 2.13 | 393.81 | 94.14 | 1 |
| **S842213** | S842213 | Legacy | LA-MHD01.001 | 16.78 | 16.78 | 4.19 | 353.90 | 178.97 | 1 |
| **S842181** | S842181 | Legacy | LA-MHD01.001 | 1.88 | 1.88 | 0.47 | 431.08 | 20.71 | 32 |
| **S841320** | S841320 | Legacy | LA-MHD01.001 | 7.57 | 7.57 | 1.89 | 453.35 | 83.60 | 2 |
| **S841314** | S841314 | Legacy | LA-MHD01.001 | 13.17 | 13.17 | 3.29 | 459.96 | 145.45 | 2 |
| **S841292** | S841292 | Legacy | LA-MHD01.001 | 9.93 | 9.93 | 2.48 | 426.45 | 109.67 | 2 |
| **S841240** | S841240 | Legacy | LA-MHD01.001 | 10.52 | 10.52 | 2.63 | 533.17 | 107.10 | 1 |
| **S835283** | S835283 | Legacy | LA-MHD01.001 | 11.14 | 11.14 | 2.79 | 453.13 | 120.39 | 2 |
| **S834633** | S834633 | Legacy | LA-MHD01.001 | 15.06 | 15.06 | 3.77 | 422.92 | 149.56 | 3 |
| **S833937** | S833937 | Legacy | LA-MHD01.001 | 12.76 | 12.76 | 3.19 | 414.98 | 130.21 | 4 |
| **S833846** | S833846 | Legacy | LA-MHD01.001 | 18.36 | 18.36 | 4.59 | 407.93 | 181.53 | 6 |
| **S833481** | S833481 | Legacy | LA-MHD01.001 | 10.04 | 10.04 | 2.51 | 399.99 | 115.10 | 3 |
| **S833037** | S833037 | Legacy | LA-MHD01.001 | 8.06 | 8.06 | 2.01 | 389.84 | 76.89 | 1 |
| **S832499** | S832499 | Legacy | LA-MHD01.001 | 6.05 | 6.05 | 1.51 | 398.00 | 64.24 | 1 |
| **S832320** | S832320 | Legacy | LA-MHD01.001 | 3.51 | 3.51 | 0.88 | 435.93 | 38.80 | 1 |
| **S832150** | S832150 | Legacy | LA-MHD01.001 | 11.28 | 11.28 | 2.82 | 479.15 | 101.23 | 7 |
| **S832145** | S832145 | Legacy | LA-MHD01.001 | 12.98 | 12.98 | 3.25 | 418.95 | 142.29 | 1 |
| **S832144** | S832144 | Legacy | LA-MHD01.001 | 10.69 | 10.69 | 2.67 | 411.01 | 118.05 | 2 |
| **S832143** | S832143 | Legacy | LA-MHD01.001 | 16.43 | 16.43 | 4.11 | 294.59 | 181.50 | 2 |
| **S832140** | S832140 | Legacy | LA-MHD01.001 | 16.78 | 16.78 | 4.20 | 336.70 | 185.36 | 2 |
| **S825902** | S825902 | Legacy | LA-MHD01.001 | 3.98 | 3.98 | 0.99 | 349.71 | 43.92 | 9 |
| **S825810** | S825810 | Legacy | LA-MHD01.001 | 7.29 | 7.29 | 1.82 | 343.76 | 80.49 | 1 |
| **S825730** | S825730 | Legacy | LA-MHD01.001 | 1.96 | 1.96 | 0.49 | 461.07 | 21.65 | 1 |
| **S825021** | S825021 | Legacy | LA-MHD01.001 | 7.96 | 7.96 | 1.99 | 457.10 | 87.87 | 120 |
| **S825020** | S825020 | Legacy | LA-MHD01.001 | 12.73 | 12.73 | 3.18 | 319.73 | 140.55 | 23 |
| **S824660** | S824660 | Legacy | LA-MHD01.001 | 17.09 | 17.09 | 4.27 | 422.92 | 185.89 | 12 |
| **S824208** | S824208 | Legacy | LA-MHD01.001 | 2.15 | 2.15 | 0.54 | 478.04 | 23.70 | 8 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **S824188** | S824188 | Legacy | LA-MHD01.001 | 9.12 | 9.12 | 2.28 | 453.13 | 100.73 | 36 |
| **S823221** | S823221 | Legacy | LA-MHD01.001 | 6.48 | 6.48 | 1.62 | 496.13 | 71.55 | 8 |
| **S823004** | S823004 | Legacy | LA-MHD01.001 | 5.80 | 5.80 | 1.45 | 463.49 | 64.11 | 6 |
| **S822952** | S822952 | Legacy | LA-MHD01.001 | 1.95 | 1.95 | 0.49 | 424.90 | 8.57 | 5 |

**Unvented Drums w/ multiple issues (NCR, high Am content, sealed container >4L, liquids, impenetrable, etc.)**

| PKG_ID | Original ID | Legacy/NG | Waste Stream | GG MAR | PECI | EC PEC | Gross Weight (lbs) | FGE | Total Dose |
|---|---|---|---|---|---|---|---|---|---|
| **S901114** | S901114 | Legacy | LA-MHD01.001 | 7.32 | 7.32 | 1.83 | 437.91 | 80.80 | 35 |
| **S900215** | S900215 | Legacy | LA-MHD01.001 | 11.69 | 11.69 | 2.92 | 422.70 | 129.07 | 37 |
| **S861995** | S861995 | Legacy | LA-MHD01.001 | 8.57 | 8.57 | 2.14 | 423.80 | 90.87 | 2 |
| **S855216** | S855216 | Legacy | LA-MHD01.001 | 2.38 | 2.38 | 0.60 | 516.13 | 20.82 | 2 |
| **S852931** | S852931 | Legacy | LA-MHD01.001 | 7.88 | 7.88 | 1.97 | 485.54 | 87.08 | 5 |
| **S852592** | S852592 | Legacy | LA-MHD01.001 | 14.86 | 14.86 | 3.72 | 437.91 | 153.84 | 2 |
| **S852530** | S852530 | Legacy | LA-MHD01.001 | 16.13 | 16.13 | 4.03 | 409.91 | 178.11 | 2 |
| **S851436** | S851436 | Legacy | LA-MHD01.001 | 13.09 | 13.09 | 3.27 | 440.34 | 144.60 | 1 |
| **S851416** | S851416 | Legacy | LA-CIN01.001-Cans | | 2.78 | | 568.23 | 30.74 | 2 |
| **S851415** | S851415 | Legacy | LA-CIN01.001-Cans | | 10.36 | | 453.79 | 114.38 | 2 |
| **S844253** | S844253 | Legacy | LA-MHD01.001 | 15.19 | 15.19 | 3.80 | 365.81 | 163.80 | 12 |
| **S844215** | S844215 | Legacy | LA-MHD01.001 | 16.18 | 16.18 | 4.04 | 344.86 | 178.68 | 5 |
| **S842526** | S842526 | Legacy | LA-MHD01.001 | 16.79 | 16.79 | 4.20 | 399.99 | 182.14 | 28 |
| **S841251** | S841251 | Legacy | LA-MHD01.001 | 16.16 | 16.16 | 4.04 | 500.76 | 171.01 | 2 |
| **S841239** | S841239 | Legacy | LA-MHD01.001 | 10.13 | 10.13 | 2.53 | 461.51 | 111.84 | 2 |
| **S823229** | S823229 | Legacy | LA-MHD01.001 | 10.40 | 10.40 | 2.60 | 266.58 | 114.85 | 12 |
| **S823166** | S823166 | Legacy | LA-MHD01.001 | 4.69 | 4.69 | 1.17 | 421.38 | 51.78 | 1 |
| **S818412** | S818412 | Legacy | LA-CIN01.001-Cans | | 1.88 | | 387.86 | 20.71 | 2 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **S813471** | S813471 | Legacy | LA-CIN01.001-Cans | | 1.92 | | 457.98 | 21.17 | 40 |
| **S802701** | S802701 | Legacy | LA-CIN01.001-Cans | | 0.56 | | 396.02 | 5.39 | 1 |
| **S892963** | S892963 | Legacy | LA-MHD01.001 | 11.72 | 11.72 | 2.93 | 529.20 | 124.76 | 1 |
| **S891387** | S891387 | Legacy | LA-MHD01.001 | 10.69 | 10.69 | 2.67 | 422.26 | 117.58 | 1 |
| **S870338** | S870338 | Legacy | LA-MHD01.001 | 4.61 | 4.61 | 1.15 | 451.80 | 50.97 | 15 |

**Suspect Cement Can - Original/Parent 85-Gal and 55-Gal Drums - Submit to HE RTR for pre-screening**

| PKG_ID | Original ID | Legacy/NG | Waste Stream | GG MAR | PECL | EC PECL | Gross Weight (lbs) | FGE | Total Dose |
|---|---|---|---|---|---|---|---|---|---|
| **S851418** | S851418 | Legacy | LA-CIN01.001-Cans | | 7.74 | | 435.93 | 81.29 | 5 |
| **S844602** | S844602 | Legacy | LA-CIN01.001-Cans | | 14.53 | | 380.80 | 148.60 | 2 |
| **S843673** | S843673 | Legacy | LA-CIN01.001-Cans | | 6.97 | | 416.75 | 77.18 | 6 |
| **S843672** | S843672 | Legacy | LA-CIN01.001-Cans | | 8.96 | | 467.24 | 97.17 | 2 |
| **S841627** | S841627 | Legacy | LA-CIN01.001-Cans | | 10.46 | | 526.49 | 115.51 | 6 |
| **S822679** | S822679 | Legacy | LA-CIN01.001-Cans | | 3.20 | | 486.64 | 33.73 | 26 |
| **S793450** | S793450 | Legacy | LA-CIN01.001-Cans | | 1.01 | | 469.00 | 6.97 | 2 |
| **S855677** | S855677 | Legacy | LA-CIN01.001-Cans | 5.23 | 5.23 | | 435.93 | 54.14 | 1 |
| **S852588** | S852588 | Legacy | LA-CIN01.001-Cans | 19.16 | 19.16 | | 326.34 | 197.06 | 1 |
| **S846055** | S846055 | Legacy | LA-CIN01.001-Cans | 5.23 | 5.23 | | 463.49 | 57.76 | 2 |

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| **S843594** | S843594 | Legacy | LA-CIN01.001-Cans | 8.49 | 8.49 | | | 523.25 | 93.76 | 2 |
| **S843593** | S843593 | Legacy | LA-CIN01.001-Cans | 3.06 | 3.06 | | | 450.04 | 33.84 | 2 |
| **S833409** | S833409 | Legacy | LA-CIN01.001-Cans | 6.18 | 6.18 | | | 485.10 | 64.43 | 2 |
| **S823127** | S823127 | Legacy | LA-CIN01.001-Cans | 0.77 | 0.77 | | | 577.71 | 8.47 | 9 |
| **S823016** | S823016 | Legacy | LA-CIN01.001-Cans | 10.45 | 10.45 | | | 407.93 | 114.98 | 2 |
| **S818449** | S818449 | Legacy | LA-CIN01.001-Cans | 2.39 | 2.39 | | | 433.94 | 26.43 | 8 |
| **S818382** | S818382 | Legacy | LA-CIN01.001-Cans | 2.97 | 2.97 | | | 419.83 | 32.76 | 1 |
| **S818255** | S818255 | Legacy | LA-CIN01.001-Cans | 2.22 | 2.22 | | | 388.74 | 24.48 | 18 |
| **S816890** | S816890 | Legacy | LA-CIN01.001-Cans | 0.98 | 0.98 | | | 412.34 | 10.14 | 2 |
| **S816837** | S816837 | Legacy | LA-CIN01.001-Cans | 1.05 | 1.05 | | | 416.75 | 11.58 | 1 |
| **S816768** | S816768 | Legacy | LA-CIN01.001-Cans | | 3.56 | | | 446.95 | 34.96 | 6 |
| **S816692** | S816692 | Legacy | LA-CIN01.001-Cans | 2.85 | 2.85 | | | 403.52 | 30.51 | 0 |
| **S813676** | S813676 | Legacy | LA-CIN01.001-Cans | 1.72 | 1.72 | | | 386.76 | 17.74 | 2 |
| **S811692** | S811692 | Legacy | LA-CIN01.001-Cans | 0.83 | 0.83 | | | 376.83 | 4.24 | 1 |
| **S804989** | S804989 | Legacy | LA-CIN01.001-Cans | 1.05 | 1.05 | | | 409.91 | 11.54 | 3 |
| **S803613** | S803613 | Legacy | LA-CIN01.001-Cans | 0.63 | 0.63 | | | 322.81 | 4.51 | 5 |

**Attachment 2**

Central Characterization Project (CCP)

Acceptable Knowledge Summary Report for Los Alamos National Laboratory TA-55 Mixed Transuranic Waste (CCP–AK-LANL-006), Revision 13, February 10, 2014

Controlled
Copy

**P2010-3583**

**CCP-AK-LANL-006**

# Central Characterization Program
# Acceptable Knowledge Summary Report
# For

# LOS ALAMOS NATIONAL LABORATORY
# TA-55 MIXED TRANSURANIC WASTE

**WASTE STREAMS:**
**LA-MHD01.001**
**LA-CIN01.001**
**LA-MIN02-V.001**
**LA-MIN04-S.001**

**Revision 13**

**February 10, 2014**

Mike Ramirez
Printed Name
**APPROVED FOR USE**

Controlled
Copy



RECORD OF REVISION

| Revision Number | Date Approved | Description of Revision |
|---|---|---|
| 0 | 06/10/2004 | Initial issue. |
| 1 | 07/08/2004 | Sections 2.0 and 5.5 have been modified to identify the TRUPACT-II Content Codes (TRUCONs) that will be confirmed by Real-Time Radiography (RTR) and/or Visual Examination (VE) and to clarify that other TRUCONs may also be suitable for individual containers in this waste stream pending further evaluation on a container basis. |
| 2 | 04/14/2005 | Calculations for payload management have been added to Section 4.3.6. The waste stream description has been modified to clarify the waste does not contain greater than 1% Waste Material Type IV.1. Various editorial corrections have been made throughout the report. |
| 3 | 04/13/2006 | Sections 4.0 through 5.0, Section 9.0, Attachment 2, and Attachment 4 have been modified to distinguish between inactive and active waste generating processes, to identify new active waste generating processes, to expand existing process descriptions, and to include additional chemical and material inputs. These updates were based on site personnel interviews and reviews of acceptable knowledge documents performed during the generation of the detailed Pu-239 Operations process flow diagrams. |
| 4 | 07/31/2006 | Revised to incorporate plutonium (Pu)-238 debris waste stream containers (LA-MHD02.001) from CCP-AK-LANL-007, *Los Alamos National Laboratory Pu-238 Contaminated Mixed Heterogeneous Debris Waste Stream LA-MHD02.001* into waste stream LA-MHD01.001 generated by operations in the Technical Area (TA)-55 Plutonium Facility Building (PF-4). |
| 5 | 11/16/2006 | Revised to implement the Waste Isolation Pilot Plant Hazardous Waste Facility Permit requirements resulting from the Section 311/Remote-Handled (RH) Permit Modification Request (PMR) by including the Waste Material Parameter Assessment for waste stream LA-MHD01.001. |

Controlled
Copy



RECORD OF REVISION (Continued)

| Revision Number | Date Approved | Description of Revision |
|---|---|---|
| 6 | 03/27/2007 | Revised to include new cemented inorganic homogeneous solid waste stream number LA-CIN01.001 generated by the cement fixation process in TA-55 Plutonium Facility Building (PF-4). This new waste stream is explained in detail in Section 6.0. |
| 7 | 11/30/2007 | Revised to include additional containers to waste stream LA-MHD01.001 and to update the affected sections (types and quantities of Transuranic (TRU) waste generated, waste material parameters, estimated radionuclide distributions); to expand descriptions of waste generating processes that produced ash, hydroxide cakes, salts, and contaminated absorbent; to address internal packaging of waste containers; to address repackaging operations; and to incorporate miscellaneous editorial changes. This revision also includes new absorbed liquid homogeneous solid waste stream number LA-MIN02-V.001. This new waste stream is explained in detail in Section 7.0. |
| 8 | 03/12/2008 | Revised to remove originally generated homogeneous containers from waste stream LA-MHD01.001 added during Revision 7; to address a change in packaging for waste stream LA-CIN01.001; to address repackaging and Decontamination and Decommissioning operations; and to incorporate miscellaneous editorial changes. |
| 9 | 01/27/2009 | Revised to include additional containers to waste stream LA-MHD01.001 that were originally characterized as homogeneous by Los Alamos National Laboratory and to update the affected sections (types and quantities of transuranic waste generated, waste material parameters, estimated radionuclide distributions); to properly identify chemicals in Table 9, Chemical Identification and Use Summary, as ignitable, corrosive, and/or reactive in their pure form; and to incorporate miscellaneous editorial changes. This revision also includes new salt homogeneous solid waste stream number LA-MIN04-S.001. This new waste stream is explained in detail in Section 8.0. |

RECORD OF REVISION (Continued)

| Revision Number | Date Approved | Description of Revision |
|---|---|---|
| 10 | 05/04/2010 | Revised to include various changes identified during the 2009 recertification audit; to expand the spent nuclear fuel and high-level waste assessment; to address facility and equipment maintenance operations; to address below-grade retrieval operations; to add below-grade containers to waste streams LA-MHD01.001 and LA-CIN01.001 and to update the affected sections (e.g., types and quantities of Transuranic [TRU] waste generated, estimated radionuclide distributions); to add containers to waste streams LA-MIN02-V.001 and LA-MIN04-S.001 and to update the affected sections (e.g., types and quantities of TRU waste generated, estimated radionuclide distributions); and to include miscellaneous changes to Sections 1.0, 2.0, 3.0, 4.0, 5.0, 7.0, 8.0, 10.0, 11.0, and 12.0. |
| 11 | 09/23/2011 | Revised to incorporate changes required by the Waste Isolation Pilot Plant (WIPP) Permit renewal dated November 30, 2010; to include changes identified during the 2011 recertification audit, to update the Annual Transuranic Waste Inventory Report Identification numbers; to expand the waste stream correlation section; to clarify the waste packaging configurations; and to delete the Supplemental Waste Stream Information section. This revision also includes miscellaneous changes made throughout the report. |
| 12 | 12/12/2012 | Revised to expand/modify Sections 1.0, 2.0, and 3.0; to add TRUCON code SQ133 to waste stream LA-MHD01.001; to expand the waste stream description for LA-MIN02-V.001 and to add TRUCON code LA226; to add new TA-54 repackaging facility description; to add containers to waste streams LA-MHD01.001, LA-CIN01.001, LA-MIN02-V.001, and LA-MIN04-S.001 and to update the affected sections (e.g., types and quantities of TRU waste generated, estimated radionuclide distributions); to expand the ignitability, corrosivity, and reactivity sections; and to clarify the waste packaging configurations. This revision also includes miscellaneous changes made throughout. |

Controlled
Copy



RECORD OF REVISION (Continued)

| Revision Number | Date Approved | Description of Revision |
|---|---|---|
| 13 | 02/10/2014 | Revised to clarify the TRUPACT-II Content Codes and the waste stream descriptions for all four waste streams, to update the waste stream LA-MHD01.001 *Annual Transuranic Waste Inventory Report* numbers, to update the Description of Waste Generating Process section, to update the waste stream LA-MHD01.001 future projected waste generation volume, to discuss the use and characterization of hydrofluoric acid, to incorporate changes identified in the 2013 recertification audit, to incorporate changes identified in the 2013 U.S. Environmental Protection Agency (EPA) Continued Compliance audit, and to incorporate various changes. |

Controlled
Copy



TABLE OF CONTENTS

1.0 EXECUTIVE SUMMARY ..... 16

2.0 WASTE STREAM IDENTIFICATION SUMMARY ..... 18
2.1 Waste Stream LA-MHD01.001 (Heterogeneous Debris) ..... 19
2.2 Waste Stream LA-CIN01.001 (Cemented TRU Waste) ..... 22
2.3 Waste Stream LA-MIN02-V.001 (Absorbed Waste) ..... 24
2.4 Waste Stream LA-MIN04-S.001 (Salt Waste) ..... 26

3.0 ACCEPTABLE KNOWLEDGE DATA AND INFORMATION ..... 28

4.0 REQUIRED PROGRAM INFORMATION ..... 29
4.1 Facility Location ..... 29
4.2 LANL Operational History ..... 29
4.2.1 LANL Site Mission ..... 30
4.2.2 TA-55 PF-4 Mission ..... 30
4.2.3 Defense Waste Assessment ..... 31
4.2.4 Spent Nuclear Fuel and High-Level Waste Assessment ..... 33
4.3 TRU Waste Management ..... 34
4.3.1 TRU Waste Identification and Categorization ..... 34
4.3.2 Historical TRU Waste Management Practices ..... 36
4.3.3 Present-Day TRU Waste Management Practices ..... 37
4.3.4 TRU Waste Generator Documentation Requirements ..... 38
4.3.5 LANL Treatment, Storage and Disposal Facilities for TRU Waste ..... 41
4.3.6 Types and Quantity of TRU Waste Generated ..... 42
4.3.7 Correlation of Waste Streams Generated from the Same Building and Process ..... 42
4.4 Description of Waste Generating Process ..... 46
4.4.1 Overview ..... 46
4.4.2 Nitrate Operations ..... 48
4.4.3 Miscellaneous Operations ..... 51
4.4.4 Special Processing Operations ..... 56
4.4.5 Metal Operations ..... 57
4.4.6 Pyrochemical and Chloride Operations ..... 62
4.4.7 Pu-238 Operations ..... 66
4.4.8 Facility and Equipment Maintenance Operations ..... 73
4.4.9 Decontamination and Decommissioning (D&D) Operations ..... 74
4.4.10 Waste Repackaging and Prohibited Item Disposition ..... 75
4.4.11 Below-Grade Retrieval Project ..... 76
4.5 Waste Certification Procedures ..... 77

5.0 REQUIRED WASTE STREAM INFORMATION: LA-MHD01.001 ..... 78
5.1 Area and Building of Generation ..... 78
5.2 Waste Stream Volume and Period of Generation ..... 78
5.3 Waste Generating Activities ..... 79

5.4 Type of Wastes Generated ....79
5.4.1 Material Input Related to Physical Form ....80
5.4.1.1 Waste Matrix Code .... 81
5.4.1.2 Waste Material Parameters .... 81
5.4.2 Radiological Characterization ....82
5.4.2.1 Pu-238, Pu-239, Pu-240, Pu-241, and Pu-242 .... 82
5.4.2.2 U-233, U-234, U-235, and U-238 .... 83
5.4.2.3 Am-241 .... 84
5.4.2.4 Other Radionuclides Present Due to Decay .... 85
5.4.2.5 Cesium (Cs)-137 and Strontium (Sr)-90 .... 85
5.4.2.6 Other Radionuclides Introduced as Feed Material .... 86
5.4.2.7 Estimated Predominant Isotopes and 95 percent Total Activity. 88
5.4.2.8 Use of Radionuclide Isotopic Ratios .... 88
5.4.3 Chemical Content Identification – Hazardous Constituents ....90
5.4.3.1 Chemical Inputs .... 95
5.4.3.2 F-, K-, P-, and U-Listed Constituents .... 105
5.4.3.3 Toxicity Characteristic Constituents .... 107
5.4.3.4 Ignitables, Corrosives, and Reactives .... 107
5.4.3.5 Polychlorinated Biphenyls (PCBs) .... 109
5.4.4 Prohibited Items ....110
5.4.4.1 Compressed Gases, Liquids, Nonradionuclide Pyrophorics, Sealed Containers >Four Liters In Volume, >1 Percent Radionuclide Pyrophorics, and >200 mrem/hr Waste .... 110
5.4.4.2 Remediation of Prohibited Items .... 111
5.5 Waste Packaging ....112

6.0 REQUIRED WASTE STREAM INFORMATION: LA-CIN01.001 .... 115
6.1 Area and Building of Generation ....115
6.2 Waste Stream Volume and Period of Generation ....115
6.3 Waste Generating Activities ....116
6.4 Type of Wastes Generated ....116
6.4.1 Material Input Related to Physical Form ....116
6.4.1.1 Waste Matrix Code .... 117
6.4.1.2 Waste Material Parameters .... 117
6.4.2 Radiological Characterization ....118
6.4.2.1 Pu-238, Pu-239, Pu-240, Pu-241, and Pu-242 .... 118
6.4.2.2 U-233, U-234, U-235, and U-238 .... 119
6.4.2.3 Am-241 .... 119
6.4.2.4 Other Radionuclides Present Due to Decay .... 120
6.4.2.5 Cs-137 and Sr-90 .... 120
6.4.2.6 Other Radionuclides Introduced as Feed Material .... 120
6.4.2.7 Estimated Predominant Isotopes and 95 percent Total Activity121
6.4.2.8 Use of Radionuclide Isotopic Ratios .... 121
6.4.3 Chemical Content Identification – Hazardous Constituents ....123
6.4.3.1 Chemical Inputs .... 123

6.4.3.2 F-, K-, P-, and U-Listed Constituents ..... 124
6.4.3.3 Toxicity Characteristic Constituents ..... 125
6.4.3.4 Ignitables, Corrosives, and Reactives ..... 125
6.4.3.5 Polychlorinated Biphenyls (PCBs) ..... 126
6.4.3.6 Flammable Volatile Organic Compounds ..... 127
6.4.4 Prohibited Items ..... 127
6.4.4.1 Compressed Gases, Liquids, Nonradionuclide Pyrophorics, Sealed Containers > Four Liters In Volume, >1 Percent Radionuclide Pyrophorics, and >200 mrem/hr Waste ..... 127
6.4.4.2 Remediation Of Prohibited Items ..... 128
6.5 Waste Packaging ..... 128

7.0 REQUIRED WASTE STREAM INFORMATION: LA-MIN02-V.001 ..... 131
7.1 Area and Building of Generation ..... 131
7.2 Waste Stream Volume and Period of Generation ..... 131
7.3 Waste Generating Activities ..... 131
7.4 Type of Wastes Generated ..... 132
7.4.1 Material Input Related to Physical Form ..... 132
7.4.1.1 Waste Matrix Code ..... 133
7.4.1.2 Waste Material Parameters ..... 133
7.4.2 Radiological Characterization ..... 134
7.4.2.1 Pu-238, Pu-239, Pu-240, Pu-241, and Pu-242 ..... 134
7.4.2.2 U-233, U-234, U-235, and U-238 ..... 135
7.4.2.3 Am-241 ..... 135
7.4.2.4 Other Radionuclides Present Due to Decay ..... 136
7.4.2.5 Cs-137 and Sr-90 ..... 136
7.4.2.6 Other Radionuclides Introduced as Feed Material ..... 136
7.4.2.7 Estimated Predominant Isotopes and 95 percent Total Activity 137
7.4.2.8 Use of Radionuclide Isotopic Ratios ..... 137
7.4.3 Chemical Content Identification – Hazardous Constituents ..... 138
7.4.3.1 Chemical Inputs ..... 139
7.4.3.2 F-, K-, P-, and U-Listed Constituents ..... 140
7.4.3.3 Toxicity Characteristic Constituents ..... 141
7.4.3.4 Ignitables, Corrosives, and Reactives ..... 141
7.4.3.5 Polychlorinated Biphenyls (PCBs) ..... 142
7.4.4 Prohibited Items ..... 143
7.4.4.1 Compressed Gases, Liquids, Nonradionuclide Pyrophorics, Sealed Containers > Four Liters In Volume, >1 Percent Radionuclide Pyrophorics, and >200 mrem/hr Waste ..... 143
7.4.4.2 Remediation Of Prohibited Items ..... 143
7.5 Waste Packaging ..... 144

8.0 REQUIRED WASTE STREAM INFORMATION: LA-MIN04-S.001 ..... 146
8.1 Area and Building of Generation ..... 146
8.2 Waste Stream Volume and Period of Generation ..... 146

Controlled
Copy



8.3 Waste Generating Activities ....146
8.4 Type of Wastes Generated ....147
8.4.1 Material Input Related to Physical Form ....147
8.4.1.1 Waste Matrix Code .... 148
8.4.1.2 Waste Material Parameters .... 148
8.4.2 Radiological Characterization ....149
8.4.2.1 Pu-238, Pu-239, Pu-240, Pu-241, and Pu-242 .... 149
8.4.2.2 U-233, U-234, U-235, and U-238 .... 150
8.4.2.3 Am-241 .... 150
8.4.2.4 Other Radionuclides Present Due to Decay .... 151
8.4.2.5 Cs-137 and Sr-90 .... 151
8.4.2.6 Other Radionuclides Introduced as Feed Material .... 151
8.4.2.7 Estimated Predominant Isotopes and 95 percent Total Activity 152
8.4.2.8 Use of Radionuclide Isotopic Ratios .... 152
8.4.3 Chemical Content Identification – Hazardous Constituents ....153
8.4.3.1 Chemical Inputs .... 154
8.4.3.2 F-, K-, P-, and U-Listed Constituents .... 154
8.4.3.3 Toxicity Characteristic Constituents .... 156
8.4.3.4 Ignitables, Corrosives, and Reactives .... 156
8.4.3.5 Polychlorinated Biphenyls (PCBs) .... 157
8.4.4 Prohibited Items ....157
8.4.4.1 Compressed Gases, Liquids, Nonradionuclide Pyrophorics, Sealed Containers Greater Than Four Liters In Volume, >1 Percent Radionuclide Pyrophorics, and >200 mrem/hr Waste 157
8.4.4.2 Remediation of Prohibited Items .... 158
8.5 Waste Packaging ....158

9.0 CONTAINER-SPECIFIC INFORMATION .... 160

10.0 REFERENCES .... 161

11.0 AK SOURCE DOCUMENTS .... 163

LIST OF TABLES

Table 1. LA-MHD01.001 Approximate Waste Stream Volume ..... 79
Table 2. Waste Material Parameter Estimates for LA-MHD01.001 ..... 82
Table 3. Average Isotopic Content of Plutonium Material Types and Enrichments ..... 83
Table 4. Average Isotopic Content of Uranium Material Types and Enrichments ..... 84
Table 5. Secondary Radionuclides in Plutonium Recovery TRU Waste..... 87
Table 6. Estimated Radionuclide Distribution in LA-MHD01.001 ..... 89
Table 7. Waste Stream LA-MHD01.001 Hazardous Waste Characterization Summary ..... 91
Table 8. Feed Materials for TA-55 Operations ..... 92
Table 9. Chemical Identification and Use Summary..... 96
Table 10. LA-CIN01.001 Approximate Waste Stream Volume..... 115
Table 11. Waste Stream LA-CIN01.001 Waste Material Parameter Estimates..... 118
Table 12. Estimated Radionuclide Distribution in LA-CIN01.001 ..... 122
Table 13. Waste Stream LA-CIN01.001 Hazardous Waste Characterization Summary ..... 123
Table 14. LA-MIN02-V.001 Approximate Waste Stream Volume..... 131
Table 15. Waste Stream LA-MIN02-V.001 Waste Material Parameter Estimates..... 134
Table 16. Estimated Radionuclide Distribution in LA-MIN02-V.001 ..... 138
Table 17. Waste Stream LA-MIN02-V.001 Hazardous Waste Characterization Summary..... 139
Table 18. LA-MIN04-S.001 Approximate Waste Stream Volume..... 146
Table 19. Waste Stream LA-MIN04-S.001 Waste Material Parameter Estimates..... 149
Table 20. Estimated Radionuclide Distribution in LA-MIN04-S.001 ..... 153
Table 21. Waste Stream LA-MIN04-S.001 Hazardous Waste Characterization Summary154

LIST OF FIGURES

Figure 1. Location of LANL Site .....177
Figure 2. Location of the PF-4 at TA-55 LANL Site .....178
Figure 3. RSWD Code Descriptions Table .....179
Figure 4. Item Description Codes (IDC) Table .....180
Figure 5. TA-55 Process/Status Code Index Table .....182
Figure 6. Example Generator Container Specific Documentation .....191
Figure 7. Process Flow Diagram for Nitrate Operations (Legacy) .....210
Figure 8. Process Flow Diagram for Nitrate Operations (Newly Generated) .....211
Figure 9. Simplified Process Flow Diagram for Miscellaneous Operations (Legacy) .....212
Figure 10. Simplified Process Flow Diagram for Miscellaneous Operations (Newly Generated) .....213
Figure 11. Simplified Process Flow Diagram for Special Processing (Legacy) .....214
Figure 12. Simplified Process Flow Diagram for Special Operations (Newly Generated) 215
Figure 13. Simplified Process Flow Diagram for Metal Operations (Legacy) .....216
Figure 14. Simplified Process Flow Diagram for Metal Operations (Newly Generated) ...219
Figure 15. Simplified Process Flow Diagram for Pyrochemical Operations (Legacy).....220
Figure 16. Simplified Process Flow Diagram for Chloride Operations (Legacy).....221

Controlled
Copy



LIST OF FIGURES (Continued)

Figure 17. Simplified Process Flow Diagram for Pyrochemical and Chloride Operations (Newly Generated) .....222
Figure 18. Simplified Process Flow Diagram for Pu-238 Operations (Legacy).....223
Figure 19. Simplified Process Flow Diagram for Pu-238 Operations (Newly Generated) 226
Figure 20. Waste Repackaging and Prohibited Item Disposition Flow Diagram.....227
Figure 21. Below-Grade Drum Retrieval Flow Diagram .....228
Figure 22. Below-Grade Crate Retrieval Flow Diagram .....229

LIST OF ACRONYMS AND ABBREVIATIONS

| | |
|---|---|
| AEC | U. S. Atomic Energy Commission |
| AK | Acceptable Knowledge |
| AKIS | Acceptable Knowledge Information Summary |
| ALARA | as low as reasonably achievable |
| ARIES | Advanced Recovery and Integrated Extraction System |
| ATLAS | Advanced Testing Line for Actinide Separations |
| ATWIR | *Annual Transuranic Waste Inventory Report* |
| BDR | Batch Data Report |
| $CaCl_2$ | calcium chloride |
| CBFO | Carlsbad Field Office |
| CCP | Central Characterization Program |
| CFR | Code of Federal Regulations |
| CH | contact-handled |
| CH-TRAMPAC | *Contact-Handled Transuranic Authorized Methods for Payload Control* |
| CMB | corrugated metal box |
| CMPO | octylphenyl di-isobutyl carbamoylmethyl phosphine oxide |
| CMR | Chemistry and Metallurgy Research |
| C–N–O | carbon–nitrogen–oxygen |
| COM | combustible waste |
| CSMO | Central Scrap Management Office |
| CWSR | Certified Waste Storage Record |
| D&D | decontamination and decommissioning |
| DBBP | dibutyl butyl-phosphonate |
| DCHP | dicesium hexachloroplutonate |
| DHDCMP | dihexyl N, N-diethylcarbamoylmethyl phosphonate |
| DL | Discard Limit |
| DOE | U.S. Department of Energy |
| DOR | Direct Oxide Reduction |
| DOT | U.S. Department of Transportation |
| DVRS | Decontamination and Volume Reduction System |
| DWLS | Discardable Waste Log Sheet |
| EPA | U.S. Environmental Protection Agency |
| ER | electrorefining |
| FGE | fissile gram equivalent |
| FOOF | dioxygen difluoride |
| FRP | fiberglass reinforced plywood |
| FVOC | Flammable Volatile Organic Compound |
| GPHS | General Purpose Heat Source |
| HEPA | high-efficiency particulate air |
| HWFP | Hazardous Waste Facility Permit |
| HWN | Hazardous Waste Number |
| ICP | inductively coupled plasma |

LIST OF ACRONYMS AND ABBREVIATIONS (Continued)

| | |
|---|---|
| ID | item identification |
| IDC | item Description Code |
| KCl | potassium chloride |
| LANL | Los Alamos National Laboratory |
| LANS | Los Alamos National Security, LLC |
| LDR | Land Disposal Restrictions |
| LIG | Laboratory Implementation Guidance |
| LIR | Laboratory Implementation Requirements |
| LLW | low-level waste |
| LPR | Laboratory Performance Requirement |
| LWD | Legacy Waste Disposition |
| LWRHU | Light Weight Radioisotope Heater Unit |
| MASS | Material Accountability and Safeguards System |
| MCDOR | Multiple-Cycle Direct Oxide Reduction |
| MEGAS | Multiple Energy Gamma Assay System |
| MET | metal |
| $MgCl_2$ | magnesium chloride |
| MgO | magnesium oxide |
| MIS | Material Identification and Surveillance |
| mm | millimeter |
| mrem/hr | millirem per hour |
| MSE | molten-salt extraction |
| MSDS | material safety data sheets |
| MT | Material Type |
| MWG | MilliWatt Generator |
| NaCl | sodium chloride |
| NASA | National Aeronautics and Space Administration |
| nCi/g | nanocuries per gram |
| NDA | Nondestructive Assay |
| ng/g | nanograms per gram |
| NMT | Nuclear Material Technology |
| NWPA | Nuclear Waste Policy Act |
| PCB | polychlorinated biphenyl |
| PF-4 | Plutonium Facility Building |
| pg/g | picograms per gram |
| PLS | plastic |
| POC | pipe overpack container |
| PPE | personal protective equipment |
| ppm | parts per million |
| P/S | process/status |
| Pu-Be | plutonium-beryllium |
| $PuCl^3$ | plutonium chloride |
| Pu-ICE | Plutonium Isentropic Compression Experiments |

LIST OF ACRONYMS AND ABBREVIATIONS (Continued)

| | |
|---|---|
| QA | Quality Assurance |
| R&D | Research and Development |
| RCRA | Resource Conservation and Recovery Act |
| RH | remote-handled |
| RLWTF | Radioactive Liquid Waste Treatment Facility |
| RSWD | Radioactive Solid Waste Disposal |
| RTG | Radioisotope Thermogenerators |
| RTR | real-time radiography |
| RUB | rubber |
| SME | Subject Matter Expert |
| SNM | special nuclear material |
| SNL | Sandia National Laboratories |
| SOP | standard operating procedure |
| SRF | Size Reduction Facility |
| SRL | Special Recovery Line |
| SRS | Savannah River Site |
| SWB | standard waste box |
| TA | Technical Area |
| TBP | tributyl phosphate |
| TDOP | ten drum overpack |
| TIG | tungsten inert gas |
| TOPO | trioctylphosphine oxide |
| TRU | transuranic |
| TRUCON | TRUPACT-II Content Code |
| TRUPACT-II | Transuranic Waste Transporter-Model II |
| TSCA | Toxic Substances Control Act |
| TSDFs | treatment, storage, and disposal facilities |
| TWCP | TRU Waste Certification Program |
| TWID | TRU Waste Interface Document |
| TWISP | Transuranic Waste Inspectable Storage Project |
| TWSR | TRU Waste Storage Record |
| UC | University of California |
| VE | visual examination |
| VOC | volatile organic compound |
| WAC | Waste Acceptance Criteria |
| WAP | Waste Analysis Plan |
| WCRR | Waste Characterization Reduction and Repackaging |
| WDS | Waste Data System |
| WEF | Waste Acceptance Criteria Exception Form |
| WIPP | Waste Isolation Pilot Plant |
| WIPP-WAC | *Waste Isolation Pilot Plant Waste Acceptance Criteria* |
| WIPP-WAP | *Waste Isolation Pilot Plant Hazardous Waste Facility Permit, Waste Analysis Plan* |

Controlled
Copy



LIST OF ACRONYMS AND ABBREVIATIONS (Continued)

| | |
|---|---|
| WMP | Waste Material Parameter |
| WMS | Waste Management System |
| WODF | Waste Origination and Disposition Form |
| WPF | Waste Profile Form |
| WPRF | Waste Profile Request Form |
| wt % | weight percent |
| WWIS | WIPP Waste Information System |
| XBL | crucibles |
| XES | x-ray energy spectroscopy |

# 1.0 EXECUTIVE SUMMARY

This Acceptable Knowledge (AK) Summary Report has been prepared for the Central Characterization Program (CCP) for contact-handled (CH) transuranic (TRU) waste generated at Technical Area (TA)-55 of the Los Alamos National Laboratory (LANL). This report was prepared in accordance with CCP-TP-005, *CCP Acceptable Knowledge Documentation* (Reference 8), to implement the AK requirements of the *Waste Isolation Pilot Plant Hazardous Waste Facility Permit, Waste Analysis Plan* (WIPP-WAP) (Reference 1) and the DOE/WIPP-02-3122, *Transuranic Waste Acceptance Criteria for the Waste Isolation Pilot Plant* (WIPP-WAC) (Reference 3).

The WIPP-WAP AK requirements are addressed in CCP-PO-001, *CCP Transuranic Waste Characterization Quality Assurance Project Plan* (Reference 7). The WIPP-WAC AK requirements are addressed in CCP-PO-002, *CCP Transuranic Waste Certification Plan* (Reference 16). Additionally, this report provides the AK information required by CCP-PO-003, *CCP Transuranic Authorized Methods for Payload Control (CCP CH-TRAMPAC)* (Reference 14).

The CCP is tasked with certification of CH TRU waste for transportation to and disposal at the Waste Isolation Pilot Plant (WIPP). CCP procedure CCP-TP-005 (Reference 8), describes how AK is compiled and confirmed by the CCP. The CCP is responsible for collection, review, and management of AK documentation in accordance with CCP-TP-005 and reviews and approves this AK Summary Report. CCP maintains responsibility for this AK Summary Report and all CCP-TP-005 generated forms and records as quality assurance (QA) records. In addition, CCP maintains a copy of the “historical source documents” as non-QA records.

This report presents the required characterization information for the mixed heterogeneous debris waste stream LA-MHD01.001, the mixed cement waste stream LA-CIN01.001, the mixed absorbent waste stream LA-MIN02-V.001, and the mixed salt waste stream LA-MIN04-S.001. As described in Section 4.3.7, AK information from the plutonium (Pu)-238 debris from waste stream LA-MHD02.001 previously described in CCP-AK-LANL-007, *Los Alamos National Laboratory Pu-238 Contaminated Mixed Heterogeneous Debris Waste Stream LA-MHD02.001* (Reference 20) has been combined into this report.

This report, along with referenced supporting documents, provides a defensible and auditable record of AK for the designated waste streams. The references and AK sources used to prepare this report are listed in Sections 10.0 and 11.0. The AK sources cited throughout this report are identified by alphanumeric designations correspond to a unique Source Document Tracking Number (i.e., C001, D001, DR001, M001, P001, and U001).

Controlled
Copy



Due to the incorporation of waste stream LA-MHD02.001 containers into waste stream LA-MHD01.001, the AK sources collected for CCP-AK-LANL-007 have been combined with the AK sources collected originally for this report (References 20 and M312). Due to the collection and AK review of the same documents during the original preparation of this report and the CCP-AK-LANL-007 report, the sources identified in the text of this report can be redundant; referencing the same source of information collected for both reports, but assigned a different AK Source Document Tracking Number. However, redundant references from both reports were not included in all cases, if it was determined that the single reference was sufficient to support the applicable AK discussion.

This report includes information relating to the facility's history, configuration, equipment, process operations, and waste management practices. Information contained in this report was obtained from numerous sources, including facility safety basis documentation, database information, historical document archives, generator and storage facility waste records and documents, material safety data sheets (MSDS), and interviews with facility personnel.

This report and supporting references provide the mandatory waste program management and waste stream-specific AK information required by the WIPP-WAP (Reference 1).

Controlled
Copy



## 2.0 WASTE STREAM IDENTIFICATION SUMMARY

**Site Where TRU Waste Was Generated:**

LANL
P.O. Box 1663
Los Alamos, New Mexico 87545

**Facility Where TRU Waste Was Generated:**

TA-55 Plutonium Facility Building 4 (PF-4)

**LANL U.S. Environmental Protection Agency (EPA) Hazardous Waste Generator Identification Number:**

NM0890010515

**Facility Mission:**

The primary mission of LANL has been nuclear weapons research and development (R&D). LANL's current central mission is to enhance global security by ensuring the safety and reliability of the U.S. nuclear stockpile, developing technologies to reduce threats from weapons of mass destruction, and solving problems related to energy, environment, infrastructure, health and national security concerns. This mission supports disciplines that enable LANL to contribute to defense, civilian, and industrial needs, including the research, design, development, and analysis of nuclear weapons components; support to research programs in the national interest; energy and environmental research; and environmental management.

The primary missions of the Plutonium Facility Building (PF-4) have included basic special nuclear material (SNM) research and technology development, processing a variety of plutonium-containing materials, and preparing reactor fuels, heat sources, and other SNM devices.

Since 1978, PF-4 has been located at TA-55. Operations commenced in 1979 for the extraction and recovery of plutonium from residues and scraps generated from operations at various LANL facilities and other U.S. Department of Energy (DOE) sites in the defense complex. The scrap and residues are processed to recover as much plutonium as economically feasible. The recovered plutonium is converted into pure plutonium feedstock. This recovery process, associated maintenance operations, limited manufacture of finished parts from purified plutonium, and plutonium research are the primary sources of TRU-contaminated debris, immobilized or solidified liquids and solids, and salts that comprise the waste in waste streams LA-MHD01.001, LA-CIN01.001, LA-MIN02-V.001, and LA-MIN04-S.001.

**Waste Streams:**

The waste streams delineated in this report and their associated Annual Transuranic Waste Inventory Report (ATWIR) numbers are presented in Sections 2.1, 2.2, 2.3, and 2.4.

2.1 Waste Stream LA-MHD01.001 (Heterogeneous Debris)

| | |
|---|---|
| **Summary Category Group:** | S5000 – Debris Waste |
| **Waste Matrix Code Group:** | Heterogeneous Debris Waste |
| **Waste Matrix Code:** | S5400 |
| **TRUPACT-II Content Code (TRUCON):** | LA125/225* |

*Real-time radiography (RTR) and/or visual examination (VE) will confirm the primary TRUCON code LA125/225; however, TRUCON codes LA115/215, LA116/216, LA117/217, LA118/218, LA119/219, LA122/222, LA123/223, LA154, SQ133/233, and SQ154 may be used pending further evaluation by the Waste Certification Official of container-specific information.

| | |
|---|---|
| **Waste Stream ATWIR Identification Numbers** (Reference 6)**:** | LA-TA-55-19, LA-TA-55-21, LA-TA-55-30, LA-TA-55-43, LA-NCD01, LA-MHD01.001, LA-LAMHD02238 |
| **Layers of Confinement:** | Maximum of six layers** |

**VE has identified one heterogeneous debris container with a total of seven layers of confinement. The configuration included five inner bags and two liner bags. This configuration is non-routine and considered to be an isolated incident (Reference DR007).

**Waste Stream Description:**

Waste stream LA-MHD01.001 consists of mixed heterogeneous debris waste generated in TA-55. The debris waste includes paper, rags, plastic, rubber, wood-based high-efficiency particulate air (HEPA) filters, other plastic-based and cellulose-based items (e.g., personal protective equipment [PPE]), noncombustible items (e.g., metal and glass), and lesser quantities of homogeneous solids (less than 50 percent by volume) contaminated with nuclear materials (e.g., americium oxide). Plastic-based waste includes (but may not be limited to): bottles, dry-box gloves (unleaded neoprene base), gloves including leaded gloves, ion-exchange resins, Plexiglas, polyethylene and

vinyl, polystyrene, polyvinyl chloride plastic, tape, Tygon tubing, and vials. Rubber- and Teflon-based waste includes rubber gloves, Teflon tape, gaskets, and stoppers. Cellulose-based waste includes (but may not be limited to): booties, cardboard, cotton gloves, coveralls, laboratory coats, paper, rags, wood, and similar materials. Noncombustible debris waste includes (but may not be limited to): bottles (e.g., glass and metal), cans (e.g., steel and brass), composite HEPA filters, crucibles, equipment (e.g., furnaces, foundry parts, machine tools and parts), fluorescent bulbs, glass, gloveboxes, glovebox windows, graphite, lead (e.g., shielding), metal pipes, miscellaneous labware, metal (e.g., beryllium), motors, pumps, slag, small tools, and ventilation ductwork. Homogeneous solid waste (less than 50 percent by volume) includes: hydroxide cake/filter materials, salts, and ash residues. Hydroxide cake/filter materials are composed of precipitated materials such as americium cadmium, calcium, chromium, iron, lead, magnesium, mercury, neptunium, plutonium potassium, silver, sodium hydroxide, thorium, and uranium. Salt waste can include varying mixtures of calcium chloride, cesium chloride, lithium chloride, magnesium chloride, potassium chloride, sodium chloride, zinc chloride, residual entrained calcium and zinc metal, and various plutonium and americium compounds. Ash residues originate from the thermal reduction of organic-based waste products that were contaminated with plutonium (e.g., plastics, rubber, wood, cellulosics, and oils) and may include incomplete combustion products such as small pieces of plastic and metal debris items. The waste stream also includes a small fraction liquids (e.g., waste oils and organics) and solids (e.g., nitrate salts) absorbed or mixed with absorbent materials which may include Ascarite II (sodium hydroxide coated silicate), diatomaceous earth (silica and quartz), kitty litter (clay), vermiculite (hydrated magnesium-aluminum-iron silicate), and/or zeolite (aluminosilicate mineral). Finally, some secondary waste generated during remediation/repackaging operations may be added to the waste containers including but not limited to: absorbent (e.g., Waste Lock 770 [sodium polyacrylate]), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., metal, plastic bags, plywood sheathing, rigid liner lids cut into pieces).

On a waste stream basis, the two predominant isotopes by mass for waste stream LA-MHD01.001 are Pu-239 and uranium (U)-238, and over 95 percent of the total activity is from Pu-238, Pu-239, and Pu-241. The radiological characterization information is presented in Section 5.4.2.

The waste stream contains Resource Conservation and Recovery Act (RCRA)-regulated constituents and is assigned the following EPA Hazardous Waste Numbers (HWNs): F001, F002, F005, D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040. This waste stream may also include wastes containing or contaminated with polychlorinated biphenyls (PCBs). Refer to Section 5.4.3 for the waste stream chemical content evaluation.

Prohibited items are known to be present in the waste stream. Procedures allowed containers greater than four liters, sealed with tape, to be used for waste packaging until LANL WIPP-approved procedures were implemented. The presence of containerized (e.g., butane lighter, lighter fluid can, unpunctured aerosol cans, vials) and uncontainerized liquids have also been observed. Lead shielding is often used to increase handling safety, and thick shielding can obscure RTR observations. Additionally, based on interviews with site personnel performing VE and prohibited item disposition repackaging, internal cans (both shielded and unshielded) have been measured for dose rate during repackaging and found to contain waste with radiation levels exceeding 200 millirem per hour (mrem/hr). Waste packages containing prohibited items identified during characterization activities will be segregated then dispositioned appropriately and/or repackaged to remove the items prior to certification and shipment. Refer to Section 5.4.4 for detailed waste stream prohibited items information.

Waste packaging procedures for LANL waste streams have been modified several times since the beginning of recovery operations, and containers in this waste stream include a variety of configurations with up to six layers of confinement. RTR and/or VE will confirm TRUCON code LA125/225. LA125/225 describes the broadest type of materials and bounds all waste packages in this waste stream. However, TRUCON codes LA115/215, LA116/216, LA117/217, LA118/218, LA119/219, LA122/222, LA123/223, LA154, SQ133/233, and SQ154 have been identified as suitable TRUCON codes for individual containers in this waste stream. Refer to Section 5.5 for detailed packaging information.

Waste stream LA-MHD01.001 meets the definition of waste materials that have common physical form, that contain similar hazardous constituents, and that are generated from a single process or activity. This waste stream was generated during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, decontamination and decommissioning (D&D), waste repackaging, and below-grade retrieval operations. Refer to Section 4.3.7 for detailed waste stream delineation information.

Controlled
Copy



## 2.2 Waste Stream LA-CIN01.001 (Cemented TRU Waste)

**Summary Category Group:** S3000 – Homogeneous Solids

**Waste Matrix Code Group:** Solidified Inorganics

**Waste Matrix Code:** S3150

**TRUPACT-II Content Code:** LA126/226*

*RTR will confirm TRUCON code LA126/226; however, TRUCON code LA114/214 may be used pending evaluation by the Waste Certification Official of container-specific information.

**Waste Stream ATWIR Identification Numbers** (Reference 6)**:** LA-TA-55-38, LA-CIN01.001

**Layers of Confinement:** Maximum of six layers

**Waste Stream Description:**

Waste stream LA-CIN01.001 consists primarily of inorganic homogeneous solid waste (cemented TRU waste) generated in TA-55. The waste includes materials encased in Portland or gypsum cement such as aqueous and organic liquids from the six operational areas (e.g. nitrate operations), ash, calcium chloride salts, chloride solutions, evaporator bottoms and salts, filter aid, filter cakes (e.g., hydroxide cake), plutonium/uranium filings and fines, glovebox sweepings, graphite powder, HEPA filter media, leached ash residues, leached particulate solids (e.g., ash, sand, slag, and crucible parts), oxides (e.g., americium, metal, and uranium), miscellaneous oils (e.g., pump oil), silica solids, solvents, spent ion exchange resins, trioctyl phosphineoxide and iodine in kerosene, and uranium solutions. A small fraction of debris waste (less than 50 percent by volume) including plastic packaging, metal packaging, and PPE (e.g., leaded gloves) may also be present. Finally, some secondary waste generated during remediation/repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770 [sodium polyacrylate]), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., metal, plastic bags, plywood sheathing, rigid liner lids cut into pieces).

Controlled
Copy



On a waste stream basis, the two predominant isotopes by mass for waste stream LA-CIN01.001 are Pu-239 and U-238 and over 95 percent of the total activity is from americium (Am)-241, Pu-238, Pu-239, and Pu-241. The radiological characterization information is presented in Section 6.4.2.

The waste stream contains RCRA-regulated constituents and is assigned the following EPA HWNs: F001, F002, F005, D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040. This waste stream does not include wastes containing or contaminated with PCBs. Refer to Section 6.4.3 for the waste stream chemical content evaluation.

Prohibited items are known to be present in the waste stream. The potential for prohibited quantities of liquid due to dewatering is anticipated. In addition, procedures allowed containers greater than four liters, sealed with tape, to be used for waste packaging until WIPP certification procedures were implemented. The presence of containerized (e.g., butane lighter, lighter fluid can, unpunctured aerosol can, vials) and uncontainerized liquids have also been observed in TA-55 waste. Lead shielding is often used to increase handling safety, and thick shielding can obscure RTR observations. Additionally, based on interviews with site personnel performing VE and prohibited item disposition repackaging, internal cans (both shielded and unshielded) have been measured for dose rate during repackaging and found to contain waste with radiation levels exceeding 200 mrem/hr. Waste packages containing prohibited items identified during characterization activities will be segregated then dispositioned appropriately and/or repackaged to remove the items prior to certification and shipment. Refer to Section 6.4.4 for detailed waste stream prohibited items information.

Waste packaging procedures for LANL waste streams have been modified several times since the beginning of recovery operations and containers in this waste stream include a variety of configurations with up to six layers of confinement. RTR will confirm TRUCON code LA126/226. However, TRUCON code LA114/214 has been identified as suitable for individual containers in this waste stream. Refer to Section 6.5 for detailed packaging information.

Waste stream LA-CIN01.001 meets the definition of waste materials that have common physical form, that contain similar hazardous constituents, and that are generated from a single process or activity. This waste stream was generated during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations. Refer to Section 4.3.7 for detailed waste stream delineation information.

## 2.3 Waste Stream LA-MIN02-V.001 (Absorbed Waste)

**Summary Category Group:** S3000 – Homogeneous Solids

**Waste Matrix Code Group:** Solidified Inorganics

**Waste Matrix Code:** S3110

**TRUPACT-II Content Code:** LA112/212*

*RTR will confirm TRUCON code LA112/212; however, TRUCON codes LA126/226, SQ112/212, SQ113/213, and SQ129/229 may be used pending evaluation by the Waste Certification Official of container-specific information.

**Waste Stream ATWIR Identification Number** (Reference 6)**:** LA-MIN02-V.001

**Layers of Confinement:** Maximum of four layers

**Waste Stream Description:**

Waste stream LA-MIN02-V.001 consists primarily of inorganic particulate waste generated in TA-55. The waste is largely comprised of TRU waste such as liquids and solids absorbed or mixed with absorbent (e.g., Ascarite II, [sodium hydroxide coated silicate], diatomaceous earth [silica and quartz], kitty litter [clay], vermiculite [hydrated magnesium-aluminum-iron silicate], and/or zeolite [aluminosilicate mineral]). Examples of absorbed liquids include acids (e.g., hydrochloric acid, hydrofluoric acid, and nitric acid); carbon tetrachloride; ethylene glycol; kerosene; methanol; methylene chloride; silicone based liquids (e.g., silicone oil); tetrachloroethylene; tributyl phosphate; trichloroethylene; and various types of oils including hydraulic, vacuum pump, grinding, and lapping (mixture of mineral oil and lard). Solids mixed with absorbents are typically evaporator salts (i.e., nitrate salts). The waste is also expected to contain heavy metals such as cadmium, chromium, and lead. Liquids and solids not absorbed or mixed with absorbent are often cemented and disposed of separately in waste stream LA-CIN01.001. A small fraction of debris waste (less than 50 percent by volume) including plastic packaging, metal packaging, lead (e.g., shielding), PPE, and metal fines may also be present. Finally, some secondary waste generated during remediation/repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770 [sodium polyacrylate]), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., metal, plastic bags, plywood sheathing, rigid liner lids cut into pieces).

On a waste stream basis, the two predominant isotopes by mass for waste stream LA-MIN02-V.001 are Pu-239 and U-238 while over 95 percent of the total activity is from Pu-239, Pu-240, and Pu-241. The radiological characterization information is presented in Section 7.4.2.

The waste stream contains RCRA-regulated constituents and is assigned the following EPA HWNs: F001, F002, F005, D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040. This waste stream does not include wastes containing or contaminated with PCBs. Refer to Section 7.4.3 for the waste stream chemical content evaluation.

Based on the review of container documentation and documented waste management practices, no prohibited items are specifically identified in the waste stream. However, the presence of prohibited quantities of liquid due to dewatering or incomplete absorption is possible. In addition, procedures also allowed containers greater than four liters, sealed with tape, to be used for waste packaging until LANL WIPP-approved procedures were implemented. The presence of containerized (e.g., butane lighter, lighter fluid can, unpunctured aerosol cans, vials) and uncontainerized liquids have also been observed in TA-55 waste. Lead shielding is often used to increase handling safety, and thick shielding can obscure RTR observations. Additionally, based on interviews with site personnel performing VE and prohibited item disposition repackaging, internal cans (both shielded and unshielded) have been measured for dose rate during repackaging and found to contain waste with radiation levels exceeding 200 mrem/hr. Waste packages containing prohibited items identified during characterization activities will be segregated then dispositioned appropriately and/or repackaged to remove the items prior to certification and shipment. Refer to Section 7.4.4 for detailed waste stream prohibited items information.

Waste packaging procedures for LANL waste streams have been modified several times since the beginning of recovery operations and containers in this waste stream include a variety of configurations with up to four layers of confinement. RTR will confirm TRUCON code LA112/212. However, TRUCON codes LA126/226, SQ112/212, SQ113/213, and SQ129/229 have been identified as suitable for individual containers in this waste stream. Refer to Section 7.5 for detailed packaging information.

Waste stream LA-MIN02-V.001 meets the definition of waste materials that have common physical form, that contain similar hazardous constituents, and that are generated from a single process or activity. This waste stream was generated during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations. Refer to Section 4.3.7 for detailed waste stream delineation information.

## 2.4 Waste Stream LA-MIN04-S.001 (Salt Waste)

| | |
|---|---|
| **Summary Category Group:** | S3000 – Homogeneous Solids |
| **Waste Matrix Code Group:** | Salt Waste |
| **Waste Matrix Code:** | S3140 |
| **TRUPACT-II Content Code:** | LA124/224 |
| **Waste Stream ATWIR Identification Number** (Reference 6)**:** | LA-MIN04-S.001 |
| **Layers of Confinement:** | Maximum of Four Layers |

**Waste Stream Description:**

Waste stream LA-MIN04-S.001 consists primarily of inorganic homogeneous solid waste (salt waste) generated in TA-55. The waste is largely comprised of salts which are a byproduct from a variety of plutonium metal purification operations including electrorefining, molten salt extraction, salt stripping, fluoride reduction, and direct oxide reduction. Salts serve as a transportation vehicle for plutonium ions and provide a trap for impurities that are driven or extracted out during the purification process. Salt waste can include varying mixtures of calcium chloride, cesium chloride, lithium chloride, magnesium chloride, potassium chloride, sodium chloride, zinc chloride, residual entrained calcium and zinc metal, and various plutonium and americium compounds. The waste may also be contaminated with solvent metals and reagent materials such as barium, bismuth, cadmium, calcium carbonate, gallium, lead, molybdenum, niobium, tantalum, titanium, tungsten, vanadium, yttrium (Y), and zirconium. Salts can be cemented and disposed of separately in waste stream LA-CIN01.001. A small fraction of debris waste (less than 50 percent by volume) including plastic packaging, metal packaging, PPE, and magnesium oxide (MgO) crucible pieces may also be present. Finally, some secondary waste generated during remediation/repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770 [sodium polyacrylate]), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., metal, plastic bags, plywood sheathing, rigid liner lids cut into pieces).

On a waste stream basis, the two predominant isotopes by mass for waste stream LA-MIN04-S.001 are Pu-239 and U-238 while over 95 percent of the total activity is from Pu-239, Pu-240, and Pu-241. The radiological characterization information is presented in Section 8.4.2.

Controlled
Copy



The waste stream contains RCRA-regulated constituents and is assigned the following EPA HWNs: F001, F002, F005, D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040. This waste stream does not include wastes containing or contaminated with PCBs. Refer to Section 8.4.3 for the waste stream chemical content evaluation.

Based on the review of container documentation and documented waste management practices, no prohibited items are specifically identified in the waste stream. However, procedures allowed containers greater than four liters, sealed with tape, to be used for waste packaging until LANL WIPP-approved procedures were implemented. The presence of containerized (e.g., butane lighter, lighter fluid can, unpunctured aerosol cans, vials) and uncontainerized liquids have also been observed in TA-55 waste. Lead shielding is often used to increase handling safety, and thick shielding can obscure RTR observations. Additionally, based on interviews with site personnel performing VE and prohibited item disposition repackaging, internal cans (both shielded and unshielded) have been measured for dose rate during repackaging and found to contain waste with radiation levels exceeding 200 mrem/hr. Waste packages containing prohibited items identified during characterization activities will be segregated then dispositioned appropriately and/or repackaged to remove the items prior to certification and shipment. Refer to Section 8.4.4 for detailed waste stream prohibited items information.

Waste packaging procedures for LANL waste streams have been modified several times since the beginning of recovery operations and containers in this waste stream include a variety of configurations with up to four layers of confinement. RTR will confirm TRUCON code LA124/224. Refer to Section 8.5 for detailed packaging information.

Waste stream LA-MIN04-S.001 meets the definition of waste materials that have common physical form, that contain similar hazardous constituents, and that are generated from a single process or activity. This waste stream was generated during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations. Refer to Section 4.3.7 for detailed waste stream delineation information.

Controlled
Copy



# 3.0 ACCEPTABLE KNOWLEDGE DATA AND INFORMATION

TRU waste destined for disposal at the WIPP must be characterized prior to shipment. The WIPP-WAP (Reference 1) permits use of knowledge of the materials and processes that generate and control the waste, and a clear and convincing argument about the characteristics of the waste is provided. The AK characterization documented herein complies with the requirements of the WIPP-WAP and was developed in accordance with CCP-PO-001 (Reference 7), and CCP-TP-005 (Reference 8).

The references and AK sources used to prepare this report are listed in Section 10.0 and 11.0, respectively. The AK sources referenced within this report by alphanumeric designations (e.g., C001, D001, DR001, M001, P001, and U001) correspond to the Source Document Tracking Number using the following convention:

- C – Correspondence
- D – Documents
- DR – Discrepancy Resolution
- M – Miscellaneous
- P – Procedures
- U – Unpublished

# 4.0 REQUIRED PROGRAM INFORMATION

This section presents the waste management program information required by the WIPP-WAP (Reference 1). Included is a brief operational history of this facility, summaries of the missions, discussions of waste generating operations, and descriptions of the site's waste management program as it relates to these waste streams. Attachment 1 of CCP-TP-005 (Reference 8) provides a list of TRU waste management program information required to be developed as part of the AK record.

## 4.1 Facility Location

LANL is located in Los Alamos County in north-central New Mexico, approximately 60 miles north-northeast of Albuquerque and 25 miles northwest of Santa Fe. LANL has been owned and operated by the DOE and its predecessor for over 50 years. The LANL site encompasses 43 square miles subdivided into 49 TAs. Figure 1, Location of LANL Site, shows the location of LANL and the TAs. As illustrated by Figure 2, Location of the PF-4 at TA-55 LANL Site, PF-4 is located in TA-55 (References D025 and D084).

## 4.2 LANL Operational History

In 1942, the U.S. Army Manhattan Engineering District established Project Y to develop the atomic bomb. The research quickly progressed to a point that required a remote site for experimental work, and the Army selected the Los Alamos Ranch School for Boys as an appropriate location. The Undersecretary of War directed acquisition of the school site, which consisted of a group of approximately 50 log buildings on a 790-acre site northwest of Santa Fe. The project ultimately acquired an additional 3,120 privately-owned acres and 45,666 acres of public land managed by the U.S. Forest Service. In 1943, this land became known as the Los Alamos Site, later as the Los Alamos Scientific Laboratory. It is now named the Los Alamos National Laboratory. Since its inception, the University of California (UC) has operated LANL for the federal government. With the end of World War II and the growth of international competition, a national policy of maintaining superiority in the field of atomic energy was established. Congress chose to sustain the Los Alamos site; the U. S. Atomic Energy Commission (AEC) received control of LANL from the Army and renewed the operating contract with UC. During subsequent years, LANL continued to expand at a steady rate, first under the AEC and later under the Energy Research and Development Administration. Since 1978, LANL has operated under the control of the DOE.
In 2006, a consortium of Bechtel, UC, BWX Technologies, and URS Energy and Construction (URS acquired Washington Group International in 2007) formed Los Alamos National Security, LLC (LANS) to operate LANL (References D041, D071, D082, and D083).

### 4.2.1 LANL Site Mission

Since its inception, the primary mission of LANL has been nuclear weapons R&D. LANL's current mission supports disciplines that enable LANL to contribute to defense, civilian, and industrial needs. Included in this mission are the research, design, development, and analysis of nuclear weapons components; support for research programs in the national interest; energy and environmental research; and environmental management. In achieving mission objectives, LANL used, and continues to use, hazardous and radioactive materials. Solid waste containing TRU contamination has been, and continues to be, generated as a result of plutonium R&D, processing and recovery operations, facility and equipment maintenance, and D&D projects (References D071, D082, and D083).

### 4.2.2 TA-55 PF-4 Mission

Since the beginning of its operations in 1979, the primary missions of the PF-4 were basic SNM research and technology development; processing a variety of plutonium-containing materials; and preparing reactor fuels, heat sources, and other SNM devices. Research and technology development at the PF-4 includes collaborations with other LANL facilities and DOE sites (e.g., Sandia National Laboratories [SNL]). The PF-4 has been used for the extraction and recovery of plutonium from waste, residues, site return, and scrap generated from operations at various LANL facilities and other DOE sites in the defense complex. These materials are processed to recover as much plutonium as economically feasible. The recovered plutonium is converted into pure plutonium feedstock to be returned to weapons production or related operations. The plutonium recovery process handles primarily Pu-239 and Pu-242 based samples. These are categorized based upon isotopic make-up into various Material Types (MTs). The associated research operations involve other plutonium isotopes, different uranium isotopes, and minor amounts of several other radioisotopes (References C238, D025, D045, D071, D092, M019, M215, M216, M217, M218, M219, and M222).

In addition to weapons production, Pu-238 heat sources have been manufactured at LANL by the Actinide Ceramics and Fabrication Group in PF-4. The operations associated with heat source manufacturing, metallography, Pu-238 recovery, and scrap processing have been conducted in the 200 Wing (Rooms 201, 204, 205, 206, and 207) of PF-4. As described in Section 4.4.7, the following Pu-238 heat source programs have been conducted in PF-4 since 1979 (References C192, C194, C197, C212, C220, and D071):

- Defense Programs MilliWatt Generator (MWG): Between 1979 and 1990, the Savannah River Site (SRS) produced the Pu-238 feed material to manufacture MWG heat sources to provide electrical power for defense nuclear weapons and defense satellite programs.

- National Aeronautics and Space Administration (NASA) Space Missions: Between 1979 and 1990, some of the Pu-238 was used for NASA space missions, including the 1984-1985 Galileo space mission.

- War Reserve Quality Heat Sources and Defense Program Radioisotope Thermogenerators (RTGs): From 1981 to 1990, LANL manufactured 3,000 War Reserve Quality Heat Sources under the Defense Program MWG Heat Source Program. These heat sources were transferred to the General Electric Neutron Devices Facility to be incorporated into Defense Program RTGs.

- NASA General Purpose Heat Source (GPHS) and Light Weight Radioisotope Heater Unit (LWRHU) Programs: From 1992 to 2002, a portion of the Pu-238 used in NASA's GPHS and LWRHU for the Cassini space mission was recycled from Defense Program Pu-238 and from the MWG Heat Source Program.

- Defense Program MWG Heat Source Recycling: Recycling, recovery, and reprocessing of Pu-238 from Defense Program MWG heat sources for use in both Defense Program and NASA missions have continued intermittently through 2002 and were expanded in 2003. Approximately 200 sources a year were recycled to meet projected production schedule requirements for both national security and NASA programs. This process is currently inactive.

These TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations are the sources of these waste streams. Although TA-55 is comprised of several support buildings, waste streams LA-MHD01.001, LA-CIN01.001, LA-MIN02-V.001, and LA-MIN04-S.001 are limited to waste originally generated in PF-4 at TA-55.

### 4.2.3 Defense Waste Assessment

DOE/WIPP-02-3122 (Reference 3) requires generator sites to use AK to determine if the TRU waste streams to be disposed at WIPP meet the definition of TRU defense waste. Based on guidance from DOE, TRU waste is eligible for disposal at WIPP if it has been generated in whole or part by one of the atomic energy defense activities listed in Section 10101(3) of the *Nuclear Waste Policy Act of 1982* (NWPA) (Reference 19).

Waste streams LA-MHD01.001, LA-CIN01.001, LA-MIN02-V.001, and LA-MIN04-S.001 were generated by or originated from materials used in the process to recover plutonium from residues, metal fabrication, and R&D in support of weapons development. These plutonium processing operations include:

Controlled
Copy



- Preparing ultra-pure plutonium metals, alloys, and compounds
- Preparing (on a large scale) specific alloys, including casting and machining these materials into specific shapes
- Determining high-temperature thermodynamic properties of plutonium
- Reclaiming plutonium from scrap and residues produced by numerous feed sources
- Disassembling components for inspection and analysis
- Manufacturing of parts on a limited basis
- Processing plutonium oxide, uranium oxide, americium oxide and mixtures of plutonium and uranium oxides for reactor fuels

The operations generating wastes in LA-MHD01.001, LA-CIN01.001, LA-MIN02-V.001, and LA-MIN04-S.001 are described in detail in Section 4.4 of this report. Although some non-defense program related projects were performed in PF-4, most of the operations generating these waste streams are consistent with the WIPP-WAC defense description. Waste from non-defense program operations were commingled in the final waste containers to such an extent that segregation is not possible. It should be noted that a defense determination has previously been accepted for waste originating from these PF-4 weapons operations (References C040, C057, C067, C082, and D041).

TRU waste contained in these waste streams were also contaminated by the programs associated with the manufacturing of Pu-238 heat sources described in Section 4.4.7. The original source of plutonium for all LANL Pu-238 operations was the defense production K Reactor at the SRS. From 1979 to 1980, Pu-238 was generated by two production campaigns involving the irradiation of neptunium targets. The neptunium was a defense by-product from the production of Pu-238 for weapons. Pu-238 of such domestic origin is considered “defense born” from waste management activities associated with by-product materials from “atomic energy defense activities” (References C192 and C212).

As described in Section 4.4.7, both defense and non-defense programs were conducted in PF-4. Processing and manufacturing of heat sources for defense and non-defense applications use identical processing steps and common equipment and glovebox lines. Processing can occur simultaneously within the same line of gloveboxes and TRU waste is generated throughout the process and manufacturing steps. The wastes from defense and non-defense Pu-238 programs are not segregated; the wastes from these campaigns are packaged in the same waste containers. The resulting process wastes are commingled and managed as defense TRU waste generated in whole or part by

atomic energy defense activities. It has also been determined that future segregation of defense from non-defense waste by Pu-238 operations at LANL is not feasible, due to the fact that these projects are performed in the same lines. Additionally, since the source of Pu-238 feed for these programs includes recycled Pu-238 materials, the resulting wastes will be commingled with contamination originating from defense activities (References C190, C192, C204, C212, and M308).

In May of 2004, the DOE Carlsbad Field Office (CBFO) determined that the LANL Pu-238 wastes originally generated at PF-4 in TA-55 are generated in whole or in part by atomic energy defense activities and therefore are defense wastes that can be disposed of at the WIPP if all of the other requirements applicable to TRU waste to be placed in the repository are met (Reference C212).

Based on a review of the AK, waste containers in LA-MHD01.001, LA-CIN01.001, LA-MIN02-V.001, and LA-MIN04-S.001 meet the WIPP-WAC (Reference 3) definition of TRU defense waste and can be categorized as items D, E, and G of the activities listed in Section 10101(3) of the NWPA (Reference 19), and detailed in the *Interim Guidance on Ensuring that Waste Qualifies for Disposal at the Waste Isolation Pilot Plant* (Reference 4):

- Defense nuclear waste and materials by-products management
- Defense nuclear materials production
- Defense research and development

#### 4.2.4 Spent Nuclear Fuel and High-Level Waste Assessment

Public Law 102-579, *The Waste Isolation Pilot Plant Land Withdrawal Act* (Reference 5) prohibits the disposal of spent nuclear fuel and high-level waste as defined by the NWPA (Reference 19) at WIPP. According to the NWPA, spent nuclear fuel is “fuel that has been withdrawn from a nuclear reactor following irradiation, the constituent elements of which have not been separated by reprocessing.” The *DOE Radioactive Waste Management Manual* (Reference 11) expands on this definition to clarify that “Test specimens of fissionable material irradiated for research and development only, and not production of power or plutonium, may be classified as waste, and managed in accordance with the requirements of this Order when it is technically infeasible, cost prohibitive, or would increase worker exposure to separate the remaining test specimens from other contaminated material.” High-level waste is defined by the NWPA as “the highly radioactive material resulting from the reprocessing of spent nuclear fuel, including liquid waste produced directly in reprocessing and any solid material derived from such liquid waste that contains fission products in sufficient concentrations, and other highly radioactive material that the Commission, consistent with existing law, determines by rule requires permanent isolation.” These waste streams consist of waste contaminated with radioactive material from TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations. These operations did not

involve separation or reprocessing of constituent elements from reactor fuel. These waste streams do not contain irradiated fuel elements withdrawn from a reactor or pieces thereof. Therefore, the wastes are not a spent nuclear fuel, not high-level waste, not historically managed as high-level waste, and are eligible for disposal at WIPP as TRU waste (References 5, 19, D023, M014, M015, P094, and P118).

## 4.3 TRU Waste Management

The LANL waste management goal is that all waste generated is stored, transported, treated, and disposed of in a manner that protects the environment, workers, and the public. The overall requirements for managing waste are summarized in the Laboratory Performance Requirement (LPR) document, *Environmental Protection* (Reference D059). Currently, LANL TRU Programs and waste management personnel are responsible for establishing waste management programs that are consistent with applicable DOE orders and state and federal regulations. The State of New Mexico issued LANL's current Hazardous Waste Facility Permit (HWFP) to the DOE and LANS in November 2010 (References D003, D025, and D041).

TRU mixed and non-mixed waste is generated at LANL primarily from R&D, processing and recovery operations, and D&D projects. On April 22, 2003, weapons fabrication and manufacturing operations at LANL were re-established with the successful production of the first nuclear weapons pit in 14 years in the DOE complex that meets specifications for use in the U.S. stockpile (References D013, D025, D041, and M006).

The following sections discuss TRU waste identification systems used at LANL; historical and present-day TRU waste management practices; and LANL treatment, storage, and disposal facilities (TSDFs) for TRU mixed waste.

### 4.3.1 TRU Waste Identification and Categorization

Several waste identification and categorization conventions have been used as part of waste management operations for TRU mixed waste generated at LANL. The waste identification system used for a particular waste container depends largely upon the date of placement into storage. Specific waste identification conventions at LANL include the assignment of Radioactive Solid Waste Disposal (RSWD) Codes, Item Description Codes (IDCs), Nuclear MT, Process/Status (P/S) Codes, SNM Matrix Codes, and TRUCON Codes to containers of TRU waste. When applicable, these waste identification conventions were used to assist the original waste stream delineations (References 9, D083, and D084).

<u>RSWD Codes</u>

RSWD Codes were first used at LANL in January 1971 and were discontinued in 1992. The RSWD Codes are a two-digit code preceded by the letter "A". The RSWD Codes were used at LANL to categorize TRU waste forms generated by the various on-site

facilities. The RSWD Codes associated with waste in these waste streams are defined in Figure 3, RSWD Code Descriptions Table (References D025, D041, D083, and M296).

IDCs

IDCs were first used at LANL in July 1984 and discontinued in 1992. The IDCs generally consist of a three-digit number representing the most general descriptions of TRU waste. The IDCs associated with waste in these waste streams are listed in Figure 4, Item Description Codes (IDC) Table (References D025, D041, D083, and M296).

TRUCON Codes

TRUCON codes were first used at LANL in October 1992, and are presently in use. The system of TRUCON codes was developed by the DOE to provide a consistent waste description for TRU waste generated throughout all of DOE's facilities. The TRUCON codes are intended to assist DOE in establishing the characteristics of TRU waste to be certified for transportation to the WIPP. LANL TRUCON codes consist of a three-digit number preceded by the letters "LA" and followed by a single character suffix that further defines the waste type, source, and/or packaging configuration. Detailed definitions of the LANL TRUCON codes are found in the TRUCON codes (References 9, D025, D041, D083, and D084).

LANL identification systems used for tracking SNM provide additional information about the physical form and chemical content of TRU waste. SNM tracking systems include the use of P/S Codes, SNM Matrix Codes, and MT Codes (References D025 and D041).

P/S Codes

Individual plutonium processing operations at the LANL PF-4 are assigned a unique identifier called a P/S Code. These codes are used for the purpose of nuclear material accounting. A consolidated listing of the P/S Codes is provided in Figure 5, TA-55 Process/Status Code Index Table (References D025, D041, D083, and M298).

Waste items are labeled with a unique Item Identification (ID) Code that contains information on the waste material parameter of the item (the SNM Matrix Code) and an embedded P/S Code that corresponds to nuclear materials accountability for the operation that produced the waste item. The P/S Code refers to a specific part of an operation within the overall plutonium-recovery process, but generally applies to more than one glovebox, or to the same operation carried out in multiple locations or gloveboxes in the PF-4. Recording the P/S Codes on disposal documents was inconsistent until about 1995 (References D025, D041, D083, D084, M019, M215, M216, M217, M218, M219, M222, M224, M226, M236, M296, and P036).

Starting in 1987, PF-4 began its current system of tracking waste items by their nuclear material content, using the computerized Material Accountability and Safeguards System (MASS). The MASS and associated P/S Codes were developed and are used strictly to track accountable nuclear material throughout the plutonium-recovery process. However, the P/S Codes provide the finest level of detail available to associate waste items with a specific operation of origin. Therefore, the P/S Code System is used extensively in the description and documentation of AK information for RCRA and for chemical constituents for the plutonium-processing derived waste. While a P/S Code can be associated with most waste items generated after 1987 and all items generated after 1995, the P/S Code does not provide a method of segregating waste or delineating waste streams. TRU waste items are packaged into drums based on the isotopic material content of the waste and Nondestructive Assay (NDA) characteristics without regard to process of origin (References C187, D025, D041, D083, and D084).

Matrix Codes for SNM

For the purposes of SNM tracking, individual waste items generated at the PF-4 are assigned a SNM matrix type that provides a description of the waste physical form. Discard Limits (DLs) for plutonium in the various types of waste matrices are established by the waste-generating group, and approved by the LANL division office and the DOE Albuquerque Operations Office (References C187, D025, D041, D083, and D084).

MTs

In addition to the IDC, TRUCON, and RSWD Codes, which provide information about the physical form, matrix, and chemical nature of waste, LANL employs MT designations to describe the relative isotopic composition of radioactive contamination. The designated MT is used to describe the isotopic composition of common blends of radioactive materials used within the DOE complex. The most common MTs present in LANL TRU waste are weapons-grade plutonium (MT-51 and -52); fuel grade (MT-53 and -54); reactor-grade plutonium (MT-55 through -57); enriched Pu-242 (MT-42); and heat-source plutonium (MT-83). The radionuclide and MT content of LANL TRU waste is discussed in Sections 5.4.2, 6.4.2, and 7.4.2 (References D025, D041, and D083).

### 4.3.2 Historical TRU Waste Management Practices

In 1970, the AEC, a predecessor of the DOE, directed its facilities to begin storing TRU waste in such a way that it could eventually be retrieved for shipment to WIPP. LANL then began segregating TRU waste from other wastes and dedicating specific areas within Area G at TA-54 for management (References D025, D041, D083, and D084).

Historically (i.e., the period 1970 to 1987, prior to the implementation of the LANL TRU waste certification plan) wastes from all TRU waste-generating activities at LANL were handled and packaged according to the Los Alamos Scientific Laboratory Health, Safety and Environment Manual. Waste management practices for radioactive waste initially followed AEC requirements (U.S. Atomic Energy Commission AEC Manual: Chapter 0511, *Radioactive Waste Management* [AEC 1973]) (Reference 10) and later, DOE Orders 5820.1, *Management of Transuranic Contaminated Materials* and 5820.2A, *Radioactive Waste Management* (DOE, 09/30/82 and 02/06/84, respectively) (Reference 12). Detailed waste handling and management requirements were documented in division and group-level operating procedures (References D025, D041, D083, and D084).

In 1984, the *Los Alamos TRU Waste Certification Plan for Newly Generated TRU Waste* (Reference D037) was prepared for implementation with LANL newly generated TRU waste. Each LANL waste generator was required to develop an attachment to this plan to define the details of the waste certification functions and controls that applied to their specific operations and waste streams (References D025, D041, D083, and D084).

Originally located at TA-21, PF-4 was relocated to the present-day site at TA-55 in 1978, where operations commenced in 1979. Waste management at PF-4 was focused on minimizing the amount of waste generated and minimizing the plutonium content of that waste (References P102 and P188). Personnel were requested to sort potentially recyclable TRU waste items (i.e., those containing recoverable amounts of plutonium) into classes such as rubber, plastics, rags, non-plutonium metals, glass, oils, cans, sweepings, etc. These waste items were assayed, and based on the plutonium level relative to the DL, material was either sent to recovery operations or to “20-year” retrievable storage. Liquids were explicitly prohibited from any container of solid waste materials (References D025, D041, D083, D084, P102, and P188).

TRU waste generators were required to complete the RSWD form. The RSWD form included the waste IDs listed in Figure 3. An example of the RSWD form is included in Figure 6, Example Generator Container Specific Documentation. The physical description of each waste item generated at PF-4 was documented on a Discardable Waste Log Sheet, also shown in Figure 6 (References D025, D041, D083, and D084).

### 4.3.3 Present-Day TRU Waste Management Practices

Currently, LANL radioactive waste management practices follow DOE Order 435.1, *Radioactive Waste Management* (Reference 11). LANL waste management requirements applicable to TRU mixed and non-mixed waste are addressed in three Laboratory Implementation Requirements (LIRs) as follows (References D025, D041, D083, and D084):

- General Waste Management Requirements (References M014 and M300)
- Hazardous and Mixed Waste Requirements (References M016 and M301)

Controlled
Copy



- Managing Radioactive Waste (References M015 and M302)

The LANL waste analysis plan for storage of transuranic mixed waste is contained in Attachment A.2 to the LANL Hazardous Waste Permit (Reference D004).

#### 4.3.4 TRU Waste Generator Documentation Requirements

TRU waste generators at LANL are required to complete forms that document the physical, chemical, and hazardous nature of waste and provide substantial AK information. Some of these forms are specific to the Chemistry and Metallurgy Research (CMR) and Plutonium Facilities, which generate the majority of LANL's TRU waste. LANL has used a Waste Profile Form (WPF) system since May 1991. Waste generators must complete a WPF for waste-stream specific information. This form documents the process that generated the waste, the location of waste generation, the physical form of the waste, the RCRA-regulated constituents present, and the radionuclides present. Guidance to generators for completion of the WPF is given in the Laboratory Implementation Guidance (LIG) document LIG 404-00-03.1, *Waste Profile Form Guidance* (References D025, D041, M012, and M303).

Generators must provide new WPFs when a process change results in a change in waste composition or when a new waste is generated. For routinely generated waste (i.e., routine operations waste), the WPF must be re-evaluated annually to ensure the information is current and correct. The WPF includes the Land Disposal Restrictions (LDR) notification, which further documents the RCRA-regulated nature of waste. Specific information that is requested on the WPF includes (References D025, D041, D083, and D084):

- Point of generation
- Method of characterization
- Waste categories and descriptions
- Presence of toxic metals and an estimate of concentration
- Presence of organic compounds and an estimate of concentration
- Identification of RCRA-listed hazardous constituents
- Identification of RCRA hazardous characteristics (i.e., ignitability, corrosivity, reactivity, toxicity)
- Identification of the radiological characteristics of the waste

The information on the WPF must be certified as complete and accurate, as evidenced by the signature of the waste generator. The annual re-evaluation complies with the characterization frequency requirement of 20 New Mexico Administrative Code 4.1, Subpart V, 264.13(b)(4), revised November 1, 1995 (References D025 and D041). Waste generation information for individual TRU waste containers is required to be documented on the TRU Waste Storage Record (TWSR). The TWSR is reviewed and approved in accordance with AP-SWO-006, *Review and Completion of the TWSR* (Reference D058) and is not approved unless the waste is associated with a valid, active WPF. The TWSR documents the type of packaging, generating organization, radionuclide and hazardous material content of the waste, dose rates, TRUCON code, and storage site information (e.g., building number, location, date of receipt). Guidance to generators for completion of the TWSR is provided in LIG document LIG404-00-01.2, *Waste Generator Guidance for Completing the TRU Waste Storage Record* (TWSR) (References D025, D041, D083, D084, M013, M296, and M304).

The TWSR form for PF-4 waste is completed in the Nuclear Materials Technology (NMT) Division Waste Management System (WMS) database and reviewed electronically. The TWSR is reviewed and approved in accordance with AP-SWO-006, *Review and Completion of the TWSR* (Reference D058), and is not approved unless the waste is associated with a valid, active WPF. Examples for Waste Acceptance Criteria (WAC) exceptions include tritium-contaminated waste and waste packaged in nonstandard waste containers. The Waste Acceptance Criteria Exception Form (WEF) is reviewed according to AP-SWO-015, *Processing Waste Acceptance Criteria Exception Forms* (References D025, D041, and D057).

The physical description of each waste item generated is documented on a Waste Origination and Disposition Form (WODF) by the waste generator according to controlled procedures (References P090, page 24; P091, Appendix 1; and P095, Appendix B in *Inspecting, Packaging, Rejecting, and Remediating Transuranic Waste for WIPP and for TA-54 Safe Storage* ). Items are bagged out of gloveboxes and sent to the Waste Management section, where multiple items are placed into drums (References D025 and D041).

Waste items are labeled with an ID code that contains information on the waste material parameter (WMP) of the item and an embedded P/S Code that corresponds to nuclear materials accountability for the operation that produced the waste item. In the packaging operation for legacy waste, a standard form, the Discardable Waste Log Sheet (DWLS), was used to list each ID code (Reference P090, page 25; P091, Appendix 2; and P095, Appendix C). This form was signed by the waste packager and approved by QA personnel (References D025 and D041).

Controlled
Copy



Both the WODF and DWLS for each TRU waste container are maintained as hard copy records by the generator. Many of these waste tracking ID codes for individual items in containers of debris waste are compiled in a list that correlates item codes with containers or in a database maintained as the WMS (References D025, D041, and U004).

The WODF and DWLS forms were often attached to the Certified Waste Storage Record (CWSR) for legacy waste. The CWSR documented waste packaging information including the type of packaging, generating organization and location, radionuclide content, dose rates, presence of toxic or corrosive materials, and storage site information. The CWSR was modified in the early 1990s and changed to the TWSR (References D037 and P090).

Figure 6 includes an example of legacy container records. Note that this waste container example (LA00000057745) contains waste items associated with seven different P/S Codes (BM, EOC, FF, OM, SS, TIGR, and XO) (See Figure 5, TA-55 Process/Status Code Index Table). Each of the waste items is linked to a unique WODF. Information encoded in the ID code indicates that five of the seven waste items are metal (MET), while the remaining two from P/S Code SS are crucibles (XBL). These and other matrix abbreviations used by waste management personnel are listed in Appendix D of *Performing Visual Examinations of TRU Waste* (References D025, D041, and P097).

For waste generated after July 17, 2001 (i.e., LANL newly generated), the physical description of each waste item generated is documented on a WODF by the waste generator in accordance with *TA-55 Transuranic Waste Interface Document* (TWID) (Reference P092) and *Performing Visual Examinations of TRU Waste* (Reference P097). The term "LANL newly generated," as it is used in this report, is related to LANL waste management practices and is not intended to indicate how CCP will characterize LANL generated TRU waste. The WODF is generated electronically in the WMS database. The P/S Code for waste items is also documented on this form. The PF-4 at TA-55 tracks waste items both by the P/S Code from which they originated as well as by their material content, using the computerized MASS. Waste items are labeled with a code that contains information on the WMP of the item and an embedded P/S Code that corresponds to the operation that produced the waste item. In the packaging process, the WMS is used to list each ID code and record its matrix material electronically (Appendix B in *Performing Visual Examinations of TRU Waste* [Reference P097]). This form is electronically signed by the waste packager and approved by QA personnel. The WODF(s) for each item in a TRU waste container are maintained electronically and a hard copy is printed after all approvals are in place (References D025 and D041). Figure 6 includes an example of a LANL newly generated container. Note that this waste container (LA00000059359) contains waste items generated by four different P/S Codes (ITF, CA, RB, and RBJ); each waste item is listed with its own completed WODF. (The P/S Code of each waste item is listed in the Measurement Information field under PS near the center of the WODF screen).

Information encoded in the ID indicates that one of the waste items is combustible waste (COM), another is rubber (RUB), and the remaining four are plastics (PLS) (References D025 and D041).

4.3.5 LANL Treatment, Storage and Disposal Facilities for TRU Waste

LANL's inventory of TRU waste destined for disposal at the WIPP is stored at TA-54, Area G, which has been in operation since 1957. TRU waste management at Area G included drum venting, decontamination and volume reduction, and buried waste retrieval operations. The characterization requirements for storage of TRU mixed waste are contained in the LANL HWFP, Attachment A.2, *Waste Analysis Plan for Transuranic Mixed Waste* (References 17, D025, and D041).

In the late 1970s, facilities throughout the DOE complex recognized the need to upgrade the retrievability of TRU waste. As a result, LANL constructed three asphalt storage pads for TRU and TRU mixed waste storage at Area G, referred to as Storage Pads 1, 2, and 4. The waste containers were configured in densely packed arrays and subsequently covered with earth to provide protection from weather and be consistent with DOE's principle of maintaining exposure as low as reasonably achievable (ALARA) (References D025, D041, D083, and D084).

The Transuranic Waste Inspectable Storage Project (TWISP) was initiated in 1997 to retrieve waste in earthen covered storage at Area G and place the waste in an inspectable configuration in aboveground storage domes (see the *Transuranic Waste Inspectable Project (TWISP) Final Report* (Reference D056). Retrieved containers were vented and fitted with filters; thus, the completion date of the TWISP (December 31, 2001) can be used to establish the drum age criterion if RTR verifies that the drum liner lid, if present, has been punctured. The TWISP was executed in three campaigns. The first, Pad 1, began in March 1997 and was completed in November 1998. The second campaign, Pad 4, was completed in December 1999, and the third campaign, Pad 2 was completed in December 2001 (References C002, C216, D025, D041, D083, and D084).

Waste containers that fail to meet WIPP criteria are sent to the TA-50 Waste Characterization, Reduction, and Repackaging (WCRR) Facility; the TA-54 Building 412 facility formerly known as the Decontamination and Volume Reduction System (DVRS) facility; the TA-54 Dome 231 Permacon; or the TA-54 Dome 375 TRU Oversized Waste Processing Capability Project, also referred to as the Box Line Process, to be safely remediated. The WCRR facility was established in 1979 as the Size Reduction Facility (SRF) to size-reduce non-routine waste items such as decommissioned gloveboxes. In 1993, the name of the SRF was changed to the WCRR Facility to reflect the expanded remediation/repackaging mission. Size reduction operations at the WCRR Facility were discontinued around 1997. The TA-54 Building 412 facility operated for a short time in the early 2000s and resumed operations again in 2010. The TA-54 Dome 231 Permacon was established in 2006.

The TA-54 Dome 375 Box Line Process began operations in 2012. All three TA-54 facilities perform the same basic functions including sorting, segregating, size reduction, and repackaging operations on waste containers that contain WIPP nonconforming items and safely processes oversized containers (e.g., fiberglass-reinforced plywood [FRP] waste boxes, corrugated metal boxes [CMBs]). Figure 1 identifies the general location of these facilities (References C163, C165, C185, D013, D026, D041, D062, P154, P158, P159, P192, P194, P195, P196, P197, P198, P199, P203, and P204).

### 4.3.6 Types and Quantity of TRU Waste Generated

The waste streams described by this report have been characterized as TRU mixed waste. The characterization information presented in this document is based on the review of container-specific information for those containers listed in the most current AK Tracking Spreadsheet. Refer to Sections 5.2, 6.2, 7.2, and 8.2 for the container counts and volumes for each individual waste stream.

Each payload container shipped to the WIPP will be certified in accordance with CCP-PO-002 (Reference 16), as containing more than 100 nanocuries per gram (nCi/g) of alpha emitting isotopes with half-lives greater than 20 years. Overpacking of waste containers for the purposes of payload management, as described in Appendix E of the WIPP-WAC (Reference 3) will not be implemented for these waste streams. The fraction of waste containers that contain less than 100 nCi/g has not been estimated.

### 4.3.7 Correlation of Waste Streams Generated from the Same Building and Process

The WIPP-WAP defines a waste stream as waste materials that have common physical form, that contain similar hazardous constituents, and that are generated from a single process or activity (Reference 1). Based on a review of the AK documentation, waste streams LA-MHD01.001, LA-CIN01.001, LA-MIN02-V.001, and LA-MIN04-S.001, were generated during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations. Container-specific records have been reviewed to verify the physical composition and origin of the individual waste stream inventories. It has been determined that every container included in the most current AK Tracking Spreadsheet was generated from the operations described in Section 4.4. In addition, each of these waste streams have been categorized into a single Waste Matrix Code (as described in Sections 5.4.1, 6.4.1, 7.4.1, and 8.4.1) and have been classified entirely as TRU mixed waste (as described in Sections 5.4.3, 6.4.3, 7.4.3, and 8.4.3). The following subsections provided further basis for the waste stream delineations (References C171, M019, M156, M215, M216, M217, M218, M219, M222, M224, M226, M236, M238, M241, M242, M273, M274, M275, M276, M279, M296, and M298).

Evaluation of CCP-AK-LANL-007 Containers

This report has combined containers and the relevant AK information from waste stream LA-MHD02.001 previously described in CCP-AK-LANL-007 (Reference 20), with waste stream LA-MHD01.001. Waste containers from LA-MHD02.001 have been combined into waste stream LA-MHD01.001 for the following reasons (References C144 and C145):

- An exclusively Pu-238 waste stream (LA-MHD02.001) was originally created because LANL waste management operations had been attempting to segregate Pu-238 materials originating from defense and non-defense operations based on local DOE decisions made in August 1998. The May 2004 memo from CBFO to Ed Wilmont (Reference C212) resolved this issue by concluding that segregation of a non-defense waste stream is not feasible and all Pu-238 waste containers originally from TA-55 should be managed as defense waste. Additionally, waste stream LA-MHD01.001 currently includes containers loaded with packages of other MTs that have not been segregated from the waste stream based on the radiological content of the containers. Without a defense determination driver for maintaining a separate heat source waste stream, segregation of these containers is unnecessary with the designation of waste streams pursuant to the WIPP-WAP (Reference 1).

- As described in Section 4.3.1, the segregation of existing TA-55 waste containers into separate waste streams was an administrative exercise based on generator identified MTs on a container-by-container basis. Throughout the time period of generation of TA-55 TRU waste, containers were loaded with waste without regard for segregation of different MTs. Consequently, only those containers containing exclusively heat source plutonium waste could be included in waste stream LA-MHD02.001.

- During subsequent CCP characterization activities, NDA has rejected approximately four percent of the containers identified by AK as containing solely heat source plutonium because the predominant isotope was Pu-239.

- As described in Section 4.4, the operations that generated these waste materials are similar and both populations have been assigned the same EPA HWNs because of LANL waste management practices. These operations have generated a population of waste that is similar in material, physical form, and hazardous constituents.

Evaluation of Nonhazardous Debris Containers

The LANL Project 2010 (formerly the LANL TRU Waste Certification Program) delineated a small population of nonhazardous containers, based primarily on the assignment of P/S Codes for specific operations and the date of generation. Initial

shipments of this nonhazardous stream in 1999 included containers of recently-generated debris carefully selected by P/S Code to ensure a nonhazardous population (References 13, DR004, and M310).

Supplemental information was collected on a representative sample of this waste stream to verify that this lot of containers was nonhazardous. Suspect waste packages were removed from individual containers during inspection. Solid sampling of the debris materials was performed and demonstrated that the RCRA metal contaminants would not exceed the regulatory thresholds for this inventory. Since solid sampling of debris waste and inspection and segregation of hazardous items will not be performed for the remainder of the inventory, a more conservative characterization approach has been adopted for the remaining inventory, which is reflected in this report (References D075, DR004, and M310).

As described in Section 5.4.3, this approach is further justified, based on the review of the existing AK documentation for reasons including (References DR004 and M310):

- Several operations identify the potential for RCRA-regulated constituents and most of the P/S Codes generated waste containing leaded gloves prior to May 1992.
- The assignment of P/S Codes was not initiated until 1987 and the codes were inconsistently used until 1995.
- Wastes from multiple P/S Codes are routinely combined in the same container.
- Recovery operations may concentrate RCRA metal contaminants.
- Different EPA HWNs have been assigned to the waste during previous characterization efforts at LANL and RCRA allows for the conservative assignment of EPA HWNs.

All of the waste covered by this report was originally generated by the TA-55 operations described in Section 4.4. Prior to June 2005, CCP had delineated a non-mixed debris waste stream generated by PF-4 plutonium recovery operations (CCP waste stream LA-NHD01.001); however, based on CCP characterization test results, containers previously assigned to the non-mixed population have been reevaluated and assigned to the mixed debris waste stream. There are no longer any containers assigned to the non-mixed waste stream (References 13, DR004, and M310).

<u>Evaluation of Segregated Debris Containers</u>

The LANL Project 2010 also historically categorized PF-4 generated mixed debris waste into two separate waste streams based on physical composition. PF-4 packaging practices resulted in waste segregation by physical matrix type for assay purposes

(References P091 and P098). This practice resulted in many debris containers being comprised exclusively of like material, such as metal, glass, HEPA filters, and combustibles such as plastic and cellulose. LANL determined that two waste streams, one primarily combustible, and one primarily non-combustible would be delineated. However, these materials were generated from the same process operations; contain the same chemical and radiological contaminants, and PF-4 segregation practices resulted in incomplete segregation to the extent that delineation of two debris waste streams is not supported by the AK reviewed by CCP. This conclusion is further supported by an evaluation of pre-Waste Analysis Plan (WAP) RTR data for 529 containers that revealed that more than 15 percent of containers in the combustible waste stream contained more than 50 percent non-combustible material, and more than 11 percent of containers in the non-combustible waste stream contained more than 50 percent combustible material. Based on this information, it was determined that segregation of this population of debris waste containers into two waste streams is not practical and only one waste stream is defined for this population of containers (References U002 and U007).

Evaluation of Homogeneous Waste Containers

LANL's waste management practice has been to handle and package all debris and homogeneous waste in a similar fashion. In addition, waste is packaged in combinations of operations of origin; that is, waste items from several different operations are frequently combined in a single container. As a result, debris waste containers often include lesser quantities of homogeneous solids (less than 50 percent by volume). Homogeneous waste containers that include solids such as hydroxide cake/filter materials, salts, and ash residues are still generated, although infrequently. Characterization activities of these homogeneous solids have discovered that some of the containers include more than 50 percent by volume of heterogeneous debris. This is due in part to the packaging configuration associated with small quantities of homogeneous solids. Homogeneous solids are primarily generated from operations performed in gloveboxes. The waste material may be packaged into a plastic bag, a stainless-steel dressing jar, a slip-top can, and/or an unsealed metal container before it is placed into a plastic bag-out bag. Once removed from the glovebox line the bagged out container(s) may also be put into a secondary stainless-steel slip-top container. Homogeneous solids can also include debris materials such as small pieces of plastic and metal from incomplete combustion, magnesium oxide crucible pieces from metal purification, and precipitated metal fines. Based on this information, LANL generated homogenous solids, except for cemented and absorbed waste, have been reassigned to waste stream LA-MHD01.001. It is expected that some number of these containers will fail RTR or VE for containing greater than 50 percent homogeneous solid waste. These containers will be segregated from the debris waste stream and assigned to the appropriate homogenous waste stream (e.g., LA-MIN04-S.001) (References D041, DR008, M074, P155, P156, P157, and P160).

As described in Section 4.4, numerous PF-4 operations generate process liquids and homogeneous solids. The waste assigned to waste streams LA-CIN01.001, LA-MIN02-V.001, and LA-MIN04-S.001 originated exclusively from TA-55 operations. Cemented waste assigned to waste stream LA-CIN01.001 is generated by the cement fixation process, which receives aqueous and organic liquids with low plutonium concentrations, evaporator bottoms, and salts for immobilization that could have originated from any operation in PF-4. These feed materials (prior to cementation) often contain contaminants from multiple operations, and materials from specific operations are often packaged in the same drum after cementation. An evaluation of this cemented waste confirms that the final physical form by volume (i.e., solidified homogeneous solids) is the same regardless of the liquid/solid wastes treated. Absorbed waste assigned to waste stream LA-MIN02-V.001 is largely comprised of TRU liquids and solids absorbed or mixed with absorbent. An evaluation of this cemented and absorbed waste confirms that the final physical form of each homogeneous waste stream is the same regardless of the liquid/solid wastes treated. The solidification process converts the organic or inorganic material into an inorganic matrix. Salt waste assigned to waste stream LA-MIN04-S.001 is largely comprised of salts which are a byproduct from a variety of plutonium metal purification operations including electrorefining, molten salt extraction, salt stripping, fluoride reduction, and direct oxide reduction. Salts serve as a transportation vehicle for plutonium ions and provide a trap for impurities that are driven or extracted out during the purification process. As discussed in Section 4.3.1, waste in PF-4 is packaged into containers based on isotopic material content of the waste and NDA characteristics without regard to process of origin (i.e., waste from multiple operations is often packaged in the same waste container). In addition, the operations that generated this waste used the same or similar chemical and radiological materials and the waste streams have been assigned the same EPA HWNs (References C121, C147, C155, C171, C173, and D083).

Based on the rationale above, waste streams LA-MHD01.001, LA-CIN01.001, LA-MIN02-V.001, and LA-MIN04-S.001 meet the WIPP-WAP waste stream definition, and further delineation of these waste streams is either unfeasible or unnecessary (Reference 1).

## 4.4 Description of Waste Generating Process

### 4.4.1 Overview

<u>Plutonium Processing Operations</u>

Wastes were generated from materials used in the process to recover plutonium from residues, metal fabrication, and R&D operations. The variety of plutonium handling operations includes:

- Preparing ultra-pure plutonium metals, alloys, and compounds
- Preparing (on a large scale) specific alloys, including casting and machining these materials into specific shapes
- Determining high-temperature thermodynamic properties of plutonium
- Reclaiming plutonium from scrap and residues produced by numerous feed sources
- Disassembling components for inspection and analysis
- Manufacturing of parts on a limited basis
- Processing plutonium oxide, uranium oxide, americium oxide and mixtures of plutonium and uranium oxides for reactor fuels
- Pu-238 generator and heat source R&D, fabrication, testing, and recycling

Flow Diagrams

The six operational areas that contributed to these waste streams are:

- Nitrate Operations (References D008 and D036)
- Miscellaneous Operations (References D009 and D032)
- Special Processing Operations (References D010 and D030)
- Metal Operations (References D011 and D029)
- Pyrochemical and Chloride Operations (References D007, D011, and D028)
- Pu-238 Operations (References C212, C220, D071, and D080)

Sections 4.4.2 through 4.4.7 correspond to the six operational areas listed above. Each section describes the operations that generated waste assigned to the debris and homogeneous waste streams. Generalized flow diagrams for legacy and LANL newly generated waste are presented in Figures 7-19. The diagrams for these six operational areas indicate the P/S Codes associated with each of the various sub-operations.

Sections 4.4.8 and 4.4.9 correspond to facility and equipment maintenance and D&D operations which are commonly performed in TA-55. These operations originate in the same areas and generate waste and materials that contain the same chemical and

radiological contaminants described in Sections 4.4.2 through 4.4.7. Process flow diagrams for maintenance and D&D operations are not practical due to the variability and broad nature of these operations.

Section 4.4.10 corresponds to the repackaging and prohibited item disposition operations which repackage TRU waste from various LANL facilities including TA-55. The repackaged waste containers retain their original characterization; therefore, the TA-55 plutonium processing operations and associated chemical and radiological contaminants described in Sections 4.4.2 through 4.4.9 are still applicable. Figure 20, Waste Repackaging and Prohibited Item Disposition Flow Diagram includes a repackaging and prohibited item disposition flow diagram.

Section 4.4.11 corresponds to the below-grade retrieval project which includes the removal of waste from various LANL facilities including TA-55. The TA-55 below-grade waste originated from the same operations described in Sections 4.4.2 through 4.4.9. Figure 21, Below-Grade Drum Retrieval Flow Diagram and Figure 22, Below-Grade Crate Retrieval Flow Diagram include process flow diagrams depicting the general below-grade drum and crate retrieval operations.

### 4.4.2 Nitrate Operations

The overall goal of the nitrate operations is to recover plutonium from scrap and residues, and produce a purified plutonium oxide product, or for conversion into metal. The primary feed sources for the nitrate operations are plutonium residues from other recovery operations (e.g., chloride operations), metal preparation, metal fabrication, analytical laboratory operations, and residues from other DOE facilities. Nitrate operations can be broken down into the following six steps (References C129, D008, and D036):

- Pretreatment
- Dissolution
- Purification and Oxide Conversion/Refinement
- Americium Oxide Production
- Evaporation
- Cement Fixation

*Pretreatment* primarily includes physical methods used to separate scrap and residues for the next step–dissolution. It may include burning metal, thermal decomposition, crushing and pulverizing, incineration, scraping, or sorting. Historically, it also may have included calcination, caustic leaching, chemical separation (hydroxide or oxalate precipitation), distillation, filtering of liquids or oils, magnetic separation or passivation. The filtering of liquids or oils was performed under *Oil Recovery* from 1979 to 1989. Vacuum pump oils and other contaminated liquids from various operations were analyzed for nuclear material content. If they met the DL for plutonium, they were mixed with vermiculite and packaged in a drum for disposal. If the liquids contained

plutonium above the DL, they were filtered through a glass frit so as to meet the DL. Any plutonium residue caught in the filter was to be sent to recovery operations. Once in 1979, trichloroethylene was used as a diluent to reduce the viscosity of vacuum pump oil. Heavy metals were not used in the process but were expected to be present from equipment wear (References -C130, D008, D036, and M057).

After pretreatment, solids are sent to dissolution if plutonium concentrations are above the DL. If concentrations are below the DL, solids are sent to solid waste packaging. Plutonium bearing solutions are sent to purification if plutonium concentrations are above the DL. If concentrations are below the DL, solutions are sent to solid waste packaging (References D008 and D036).

*Dissolution* includes various steps that generate plutonium nitrate solutions for feed into the purification step. Primary chemicals used in dissolution are nitric acid, calcium fluoride, and/or hydrofluoric acid. Filtered solids are either returned to the dissolution operation until plutonium concentrations are below the DL or sent to the vault for storage. Processed solids with plutonium concentrations below the DL are sent to solid waste packaging for disposal. Debris items are disposed after removal of plutonium contamination above the DL. Non-acidic plutonium-bearing solutions are sent to purification. Acid solutions are sent to the evaporator (References D008 and D036).

The *Advanced Testing Line for Actinide Separations* (ATLAS) facility is a technology development operation performed in the dissolution process. The mission of the ATLAS facility is to research, develop, and demonstrate state-of-the art methods to reclaim and purify actinides from contaminated scrap. The facility has the capability to recover actinides from a wide range of feed types including oxides, ash, pyrochemical salts, metal conversion residues, and other items such as metal, alloys, and sources. This line employs dissolution, feed treatment for anion exchange, eluate precipitation, purification precipitation, calcinations, and waste treatment technologies. Chemicals used in this process include aluminum nitrate, calcium fluoride, diethyl oxalate, ferrous ammonium sulfate, formamide, hydrogen peroxide, hydroxylamine nitrate, sodium hydroxide, sodium nitrite, urea, and ascorbic, formic, hydrochloric, hydrofluoric, nitric, and sulfuric acids (References C200, D071, and P190).

*Purification and Oxide Conversion/Refinement* consists of ion exchange, precipitation, calcination, and roasting and blending operations. The ion exchange operations use resin-filled columns to collect plutonium, which binds to the resin while impurities flow through the columns; an eluting agent (nitric acid and hydroxylamine nitrate) is then used to release purified plutonium in solution. The enriched solutions are then sent to oxalate precipitation. Calcination of the oxalate converts the plutonium to oxide form. The oxide is then screened and blended. The depleted liquids are sent to the evaporator after hydroxide precipitation. An alternative purification process involves peroxide precipitation to eliminate a select set of metallic impurities. The plutonium peroxide is then separated by filtration, redissolved in nitric acid and precipitated again

as the oxalate. The calcined plutonium oxides are sent to the vault (References C129, D008, and D036).

*Americium Oxide Production* begins with hydroxide precipitation of americium from the filtrate of the plutonium peroxide precipitation. The americium hydroxide then goes through dissolution, purification and packaging much like the plutonium nitrate operations, but without the refinement step. The processed material is sent to the vault for storage (References C129 and D036).

The *Evaporator* processes plutonium-poor liquids in order to re-concentrate plutonium, if possible, or to reduce the volume of liquid waste. These solutions are collected in tanks and sent to the evaporators in batches of up to 600 liters. The solution batches are then concentrated to approximately 25 liter volumes called “bottoms.” As the bottoms cool, salts (i.e., nitrate salts) precipitate out and settle on the bottom of cooling trays. After cooling, the bottoms are sent back to ion exchange if plutonium concentrations are above the DL or to cement fixation if concentrations are below the DL. Attempts are made to re-dissolve settled salts, but if this is not readily achievable, the salts are sent to dissolution if plutonium concentrations are above the DL or sent to cement fixation if concentrations are below the DL. Nitric acid is used in the evaporator to wash nitrate salts having a plutonium concentration above the DL. Spent acid waste is sent to the Radioactive Liquid Waste Treatment Facility (RLWTF). Heavy metals that might be present are concentrated in this operation (References C130, D008, and D036).

Prior to 1992, some nitrate salts below the DL were not sent to cement fixation for immobilization but were packaged as waste. These salts were washed, vacuum dried (to reduce, but not eliminate, moisture content), double- (or triple-) bagged, and placed in 55-gallon drums. These salts are being remediated/repackaged in the WCRR Facility with an inert absorbent material (e.g., zeolite, kitty litter). The minimum inert absorbent material to nitrate salts mixture ratio is 1.5 to 1 (see Section 4.4.10). Containers of nitrate salt waste mixed with inert absorbent material are included in the mixed absorbent waste stream (References C230, C231, D089, D090, D091, and P198).

The *Cement Fixation* process immobilizes aqueous and organic liquids with low plutonium concentrations and solids (e.g., evaporator bottoms, salts) from the six operational areas (e.g., nitrate operations) in cement. Historically, filtered solids and fines were also sometimes sent to cement fixation, but this is no longer done. Prior to 1988, the cement fixation process was performed throughout TA-55 using available glovebox space. Since 1988, the process has been performed in a dedicated glovebox. Liquids and solids are typically transferred to cement fixation in containers. Reagents used during this operation include cement accelerator, gypsum cement, nitric acid (pH adjustment), organic liquid emulsifier, Portland cement, silicone defoamer, sodium citrate retarder, sodium hydroxide, and phthalate and phosphate buffer solutions for pH meter calibration. The waste materials are commonly adjusted to a specific pH prior to mixing with gypsum or Portland cement. In the past, the cement was mixed in plastic bags or in various sized containers. Waste is now mixed directly into a 55-gallon drum

attached to the glovebox. Any particulate matter is added during the stirring operation. Based on the review of the AK sources, contaminants of incoming materials may include chromium, lead, mercury, silver, acetone, benzene, butanol, carbon tetrachloride, chlorobenzene, chloroform, tetrachloroethylene, methylene chloride, methanol, pyridine, and xylene. Most of the wastes generated under this operation are classified as cemented wastes; although a small amount of debris waste is also generated (References C132, C171, C200, D008, D036, D050, D077, D078, and U005).

### 4.4.3 Miscellaneous Operations

R&D projects involve applied techniques and methods designed to study and improve operations associated with the purification, separation, extraction, recovery, and characterization of actinides (primarily plutonium). General types of these miscellaneous operations are described below.

*Actinide Chemistry R&D*. Several small-scale R&D efforts utilizing analytical instrumentation, wet chemistry, and other miscellaneous laboratory techniques primarily focus on plutonium recovery. Examples of some of these efforts include:

- Fluoride sintering of plutonium oxide takes advantage of the presence of fluoride to aid the formation of a sintered mass of plutonium oxide powder at temperatures above 700°C.

- Chlorination of plutonium oxides involves oxides with tantalum chips from the former Rocky Flats Environmental Technology Site. Chlorination is used to recover plutonium from potassium chloride and sodium chloride matrices.

- Processing of molten-salt extraction (MSE) salts generated at LANL and the former Rocky Flats Environmental Technology Site.

- Recovery of plutonium from ash involving plutonium/thorium oxide mixtures.

- Processing of neptunium oxide and metal to remove the protactinium (Pa) daughter in order to use the neptunium for NDA standards.

Process outputs from these operations may be sent to the vault, aqueous recovery, or cement fixation based on the DL (References D009 and D032).

*Experimental Oxide Characterization* is conducted in Room 208 of PF-4 as an experiment designed to calculate the surface area and pore size distribution of a sample and to analyze the surface characteristics of the sample. Mixtures of helium and nitrogen are passed through a V-shaped cell to analyze the sample inside. With the exception of nitrogen and helium, no solvents or chemicals are used in this process. Process outputs from this operation may be sent to the vault, returned to the originating

P/S Code, transferred to aqueous recovery, or cement fixation based on the DL (References D009 and D032).

The *Analytical Chemistry Laboratory* includes all analytical techniques performed in Room 124 of the PF-4. Operations involve the analysis of plutonium and americium, RCRA metals, and trace metals. Originators provide samples, which are prepared for further analyses, such as inductively-coupled plasma (ICP) and x-ray energy spectroscopy (XES). Unused liquid samples are returned to the originator, sent to radiochemistry for counting, sent to aqueous recovery operations, cement fixation, or sent to the RLWTF (References D008, D009, and D032).

*Laser Induced Breakdown Spectroscopy* is a technique that uses a powerful laser beam which, when focused on a sample, vaporizes a portion of the sample and forms a plasma. The light emitted by the plasma is analyzed in an optical spectrometer and the elemental composition and concentration of the sample can be determined. The advantages of this technique include analysis without sample preparation or dilution and portability. In this operation, originators provide plutonium containing solids or solutions which are analyzed. After analysis, the remaining sample is returned to the originator (Reference D032).

*Actinide Processing Demonstration* is a hydrothermal processing technique that involves the reaction of aqueous/organic mixtures, pure organic liquids, or contaminated combustible solids (e.g., ion exchange resins, plastic filters, and cellulose rags) with water under supercritical or near supercritical (elevated temperature and/or pressure) conditions. Feed streams may be contaminated with acetone, butanol, carbon tetrachloride, chlorobenzene, chromium, dihexyl N, N-diethylcarbamoylmethyl phosphonate, diisopropyl benzene, lead, methanol, methylene chloride, octylphenyl di isobutyl carbamoylmethyl phosphine oxide, and xylene. Effluents are liquids, oxides, and salts. Organic components are oxidized to carbon dioxide. Nitrate contaminants are converted to nitrogen gas and some nitrous oxide. Components such as chlorine, sulfur, and phosphorus are oxidized and converted to acids or salts. Process outputs from this operation may be sent to the vault, returned to the originating P/S Code, or transferred to aqueous recovery or cement fixation (References C199, D032, D077, and M223).

*Electrochemistry* operations examine the electrochemical behavior of actinide or actinide contaminated metal samples and compounds in aqueous and non-aqueous solutions. A wire is attached to the sample with conductive paint and the sample is mounted in epoxy. The surface is polished and then cleaned with ethanol. An electrochemical cell is assembled, including a reference electrode (such as saturated calomel), a counter electrode, the desired solutions, and a gas dispersion tube. The electrodes are attached to a potentiostat and the sample is polarized by the application of voltage to the working electrode. The residual solution is made more basic to precipitate the actinide. After settling, the liquid is decanted and the precipitate is filtered and dried. The filtrate is sent to Aqueous Recovery or to the RLWTF. After

drying, the residue is scraped into a storage container and sent to the vault. The remaining samples are returned to the originating P/S Code (Reference C131). *Material Identification and Surveillance* involves the preparation of batches of plutonium oxide with well-established characteristics, and non-SNM impurities as desired to determine how these materials will interact with water in long-term storage. The preparation of the batches uses any combination of milling, blending, screening, calcining, and splitting to produce the desired plutonium oxide powders. Impurities such as alkaline, alkaline earth, uranium chlorides, metal oxides, hydroxides, fluorides, carbonates, nitrates, and sulfates are added as desired and the material is sent to the vault or other operations as needed (Reference C131).

*Long Term Storage and Compatibility Testing* is an operation used to measure the chemical and physical changes that occur when plutonium metal or compounds (such as oxides) are placed in various storage configurations, in various gaseous environments, or in contact with process or commercial materials. Small Material Inventory Studies involve the loading of up to 10 grams of plutonium dioxide as well as non-special nuclear material impurities into containers. The containers are monitored for temperature, pressure and gas composition over time. The capability also exists to modify the gas composition at any given time. The containers are heated in a furnace to a temperature corresponding to self-heating of a normal storage container loaded with nuclear material. The plutonium oxide is supplied by the vault or the Material Identification and Surveillance (MIS) process. The purpose of this process is to understand any changes or reactions that might occur in long-term storage of nuclear material. The gas monitoring is accomplished using mass spectrometry or gas chromatography. At the conclusion of testing, the containers and materials are submitted for analysis, returned to MIS, or sent to the vault (References C131 and D009).

Compatibility tests, which are no longer performed, were similar to the long term storage tests, except that (1) tests were prepared with process or commercial materials in contact with the plutonium metal or compounds and stored in the glovebox, (2) the storage containers didn't have a thermocouple, (3) the container may not have been monitored by an automated data acquisition system, and (4) the container had a volume up to 1.3 liters. Materials involved include plutonium metal, alloys or compounds, process or commercial materials (including liquid solder [gallium, indium, and tin], glycol, silicone grease, Sylgard 184, or cellular silicone), and the following gases which were used as atmospheres in the storage containers: helium, hydrogen, or the constituents of air. The test materials were sent out for analysis after the tests. Gas cylinders were attached to a manifold through a two-stage regulator and not used in the gloveboxes (References C131 and D009).

*Standard Fabrication* originated as Pyrochemical Matrix Studies conducted from 1986-1992 involving rod milling prior to screening. This operation had two objectives: (1) blending large batches of homogeneous plutonium oxide for pyrochemical operations, and (2) blending similar batches for dissolution in nitrate operations.

The operation changed in August 1992 when a need developed to blend oxides to provide feed material for making NDA standards. From February 1995 to the present, the operation changed again, with the objective of determining the effect of high purity oxide, salt, and metal matrices on the accuracy of NDA measurements. Operations involve crushing, pulverizing, blending, roasting, and sieving. The results are used to determine protocols for handling and processing the matrices and to correct bias measurements. The product material consists of high-purity oxide standards for use at LANL and throughout the DOE complex (References D009 and D032).

*Metallography Operations* characterize the microstructure of metallic or ceramic pieces and establish the quality and effectiveness of welds. Materials examined consist of plutonium and uranium carbides, nitrides, and oxides, as well as zirconium and tantalum alloys, and stainless-steel. Metal pieces (pellets) are cut with a diamond saw. Ceramic and metal pieces are subjected to grinding with standard metal grinding media (e.g., papers impregnated with silicon carbides and diamond). The materials are cleaned, polished, and etched with several different chemical compounds. The spent chemicals are sent to aqueous recovery, to the RLWTF, or mixed with absorbent. The plutonium and uranium carbides, nitrides, and oxides are returned to the vault (References D009 and D032).

*Electrolytic Decontamination* conducts various electrochemistry R&D experiments in Rooms 105, 106, 112, 208, 209, and 210. Electrochemistry methodologies are designed to decontaminate items, replace operations that produce large amounts of waste, or enhance chemical reactions. Process inputs are from the vault. The process involves uranium decontamination of disassembled weapon components from various sites with various levels of surface contamination with plutonium. The operation is strictly an aqueous process in which an alkaline solution is reacted with the components to precipitate uranium. A stainless-steel cathode is used; therefore, corrosion is not an issue and the electrolyte is not degraded. Significant amounts of metal could be stripped in a short period of time. The precipitated solution comprises either uranyl hydroxide or uranyl sulfate, which is then dried for mass balance. The distillate contains small amounts of uranium. Rinse water is discarded to the RLWTF. Outputs from the process are directed to the vault or cement fixation (References D009 and D032).

*Waste Management Operations* (P/S Code WM) is currently limited to waste generated from the TRU solid waste management operation in Room 432. This practice has been in place since the beginning of 1993. Room trash boxes from PF-4 have always been handled as low-level waste (LLW). However, when the boxes were assayed to verify contamination levels, some were determined to be TRU waste. These boxes of room trash were diverted to Room 432 for repackaging as TRU waste. From May 1987 through 1992, these boxes were tracked using P/S Code XO or X0 (Inactive or unspecified P/S material) and ultimately designated as having originated in P/S Code WM. These codes were changed to P/S Code WM after 1992 (References D009, D032, and D077).

Additional controls were placed on room trash after 1992 and continue to the present. Trash is assayed with the Multiple Energy Gamma Assay System (MEGAS). When a container is rejected because of MEGAS data, the rejected container is returned to the originator for removal of any “hot” item(s). This operation also allows greater control to prevent discarding regulated materials (e.g., RCRA constituents) in room trash.
P/S Code XO indicates waste materials contaminated with RCRA constituents that are generated within specific rooms but cannot be associated with an individual P/S Code in that room. P/S Code X0 is designated for waste materials that cannot be associated with a specific room, such as a hallway, mezzanine offices, restrooms, change rooms, basement, pump rooms, and trolleys. The waste from all these areas, except the pump rooms and trolleys, would be LLW and no RCRA constituents are associated with the waste. P/S Codes XO and X0 are considered interchangeable because of the difficulty in distinguishing them on container paperwork and their inconsistent use by waste generators (References C037, D009, and D077).

*Material Management Operations* (P/S Codes M1, M2, MM, and M4) are used to introduce and remove items from the glovebox line. TRU waste typically associated with bag-out operations (e.g., stubs, tape) is packaged with other waste items and assigned HWNs based on the P/S Code from which the waste originated. Waste generated in the material management rooms is associated with glovebox maintenance operations. No other operations are conducted in these rooms (Reference D009).

The *Non-Confirming Drums* operation occurred from April 1989–April 1991 in Room 432. This operation was established to provide a mechanism for dealing with TRU drums that did not confirm TA-55 characterization information (e.g., recorded weight or nuclear material content). Non-confirming drums were temporarily set aside until such time as personnel could reprocess them under waste management operations to correct the non-confirming condition. After April 1991, non-confirming drums were dealt with immediately, and this operation was no longer needed (Reference D032).

*Extraction/Separation Studies* is no longer active, but involved the processing of actinide hydroxide cakes generated from chloride and nitrate operations. Research in this area also contributed to the development of sensors and instrumentation for online chemical analysis, and improvements in the purification operation. The R&D operations were non-routine and developmental in nature. The operations involved research, process development, small scale trouble-shooting, and occasionally preparation of various isotopes and isotopic mixtures of plutonium, uranium, americium, and neptunium (Reference D032).

*Non-Aqueous Dissolution/Extraction Operations* is no longer active, but involved the dissolution of actinide compounds and actinide-containing matrices in superacid media. The superacid solutions were evaporated to leave solid products that were analyzed by a variety of methods. The study of the organometallic chemistry of uranium and thorium in non-aqueous solvents consisted of a variety of small-scale organoactinide operations.

The organoactinide operations were designed to study the synthesis of new actinide compounds in non-aqueous media. These operations also examined the characterization and reaction chemistry, and considered applications to existing actinide processing technology. Other non-aqueous operations supported fundamental and applied actinide chemistry research, by preparing solvents and reagents for the synthesis of new compounds, and characterization and analysis of new chemical compounds using wet chemistry methods and analytical instrumentation (Reference D032).

*Measurement/Detection Operations and Studies* is no longer active, but involved the inspection of oxides and metals. Materials were retrieved from the vault, brought to the glovebox, inspected, assayed by a non-destructive method, and sampled if necessary, then repackaged and returned to the vault. Assay methods included XES, laser-based, Raman and high resolution emission spectroscopy as well as other spectroscopic techniques. In addition to elemental and isotopic analyses, other measurement studies were designed to determine the surface area and pore size distribution of a sample and to analyze its surface characteristics. These studies produced only standard glovebox waste (References C131, D009, and D032).

*Halogenation Studies* is no longer active, but involved the fluorination of samples containing plutonium residues. A gas flow loop was used to pass a fluorinating agent through a gas-solid reactor where plutonium in the solid residue reacted chemically to form solid plutonium tetrafluoride or gaseous plutonium hexafluoride. Gaseous plutonium hexafluoride was trapped in a cold trap, distilled, and reduced to plutonium tetrafluoride. Separation operations involving experimental chlorination operations were similar to the fluorination procedures. A gas loop was used to flow carbon tetrachloride and perchlorocarbons through a gas-solid reactor to chlorinate plutonium oxides to form recoverable plutonium compounds. These studies produced only legacy waste (References D009 and D032).

### 4.4.4 Special Processing Operations

Special Processing includes operations for MT 42 and R&D for MT 52 (See Table 3, Average Isotopic Content of Plutonium Material Types and Enrichments, in Section 5.4.2.2, for descriptions of plutonium material types). Because processing MT 42 is a smaller-scale version of the recovery operations used for MT 52, MT 42 processing has four main recovery steps (References D010 and D030):

- Head-end operations
- Nitrate ion exchange operations
- Chloride ion exchange operations
- Pyrochemical operations

Only head-end operations are covered here. Nitrate ion exchange operations are covered in Section 4.4.2. Chloride ion exchange operations and pyrochemical operations (Direct Oxide Reduction, Molten Salt Extraction, and Electrorefining) are covered in Section 4.4.6 (References C131, D010, and D030).

*Head-end Operations* includes pretreatment which may include sorting, crushing, and/or pulverizing feed materials prior to being fed into later operations. A separate pretreatment procedure is the decladding of plutonium-beryllium (Pu-Be) sources. The Pu-Be metal alloy is removed from the sources, which are then entered into the chloride line for plutonium recovery along with other materials (References D007 and D028).

The next operation is to leach or pickle items such as tools, labware, crucibles, and ash, in nitric, hydrochloric, or hydrofluoric acids to remove recoverable plutonium. Plutonium oxide is typically calcined in nitrate and chloride operations to oxidize any metallic plutonium prior to dissolution. Combustible wastes are burned and the ash sent through the rotary calciners to remove incompletely oxidized organic material (References D010 and D030).

All wastes generated by MT 52 R&D operations are replicated for MT 42, but carry different P/S Codes to differentiate and identify the radionuclide content of the waste. Outputs from Special Processing include high purity metal for casting and machining (References D010 and D030).

### 4.4.5 Metal Operations

The main goal of metal operations is to transform the high purity metal produced primarily by pyrochemical operations into alloyed metal shapes. On-going metal operations include metal casting, machining/metal work on various metals, extrusion, surface preparation, oxidizing, surveillance machining, accelerated aging, impact testing, fuel fabrication, assembly, recovery and extraction, physical property testing, burst testing, special recovery, thermal hydride/dehydride, research alloy preparation, and welding, and Z machine experiments (References C131, D011, D029, and D092).

*Casting* is a process that receives plutonium metal from pyrochemical operations or Special Processing Operations depending on material type, or from other sources. The metal is combined with other metal from different sources to produce a product metal that meets purity specifications. Specification metal is then cast as a prealloyed feed aliquot at which time gallium metal is added. It is analyzed chemically in-line to determine the proper gallium content and the metal is placed into in-line storage. Metal is pulled from in-line storage to cast into shapes. Shapes generated by this process are sent to machining, various P/S Codes for testing, plutonium standards extrusion, reduction to metal or salt stripping. Plutonium oxide byproduct is sent to aqueous recovery (References D011 and D029).

*Machining* involves a variety of operations on cast parts obtained from Casting. Machining operations include turning, milling, grinding, and boring. The objective of the machining operations is to bring the parts to their formal dimensional specifications. Operations within machining use dry machining techniques. Cleaning solvents were used in machining operations in the past, and still are occasionally used, although with less-hazardous substitutes. Freon TF is used to remove oil from turnings (degreasing) before they are sent to recovery. Tetrachloroethylene is used to degrease metal parts after they are machined. Machined parts are sent to assembly operations or the vault. Scrap metal and turnings are sent to salt stripping and casting for recovery/reuse (References D011 and D029).

*Plutonium Standards Extrusion* uses high purity metal ingots from casting or machining which are placed in an extruder. The extruder is operated to produce a metallic wire that is cut into 1 gram pieces. Each 100 gram lot of wire pieces is sealed in a stainless-steel storage container for later packaging and shipment as required. The extrusion system consists of a hydraulic press and a microprocessor controlled hydraulic pumping system including a 0.156 inch diameter extruding die. The entire operation is performed in an inert glovebox to prevent oxidation of the metal. Plutonium standards are sent to the vault for storage (Reference C131).

*Plutonium Surfaces* studies receive samples from other operations and characterize them by the Sievert's Equilibrium System, x-ray, and other physical examinations. These methods can determine pressure-composition-temperature curves for actinide hydride/deuteride compounds or prepare samples of these compounds. These techniques also determine structures of actinide samples and measure helium release in aged plutonium. The samples may require mounting prior to characterization. Samples are returned to the originating P/S Code or to the vault (Reference C131).

*Uranium Conversion* involves the oxidation of uranium metal in air or a controlled oxygen environment at temperatures up to 1,100$^{o}$ C in a glovebox environment. The uranium pieces are usually received from the vault. The metal may be cut into pieces to fit into the crucible, which is then placed in the furnace and heated to the desired temperature in a slow flow of oxidizing gas. The oxide powder is then rod- or ball-milled to reduce particle size. It is then placed in a bottle before being removed from the glovebox line and transferred to the vault (References C131 and D011).

*Surveillance Machining* focuses on receiving metal shapes and machining the required metallic samples for a variety of analyses that can document what changes may or may not have occurred in the shaped item over its lifetime. The turnings are ultimately oxidized, while classified shapes and miscellaneous metal go to a variety of operations or to the vault (Reference C131).

*Accelerated Aging of Plutonium* is similar to casting and machining. Plutonium and other actinide based metals and materials are cast, machined, and inspected in the Actinide Research Machining Glovebox in the 300 wing of PF-4. This program employs Pu-238 to rapidly age weapons-grade plutonium, permitting accelerated self-irradiation induced changes in the material as a function of time. The Pu-238 enrichment level of weapons grade plutonium is performed at approximately 5 to 7.5 percent by weight. The Pu-238 is blended with the weapons-grade plutonium during the casting operation. Machining operations include turning, milling, grinding, and boring. Unlike machining, Freon TF is not used to degrease metal chips and turnings. However, trichloroethylene is used to clean machined parts. Machined parts are sent to metallography for testing. Plutonium scrap and turnings are sent to Casting and Salt Stripping for reuse/recovery. Oxide from casting is sent to Roasting and Blending for further processing (References C131, D011, D081, and P189).

*The Impact Test Facility* uses a 7-inch gas gun and a 40-millimeter (mm) powder gun. The 7-inch gun is used for Pu-238 experiments, such as heat source impact testing and impact testing of Pu-238 capsules in graphite blocks. The entire test is conducted in a tube so that the material is contained. The entire tube with contents is transferred back to NMT-9 for recovery elsewhere in PF-4. No TRU waste is generated from the 7-inch gun experiments under normal circumstances. The 40-mm gun enables the experimenter to generate data on materials in high stress environments. During the test, a projectile propelled to hypervelocity by a charge of smokeless powder, strikes an instrumented target contained within a glovebox. The target is shattered into macro and microscopic pieces during the impact and the projectile is arrested by a series of stopping plates. Target materials can range from surrogate materials to actinides. Post test, the remains of the target material, projectile, instrumentation, and stopping plates are removed as waste or are reused (References D011 and D029).

*The Kolsky Bar Test Facility* is a gas gun operation for physical property testing. A stainless-steel bar with plastic seals at each end is fired by gas pressure down a stainless-steel barrel that strikes a target, usually plutonium. Behind the target is another stainless-steel bar instrumented with sensors. This bar is butted against a plastic wrapped lead brick at the back of the chamber. Wastes include rags, HEPA filters, and gloves. The rags generated by this process may contain some lead/lead oxide from cleaning operations. The barrel is cleaned with a cotton swab. No solvents are used. Residual plutonium is returned to the originating P/S Code (References D011 and D029).

*Fuel Fabrication* entails the development of reactor fuel. Enriched uranium oxide, depleted uranium, and/or plutonium oxide is blended and mixed with graphite and stearic acid. The blended mixed oxide is then pressed into briquettes. The briquettes are heated, size reduced, and pressed into pellets. The pellets are heated/sintered and inspected. Grinding may be necessary to meet specifications. The accepted mixed oxide fuel pellets are transferred into the cladding glovebox. The cladding tube is held in a lathe while the pellets are pushed into the cladding with a pushrod. A

stainless-steel shroud tube is placed in the cladding tube prior to insertion of the pellets. A spring and end cap is placed in the open end of the cladding tube, and a tungsten inert gas (TIG) weld is made at the joint between the end cap and the cladding. Cladding, spring, and end cap are stainless-steel. Bonding of the fuel is done with either helium or sodium. Any excess sodium is reacted with Dowanol to form a stable sodium salt, which prevents metallic sodium from entering the waste streams. As a result of the current effort in mixed oxide fuel development, the issue of gallium removal becomes important. Completed fuel rods are sent to the vault for storage prior to distribution. Oxides and rejected pellets are sent to aqueous recovery or the vault (References D011 and D029).

*Assembly Operations* involves bringing nuclear material out of the glovebox and encapsulating it in a cold container. This outer container can be a bolted assembly or a welded assembly using electron beam, pressurized inert-gas metal arc, TIG, or laser welding techniques. No solvents are used. Wastes include aluminum foil, plastic bags, and gloves. The waste generated from this process is nearly always LLW, but some TRU waste may be generated. The assembled containers are sent to the vault for storage (References D011 and D029).

The *Advanced Recovery and Integrated Extraction System* (ARIES) is a demonstration operation, which receives and disassembles pits, plutonium hydrides and metallic plutonium, from which it produces plutonium metal or oxide powder. The product is canned for long-term storage. Wastes include plutonium-contaminated debris waste. Operation of the ARIES Electrolytic Can Decontamination System decontaminates the external surfaces of canned plutonium using an electrolytic decontamination system. An electrolyte (sodium sulfate) and water are used in the system in a recycle mode. Sodium hydroxide is used for pH control. Wastes include electrolyte and water solutions contaminated with plutonium. This liquid waste is sent either to cement fixation or to the RLWTF at TA-50. The plutonium metal and oxide powder is sent to the vault (References D011 and D029).

*Physical Properties* is a procedure that describes techniques for the study of physical properties of alloys, including the structural, magnetic, electronic, and metallurgical properties of actinide metals, alloys and compounds from various operations. A muffle furnace with an argon atmosphere is used for testing sample homogeneity or compatibility, and for temporary storage. Measurements include dilatometry (thermal expansion) and electrical resistivity. A Carver press is used to produce sample wires and pellets. The process takes place in Room 113, glovebox G 187. The actinide metals, alloys, and compounds are returned to the originating P/S Code (References D011 and D029).

*Burst Testing* involves the placement of hemi-shells on a test stand. A buffered test solution is pumped into the shell, pressurizing it until it bursts. Strain gauges monitor the deformation of the shell. The test solution is sodium tetraborate and sodium hydroxide and is filtered and reused. The solution is eventually discarded in the caustic

waste line to the RLWTF at TA-50. Strain gauges have electrical contact points that are tin-lead solder. No solvents are used. The tested hemi-shells are sent to the vault for storage (References D011 and D029).

The *Special Recovery Line* (SRL) conducts pit disassembly on pits which are contaminated with tritium. Tritium is recovered if it is above a specified activity. Separation of pit components is done using a special abrasive cut-off wheel. The pit is cut in half, and the shells are cleaned with copper wool and Freon TF. Scrap is sent to recovery or to waste management depending on whether the material is SNM or not. After the shells are cleaned with the copper wool and Freon TF, they are placed in an ultrasonic bath for cleaning using product SF-2I. Tritium-contaminated water is collected and poured over zeolite absorbent for disposal. Small-scale decontamination of tritium-contaminated plutonium and other SNM is done in the SRL furnace. The SRL furnace area consists of different sections, including metal handling, tritium removal furnace, equipment for collecting tritium liberated in furnace, and effluent treatment system. The procedure that describes the operation of the furnace and furnace gas treatment system contains no details on disposition of output materials, or post-run cleaning operations. Plutonium, uranium, and tritium are sent to the vault for storage. Plutonium metal is also sent to casting, machining, or salt stripping for reuse/recovery (References D011 and D029).

*Thermal Hydride/Dehydride:*

a) Plutonium Hydriding System. The plutonium hydriding process studies the reactions of plutonium alloys and other actinides with hydrogen and other gases. The process takes place in Room 114, glovebox 110, and uses no chemicals other than the gases. The plutonium alloys and actinides are returned to the originating P/S Code (Reference D029).

b) Operating the Hydride-Dehydride Systems. The hydride-dehydride operating procedure describes how to safely form plutonium hydride, and then to decompose it to plutonium metal. Three phases are involved: phase one uses hydrogen gas in large amounts and dehydriding is done in a separate reactor. Phases two and three use a closed loop, minimal hydrogen gas, and a single reactor. The process takes place in Room 114, GB 116, GB 119 and GB 154. No chemicals are used besides the gases. The plutonium metal is sent to the vault for storage (Reference D029).

*Welding* operations fall into two categories: encapsulation of radioactive isotopes and other welding operations. Two methods of welding are employed: a gas tungsten arc welder and an electron beam welder. Encapsulation of radioactive isotopes involves placing the isotope to be sealed into a stainless-steel capsule and subsequently welding the capsule closed. The exterior of the capsule is cleaned with Freon TF. The Freon TF is allowed to evaporate; hence no wiping of the capsule surface with rags is required. Other welding operations include welding of plutonium samples on vanadium in an argon atmosphere, brazing gold to repair platinum frits, welding titanium to repair

titanium boats, and welding of aluminum. No welding of lead occurs. Welding outside of the glovebox line is also done under this P/S Code. The welded parts are either returned to the originating P/S Code or sent to the vault for storage (Reference D029).

*Z Machine Experiments:*

The Z machine was developed to simulate nuclear explosions and conduct testing to ensure the viability of the nuclear weapons stockpile. The Z machine is also used to evaluate the effects of X-rays on various weapon components and materials. LANL and SNL have developed a long-term program for performing experiments on the Z machine using transuranic materials produced at TA-55. LANL requests and oversees Z machine experiments at SNL, including the Plutonium Isentropic Compression Experiments (Pu-ICE) which create conditions on a small scale similar to those experienced by matter with the detonation of nuclear weapons. The Pu-ICE containment systems used in the experiments are manufactured/machined components made up primarily of ferrous metals (97.2% by weight) and non-ferrous metals (2.4% by weight), with minor amounts of other materials such as carbon, epoxy, glass, plastic, rubber, and vacuum grease. TA-55 first fabricates the plutonium targets and loads them into the load assembly component of the containment system. The load assembly component is then shipped to SNL. The containment system consists of three parts: an ultra-fast closure valve and vent tank, an upper containment chamber, and a load assembly. SNL performs the experiment in the Z machine and temporarily stores the resulting Pu-ICE post-shot containment system in a 55-gallon drum. As part of the experiment detonators with high explosives are used; however, the high explosives are completely expended during the experiment. LANL owns the plutonium used in the Pu-ICE and maintains ownership of the associated waste (i.e., TA-55 is the waste generator). The post-shot containment systems are then shipped back to TA-55 to complete the certified characterization process and final disposition. It is estimated approximately 30 post-shot containment systems will be generated through fiscal year 2016 (References C237, C238, C239, D092, D093, and D094).

### 4.4.6 Pyrochemical and Chloride Operations

Pyrochemical operations include metal preparation, metal purification, and ancillary metal production operations (chloride operations and metal oxidation). Pyrochemical outputs are most often high-purity metal feed materials for metal operations (References D011 and D028).

<u>Metal preparation includes the following:</u>

In the single pass *Direct Oxide Reduction* (DOR) operation, plutonium oxide and calcium metal are reacted in molten calcium chloride ($CaCl_2$) to produce plutonium metal. The reaction is conducted in an MgO crucible. After cooling, a plutonium metal button is removed by breaking the crucible. A layer of salt above the button contains

unreacted oxide and metal shot, which is sometimes recovered by heating with addition of fresh salt plus calcium metal (Reference D028).

*Multiple-Cycle Direct Oxide Reduction* (MCDOR) is used to minimize the salt waste. During the MCDOR operation, the molten salt is regenerated by sparging the $CaCl_2$-CaO mixture with chlorine gas between multiple plutonium metal production runs. After approximately five cycles of metal production, the mixture is cooled and the salt and metal phases are separated. The plutonium metal is sent to casting or electrorefining. Impure plutonium metal is sent to molten salt extraction. Salts and crucibles above the DL are sent to chloride operations or the vault. Salts and crucibles below the DL are sent to solid waste packaging for disposal. Caustic solution from the chlorine off-gas scrubber is sent to chloride operations or the RLWTF (References D011 and D028).

*Metal Preparation Line* is no longer active, but produced plutonium metal from fluoride salts. Hydrogen fluoride gas was reacted with plutonium oxides obtained from calcination of oxalate or peroxide precipitates from the aqueous nitrate or chloride process lines. The plutonium fluoride was further reacted with calcium metal to produce plutonium metal, which could then be recovered as a small globule, or button, by breaking the crucible. This operation generated only legacy waste (References D011 and D028).

<u>Metal purification operations include the following:</u>

MSE is used to separate americium and the more reactive elements such as rare earth elements, alkali metals, and alkaline earth metals from plutonium metal (Reference D048). This operation is employed only if the americium content is greater than 1,000 parts per million (ppm). In the original operation (from 1979 to 1988), magnesium chloride ($MgCl_2$) was added to the impure plutonium metal in a eutectic mixture of sodium chloride (NaCl) and potassium chloride (KCl), contained in a MgO crucible, and heated to 750°C. The $MgCl_2$ oxidized americium to americium chloride although some plutonium was also converted to the chloride salt form. In 1988 and continuing to the present, the MSE operation uses $CaCl_2$, NaCl, KCl, and plutonium chloride ($PuCl_3$) produced by in-situ chlorination in a tantalum or MgO crucible. Ninety percent of the americium and ten percent of the plutonium are transferred from the feed metal to the salt. After cooling, the salt and metal are mechanically separated. The salts and crucibles above the DL are transferred to the vault or chloride operations. Salts and crucibles below the DL are sent to solid waste packaging for disposal. The plutonium metal is sent to electrorefining or metal oxidation. Caustic solution from the chlorine off-gas scrubber is sent to chloride operation or the RLWTF (References D011 and D028).

The *Electrorefining* (ER) operation takes impure metal from the MSE and DOR/MCDOR operations and produces high purity plutonium metal. Impure plutonium is cast as an anode, which is then placed in a MgO crucible with a salt mixture, a metal cathode

(typically tungsten), and a seeding reagent that is $MgCl_2$, NaCl, or KCl. After the anode and salt are melted, current is applied to the system, and plutonium at the anode is oxidized to plutonium ions that travel to the cathode and are reduced back to the metal state. Impurities in the original plutonium anode that are more electropositive or have a greater negative free energy of formation than plutonium (including barium and americium) dissolve and remain in the salt, while impurities more electronegative than plutonium (including cadmium, chromium, lead, and silver) remain in the anode. After cooling, the crucible is broken and the residues are physically separated from the high purity product metal. Anode heels were sent to pyroredox from 1984 to 1986. Currently, salts and crucibles above the DL are sent to chloride operations or the vault. Salts and crucibles below the DL are sent to solid waste packaging for disposal. Purified plutonium is sent to casting and the vault. Caustic solution from the chlorine off-gas scrubber is sent to chloride operation or the RLWTF (References D011 and D028).

*Ingot Casting* is included in the Electrorefining section of pyrochemical operations. Metal is melted in a MgO crucible to cast the ingot (References D011 and D028).

From 1987 to 1989, secondary solvent metals such as cadmium, bismuth, lead, and gallium were added to experimental studies of the ER operation (References D011 and D028).

<u>Ancillary metal production operations include the following:</u>

*Chloride Operations:*
The overall goal of chloride operations is to recover plutonium from scrap and residues and produce a purified plutonium oxide for conversion to metal. The feed sources have included plutonium residues from pyrochemical operations, Pu-Be neutron sources, analytical chemistry laboratory solutions, and residues from other DOE facilities. Chloride operations can be broken down into the following four steps (Reference D007):

- Pretreatment
- Dissolution
- Purification
- Hydroxide precipitation

*Pretreatment* for chloride operations is discussed in the *Head-end Operations* section of special operations (refer to Section 4.4.4).

*Dissolution* uses hydrochloric acid to leach and dissolve plutonium from salts, scrap, crucibles, residues, and various solutions, including solutions from the analytical chemistry laboratory. Enriched solutions undergo further purification and solid wastes are discarded as debris waste or sent to cement fixation in nitrate operations (refer to Section 4.4.2) (Reference D007).

Controlled
Copy



*Purification* includes solvent extraction, ion exchange and oxalate precipitation, depending on the chemical nature of the material to be purified. Ion exchange columns are used to collect plutonium and to separate plutonium from impurities. Enriched solutions may be further treated with oxalic acid to precipitate plutonium oxalate. The resulting plutonium precipitate is sent to nitrate operations to be calcined and eventually to the vault. The liquid solution (filtrate) goes to hydroxide precipitation for further processing. Solid wastes are discarded as debris waste or sent to cement fixation for immobilization. Tetrachloroethylene, which was used in the solvent extraction process until 1992, contaminated the debris waste and the liquid waste absorbed in vermiculite (Reference D007).

*Hydroxide Precipitation* takes plutonium in filtrate solutions from the purification steps and precipitates it with potassium or sodium hydroxide. Heavy metals are concentrated in the plutonium-rich hydroxide cakes. The sources of heavy metals vary but may include one or more of the following: (a) feed materials that consist of or contain these metals; (b) leaching of chromium from stainless-steel equipment components; or (c) the use of silver salt (until 1994) in the measurement of chloride content. The resulting plutonium-enriched hydroxide cakes may become feed material for nitrate operations, be returned to the dissolution step for re-processing, may be sent to cement fixation for immobilization, or may be discarded as solid waste if they meet the approved DLs. Liquid meeting the TA-50 WAC is sent to the TA-50 RLWTF using the caustic waste line (Reference D007).

In *Metal Oxidation* small pieces of metal remaining on furnace or crucible surfaces are collected for conversion to the oxide phase. These metal pieces are placed in a furnace for the conversion process. The oxide is then transferred to the vault (References D011 and D028).

*Salt Stripping* is no longer an active operation, but the MSE and ER salts were further treated by salt stripping, oxygen sparging or carbonate oxidation, and salt distillation. The salt stripping operation treated the residue by melting and stirring the salt with calcium metal in a MgO crucible at 850°C. This treatment reduced the plutonium in the salt to metal and allowed the metal to coalesce for physical removal and recovery. After cooling, the crucible was broken and the metal physically separated and recycled to the ER operation or burned to oxide and sent back through aqueous recovery. The crucible shards were leached in hydrochloric acid, and then discarded (References D011 and D028).

Oxygen sparging and carbonate oxidation (since 1996) were used to ensure that any plutonium, americium, or metallic sodium or potassium left in the salts was converted to nonpyrophoric oxide forms (References D011 and D028). Vanadium pentoxide was used in place of carbonate to convert metals to oxide as part of the salt stripping operation from February to June 1998. Wastes that potentially contain residual vanadium pentoxide were, at one time, assigned the EPA hazardous waste code P120.

However, this assignment has been rescinded: see Sections 5.4.3.2, 6.4.3.2, 7.4.3.2, and 8.4.3.2 (Reference D028).

*Salt Distillation* is no longer an active process, but allowed for the recovery of plutonium oxide from the chloride salt and produced purified chloride salt for reuse (References D011 and D028).

The *Pyroredox* operation was used to recover plutonium from spent anode heels in the mid- to late 1980s. The anode heel was polished with calcium metal to remove surface oxide, and then oxidized to plutonium (III) with zinc chloride in molten KCl, forming $PuCl_3$. Elements more electropositive than zinc (including barium) were oxidized into the salt phase, and the zinc formed a metal button. The salt was then mixed with calcium metal in $CaCl_2$ to reduce the plutonium to the metal phase, as well as to reduce all elements more electronegative than calcium. The salt phase containing small amounts of the impurity barium was mechanically separated from the metal phase and discarded. The metal phase containing zinc was placed in the vault or further treated, and the plutonium eventually was routed back to ER. This operation generated only legacy waste (References D011 and D028).

The *Metal Coalescence* operation is no longer active. Metal coalescence was used for plutonium turnings to coalesce the turnings into a metal button. Calcium metal and $CaCl_2$ were added to a MgO crucible along with the turnings and melted. Salts and crucibles above the DL were sent to chloride operations for recovery. Salts and crucibles below the DL were sent to solid waste packaging for disposal. Plutonium metal was sent to ER or the vault (References C131, D011, and D028).

The *Neptunium* operation processed neptunium contaminated residues from the vault in 1993. This operation generated only legacy waste (Reference D028).

*Plutonium Trichloride Preparation* was accomplished by bubbling a carrier gas (such as chlorine) through carbon tetrachloride and passing the mixed gas stream through a bed of plutonium oxide at 500 - 600°C before being absorbed in a 5 - 6 molar potassium hydroxide solution. In this operation (January 1987– June 1989) the carbon tetrachloride was broken down into phosgene, carbon monoxide, and carbon dioxide gases. In June 1989 the operation switched to the use of phosgene gas as the carrier gas until the operation ended in May 1991. Feed material was high purity oxides from the vault or from other P/S Codes. The product plutonium trichloride was reduced to metal by the MSE or ER operations. This operation only generated legacy waste (Reference D028).

### 4.4.7 Pu-238 Operations

*Heat Source Fabrication:*
As described in Section 4.2.2, Pu-238 heat sources fabricated at TA-55 included the GPHS, LWRHU, and MWG sources. Current heat source production involves fuel fabrication and scrap and process residues processing. The primary P/S Code

associated with heat source fabrication operations described in this section is P1 (routine Pu-238 heat source). Pellet production and welding and decontamination operations were also part of heat source fabrication but they are no longer active (References C198 and C220).

*Fuel Fabrication:*
The source of all feed material for Pu-238 fuel fabrication is oxide, originating directly or indirectly from the SRS K Reactor. The feed material selected for fabrication is weighed then prepared using splitting, ball milling, slugging and screening, and granule seasoning. The material also undergoes oxygen isotopic exchange, involving the replacement of oxygen-17 and oxygen-18 with oxygen-16 by heating the feed material in a furnace (750°C). In GPHS processing prior to its inactivation and LWRHU processing, oxygen exchange is followed by heating to 1,000°C to release alpha-decay helium from the plutonium oxide crystal structure. The fuels are further heated or "seasoned" at temperatures ranging from 1,100 to 1,600°C and the resulting oxides are sent to be hot pressed into fuel pellets (References C192, C194, C212, C220, D080, and M285).

During the fuel fabrication process, analytical samples are frequently required for both Pu-238 oxide feed material and product specimens either to characterize the material or to determine whether the material meets current production specifications. The primary sampling capsules containing the oxide samples are cleaned in an ultrasonic bath with ethanol and allowed to air-dry before being placed into a secondary plastic container. Sampling tools are wiped down with cheesecloth containing ethanol (References C195 and P180).

The oxide samples are taken to perform particle size analysis. Ethylene glycol is used to suspend the Pu-238 oxide powder in a disposable polystyrene cuvette. The cuvette is sealed with a polystyrene cap coated with Duco cement. After the glue has set, the cuvette is ultrasonically cleaned in a water bath containing a high-purity soap (e.g., Alconox), is cleaned a second time in a bath of distilled water, and is wiped down with a cheesecloth pad soaked in Fantastik (nonhazardous) cleaning solution. The cuvette is then transferred to another hood for final decontamination with Fantastik-soaked cheesecloth. This process of cleaning and transferring the cuvette occurred up to 1994. From early 1994 onward, the water bath does not contain soap and Fantastik is not used because all work is performed in the same glovebox line and there is no need to decontaminate the cuvette. Before 1994, if the water was radioactively contaminated, it was discarded to the TA-50 RLWTF. Since 1994, the water has been evaporated (References C197 and M286).

Upon completion of the analysis, the ethylene glycol containing the Pu-238 oxide is poured through a coarse sieve and collected in a polyethylene bottle. When 200 - 500 milliliters of ethylene glycol has accumulated in the bottle, the contents are poured through a filter. The residue and filter paper are allowed to dry and are sent to a plutonium recovery process. The contaminated ethylene glycol is collected until a

sufficient amount is available to discard, and then it is poured onto a bed of vermiculite for absorption (References C194 and M286).

The *Scrap and Process Residues Processing* operation receives materials from the vault and various other operations, such as fuel fabrication, pellet production, calorimetry, and metallography. This is a physical process consisting of weighing, sorting, segregating, and loading into a shipping container. The product from this process either goes to the vault or feeds into calorimetry operations (References D080 and M285).

The *Metallography* process began in 1992 and is still active. It receives feed material from P/S Code P1 operations in the form of Pu-238 oxide fuel recovered from encapsulated heat sources, impacted heat sources, fuel pellets, or other sources. The metallography process is a physical process involving cutting, mounting, grinding, polishing, photography, and etching of Pu-238 fuel specimens (References C194 and M287).

An epoxy-based mounting resin, hardener, and mount filler is used to mount the Pu-238 oxide. The epoxy resin, hardener, and mount filler consist of diethylenetriamine, Epon Resin 8132 (nonhazardous), and a Citofix/Durofix liquid (nonhazardous). Epon Resin 8132 is a liquid that polymerizes when mixed with an amine (e.g., diethylenetriamine). The Citofix/Durofix liquid is also a polymer. One end of a phenolic ring is covered with aluminum tape. The Pu-238 oxide sample is placed in the center of the interior surface of the tape. The mixture of epoxy resin, hardener, and filler is poured into the mount ring. The mounted sample is placed in a small aluminum film can, which is placed in a pressure bomb. The bomb is pressurized for a minimum of ten hours, vented, and the sample is removed. The mounted Pu-238 oxide sample then undergoes grinding and polishing (References C197 and P181).

Manual grinding and polishing involves moving the mounted sample across wet silicon carbide grinding papers of varying grits that are laid over a glass plate. Between each grinding step and after the last grinding step, the sample is ultrasonically cleaned in distilled water. The mounted sample is polished using aqueous suspensions of aluminum oxide or diamond powder. After polishing, the sample is cleaned in distilled water. Automated grinding and polishing involves using programmable equipment. The grinding process uses a metal or cloth plate that has been coated with an abrasive slurry. This process also involves cleaning the polished sample in distilled water (Reference P181).

Whenever there is a requirement to examine and/or document the Pu-238 oxide grain boundaries, the surface of the polished sample is etched using a solution consisting of hydrobromic, hydrochloric, and hydrofluoric acids. The sample is rinsed with distilled water and allowed to dry (Reference P181).

Residues from the metallography process feed into the P/S Code P1 process. Before 1994, the Pu-238 oxide was physically removed from the plastic mount (no solvent or chemical was used), and the mount was bagged out with other plastic debris. The Pu-238 oxide sample removed from the mount was sent to the P1 scrap and process residue processing operation for plutonium recovery. However, since 1994, the Pu-238 oxide has been left on the mount and archived (stored) in the glovebox line (References C197 and M287).

The waste generated from the metallography process includes aluminum tape, grinding papers and polishing cloths, aqueous abrasive slurries, acid etching solutions, and aqueous washing and cleaning solutions. The grinding papers and polishing cloths are dried and discarded as debris waste, as is the aluminum tape. The aqueous abrasive slurries are feed material for the Pu-238 waste solidification process. Any etching solution remaining on the Pu-238 oxide sample is rinsed off using distilled water and is collected with the aqueous wash solutions. These solutions are also sent to the waste solidification process (Reference P181).

The *Routine Pu-238 Waste Solidification* process of precipitating Pu-238 in waste solutions (P/S R8) has been conducted since 1979 and is still active. The feed material for this process comes from analytical operations, Pu-238 heat source fabrication operations, metallography operations, and other LANL groups. The feed solutions are strongly acidic, contain heavy metals, and have Pu-238 concentrations that are orders of magnitude above the DL for radioactive waste solutions. The solidification process uses sodium hydroxide, ferric nitrate, and phenolphthalein in ethanol to precipitate the Pu-238 (References C194, C196, M293, and P182).

Ferric nitrate solids are dissolved into the feed solutions to act as a flocculent. Concentrated sodium hydroxide solution is then added to convert the acidic solutions into caustic solutions, and cause the ferric ions and the Pu-238 ions in the solutions to co-precipitate as hydroxides. Phenolphthalein solution is used to indicate when the solution is basic. After sedimentation and vacuum filtration, the liquid portion (filtrate) is sampled and alpha-assayed to determine the residual Pu-238 concentration. The sludge is heated (calcined) to oxidize the hydroxides for disposal. This procedure is repeated as necessary for the filtrate until the Pu-238 concentration in the filtrate is below the DL (References P155 and P182).

The waste generated by this process consists of calcined ferric oxide solids containing Pu-238, a caustic solution containing Pu-238 below the DL, and solid debris. The oxide solids are sent to the vault or disposed as waste, depending on the Pu-238 concentration. Waste containers that are predominantly debris may contain small quantities of the oxide solids. The caustic solution is discarded into the caustic drain to the pretreatment plant at the RLWTF (TA-50, Building 1, Room 60) (References P155 and P182).

Controlled
Copy



*Aqueous Scrap Processing* involves the purification of Pu-238 oxide in a nitric acid stream, similar to the recovery operations already established for Pu-239 as part of TA-55 nitrate operations (Reference C210).

During comminution, the weighed Pu-238 solid is ground to a particle size less than five microns. After the comminution, all or a portion of the ground material is put into a dissolution vessel. The Pu-238 solid is dissolved in a mixture of refluxing concentrated nitric acid and hydrofluoric acid for up to eight hours. After dissolution is performed, the Pu-238-rich solution is filtered through a five micron Teflon membrane. A portion of the filtrate may be processed through ion exchange, or the entire filtrate may be treated for oxalate precipitation (References C210 and D080).

Oxalate precipitation involves an acid adjustment of the filtrate with nitric acid while the solution is continuously stirred using the mechanical stir bar. Urea is added to scavenge nitrite salt that could interfere with further chemical pretreatment. Hydroxylamine nitrate is added to adjust the valence of the plutonium to (III). Oxalic acid is added to form a plutonium-oxalate precipitate. The precipitate is filtered, and calcination converts the Pu-238 oxalate to Pu-238 oxide product. The solid product is cooled, weighed, and stored (Reference D080).

The dissolution Pu-238 filtrate destined for ion exchange may undergo an aluminum nitrate treatment. The dissolution Pu-238-filtrate is added to aluminum nitrate dissolved in dilute nitric acid, followed by a filtration step to collect any formed solids (typically, the aluminum nitrate treatment is not performed). The filtrate then undergoes a pretreatment involving urea, sodium nitrite, and ferric salt prior to ion exchange. The plutonium-rich eluate is collected and undergoes oxalate precipitation as described above. The plutonium-lean effluent, which contains impurity metal ions, as well as the aluminum from the aluminum nitrate treatment, is neutralized to pH 10-12 with sodium hydroxide. Under these neutralization conditions, the majority of the impurity ions and Pu-238 (not precipitated as an oxalate precipitate) will precipitate as metal hydroxides (References C210, C213, D079, and D080).

The hydroxide precipitate is calcined then stored, and the hydroxide filtrate is sampled to determine the radioactivity level. Waste containers that are predominantly debris may contain small quantities of the metal hydroxides. If above the DL, the hydroxide filtrates are transferred to the residue solidification process. In this process, soluble Pu-238 is recovered with ferric nitrate and sodium hydroxide, and the filtrate resulting from the solidification process is sent to the TA-50 RLWTF through the caustic waste line. The Pu-238 in the hydroxide filtrates can also be recovered by an ultrafiltration/polymer filtration process operated by NMT-11 personnel. The Pu-238 oxide product is sent to P/S Code P1. The hydroxide cakes are stored either in the vault or in the glovebox line under P/S Codes MM for disposal or ASP for recovery (References C210 and D080).

*Induction Heating and Levitation* is a technique used to achieve minimal contamination of conductive material. This technique uses Pu-238 metal from various operations and produces small quantities of uncontaminated metal by suspending and then melting the material inside of an induction coil with induction heating. Once the material has melted, the power is shut off, and the molten mass can be dropped or forced into a mold for forming. This process was designed to drive off impurities from the metal by melting it in a vacuum and not reintroducing impurities from a container during the time the material is in the molten state. The purified Pu-238 metal is sent to the vault (References C220 and M306).

*Pu-238 Direct Oxide Reduction* was an activity that was performed in October 1998 and October 1999 to produce Pu-238 metal for the accelerated plutonium aging program. There are no current plans to perform this operation again, but the code is still active. In this process, plutonium oxide and calcium metal are reacted in molten calcium chloride to produce plutonium metal. The reaction is conducted in a MgO crucible at 820° to 875°C. The reaction proceeds to completion when excess calcium is present and when sufficient calcium chloride is available to dissolve the calcium oxide product. After cooling, a plutonium metal button is removed by breaking the crucible. The salts are exposed to air to oxidize pyrophoric metals that might be present. The salt is then either routed through aqueous recovery operations to recover the plutonium or discarded as waste with the crucible pieces. The plutonium button is sent to the vault (References C211, C221, D080, and P189).

Traditionally, the *Thermal Decomposition of Cellulose* process incinerated organic-based materials contaminated with plutonium to ash to reduce the volume of waste generated or to recover the plutonium using a nitrate dissolution process. Due to increasingly stringent regulations governing the combustion products associated with incineration, the incinerator process was modified to thermally decompose organic-based materials in an argon atmosphere in 1995. The thermal decomposition unit is also referenced in nitrate operations. It consists of a pyrolysis or passivation chamber, a caustic scrubber (potassium hydroxide) unit, and vacuum system. Organic-based materials designated for passivation have been limited to rags (cheesecloth) contaminated with nitric acid solution (References C200, D071, M299, and P156).

During processing, oil contaminated rags are separated from nitrated rags. The nitrated rags are moistened with water to reduce reactivity and excess water is removed using a filtration screen. The rags are then combined, placed in a furnace can, and reduced to ash in an argon atmosphere in the furnace. The ash, rinse water, filter residues, and caustic solution are further processed to recover the plutonium, if these materials are determined to exceed the DL. These materials are sent for disposal, if below the DL. Liquid waste below the DL is sent to the RLWTF at TA-50 (References C200, D071, M299, and P156,).

The *Routine Scrap Processing*, which operated from 1988 to 1996, received Pu-238 feed materials (Pu-238 oxide) from calorimetry operations, heat source operations (P/S Codes P1 and GPHS), and the vault. The scrap processing operation involved opening, weighing, sorting, and segregating the Pu-238 oxide that arrived in a stainless-steel inner shipping container (EP-60). The Pu-238 oxide was then transferred into an outer shipping container (EP-61) and sent to the calorimetry process, and then to the vault (References C194, M288, and M289).

The *Recovery of Pu-238 Oxide from Contaminated Iridium* process occurred from 1990 to 1992. The feed material for this process came from metal items in the iridium inventory in PF-4 or in the CMR Facility at TA-3. This process used both molten magnesium chloride and electrochemical dissolution to remove Pu-238 from iridium (References M290 and M291).

The first step in this process involved immersing the Pu-238 oxide-contaminated iridium metal in molten magnesium chloride. The magnesium chloride was melted in a MgO crucible. The same salt was used for subsequent runs until it had lost its effectiveness. The iridium shells were placed into a tantalum basket and immersed in the molten salt. At the end of the treatment, the iridium metal was removed from the salt and the salt coating on the metal was removed with a water wash. This water wash was sent to the Pu-238 solidification process. The spent salt and crucibles were bagged out and assayed before being discarded as Pu-238 contaminated TRU solid waste. The iridium metal was sent to the vault unless additional treatment was necessary (References C194 and C197).

If further treatment was required, the iridium metal underwent electrochemical dissolution. The electrolyte solution consisted of a dilute mineral acid (nitric acid, hydrochloric acid, or sulfuric acid) with optional salt. The iridium metal was immersed in the solution, and a current was passed between the iridium metal and a graphite reference electrode. At the end of the run, the iridium metal was washed with water and allowed to dry. The clean iridium metal was sent to the vault. The spent electrolyte solution, which was acidic and contaminated with small amounts of iridium and Pu-238, and the water wash were sent to the Pu-238 solidification process (References C197, M290, and M292).

The *Recovery of Pu-238 from Sucrose Solutions* occurred from 1979 to 1988. The feed material for this process consisted of a 35 percent sucrose solution composed of sodium pyrophosphate, water, and sucrose. Sucrose solutions were used as a dispersive medium in particle size analysis of Pu-238 oxide; therefore, the feed solutions contained recoverable amounts of Pu-238 oxide (References D080 and M294).

The Pu-238 was recovered from these sucrose suspensions by filtering out the Pu-238 oxide in a ceramic filter boat and evaporating the solution to dryness over low heat. The Pu-238 oxide residue was scraped off the filter paper and calcined, then sent

off-site for reprocessing. The residue from the evaporated solution was calcined and sent for discard if the Pu-238 content was below the DL (References D080 and M294).

The *Pellet Production* process is no longer active. The original feed material for the pellet production process consisted of Pu-238 oxide from fuel fabrication. This material underwent the physical operations of screening and weighing, die loading, hot pressing, sintering, and dimensioning. The product was sent to the vault and any residues were sent to the scrap and process residues processing operation (References C220, D074, D080, and M285).

The *Welding and Decontamination* process is no longer active. Heat source capsules were welded and a solution of nitric and hydrofluoric acid was used for decontaminating the fuel clads. The clad heat sources were immersed in the solution a minimum of three times to allow the acids to dissolve any plutonium oxide particles on the clad surface. Each time, the heat sources were removed from the acid solution and placed on a rag dampened with water. A rubbing action removed contamination while the heat of the source caused the acid solution and water on the rag to evaporate at a fairly rapid rate. The TRU acid solutions generated by the decontamination steps were neutralized to precipitate plutonium, and the filtrate was discarded into the caustic waste line to the RLWTF at TA-50. The plutonium precipitate was discarded if it met the DL. The only other process chemical, UCAR C-34, was an epoxy for sealing the graphite aeroshell of the LWRHU heat source assembly. The epoxy was not RCRA-regulated (References C220, D080, and M284).

The *Material Reclamation* process is no longer active. The process was used to remove specially identified Pu-238/beryllium (Be) neutron source material from its packaging and place it into packaging authorized for shipment to the WIPP. Waste disposal was chosen over reclaiming the source material because there was no capability for purifying and reclaiming the Pu-238. This process involved the disassembly of source materials retrieved from the vault, crushing and sieving the source material, and packaging the products and byproducts as waste. The original packaging was also disposed of as waste (References C156, D060, and P170).

#### 4.4.8 Facility and Equipment Maintenance Operations

Facility and equipment maintenance operations conducted in TA-55 involve cleaning and decontamination, equipment inspection and replacement, modification and repair of facilities, and general housekeeping. Cleaning and decontamination operations include physical wiping and the use of cleaning solutions (e.g., Fantastik, water) to remove potential contamination and to restore work areas and equipment to their original condition. Paper, plastic, and rags with a cleaning solution are used to remove or contain the spread of contamination. Equipment inspection, calibration, and replacement operations are performed to ensure continued operability and process efficiency. Solid wastes generated from these operations may include paper and plastic wastes, glass, small equipment (e.g., labware, motors, pumps), and small tools.

Modification of facilities include plumbing; electrical fixtures and equipment installation; and installation or removal of gloveboxes, ventilation ductwork, and windows. General housekeeping includes cleaning, repair, and organization of the facility/infrastructure. Solid wastes generated from these operations may include HEPA filters, glass, glovebox gloves, paper, plastic, and rags. Solid waste generated from these operations is disposed of as TRU or LLW waste. General facility maintenance solutions (e.g., wet vacuum water, mop water) are sent to the evaporator or the RLWTF (References D002, D008, D009, D011, D013, D014, D017, D023, D024, D026, D032, D045, M011, P001, P102, and P155).

#### 4.4.9 Decontamination and Decommissioning (D&D) Operations

D&D operations are commonly performed at PF-4 in TA-55 to reduce the amount of floor space posted as radiological controlled areas and to support upgrades to existing facilities and equipment. These efforts assist in contamination control and result in a decrease in the amount of radiological waste generated at TA-55. These radiological controlled areas house the equipment and material used to perform the above listed operations and the waste generated during D&D operations contain the same chemical and radiological contaminants. No hazardous chemicals are added to the waste during the D&D operations. Commercially available, non-hazardous cleaning products, such as Fantastik, are used to remove loose contaminants. The goal of the D&D is to reduce the amount of TRU waste generated as much as possible through decontamination and size reduction (References D002, D013, D014, D026, D034, and D041).

Decontamination operations are used to accomplish several goals, such as reducing occupational exposures, limiting potential releases of radioactive materials, permitting the reuse of components, and reducing the amount of TRU waste generated. Decontamination operations included the use of mechanical and chemical cleaning techniques such as brushing, stripping, washing, and wiping to remove contamination. In addition, physical isolation and draining of equipment are performed when necessary. Based on the radiological contamination, drained liquids are either further treated or solidified. Decommissioning operations included the physical removal of contaminated gloveboxes, equipment, machinery, furnishings, and support systems. This included the removal and size reduction of glovebox internals, process piping and supports, tanks and ancillary equipment, and other fixed equipment such as ducting, wires, conduits, electrical panels, and cabinets. Gloveboxes and equipment are size reduced as necessary and packaged for disposal. Size reduction operations are sometimes performed in other facilities as discussed below in the repackaging and prohibited item disposition section. Secondary waste such as combustibles, metal, and plastic generated during D&D is expected to be part of the waste. D&D operations also included the removal of stored radiological and hazardous materials and other related actions (References D002, D013, D014, D026, D034, and D041).

4.4.10 Waste Repackaging and Prohibited Item Disposition

Waste repackaging and prohibited item disposition can be performed in four facilities outside of TA-55. Containers that fail to meet WIPP criteria are sent to these facilities to be safely remediated. The first facility was established in 1979 at TA-50 as the SRF to size-reduce non-routine items such as decommissioned gloveboxes, ductwork, and process equipment to fit in 55-gallon drums or standard waste box (SWBs). A plasma torch was commonly used during size reduction operations to cut up these large items into manageable pieces. The SRF historically combined waste from multiple facilities and these containers will be identified and characterized under a separate TA-50 waste stream. As LANL TRU waste characterization and certification activities increased, the mission of the SRF was expanded to include various operations to support TRU waste characterization. In 1993, the name of the SRF was changed to the WCRR Facility to reflect the expanded remediation and repackaging mission. Size reduction operations at the WCRR Facility were discontinued around 1997. Recently, the WCRR Facility has started remediating/repackaging nitrate salt waste with an inert absorbent material (e.g., zeolite, kitty litter). The minimum inert absorbent material to nitrate salts mixture ratio is 1.5 to 1. The second repackaging facility, the TA-54 Building 412 facility, operated for a short time in the early 2000s and resumed operations again in 2010. The third facility, the TA-54 Dome 231 Permacon, was established in 2006 at which time CCP personnel began observing operations. The fourth facility, the Box Line Process, began operations in 2012 at the TA-54 Dome 375. All three TA-54 facilities perform the same basic functions including sorting, segregating, size reduction, and repackaging operations on waste containers (e.g., 55-gallon drums) that contain WIPP nonconforming items. The facilities also safely process oversized containers (e.g., FRPs, CMBs). They disassemble oversized containers (e.g., FRPs), process waste items located within, size reduce waste items (if necessary), and process the original packaging (e.g., plywood sheathing). They then repackage these wastes in standard containers (e.g., 55-gallon drums, SWBs) that can be permanently disposed of at the appropriate disposal facilities. These facilities also process (i.e., modify and vent) CMBs in order to load them into ten drum overpacks (TDOPs). Modification of the CMBs includes cutting the edges of the box so it will fit into a TDOP. The original packaging materials (e.g., plywood sheathing) will be managed as either TRU or LLW waste(References C163, C165, C185, D013, D026, D041, D062, D089, D090, D091, P154, P158, P159, P192, P194, P195, P196, P197, P198, P199, P203, and P204).

These facilities are used to perform VE, repackaging, and prohibited item dispositioning of TRU waste. VE is performed to provide information that is used to 1) confirm the waste stream delineation by AK, 2) ensure the absence of prohibited items, and 3) characterize retrievably stored waste with inadequate AK, in lieu of RTR. Waste containers with prohibited items are segregated then dispositioned appropriately and/or repackaged into new containers, during which time liquids are absorbed, sealed containers greater than four liters are opened, and other items (e.g., unpunctured aerosol cans) are removed and segregated if necessary prior to certification and shipment. Waste items with high dose rates may be repackaged into a pipe overpack

container (POC). Current repackaging procedures ensure that waste items placed into a new container originate from a single parent container. Therefore, if repackaging is necessary the original TA-55 characterization is retained. Some secondary waste generated during remediation and repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., metal, plastic bags, plywood sheathing, rigid liner lids cut into pieces). Although these operations are performed outside of TA-55, there is no cross contamination with waste from other LANL facilities for the containers covered in this report (References C150, C177, M316, P154, P158, P159, P192, P194, P195, P196, P197, P198, P199, and P203).

4.4.11 Below-Grade Retrieval Project

Since 1970, TRU waste generated by LANL has been retrievably stored at TA-54, Area G in anticipation of disposal at WIPP. Some of this waste, generated between 1970 and 1998, has been stored below ground. The below ground TRU storage includes a trench containing corrugated metal pipes, Pit 9, four trenches (A–D), and remote-handled (RH) shafts. Based on a review of available AK, only Pit 9 and Trenches A–D contain CH waste from TA-55. LANL has established the Legacy Waste Disposition (LWD) Project to ensure the safe retrieval of containerized TRU waste from below ground storage (References D063, D064, and D067).

Pit 9 was excavated in the spring of 1974 and completed for use in November of 1974. Pit 9 is located in the central portion of TA-54, Area G. Pit 9 is approximately 400 feet long, 20 feet deep, and 30 feet wide. The south end was excavated to an almost vertical slope while the north end has a 6 to 1 slope for access to the pit. The pit was used for retrievable storage of 30-, 55-, and 85-gallon drums, crates, and FRPs containing TRU waste. The primary mission of the Pit 9 LWD Project is to retrieve and relocate 4,082 waste packages containing TRU waste into an inspectable storage configuration (References D063, D064, D065, D066, and M280).

Trenches A–D received TRU waste between 1974 and 1985 for storage until it could be disposed of at WIPP. Trenches A–D were excavated to different dimensions based upon the quantity of waste to be stored and the trench proximity to adjacent disposal pits. Placement of waste into Trench A occurred between March 1974 and October 1974. Trench B was active between April 1976 and April 1977. Waste placement in Trench C began in April 1977 and ended in September 1981. Trench D was active between September 1981 and December 1985. The TRU waste stored in the trenches consists of 30-gallon containers placed inside concrete casks (References D067, D068, M281, and P174).

Controlled
Copy



The primary mission of the LWD Project at TA-54, Area G is to retrieve, characterize, repackage, as necessary, and dispose of below-grade TRU waste. Retrieval operations typically include workspace setup, removal of below ground storage material (e.g., soil, plastic, plywood), inspection of waste containers to be removed (i.e., evaluation of container integrity), radiological survey of the containers, physical removal of the containers using various mechanical means, and workspace cleanup. Retrieved containers that are intact may be washed with water and detergent to remove soil or contamination if found. The wash water is treated separately from the containerized waste. Depending on the type and condition of the retrieved container further repackaging or processing may be required. For instance, drums with integrity or prohibited item (e.g., liquids) issues may be repackaged or overpacked (i.e., 30-gallon drum placed into a 55-gallon drum) in the facilities/operations described in Section 4.4.10. The eventual number of 55-gallon drum equivalents generated will be dependent on the radiological characteristics of the waste containers, and the condition of the retrievably stored below-grade containers. Materials used during retrieval operations that may contaminate the waste include plastic sheeting, bags, and PPE (References C178, D063, D064, D067, and P174).

## 4.5 Waste Certification Procedures

TRU mixed waste in waste streams LA-MHD01.001, LA-CIN01.001, LA-MIN02-V.001, and LA-MIN04-S.001 will be certified in accordance with CCP-PO-001 (Reference 7).

Controlled
Copy



## 5.0 REQUIRED WASTE STREAM INFORMATION: LA-MHD01.001

This section presents the mandatory waste stream AK required by the WIPP-WAP (Reference 1). Attachment 1 of procedure CCP-TP-005 (Reference 8) provides a list of the TRU waste stream information required to be developed as part of the AK record.

### 5.1 Area and Building of Generation

All of the debris waste covered by this AK Summary Report originated from TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations described in Section 4.4. Container-specific records are reviewed for each container to verify the physical composition and origin of the waste stream inventory (References M019, M156, M215, M216, M217, M218, M219, M222, M224, M226, M238, M273, M274, M275, M276, M296, and M298).

### 5.2 Waste Stream Volume and Period of Generation

Waste stream LA-MHD01.001 is mixed heterogeneous debris generated from 1978 to present. Although plutonium operations commenced in 1979, material has been located in TA-55 since 1978. Table 1, LA-MHD01.001 Approximate Waste Stream Volume, summarizes the volume of this waste stream. Of the 16,591containers in this waste stream, 713 are presently in below-grade retrievable storage at TA-54, Area G. The projected volume of retrievably stored below-grade containers may change based on the radiological characteristics and the condition of the containers. The future projected generation of heterogeneous debris waste from fiscal year 2014 through fiscal year 2016 is approximately 2,400 55-gallon drums (504 cubic meters). There is no projected end date for the termination of operations that generate this waste stream (References C152, C153, C175, C179, C219, C225, C232, C233, C240, D025, D041, M156, M241, and M298).

Controlled
Copy



Table 1. LA-MHD01.001 Approximate Waste Stream Volume

| Containers | Volume (cubic meters) |
|---|---|
| 174 30-gallon drum | 19.76 |
| 15,420 55-gallon drums (includes POCs) | 3,238.2 |
| 600 85-gallon drums | 192 |
| 3 110-gallon drums | 1.25 |
| 308 SWBs | 579.04 |
| 86 Other Containers | 490.2 |
| 16,591Total | 4,520.45 |

## 5.3 Waste Generating Activities

Wastes are generated from materials used during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations described in detail in Section 4.4 and include (References D025 and D041):

- Preparing ultra-pure plutonium metals, alloys, and compounds
- Preparing (on a large scale) specific alloys, including casting and machining these materials into specific shapes
- Determining high-temperature thermodynamic properties of plutonium
- Reclaiming plutonium from scrap and residues produced by numerous feed sources
- Disassembling components for inspection and analysis
- Manufacturing of parts on a limited basis
- Processing mixtures of plutonium and uranium oxides for reactor fuels
- Pu-238 generator and heat source R&D, fabrication, testing, and recycling

## 5.4 Type of Wastes Generated

This section describes the process inputs, Waste Matrix Code assignment, WMPs, radionuclide contaminants, and RCRA hazardous waste determinations for waste stream LA-MHD01.001. The waste stream is characterized based on knowledge of the

materials, knowledge of the operations generating the waste, and physical descriptions of the waste.

### 5.4.1 Material Input Related to Physical Form

Waste stream LA-MHD01.001 consists of mixed heterogeneous debris waste generated in TA-55. The debris waste includes paper, rags, plastic, rubber, wood based HEPA filters, other plastic based and cellulose based items (e.g., PPE), noncombustible (e.g., metal and glass), and lesser quantities of homogeneous solids (less than 50 percent by volume) contaminated with nuclear materials (e.g., americium oxide). Plastic-based waste includes (but may not be limited to): bottles, dry-box gloves (unleaded neoprene base), gloves including leaded gloves, ion-exchange resins, Plexiglas, polyethylene and vinyl, polystyrene, polyvinyl chloride plastic, tape, Tygon tubing, and vials. Rubber- and Teflon-based waste includes rubber gloves, Teflon tape, gaskets, and stoppers. Cellulose-based waste includes (but may not be limited to): booties, cardboard, cotton gloves, coveralls, laboratory coats, paper, rags, wood, and similar materials. Noncombustible debris waste includes (but may not be limited to): bottles (e.g., glass), cans (e.g., steel and brass), composite HEPA filters, crucibles, equipment (e.g., furnaces, foundry parts, machine tools and parts), fluorescent bulbs, glass, gloveboxes, glovebox windows, graphite, lead (e.g., shielding), metal pipes, miscellaneous labware, metal (e.g., beryllium), motors, pumps, slag, small tools, and ventilation ductwork. Homogeneous solid waste (less than 50 percent by volume) includes: hydroxide cake/filter materials, salts, and ash residues. Hydroxide cake/filter materials are composed of precipitated materials such as americium cadmium, calcium, chromium, iron, lead, magnesium, mercury, neptunium, plutonium potassium, silver, sodium hydroxide, thorium, and uranium. Salt waste can include varying mixtures of calcium chloride, cesium chloride, lithium chloride, magnesium chloride, potassium chloride, sodium chloride, zinc chloride, residual entrained calcium and zinc metal, and various plutonium and americium compounds. Ash residues originate from the thermal reduction of organic-based waste products that were contaminated with plutonium (e.g., plastics, rubber, wood, cellulosics, and oils) and may include incomplete combustion products such as small pieces of plastic and metal debris items. The waste stream also includes a small fraction liquids (e.g., waste oils and organics) and solids (e.g., nitrate salts) absorbed or mixed with absorbent materials which may include Ascarite II, (sodium hydroxide coated silicate), diatomaceous earth (silica and quartz), kitty litter (clay), vermiculite (hydrated magnesium-aluminum-iron silicate), and/or zeolite (aluminosilicate mineral). Finally, some secondary waste generated during remediation/repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770 [sodium polyacrylate]), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., metal, plastic bags, plywood sheathing, rigid liner lids cut into pieces) (References C150, C176, C177, D025, D041, D083, D084, M019, M215, M216, M217, M218, M219, M222, M316, and P178).

#### 5.4.1.1 Waste Matrix Code

Based on the evaluation of the materials contained in this waste stream and LANL waste management practices, this waste stream is comprised of greater than 50 percent by volume heterogeneous inorganic and organic debris such as metal, glass, graphite, plastic, cellulosic materials, rubber, and filters. Therefore, Waste Matrix Code S5400, Heterogeneous Debris, is assigned to waste stream LA-MHD01.001. Although the waste stream, as a whole, is comprised of more than 50 percent by volume heterogeneous debris, any container may include nearly any percentage of the WMPs listed in Section 5.4.1.2. However, containers including greater than 50 percent by volume homogeneous solids (e.g., hydroxide cake/filter materials, salts, and ash residues) will be excluded from this waste stream (References 2, D025, D041, D083, D084, DR001, DR005, M019, M156, M157, M158, M215, M216, M217, M218, M219, M222, M224, M226, M238, M273, M274, M275, M276, M296, and M298).

#### 5.4.1.2 Waste Material Parameters

To estimate the WMPs for waste stream LA-MHD01.001, WMP data were obtained from the Waste Data System (WDS), formerly known as the WIPP Waste Information System (WWIS) database, as of October 3, 2006. The WMP data were derived from RTR and VE of this waste stream by the CCP TRU Waste Certification Program (TWCP) at LANL for this waste stream. In cases where WDS data included both RTR and VE data for the same container, only the VE data was included in this assessment.

The WMPs for waste stream LA-MHD01.001 were estimated by reviewing the WDS waste container inventory records for 1,917 containers. The WDS data provides a weight for packaged waste materials, which were categorized into one or more of the following WMPs: iron based metals/alloys, aluminum based metals/alloys, other metals/alloys, other inorganic materials, cellulosics, rubber, plastics, and inorganic matrix. The 1,917 containers included in the evaluation represent approximately 14 percent of the current waste stream (Reference C179). The waste generation date range for containers included in the evaluation is from December 1979 to June 2004, compared to the generation date range for this waste stream of November 1979 to present. Therefore, it is assumed that the WMP data for the 1,917 containers are representative of waste stream LA-MHD01.001 as a whole. Average, minimum, and maximum WMP weight percentages were calculated using the WDS data, and the results of this analysis are presented in Table 2, Waste Material Parameter Estimates for LA-MHD01.001.

The statistical analysis of the data is documented in a memorandum (included with Attachment 6) as required by CCP-TP-005 (Reference 8).

Table 2. Waste Material Parameter Estimates for LA-MHD01.001

| WMP Description | Average Weight Percent | Weight Percent Range |
|---|---|---|
| Iron-based Metals/Alloys | 42.05% | 0.00% - 100.00% |
| Aluminum-based Metals/Alloys | 0.17% | 0.00% - 77.51% |
| Other Metals | 5.04% | 0.00% - 91.45% |
| Other Inorganic Materials | 27.27% | 0.00% - 100.00% |
| Cellulosics | 3.48% | 0.00% - 95.86% |
| Rubber | 5.22% | 0.00% - 98.67% |
| Plastics (waste materials) | 16.10% | 0.00% - 100.00% |
| Organic Matrix | 0.00% | 0.00% - 0.00% |
| Inorganic Matrix | 0.67% | 0.00% - 72.48% |
| Soils/Gravel | 0.00% | 0.00% - 0.00% |
| **Total Inorganic Waste Average** | **75.20%** | |
| **Total Organic Waste Average** | **24.80%** | |

### 5.4.2 Radiological Characterization

#### 5.4.2.1 Pu-238, Pu-239, Pu-240, Pu-241, and Pu-242

The primary plutonium material type inputs for the plutonium recovery process are listed in Table 3. However, other MTs are occasionally introduced as feed material. The assignment of MTs is used to describe the isotopic composition of common blends of radioactive materials used within the DOE complex (References C186, C194, C209, C219, C222, D025, D073, D074, D076, D080, D083, M019, M156, M159, M215, M216, M217, M218, M219, M222, M238, M273, M274, M275, M276, M283, M295, and M309).

Recovery operations are not expected to alter the plutonium isotopic ratios of the feed material. The material type used in the operation generating each waste item is documented on generator records; however, in many cases, items of different material types are packaged into the same waste container, so that a variety of plutonium isotopic ratios may be detected by radioassay. In addition, cross-contamination of equipment with different material types can lead to variable material types detected by radioassay (References D025, M019, M156, M159, M160, M215, M216, M217, M218, M219, M222, M238, M273, M274, M275, and M276).

The primary MT that feeds into the Pu-238 operations described in this report is heat source grade plutonium (MT 83), and these operations are not expected to alter the plutonium isotopic ratios of the feed material. Table 3 identifies the isotopic distribution of MT 83 based on 100 isotopic analyses and was decay corrected assuming the material was not chemically separated for 45 years (References C125, C186, C194, C209, C219, C222, D073, D074, D076, D080, D083, M283, M295, and M309).

5.4.2.2 U-233, U-234, U-235, and U-238

U-233 and U-238 are not normally components of the plutonium MTs handled at PF-4. U-235 is present from the decay of Pu-239 only at 0.1 percent by weight of the total plutonium content. However, all three isotopes have been introduced as special material. In addition, uranium-plutonium oxide mixtures have been processed to recover the plutonium. Significant quantities of U-234 will be present from the decay of Pu-238 in containers originating from heat source plutonium operations (References C222 and D025).

Table 3. Average Isotopic Content of Plutonium Material Types and Enrichments

| Material Type (MT) | Plutonium Isotope (Wt. %) | | | | | | Estimated Weight% Relative to Total Plutonium[a] | | |
|---|---|---|---|---|---|---|---|---|---|
| | Pu-238 | Pu-239 | Pu-240 | Pu-241 | Pu-242 | Pu-244 | U-234 | U-235 | Am-241 |
| MT 51 | 0.006 | 96.77 | 3.13 | 0.076 | 0.018 | - | 0.001 | 0.1 | 0.06 |
| MT 52 | 0.01 | 93.78 | 6.0 | 0.2 | 0.02 | - | 0.002 | 0.1 | 0.2 |
| MT 53 | 0.03 | 91.08 | 8.45 | 0.366 | 0.071 | - | 0.007 | 0.09 | 0.3 |
| MT 54 | 0.046 | 87.42 | 11.5 | 0.81 | 0.22 | - | 0.01 | 0.09 | 0.7 |
| MT 55 | 0.06 | 83.88 | 14.73 | 1.03 | 0.304 | - | 0.02 | 0.09 | 0.9 |
| MT 56 | 0.061 | 81.9 | 16.51 | 1.18 | 0.355 | - | 0.02 | 0.09 | 1.0 |
| MT 57 | 0.433 | 74.63 | 20.7 | 2.55 | 1.69 | - | 0.1 | 0.08 | 2.0 |
| MT 42 | 0.73 | 1.06 | 6.40 | 1.97 | 89.83 | - | 0.3 | 0.0009 | 3.0 |
| MT 83 | 78.9 | 18.4 | 2.5 | 0.055 | 0.15 | - | 33.1 | 0.02 | 0.42 |

[a] These ratios are calculated under the assumption that there is no chemical fractionation.
Sources: References C100, C101, C124, C125, D025, M017, and M309.

In general, uranium and its isotopes are expected to be present only at trace levels, if at all, if the feed material did not purposely contain uranium. However, some reactor fuel development, uranium-plutonium separation and pit disassembly operations have uranium material as the feed material. The primary uranium MT inputs are listed in Table 4, Average Isotopic Content of Uranium Material Types and Enrichments.

Table 4. Average Isotopic Content of Uranium Material Types and Enrichments

| Material Type | U-234 | U-235 | U-236 | U-238 |
|---|---|---|---|---|
| MT 12 | 0.0015 | 0.23 | 0.008 | 99.77 |
| MT 35 | 0.36 | 37.6 | 0.14 | 61.9 |
| MT 36 | 0.63 | 62.44 | 0.18 | 36.75 |
| MT 38 | 1.03 | 93.04 | 0.41 | 5.53 |
| MT 39 | 1.32 | 97.52 | 0.17 | 0.99 |

Sources: References C100, D025, and M017.

U-234 content must be estimated since this isotope cannot be reliably measured using NDA techniques (Reference C001). The MT provides the basis for estimating an upper bound for U-234 based on the rate of decay of the precursor, Pu-238, and the assumption that there is no other source of uranium in the waste material. The content of U-234 in the Pu-239 MTs is calculated as the sum of the contributions expected from decay of Pu-238 and from uranium input to the operation, with the value of 0.014 conservatively used for the ratio of abundances of U-234 to U-235 in typical uranium MTs. The standard uranium MTs provide an estimate of the ratio of U-234 to U-235 where one of the MTs listed in Table 4 is an indicated MT in the waste container (Reference D025).

#### 5.4.2.3 Am-241

AK on the MT inputs provides the basis for estimating an upper bound for Am-241 content based on the rate of decay of the precursor, Pu-241. The purpose of such bounding calculations is to provide a basis for identifying significant enrichment or depletion of Am-241 based on radioassay results for individual waste containers. The calculations assume that (a) none of these isotopes were initially present in the material, (b) the oldest plutonium material in inventory dates back to January 1, 1960, and (c) the legacy waste was packaged on January 1, 1996, making it 36 years old at that time. In general, wastes from the plutonium recovery process are enriched with Am-241, because a primary intent of the recovery process is to reduce the americium content of the retained plutonium (References C222 and D025).

No correlation is expected among the different radioelements, Pu, neptunium (Np), U, Pa, or Am. The differences in valence states and chemical affinities among these elements are expected to result in substantial fractionation during several recovery operations, including ion exchange, solvent extraction, hydroxide precipitation, and dissolution (Reference D025).

5.4.2.4 Other Radionuclides Present Due to Decay

Other radionuclides will be present in most of the wastes from the decay of a plutonium isotopic precursor or as a contaminant in the feed material (References C067, C073, C208, C209, and D025):

- Np-237, the decay product of Am-241 (half-life, 458 year), is expected to be present in minor amounts in most waste from recovery operations.
- Am-243, the decay product of Pu-243 (half-life, 5.0 hour), is expected to be present in minor amounts in most wastes from recovery operations. Pu-243 is produced by neutron capture on Pu-242 during fuel irradiation.
- Pa-231, the decay-chain daughter of U-235, is expected to be present in trace amounts in some wastes due to its widespread presence as a contaminant in recovery operations.
- Actinium (Ac)-227, the decay-chain daughter of Pa-231, is expected to be present in trace amounts where Pa-231 is present, but at several orders of magnitude less than Pa-231.

5.4.2.5 Cesium (Cs)-137 and Strontium (Sr)-90

Cs-137

Cs-137 is a product of the spontaneous fission of Pu-238, Pu-239, and especially Pu-240. Cs-137 is also a trace contaminant in purified plutonium from the production reactors (References C067 and C073). In the latter case, the remaining cesium could be on the order of 0.5 nanograms per gram (ng/g) plutonium. In the former instance the formation of Cs-137 due to spontaneous fission would lead to about 0.4 picograms per gram (pg/g) plutonium in plutonium that is 10 years old. Because Cs-137 due to spontaneous fission is about a factor of a thousand less than that due to residual contamination from the original separation on the production fuel, the latter is the dominant source of cesium in waste (References C208, C209, and D025).

Sr-90

Based on interviews with a Subject Matter Expert (SME), no spent nuclear fuel or other material containing Sr-90 were introduced into the TRU waste streams (Reference C076). No references or procedures related to spent fuel processing were located in the AK investigation of records. No generator documents (i.e., WODF, DWLS, TWSR, WPF) identified spent fuel or Sr-90 as inputs or as present in the waste (References C208, C209, and D025). During review of WPFs and database records from the waste storage facility (TA-54), use of material containing Sr-90 was identified in 771 containers of waste originating from TA-03 and TA-21. WPFs indicate processing

of fuel pins in metallography operations and of samples of Hanford Tank waste in chemistry experiments. These operations and wastes are segregated by facility of origin, and the wastes are not commingled with wastes from LANL. Like Cs-137, Sr-90 is a high yield fission product and is unlikely to be present except as a trace remnant from plutonium production/processing. Unlike Cs-137, however, Sr-90 (together with its Y-90 daughter) emits no significant gamma radiation that would allow it to be quantified by direct gamma counting. Therefore, no reliable means exist for the direct NDA of Sr-90. However, because of the requirement that an estimate of Sr-90 content be made, the following approach is taken. In plutonium production runs, Cs-137 and Sr-90 are produced at approximately the same level. These two nuclides have very similar half-lives (~ 30 y) and will therefore be present at roughly the same activity level prior to commencement of any processing operations. If it is assumed that strontium and cesium are not fractionated from one another during chemical processing, Cs-137 may be used as a marker for Sr-90 activity at a ratio of 1:1 (Reference D025).

#### 5.4.2.6 Other Radionuclides Introduced as Feed Material

Secondary radionuclides are also present in the waste due to operations involving feed materials other than plutonium (Reference C076). Additional radionuclides expected to be present in each operation were listed by a panel of experts from LANL. The resulting list is documented in a memorandum linking the radionuclides to P/S Codes (References C076 and C108). The list includes Ac-227, Am-241, Am-243, cerium (Ce)-144, curium (Cm)-244, Np-237, Pa-231, Pu-238, Th-230, Th-232, U-233, U-235, and U-238 (see Table 5, Secondary Radionuclides in Plutonium Recovery TRU Waste).

The possible presence of Cm-244 in TRU waste is of particular interest to radioassay operations because it can affect the choice of a radioassay instrument to use for optimal results. Cm-244 was introduced in recovery operations in P/S Code (Detector oxide preparation [DOP]), which started in 1988 (References C067 and D083). Material outputs from this operation sometimes are sent to P/S Codes IS (Incinerator) or WE (Welding). Cm-244 could also be part of waste under P/S Code CA (Casting) because both operations take place in the 300 Wing of PF-4. Because only one room in this area is available for bagouts, TRU waste from P/S Codes DOP and CA are sometimes combined. In addition, because rags from DOP are sent to IS, Cm-244 could be present in the ash produced by this operation, which is then processed through nitrate aqueous recovery operations. Some fraction of the Cm-244 could ultimately end up in the evaporator bottoms, which is then immobilized in cement in P/S Code CF (cement fixation) (Reference D025).

Table 5. Secondary Radionuclides in Plutonium Recovery TRU Waste

| Secondary Radionuclide | P/S Code Generating Waste |
|---|---|
| Actinium-227 | AD, ARI, BC, CV, FF, HGMS, LIBS, PF, SRL, WM, XO |
| Americium-241 | AO, AP, CA, CD, CF, CLX, CXL, DOP, EV, FA, HCD, HD, HP, IA, LR, MA, OH, PI, PR, PRR, PS, SS, SX, WE, XP; plus trace amounts expected in TRU waste generated by nearly all P/S Codes, due to ingrowth from Pu-241 decay. Waste could be either depleted or enriched in Am depending upon whether the source of contamination is the product or the residues. |
| Americium-243 | BC, CA, DOP, JA, MA, PH, PI, SS, WE |
| Cerium-144 | DOP, WE |
| Curium-244 | CA, CF, DOP, IS (Mar-Apr 1987), WE |
| Neptunium-237 | ATL, BC, CA, CF, DOP, ED, EV, IS, JA, MA, Neptunium, PI, RB, RFX, WE; plus trace amounts expected in TRU waste generated by nearly all P/S Codes, due to ingrowth from Am-241 decay. |
| Protactinium-231 | AD, BC (1989), FF, JA (1989), WE, WM, XO/X0 |
| Plutonium-238 | AAP, TDC, TSC |
| Plutonium-241 | EV, IS, TDC, TSC |
| Thorium-232 | CF, DOP, PT, WE, XO/X0 |
| Thorium-232 enriched with Thorium-230 | BC, JA, WE |
| Uranium-233 | DOP, WE |
| Uranium-235 or enriched uranium | CN, EDC, FF, GI, ME, MW, OB, PD, PI, RS, SRL, UA, UCON; and P/S Codes in nitrate operations (AL, AO, AP, AS, AT, ATL, BAC, BF, BL, BM, BU, CC, CD, CF, CH, COD, COL, CPOD, CR, DF, DP, DS, ED, ETD, EV, FA, FC, FX, GMS, HC, HCD, HD, HGMS, HP, HRA, IA, IS, LC, LG1, LG2, LR, MAG, MAS, MB, MELL, MF, ML, MPD, NC, NL, NR, OD, OH, OY, PA, PAF, PR, PS, PT, PTS, RB, RBJ, RC, RCM, RFX, RO, RR, SC, SP, SSD, SX, TDC, TSC, UPS, US, US2, VC, VP1, VP2, VP3, VUL, ZD) |
| Uranium-238 or depleted uranium | BC, CN, EDC,FF, GI, JA, LC, ME, MW, OB, PD, RC, RS, SRL, UA, UCON, UPS, US, WE, and P/S Codes in nitrate operations (AL, AO, AP, AS, AT, ATL, BAC, BF, BL, BM, BU, CC, CD, CF, CH, COD, COL, CPOD, CR, DF, DP, DS, ED, ETD, EV, FA, FC, FX, GMS, HC, HCD, HD, HGMS, HP, HRA, IA, IS, LC, LG1, LG2, LR, MAG, MAS, MB, MELL, MF, ML, MPD, NC, NL, NR, OD, OH, OY, PA, PAF, PR, PS, PT, PTS, RB, RBJ, RC, RCM, RFX, RO, RR, SC, SP, SSD, SX, TDC, TSC, UPS, US, US2, VC, VP1, VP2, VP3, VUL, ZD) |

Sources: References C069, C076, C108, C189, C209, C215, D009, D011, D025, D029, D032, D036, and D083.

Controlled
Copy



#### 5.4.2.7 Estimated Predominant Isotopes and 95 percent Total Activity

Radionuclide data established by the PF-4 waste generator on a container basis and container data from the Area G waste storage records were evaluated to determine the relative radionuclide weight and activity for waste stream LA-MHD01.001. From this evaluation, the two predominant isotopes for the waste stream are Pu-239 and U-238, while over 95 percent of the total activity in the waste stream is from Pu-238, Pu-239, and Pu-241. It should be noted that although U-238 is the second prevalent radionuclide by mass in the waste stream, it was reported in approximately 525 containers. Table 6, Estimated Radionuclide Distribution in LA-MHD01.001, identifies the relative radionuclide weight and activity percent of expected radionuclides over the entire waste stream based on the container data evaluated. As illustrated in Table 6, the radionuclide weight percent of individual radionuclides varies greatly on a container-by-container basis. Because of this variability in container loadings, some containers will not contain the waste stream predominant radionuclides but may contain other radionuclides expected in this waste stream (References C133, C153, C175, C179, C225, C232, C233, DR048, M159, M241, M298, M307, and M309).

#### 5.4.2.8 Use of Radionuclide Isotopic Ratios

For waste containers where direct measurement does not yield useable isotopic ratio information, AK may be used to supplement direct measurement data in accordance with the WIPP-WAC (Reference 3). The ratios that may be used are those identified in Tables 3 and 4 in conjunction with the corresponding nuclear material type identified by the waste generator on a container basis. The specific use and confirmation of AK related to WIPP-certified assay measurements of containers in this waste stream is documented in the memorandum written in accordance with the requirements of CCP-TP-005 (Reference 8).

Table 6. Estimated Radionuclide Distribution in LA-MHD01.001

| Radionuclide | Total Nuclide Weight%[1,5] | Total Nuclide Curie%[2,5] | Nuclide Wt% Range for Individual Containers[3,5] | Nuclide Ci% Range for Individual Containers[4,5] | Expected Present |
|---|---|---|---|---|---|
| **WIPP Required Radionuclides** | | | | | |
| Am-241 | 0.16% | 1.45% | 0 - 100.00% | 0 - 100.00% | Yes |
| Pu-238 | 0.65% | **29.66%** | 0 - 100.00% | 0 - 100.00% | Yes |
| Pu-239 | **67.43%** | **11.14%** | 0 - 100.00% | 0 - 100.00% | Yes |
| Pu-240 | 4.75% | 2.87% | 0 - 42.06% | 0 - 31.10% | Yes |
| Pu-242 | 1.17% | 0.01% | 0 - 100.00% | 0 - 100.00% | Yes |
| U-233 | Trace | Trace | 0 - 36.88% | 0 - 0.97% | Yes |
| U-234 | 0.02% | Trace | 0 - 28.84% | 0 - 0.51% | Yes |
| U-238 | **24.13%** | Trace | 0 - 99.90% | 0 - 7.33% | Yes |
| Sr-90 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Cs-137 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| **Additional Radionuclides** | | | | | |
| Ac-227 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Am-243 | Trace | Trace | 0 - 0.52% | 0 - 0.32% | Yes |
| Cd-109 | Trace | 0.60% | 0 - 1.75% | 0 - 99.40% | Yes |
| Ce-144[6] | Not Reported | | | | Yes |
| Cm-243 | Trace | Trace | 0 - Trace | 0 - 81.34% | Yes |
| Cm-244 | Trace | Trace | 0 - 3.12% | 0 - 90.33% | Yes |
| Cm-245 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Co-60 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Eu-152 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Eu-154 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| H-3 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Mn-56 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Na-22 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Np-237 | 0.03% | Trace | 0 - 100.00% | 0 - 100.00% | Yes |
| Np-239 | Trace | Trace | 0 - Trace | 0 - 97.25% | Yes |
| Pa-231 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Pa-233 | Trace | Trace | 0 - Trace | 0 - 0.11% | Yes |
| Pb-212 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Pu-241 | 0.20% | **54.27%** | 0 - 20.00% | 0 - 93.99% | Yes |
| Pu-244 | Trace | Trace | 0 - 0.29% | 0 - Trace | Yes |
| Th-228 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Th-229 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Th-230[6] | Not Reported | | | | Yes |
| Th-232 | 0.96% | Trace | 0 - 95.61% | 0 - Trace | Yes |

Table 6. Estimated Radionuclide Distribution in LA-MHD01.001 (Continued)

| Radionuclide | Total Nuclide Weight%[1,5] | Total Nuclide Curie%[2,5] | Nuclide Wt% Range for Individual Containers[3,5] | Nuclide Ci% Range for Individual Containers[4,5] | Expected Present |
|---|---|---|---|---|---|
| **Additional Radionuclides** | | | | | |
| Tl-208 | Trace | Trace | 0 - Trace | 0 - 0.01% | Yes |
| U-232 | Trace | Trace | 0 - 1.29% | 0 - 56.61% | Yes |
| U-235 | 0.49% | Trace | 0 - 98.67% | 0 - 99.02% | Yes |
| U-236 | Trace | Trace | 0 - 0.42% | 0 - Trace | Yes |
| Other radionuclides that may be present in unknown amounts (no data values were available, although the radionuclides were listed in databases) | | | | | |
| Bk-249 Cf-252 Co-57 | | | | | Yes |

1. This listing indicates the total weight percent of each radionuclide over the entire waste stream.
2. This listing indicates the total activity (curie) percent of each radionuclide over the entire waste stream.
3. This listing is the weight percent range of each radionuclide on a container-by-container basis.
4. This listing is the curie percent range of each radionuclide on a container-by-container basis.
5. “Trace” indicates <0.01 weight or activity percent for that radionuclide.
6. Radionuclides not reported but suspected present from secondary radionuclides or decay.

### 5.4.3 Chemical Content Identification – Hazardous Constituents

Waste stream LA-MHD01.001 has historically been managed in accordance with the generator site requirements and in compliance with the requirements of the New Mexico Environmental Department (NMED). Based on historical waste management and LANL’s TRU Program (reference LANL waste streams LA-TA-55-19, LA-TA-55-30, LA-MHD02-238, and LA-MHD03-DD), the containers in this waste stream were managed as hazardous and assigned EPA HWNs for arsenic (D004), barium (D005), cadmium (D006), chromium (D007), lead (D008), mercury (D009), selenium (D010), silver (D011), benzene (D018), carbon tetrachloride (D019), chlorobenzene (D021), chloroform (D022), methyl ethyl ketone (D035), pyridine (D038), tetrachloroethylene (D039), trichloroethylene (D040), and F-listed solvents (F001, F002, F003, and F005). A review of available AK documentation has determined that this waste is hazardous for the above constituents, and with the exception of F003, the HWNs were retained because this waste was previously shipped under an approved LANL profile. HWN F003 was not assigned because the waste stream does not exhibit the characteristic of ignitability. It should be noted that this waste stream also includes a small fraction of waste that LANL characterized as nonhazardous (reference LANL waste streams LA-NCD01, LA-NHD01, and LA-NHD02-238). As discussed in Section 4.3.7, supplemental information collected and CCP characterization results of LANL generated nonhazardous containers determined that this waste is hazardous. The following sections describe the characterization rationale for the assignment of EPA HWNs. Table 7, Waste Stream LA-MHD01.001 Hazardous Waste Characterization Summary, summarizes the EPA HWNs assigned to this waste stream. The HWN assignments have been applied on a waste stream basis; individual containers may not contain all of the hazardous materials listed for the waste stream as a whole (Reference C121, C147, D026, D083, and M310).

Controlled
Copy



Table 7. Waste Stream LA-MHD01.001 Hazardous Waste Characterization Summary

| Waste Stream | EPA HWNs |
|---|---|
| LA-MHD01.001 | F001, F002, F005, D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040 |

Chemical constituents of inputs are compiled from chemical lists contained in procedures and from SME input. In this section, discussions of the chemical inputs are divided into the following categories (References C121 and C147):

- Process feed materials
- Chemical Identification and Use

Table 8, Feed Materials for TA-55 Operations, provides a summary of the special nuclear material feed materials processed by the operations described in this report. Process chemicals and their respective uses are presented in the following sections (References D007, D008, D009, D010, D011, D025, D028, D029, D030, D032, D036, and D080).

Controlled
Copy



Table 8. Feed Materials for TA-55 Operations

| Feed Material | Potential Presence of RCRA-Regulated Constituents* | P/S Codes and Associated Operation Areas |
|---|---|---|
| Analytical laboratory solutions | Potentially contaminated with RCRA-regulated constituents:<br>All analytical laboratory solutions are potentially contaminated with chromium (D007), lead (D008), and mercury (D009).<br>C-AAC (formerly CLS-1) solutions potentially contaminated with mercury (D009) and lead (D008), as well as RCRA-listed organic substances used as solvents, including acetone (F003), butyl alcohol (butanol, F003), carbon tetrachloride (F001, D019), chlorobenzene (F002, D021), chloroform (D022), methanol (F003), methylene chloride (F002), tetrachloroethylene (F002, D039), xylene (F003). | Pyrochemical and Chloride operations: CLS, CW (analytical laboratory solutions from LANL Group C-AAC [formally CLS-1]);<br>Miscellaneous operations: APD (C-AAC [formerly CLS-1] solutions); ACL, ICP (PF-4 solutions)<br>Nitrate operations: CF, HP<br>Special operations: CP<br>Pu-238 operations: R8 |
| Anode heels | Typically contaminated with RCRA-regulated heavy metals cadmium (D006), chromium (D007), lead (D008), and silver (D011). Heavy metals arsenic (D004), mercury (D009), and selenium (D010) are not present because they are volatilized from the Pu oxide feed at the high temperatures to which this material is subjected in P/S Codes ER, RM, and SS (electrorefining step). | Nitrate operations: AS, BF, BU<br>Pyrochemical and Chloride operations: RA, SS |
| Ash from P/S Codes ETD, IS, SB, TDC, or from other DOE facilities | Usually suspect contaminated with barium (D005), cadmium (D006), chromium (D007), lead (D008), and silver (D011). Arsenic (D004), mercury (D009), and selenium (D010) metals are volatilized at high temperatures if present in the oxide and chloride forms. | Miscellaneous operations: CK, CV, FDL, FLU, SO, XP<br>Nitrate operations: AL, AT, ATL, ED, HGMS, HRA, IS, MPD, PTS, RC, SC<br>Special processing operations: ACD, IAM, SB, SL |
| Crucible pieces (tantalum, magnesium oxide) | Typically fairly pure, no RCRA substances present | Pyrochemical and Chloride operations: CL, CXL<br>Nitrate operations: MAS, SC<br>Special processing operations: ACD, SL<br>Pu-238 Operations: ASP |
| Disassembled weapons components (pit disassembly) | High-purity Pu and U material types, no RCRA substances present | Metal operations: CA, PH, SRL<br>Miscellaneous operations: EDC<br>Nitrate operations: BM, RB, RBJ |
| Experimental R&D feed materials; various isotopes and isotopic mixtures of actinides in various matrices | Variable purity; may or may not contain RCRA substances | Miscellaneous operations: AD, CV, EXT, HRS, RASS, SA, XES, XP<br>Nitrate operations: MAS |

Table 8. Feed Materials for TA-55 Operations (Continued)

| Feed Material | Potential Presence of RCRA-Regulated Constituents* | P/S Codes and Associated Operation Areas |
|---|---|---|
| Hydroxide cakes (output from P/S Codes ASP, CLS, CW, CXL, DO, NP, POSM, PRR) | Typically contaminated with RCRA-regulated heavy metals cadmium (D006), lead (D008), mercury (D009), silver (D011), and possibly chromium (D007) | Miscellaneous operations: AD<br>Nitrate operations: CD, HCD, HD, LG2<br>Special processing operations: CP, DO, POSM<br>Pu-238 Operations: R8 |
| Iridium Metal | Typically fairly pure, no RCRA substances present | Pu-238 Operations: RCI |
| Miscellaneous materials contaminated with Pu (e.g., sand, slag, tools, crucibles, metal, glass, plastic, labware, scrap, rags, glovebox sweepings, pump oils, HEPA filters) | May be contaminated with RCRA-regulated heavy metals silver (D011), cadmium (D006), mercury (D009), lead (D008), and possibly chromium (D007) | Miscellaneous operations: APD<br>Nitrate operations: ATL, BAC, CPOD, CR, ED, ETD, GMS, HGMS, IS (combustible material), LG1 (non-combustible material), MAG, MAS, MELL (cellulosic material), ML (metal equipment), NC (non-combustible material), NL (non-combustible material), PA (glovebox sweepings), PAF, RO (organics), SC, SP, TSC (cellulosic material), VC, ZD<br>Pyrochemical and Chloride operations: PK (hardware, metal, anode chips from other P/S Codes)<br>Special processing operations: ACD, CP, DO, NP, SB, SL<br>Pu-238 Operations: ASP |
| MSE salts | Typically fairly pure, suspect contaminated with barium (D005) | Pyrochemical and Chloride operations: CXL, MB, MS<br>Miscellaneous operations: XP<br>Nitrate operations: MB, PS<br>Special processing operations: RM |
| Neptunium residues from vault | No RCRA-regulated substances | Pyrochemical and Chloride operations: Neptunium (only active in 1993) |
| Pu chlorides and fluorides | Variable purity; may or may not contain RCRA substances | Miscellaneous operations: FDL, SO<br>Pyrochemical and Chloride operations: ER, SD, SS<br>Special processing operations: RM |

Table 8. Feed Materials for TA-55 Operations (Continued)

| Feed Material | Potential Presence of RCRA-Regulated Constituents* | P/S Codes and Associated Operation Areas |
|---|---|---|
| Pu containing solutions and liquids | Variable purity; may or may not contain RCRA-regulated substances | Nitrate operations: DS, LR, RFX, EV, CF<br>Special processing operations: CP, NP, SL<br>Pu-238 Operations: R8 |
| Pu metal or metal alloy from vault or from various operations | High purity, no RCRA-regulated substances, unless noted otherwise | Metal operations: AAP, AO, ARI, BC, BT, CA, DA, ELW, EVAC, FSPF, ITF, ITF4, ITF7, JA, KBTF, MA, MBC, MW, PCH (variable purity), PD, PE, PF, PH, PSE, RL, SRL, VD, WE, WLT<br>Miscellaneous operations: AC, AC1, AC2, ECHM, EXT, LIBS, ME, SA, SMP, VS<br>Nitrate operations: ATL, BM, BU, MF, PAF, VP1<br>Pyrochemical and Chloride operations: CRD (variable purity), MO, SCB, SS, SSMD<br>Special processing operations: ACC (variable purity), PI (variable purity), PPD, POSM, RM, SB<br>Pu-238 Operations: ASP |
| Pu oxalates | Typically fairly pure, no RCRA substances present | Nitrate operations: CC, DF, HC<br>Pu-238 Operations: ASP |
| Pu oxides | Variable purity oxides from P/S Codes RB, RBJ and others, and from the vault; suspect contaminated with RCRA-regulated heavy metals cadmium (D006), chromium (D007), and lead (D008)<br>High purity oxides from P/S Codes CA, DO, and MA, and from the vault; may or may not contain RCRA substances<br>Incoming Pu-238 oxide from SRS exceeds regulatory limits for chromium (D007) and may exceed limits for cadmium (D006), lead (D008), and silver (D011) for some fuel lots (References D073, D074, and M283). However, calculations documented in Reference D076 support the conclusion that the levels of these metals in TA-55 waste streams from Pu-238 operations are below RCRA's regulatory limits. | Metal operations: DOP (high-purity Pu and other radionuclides as oxides)<br>Miscellaneous operations: CK, CV, EOC, EXT, FDL, FLU, IB, LI, LIBS, MIS, SMIS, SO, STF, VS, XP<br>Nitrate operations: ATL, BL, CH, CPOD, DP, ED, FC, HRA, LC, MPD, OD, PT, RB, RBJ, SP, SSD, UPS, US, US2<br>Pyrochemical operations: MP (generally high purity), OR (variable purity), PTP<br>Special processing operations: DO, PX, POSM, RM<br>Pu-238 Operations: ASP, C1, GPHS, MTL, P1, SCP, WS |
| Pu-Be sources | High purity constituents, no RCRA-regulated substances | Pyrochemical and Chloride operations: PB, PUB |

Table 8. Feed Materials for TA-55 Operations (Continued)

| Feed Material | Potential Presence of RCRA-Regulated Constituents* | P/S Codes and Associated Operation Areas |
|---|---|---|
| Pyrochemical salts | Typically fairly pure, no RCRA substances other than barium (D005) are present | Pyrochemical and Chloride operations: MB, MS, PRR<br>Miscellaneous operations: EXT, IB<br>Nitrate operations: COD, COL, MB<br>Special processing operations: Me<br>Pu-238 Operations: MTL, PP, WD |
| Reactor fuel pellets/heat sources | High purity Pu and U material types, no RCRA-regulated substances | Miscellaneous operations: ME<br>Pu-238 Operations: MTL, PP, WD |
| Stainless-steel and/or tantalum residues from decladding of Pu-Be sources | High purity metals, potential leaching of chromium (D007) from stainless-steel if subjected to strong acid | Pyrochemical and Chloride operations: PUB |
| Uranium metal, carbides, nitrides and oxides | No RCRA-regulated substances | Metal Operations: FF, SRL, UCON<br>Miscellaneous Operations: ME |

*The information in this column is highly generalized. Applicability of specific HWNs to an operation as a result of the feed material must be determined on a case-by-case basis because the presence and fate of contaminants is time and function dependent.

#### 5.4.3.1 Chemical Inputs

To assign EPA HWNs, the available AK documentation is reviewed to assess chemical usage in the TA-55 PF-4 operations contributing to waste stream LA-MHD01.001, and potentially hazardous materials that may have been introduced into the waste stream. In addition, MSDSs are obtained for the commercial products to determine the presence of potentially regulated compounds. As described below in Table 9, Chemical Identification and Use Summary, several of the HWNs are assigned due to lack of analytical evidence that these constituents have not exceeded the regulatory thresholds. These chemical inputs are used during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations and have the potential to contaminate all the waste streams characterized by this report.

Table 9. Chemical Identification and Use Summary

| Chemical/Product | Use/Source | P/S Code(s) | Document Source(s) | EPA HWN(s) |
|---|---|---|---|---|
| 1,1,1-Trichloroethane | Metallographic sample cleaning (<1992) and contaminant of hydroxide solids. Degreasing solvent and component of Tap Magic. | MA, MTL, R8 | C019, C020, C089, C194, C195, M154, M160 | F001, F002 |
| 1,2-Dimethoxyethane | Organoactinide R&D reagent. | SA | P080 | NA |
| 1-Propanol | Used in cold traps and cooling baths during plutonium fluorination. | CK | D032, P071 | NA |
| Acetone | Contaminant of cement fixation process and hydroxide solids. Detected in headspace gas of Pu-238 waste. May be associated with all debris waste generated by P/S Code ME. CLS reagent. | APD, CF, CLS, CW, FF, HP, MA, ME, MOX, R8 | C019, C092, C194, D007, D076, D078, M164, M180, M186, | NA |
| Acetonitrile | Non-aqueous dissolution/extraction. | AC2 | C027, D032 | NA |
| Alconox | Pu-238 oxide sample cleaning soap. | GPHS, P1, PP | C194, D080, M286 | NA |
| Aluminum chloride | Chloride operations ion exchange reagent | CSE, CX, CXL, DO, SE | D007, P027 | NA |
| Aluminum fluoride | Plutonium recovery operations. | Unspecified | D002, D009, D023, D032, D041 | NA |
| Aluminum metal/oxide (alumina) | Metallographic sample polishing, ash fluorination gas trap, metal used in machining operations, and component of equipment/tools. | BA, MA, MTL, SO, UPS | C194, D076, D080,M085, P051, P069, P148 | NA |
| Aluminum nitrate | Pu-238 oxide purification and ATLAS R&D recovery operations reagent. Dissolution and leaching reagent. | AL, ASP, AT, ATL | C210, D080, M085, M088, M093, P190 | NA |
| Ammonium chloride | Hydroxide precipitation and plutonium chlorination reagent. | CV, DO | M048, P083 | NA |
| Ammonium hydroxide | Hydrothermal processing reagent. | APD | M223 | NA |
| Antimony pentafluoride | Organoactinide R&D reagent. | SA | P065 | NA |
| Arsenic | Contaminant of liquids, filtrates, ash, hydroxide cake, and analytical solutions. Evaporator sludge contaminant and sputter coating reagent. | EV, PE, R8, TDC | C010, C196, C197, C207, D078, D080, M153 | D004 |
| Ascarite II | Sodium hydroxide coated silicate absorbent used in fuel fabrication process. | FF | C066, M154 | NA |
| Ascorbic acid | ATLAS R&D recovery operations and dissolution reagent. | ATL, Various | M127, P190 | NA |
| Barium | Contaminant of plutonium feed, hydroxide cake, ash, actinide separation waste, pyrochemical salts, and analytical solutions. | ATL, EV, EXT, R8, TDC, Various | C038, C087, C192, C197, D075, D078, D080, M153 | D005 |
| Benzene | Cement fixation input and actinide chemistry R&D operations reagent. | AC, AC1, AC2, CF, SA | C027, D009, D032, D077P080, P081, | D018, F005, |
| Beryllium | Contaminant of plutonium/beryllium sources and metal used in machining operations. | MA, PB, PUB | C122, D007, D025, P148 | NA |

Table 9. Chemical Identification and Use Summary (Continued)

| Chemical/Product | Use/Source | P/S Code(s) | Document Source(s) | EPA HWN(s) |
|---|---|---|---|---|
| Bismuth/bismuth-tin alloy | Metal used in electrorefining and sample mounting. | ER, SMP | C031, D002. D028 | NA |
| Bromine | Fluorination of ash and R&D reagent. | SA, SO | C026, P069 | NA |
| Bromobenzene | Plutonium machining. | MA | C019 | NA |
| Bromocresol purple | Hydroxide precipitation indicator. | CX, CXL, DO | M048, M074, M182, P028 | NA |
| n-Butyl alcohol (butanol) | Associated with debris waste. Contaminant of cement fixation process. Detected in headspace gas of Pu-238 waste. CLS reagent. | ACL, APD, CF, CLS, CW, HP, ICP | C092, D007, D076, D078 | NA |
| Cadmium | Contaminant of plutonium feed, hydroxide cake, anode heels, ash, actinide separation waste, and analytical solutions. Solvent metal used in electrorefining. | AD, ATL, EXT, ER, EV, HP, IS, PX, R8, RC, SS, Various | C038, C039, C192, C196, C197, C200, D073, D075, D076, D080, M061, M153 | D006 |
| Calcium carbonate | Scrubber system, hydroxide precipitation, dissolution, and salt stripping reagent. | DO, SL, SS | M028, M048, M118, M127, M131 | NA |
| Calcium chloride | Electrorefining and direct oxide reduction reagent. | OR, SS, WS | D070, D080, M029, M113, P189 | NA |
| Calcium fluoride | ATLAS R&D recovery operations and leaching plutonium residues reagent. | AT, ATL, DO, SL | M053, M069, M093, M118, M144, P190 | NA |
| Calcium hydroxide | Neutralization of acids. | Various | C033 | NA |
| Calcium metal/oxide | Actinide R&D and direct oxide reduction reagent. | AD, OR, RM, PX, WS | M050, M130, D070, D080, P189 | NA |
| Calcium nitrate | Nitrate operations reagent. | ATL | D002, D008 | NA |
| Carbon tetrachloride | Contaminant of cement fixation process and hydroxide solids. Used in PTP between 1/87 and 6/89. Chlorination of plutonium oxide and CLS reagent. | AD, APD, ATL, CF, CLS, CV, PTP, PX, R8 | C092, C121, C194, C200, D078, M112, M129, P067 | D019, F001 |
| Cerium nitrate | Electro-oxidation reagent. | MELL | M092 | NA |
| Cesium chloride | Molten salt extraction reagent salt and dissolution reagent. | CLS, CXL, PRR, SS | D055, M184 | NA |
| Chlorobenzene | Contaminant of cement fixation process and hydroxide solids. CLS reagent. | ACL, APD, ATL, CF, CLS, CW, HP, ICP | C092, C095, C200, D007, D077, D078 | D021, F002 |
| Chloroform | Contaminant of cement fixation and miscellaneous processing (P/S XO/X0). CLS reagent. | AC, AC1, AC2, APD, CF, CLS, FF, R8, XO/X0 | C027, C092, C102, C117, C194, D077, D078 | D022 |
| Chromium | Contaminant of plutonium feed, anode heels, hydroxide cake, ash, actinide separation waste, and analytical solutions. Potentially leached from stainless-steel materials. | APD, ATL, EV, EXT, HP, IS, R8, RC, TDC, XO/X0, Various | C038, C039, C192, C196, C197, C200, C205, D073, D074, D075, D078, D080, M061, M153 | D007 |
| Citofix/Durofix | Metallographic sample mounting. | MTL | C197, M154, D080 | NA |
| Citrapeel (orange peel based degreaser) | Used to strip paint. | XO/X0 | C033, D032, M154 | NA |
| Cobalt nitrate | Electro-oxidation reagent. | MELL | M092 | NA |

Table 9. Chemical Identification and Use Summary (Continued)

| Chemical/Product | Use/Source | P/S Code(s) | Document Source(s) | EPA HWN(s) |
|---|---|---|---|---|
| Copper | Measuring physical properties standard. Component of gaskets and wool used during disassembly of parts. | BC, PI, SRL, VP2, Various | M030, M043, M084, M202, P053 | NA |
| Diamond powder | Metallographic polishing compound. | MTL | P181 | NA |
| Diatomaceous earth | Silica and quartz filter aid and absorbent material. | PT, Various | M154, M172, P005, P103, P117 | NA |
| Dibutyl butyl-phosphonate (DBBP) | Actinide R&D reagent. | AD | M050 | NA |
| Dicesium hexachloroplutonate (DCHP) | Residue precipitation reagent. | CLS, CXL, PRR | D055, M184 | NA |
| Diethylenetriamine | Metallographic sample mounting. | MTL | C197, D080 | NA |
| Diethyl oxalate | ATLAS R&D recovery operations reagent. | ATL | M144, P190 | NA |
| Dihexyl N, N-diethylcarbamoylmethyl phosphonate (DHDCMP) | Liquid-liquid extraction solvent. | APD | C023, C199 | NA |
| Diisopropyl benzene | Liquid-liquid extraction solvent, diluent, and actinide R&D reagent. | AD, APD | C023, D032, C199, P067 | NA |
| Dimethyl sulfoxide | Organoactinide R&D reagent. | SA | P080 | NA |
| n-Dodecane | Actinide R&D solvent diluent and chloride extraction reagent. | AD, CXL | M154, M182, P067 | NA |
| Dowanol (e.g., Dowanol EB) | Sodium metal neutralization reagent. | EL, FF | C079, C102, D011, D029, M154 | NA |
| Duco cement | Sealing cuvettes. | P1 | C194, D075, D080, M154 | NA |
| Envirostone Accelerator (gypsum and potassium sulfate) | Cement accelerator used in cement fixation process. | CF, HP | D078, M154, P008, P183 | |
| Epon Resin 8132 | Metallographic sample mounting. | MTL | C197, D080, M154 | NA |
| Ethanol | Used for cleaning capsules and tools during Pu-238 oxide sampling and R&D reagent. Contaminant of cement fixation and miscellaneous processing (P/S XO/X0). | AD, GPHS, ME, P1, PP, R8, XO/X0 | C089, C194, C195, D032, D077, D080, P067, P180 | NA |
| Ethylene glycol | Pu-238 oxide sampling suspension. Particle analysis of oxides. | GPHS, P1, PP | C194, C195, C197, D080, M137, M286 | NA |
| Ethyl ether | Organoactinide R&D reagent and cleaning solvent. | MA, SA | C019, M002, P080 | NA |
| Fantastik | Pu-238 oxide sampling and spray cleaner for machining. Used during decontamination operations. | GPHS, MA, P1, PP, Various | C019, C150, C194, D080, M154, M286 | NA |
| Ferric ammonium sulfate hydrate | Catalyzed electrochemical plutonium oxide dissolver reagent. | CPOD | M086 | NA |
| Ferric nitrate | Waste solidification and dissolution reagent. | DO, R8 | C194, D080, M126, P182 | NA |
| Ferrous ammonium sulfate | Nitrate anion exchange and ATLAS R&D recovery operations reagent. | ATL, IX | D030, P190 | NA |
| Ferrous chloride | Residue precipitation reagent. | CXL | D002, D007, D023, D041 | NA |
| Ferrous sulfamate | Ash leaching reagent. | AT | M093 | NA |
| Fluoristan (stannous fluoride) | ATLAS R&D recovery operations reagent. | ATL | M144, P190 | NA |

Table 9. Chemical Identification and Use Summary (Continued)

| Chemical/Product | Use/Source | P/S Code(s) | Document Source(s) | EPA HWN(s) |
|---|---|---|---|---|
| Fluorosulfonic acid | Organoactinide R&D reagent. | SA | P065 | NA |
| Formamide | ATLAS R&D recovery operations reagent. | ATL | M144, P190 | NA |
| Formic acid | Dissolution and plutonium recovery reagent. | ATL, CF, EV, Various | C076, D002, D008, D036, M144 | NA |
| Freon TF (1,1,2-trichloro, 1,2,2-trifluoroethane) | Miscellaneous processing contaminant and recovery operations reagent. Cleaning, cooling, and ultrasonic degreasing operations solvent. | CA, DA, DO, EL, MA, MW, PD, PF, RM, SBB, SCB, SRL, SS, UA, VD, VU, WE, WM, XO/X0 | C011, C017, C019, C085, C102, C104, C105, D029, D077 M026, M032, M041, M123, M212, P044, P046, P049 | F001, F002 |
| Gallium | Actinide R&D and casting reagent. Metal used in electrorefining and compatibility testing. | AAP, AD, CA, ER, SMIS | D002, D009, D011, M032, P014, P076 | NA |
| GoJo cleaner (kerosene derivative) | Parts cleaning solution. | ITF, ITF7 | D019, M154 | NA |
| Gold | Metal used in welding operations, coating material, and component of transfer boat used in plutonium fluoride reduction. | RL, WE | C018, M202, P044 | NA |
| Graphite | Graphite aeroshells and insulators, molds, blocks, and powder for fire suppression. | CA, FF, ITF, ITF4, ITF7, SS, WD | D029, D074, M032, M116, P090 | NA |
| Gypsum cement (Envirostone) | Cement used in cement fixation process. | CF, HP | C206, D071, D078, M154, P008, P183 | NA |
| Hexane | Miscellaneous processing contaminant and R&D solvent for actinide chemistry. | AC1, AC2, FF, SA, XO/X0 | C102, D077, P080, P081, | NA |
| Hydrazine dihydrochloride | Actinide R&D and sensors/instrumentation development reagent. | AD | D032, P076, P078 | NA |
| Hydrazine hydrochloride | Actinide R&D reagent. | AD | D002, D023, D032, D041 | NA |
| Hydrobromic acid | Metallographic sample etching. | MTL | C194, D080, P181 | NA |
| Hydrochloric acid | Dissolution and recovery, sample etching, and ATLAS R&D recovery operations reagent. Chloride ion exchange reagent. | ATL, CLS, CXL, DO, MTL, PPD, Various | C076, C194, D080, M048, M064, P181, P190 | NA |
| Hydrofluoric acid | Dissolution of oxide pellets, scrap processing, decontamination, fluorination, sample etching, ATLAS R&D recovery operations reagent, and metal leaching. | ASP, ATL, MP, MTL, NC, OD, PPD, PT, SP, WD, Various | C076, C192, C194, C210, C213, D079, D080, M072, M089, M090, M095, P103, P181, P190 | NA |
| Hydrogen peroxide | ATLAS R&D recovery operations reagent, peroxide precipitation, and dissolution. | AD, ATL, DO, Various | M048, M125, M144, P028, P076, P190 | NA |
| Hydroxylamine hydrochloride | Actinide R&D and ion exchange reagent. | AD, IX | D002, D023, D032, D041, M044, M050 | NA |
| Hydroxylamine nitrate | Scrap processing, ATLAS R&D recovery operations, ion exchange, and hydroxide precipitation reagent. | AD, ASP, ATL, DO, IX, PT, Various | C210, D078, D080, M044, M045, M048, M050, M076, P103, P190 | NA |

Table 9. Chemical Identification and Use Summary (Continued)

| Chemical/Product | Use/Source | P/S Code(s) | Document Source(s) | EPA HWN(s) |
|---|---|---|---|---|
| Indium | Metal used in compatibility testing. | SMIS | D009 | NA |
| Iodine | Actinide R&D reagent. | SA | C026 | NA |
| Isopar H (isoparaffin solvent) | Actinide R&D reagent. | AD | D032, M050, M154 | NA |
| Isopropanol | Miscellaneous processing waste contaminant, cleaning agent, and organoactinide R&D reagent. | BA, SA, XO/X0 | D077, P051, P080 | NA |
| Kerosene | Metallurgical sample preparation solvent. | ME | C035 | NA |
| Kitty Litter | Clay based absorbent material used during remediation/repackaging operations. | Various | M154, P198 | NA |
| Lanthanide metals | Actinide chemistry R&D reagents. | AC1, AC2 | D009, P081 | NA |
| Lanthanum nitrate | Plutonium dissolution and precipitation. | PT | D078, M076, P103 | NA |
| Lead | Leaded gloves (<1992), shielding, sheeting, and discs. Contaminant of actinide separation waste, analytical solutions, ash, hydroxide cake, plutonium feed, and solder. Solvent metal used in electrorefining. | APD, ATL, BT, DOP, ER, EV, EXT, GPHS, HP, IS, KBTF, P1, PX, R8, RC, SS, XO/X0, Various | C039, C041, C192, C196, C197, C200, D002, D011, D073, D074, D075, D076, D078, D080, M061, M153, P183, P186 | D008 |
| Lead hydroxide, oxide, and nitrate | Actinide R&D reagents. | AD | D032, M050 | D008 |
| Liqui-Moly (molybdenum lubricant) | Pellet press die lubricant. | FF, RS | M172 | NA |
| Lithium chloride | Direct oxide reduction reagent salt. | AD, OR, PX, RM | M050, M130, M134, P105 | NA |
| Lithium metal/oxide | Actinide R&D and direct oxide reduction reagent. | OR, PX, RM | M130, M134 | NA |
| Lonzest SML-20 organic liquid emulsifier | Cement fixation liquid emulsification. | CF | M154, P186 | NA |
| Lutetium | Sputter coating reagent. | PE | D023, D029 | NA |
| Magnesium chloride | Molten salt processing reagent. | RCI, SS | C194, D011, D028, D055, D076, D080 | NA |
| Magnesium hydroxide | Dissolution and oxygen sparging-pyrochemical operations. | DO, Various | M048, P028 | NA |
| Magnesium metal/oxide | Actinide R&D reagent, crucibles, and magnesia sand. | AD, RCI, SS, WS | C194, D070, D080, M050, M116, P189 | NA |
| Magnesium perchlorate | Water vapor removal reagent. | FF | C047, C066, C113 | NA |
| Mercuric nitrate | Catalyst used in nitrate operations. | VP1, VP3 | M064, D078 | D009 |
| Mercury | Contaminant of actinide separation waste, analytical solutions, ash, evaporator sludge, hydroxide cake, and plutonium feed. Component of fluorescent bulbs. | AD, ATL, HG, R8, SSMD, TDC, XO/X0 | C023, C095, C176, C196, C197, C200, C207, D029, D078, D080, M153, P109 | D009 |
| Mercury | Contaminant of actinide separation waste, analytical solutions, ash, evaporator sludge, hydroxide cake, and plutonium feed. Component of fluorescent bulbs. | AD, ATL, HG, R8, SSMD, TDC, XO/X0 | C023, C095, C176, C196, C197, C200, C207, D029, D078, D080, M153, P109 | D009 |

Table 9. Chemical Identification and Use Summary (Continued)

| Chemical/Product | Use/Source | P/S Code(s) | Document Source(s) | EPA HWN(s) |
|---|---|---|---|---|
| Mercury | Contaminant of actinide separation waste, analytical solutions, ash, evaporator sludge, hydroxide cake, and plutonium feed. Component of fluorescent bulbs. | AD, ATL, HG, R8, SSMD, TDC, XO/X0 | C023, C095, C176, C196, C197, C200, C207, D029, D078, D080, M153, P109 | D009 |
| Metalprep 79 (phosphoric acid-based metal cleaner) | Metal cleaner. | MA | C019, C020, M154 | NA |
| Methanol | Cleaning solvent, diluent, contaminant of cement fixation process. Detected in headspace gas of Pu-238 waste. CLS reagent. | AD, APD, CF, CLS, CW, HP, SO | C023, C092, D007, D076, D078, P067, P070 | NA |
| Methylene chloride | Paint stripper, contaminant of cement fixation, hydroxide cake, and miscellaneous processing (P/S XO/X0). CLS and organoactinide R&D reagent. Component of REZ-N-Bond. | AC, AC1, AC2, AD, APD, ATL, CF, CLS, CW, HP, SA, WM, XO/X0 | C027, C092, C200, C214, D007, D032, D077, D078, M174, P080 | F001, F002 |
| Methyl ethyl ketone | Degreasing solvent. Detected in headspace gas of Pu-238 waste. | MA, WM, XO/X0 | D032, D076, D077 | D035, F005 |
| Molybdenum metal/oxide | Metal used in machining operations, fuel elements, salt stripping reagent, and component of Liqui-Moly. | ELW, MA, SS, Various | C014, M028, M172, P052, P056, P148 | NA |
| MolyKote | Silicon-based lubricant used during the hand pressing of oxide pellets. | FF, RS | C102, D029, M154 | NA |
| Neutracleaner #1 and #2 | Machining operations cleaner. | MA | C019, M154 | NA |
| Nickel powder | Reactor fuel development sintering aid. | CO | C102, D029, M169 | NA |
| Niobium | Metal used in welding operations, fuel elements, and electrorefining reagent. | SS, WE, Various | M029, P044, P052, P056 | NA |
| Nitric acid | Dissolution and recovery, scrap processing, decontamination, nitrate ion exchange, and cement fixation pH adjustment. | AT, ASP, ATL CF, DS, LR, PPD, PT, RCM, RR, WD, Various | C192, C210, C213, D071, D078, D079, D080, M093, M096, M097, M098, M099, P103, P182, P183, P190 | NA |
| Oakite 90/ruststripper | Caustic metal cleaner. | EL | P033, P034 | NA |
| Octylphenyl di-isobutyl carbamoylmethyl phosphine oxide (CMPO) | Actinide R&D reagent and Liquid-liquid extraction solvent. | AD, APD | C194, C023, P067 | NA |
| Oil (e.g., 3-in-1, Dow Corning 2000, Fomblin Pump, hydraulic, mineral, Texaco Regal 32, and Vactra 2 oil) | Metal preparation, machining, cutting, polishing, and cooling. | BA, MA, ME, PCH, Various | C019, C020, D002, D009, D023, D025, D029, M154, P045, P051 | NA |
| Organicstrip | Non-regulated paint stripper. | XO/X0 | D002, D009, D023, D032, D041, M154 | NA |
| Oxalic acid | Laboratory and anion exchange reagent, scrap processing, oxide/pellet dissolution and precipitation, and ATLAS R&D recovery operations reagent. | ASP, ATL, DO, IX, LR, PPD, RFX, Various | C210, D079, D080, M127, M132, P024, P190 | NA |
| Pentane | R&D solvent for actinide chemistry. | SA | P080 | NA |
| Perchloric acid | Actinide R&D and laboratory reagent. | AC, AC1, AC2, AD, Various | C027, P076, P077, P081 | NA |

Table 9. Chemical Identification and Use Summary (Continued)

| Chemical/Product | Use/Source | P/S Code(s) | Document Source(s) | EPA HWN(s) |
|---|---|---|---|---|
| Phenolphthalein | Reagent (pH indicator). | DS, IX, LR, R8, RFX, Various | C194, D080, M076, M099, P024, P182 | NA |
| Phosphoric acid | Plutonium recovery reagent and component of Metalprep 79. | MA, Various | C019, C020, D002, D029, D041, M154 | NA |
| Platinum | Plutonium recovery operations and actinide R&D reagent. Component of electrodes, filters/screens, fuel element sleeves, and furnace can linings. | AD, CPOD, CXL, EL, IX, LR, MELL, RFX, Various | M011, M053, M067, M086, M092, P024, P026, P042, P076 | NA |
| Polychlorinated Biphenyls (PCBs) | In capacitors of fluorescent light ballasts. | Various | C157, P162 | NA |
| Polyethylene glycol | Fuel fabrication reagent. | CO | D029, D041 | NA |
| Polyoxyethylene-20-sorbitan laurate (surfactant) | Plutonium recovery operations. | Unspecified | D002, D023, D025, D036, D041, M154 | NA |
| Portland cement | Cement fixation and waste packaging absorbent. | CF, HP, Various | C206, D037, D078, M154 | NA |
| Potassium chloride | Electrorefining and molten salt extraction reagent. | OR, PX, RM, SS | D055, M023, M024, M130, M134, M206, P104, P105 | NA |
| Potassium chromate | Dissolution and chloride anion exchange reagent. | CX, DO | C098, M131, M185 | D007 |
| Potassium dichromate | Silver nitrate titrations and hydroxide precipitation reagent. | AD, CS, CSE, CW, CX, DO, PB, PUB, PT, SE | C082, D002, D007, D032, M076 | D007 |
| Potassium fluoride | Dissolution and leaching operations reagent. | DS, PT | M069, M099 | NA |
| Potassium hydroxide | Caustic scrub solution for thermal decomposition, dissolution, and reactive chemical neutralization. | DO, MP, TDC, Various | C076, M048, M072, M299 | NA |
| Potassium permanganate | Pretreatment, decontamination, and R&D reagent. | AD, Various | C094, D023, D032, P067 | NA |
| Potassium pyrosulfate | Dissolution operations reagent. | AT | M069, M093 | NA |
| Potassium thiocyanate | Dissolution operations reagent. | CPOD, Various | C094, D023, M086 | NA |
| Pyridine | Uranium triiodide reagent, R&D solvent, and contaminate in cement fixation process. | AC, AC1, AC2, CF, SA | D077, P080 | D038, F005 |
| Reillex HPQ (polyvinyl pyridine resin) | Dissolution and recovery operations ion exchange resin. | RFX, LR, IX | D010, D030, M154, P024 | NA |
| REZ-N-Bond | Solvent bonding (contains methylene chloride). | FF, ID | M154, M174 | F002 |
| Rhenium | Metal used in fuel elements. | Unspecified | P056 | NA |
| Rhodium | Actinide R&D reagent and component of fuel element sleeves. | AD, GPHS, P1 | D044, M011, M050 | NA |
| Selenium | Contaminant of liquids, filtrates, ash, hydroxide cake, and analytical solutions. | IS, R8, RC, TDC | C196, C197, C207, D045, D080, M153 | D010 |
| SF-2I (3M secondary fluid) | Machining coolant/fluid. | MA | C009, C020, M154 | NA |

Table 9. Chemical Identification and Use Summary (Continued)

| Chemical/Product | Use/Source | P/S Code(s) | Document Source(s) | EPA HWN(s) |
|---|---|---|---|---|
| Silicone adhesive (e.g., sylgard 184) | Vessel handling and unloading. Compound used in compatibility testing. | SMIS, VUL | D009, M154, M189 | NA |
| Silicone defoamer | Cement fixation reagent. | CF | M154, P152, P153, P183, P185 | NA |
| Silicone lubricant | Metal operations lubricant. | BA | D029, P051 | NA |
| Silver | Contaminant of plutonium feed, hydroxide cake, ash, actinide separation waste, cement fixation inputs, and laboratory reagent. | AC1, ASP, CPOD, EV, EXT, HP, IS, R8, RC, TDC, Various | C027, C038, C039, C192, C196, C197, C207, D075, D078, D080, M086, M153 | D011 |
| Silver nitrate | Leaching, solvent extraction, and laboratory reagent. | AT, CPOD, CS, CSE, CW, CX, DO, PB, PUB, SE | D007, C200, D078, M054, M080, M086, M093, M131 | D011 |
| Sodium bicarbonate | Dissolution and ash fluorination reagent. | CK, DO, SO | M131, P069, P071 | NA |
| Sodium carbonate | Actinide R&D and plutonium recovery operations reagent. | AD, ER | D045, P078 | NA |
| Sodium chloride | Electrochemical and plutonium recovery operations reagent salt. | CPOD, EDC, RM, SS | D055, M029, M086, M206, P104, P147 | NA |
| Sodium chlorite | Actinide R&D and plutonium recovery operations reagent. | AD, CX | P067, M181 | NA |
| Sodium chromate | Plutonium dissolution and precipitation. | PT | D078, P103 | D007 |
| Sodium citrate retarder | Cement fixation reagent. | CF, HP | D078, M154, P008 | NA |
| Sodium dithionate | Actinide R&D and dissolution reagent. | AD, DO | M127, P067 | NA |
| Sodium fluoride | Dissolution operations reagent. | AT | M069, M093 | NA |
| Sodium hydroxide | Cement fixation (pH adjustment), Pu-238 purification, caustic scrubber solution, dissolution, and ATLAS R&D recovery operations reagent. | ASP, ATL, CF, COD, COL, HP, R8, Various | C094, C194, C210, D071, D078, M064, M072, M293, P183, P190 | NA |
| Sodium metal/oxide | Actinide R&D reagent, electrorefining, fuel cladding, sodium bonding, and oxide reduction. | AD, EL, OR, RM, PX, SS | C054, C064, C079, M050, M130, M134, P096 | NA |
| Sodium metaphosphate | Heat source fabrication operations. | R8 | C195 | NA |
| Sodium nitrate | Ion exchange, scrap processing, and ATLAS R&D recovery operations reagent. | ASP, ATL | C210, D080, P190 | NA |
| Sodium nitrite | Dissolution, leaching, and ATLAS R&D recovery operations reagent. | AT, ATL, DO | M093, M131, M144 | NA |
| Sodium oxalate | Dissolution and precipitation reagent. | DO, PPD | C079, D079, M048 | NA |
| Sodium pyrophosphate | Sucrose recovery of Pu-238. | R8 | C194, D076, D080 | NA |
| Sodium sulfate | Electrolytic decontamination reagent. | ARI, EDC | D011, P147 | NA |
| Sodium tetraborate | Pressure testing reagent. | BT | C083, D011 | NA |
| Stannous chloride | Plutonium recovery reagent. | CXL, PUB | D007, D023 | NA |
| Stearic acid | Fuel production reagent, recovery operations, and component of silicone adhesive. | CO, OB, Various | D002, D023, D029, M154 | NA |
| Sucrose | Sucrose recovery of Pu-238 and microspherical fuel reagent. | FF, R8 | D029, C194, D080, M294 | NA |

Table 9. Chemical Identification and Use Summary (Continued)

| Chemical/Product | Use/Source | P/S Code(s) | Document Source(s) | EPA HWN(s) |
|---|---|---|---|---|
| Sulfuric acid | Peroxide precipitation, dissolution, R&D, Pu-238 recovery from iridium, and ATLAS R&D recovery operations reagent. | AD, ATL, DO, PR, RCI, Various | M103, M125, M151, P078, D080, P190 | NA |
| Tantalum | Metal used in welding operations, fuel elements, and crucibles. Dissolution and electrorefining reagent. | AAP, DO, PUB, SS, WE, Various | M029, P014, P025, P044, P052, P056 | NA |
| Tap Magic | Machining coolant (contains 1,1,1-trichloroethane). | MA | C009, C019, C020, M154 | F002 |
| Tetrachloroethylene | Degreasing, cleaning solvent, diluent, contaminant of cement fixation process and hydroxide solids. CLS reagent. | AD, APD, CF, CLS, CSE, CV, CW, HP, SE | C092, C200, D007, D032, D078, P067 | D039, F001, F002 |
| Tetraethylamine chloride | Actinide R&D reagent. | AD | D032, P076 | NA |
| Tetraethylammonium hydroxide | Actinide R&D reagent. | AD | D032, P076 | NA |
| Tetrahydrofuran | Synthesis R&D reagent, organoactinide R&D reagent, Np and Pu metal cleaner. | AC, AC1, AC2, SA | C026, C027, D032, P080 | NA |
| Thionyl chloride | Plutonium chlorination reagent. | CV, PTP | D045, P083 | NA |
| Titanium | Metal used in welding operations and electrorefining reagent. Component of electrodes and miscellaneous equipment. | BA, CPOD, MELL, SS, WE | M029, M086, M092, M200, P044, P051 | NA |
| Toluene | Actinide and organoactinide R&D reagent. Detected in headspace gas of Pu-238 waste. | AC, AC1, AC2, SA | C027, D032, D076, P080, | F005 |
| Tributyl phosphate (TBP) | Actinide R&D and hydrothermal processing reagent. | AD, APD | D032, P064, P067 | NA |
| Trichloroethylene | Clean and polish machined parts. Miscellaneous process and hydroxide cake contaminant. Hydrothermal processing and solvent extraction reagent. | AAP, APD, CK, EL, FF, MA, ME, WM, XO/X0, Various | C009, C019, C035, C102, C200, D077, D081, M223, P071, P085 | D040, F001, F002 |
| Trioctylphosphine oxide (TOPO) | Plutonium operations reagent and cement fixation contaminate. | CF, HP, Various | C094, D036, P011 | NA |
| Tungsten | Metal used in welding operations and equipment, fuel elements, measure physical properties standard, and electrorefining reagent. | BC, RM, SS, WE, Various | M029, M030, M037, P044, P052, P056 | NA |
| UCAR C-34 | Epoxy used for sealing aeroshells. | WD | C192, D080, M154 | NA |
| Urea | Plutonium recovery operations, Pu-238 purification, and ATLAS R&D reagent. | ASP, ATL, DO, DS, IX, LR, RFX, RR, Various | C210, D080, M045, M054, P024, P190 | NA |
| Vacuum grease | Vessel handling and unloading and machining operations reagent. | AAP, PI, SRL, VP2, VUL | M043, M084, M154, M189, P014, P053 | NA |
| Vanadium | Metal used in machining and welding operations. | MA, WE | D029, P148 | NA |
| Vanadium pentoxide | Salt distillation and stripping reagent. | SD, SS | C061, C068, M028, P110 | NA |
| Varian Torr Seal epoxy | Sealing oxide sample containers. | GPHS, P1, PP | M154, P180 | NA |

Table 9. Chemical Identification and Use Summary (Continued)

| Chemical/Product | Use/Source | P/S Code(s) | Document Source(s) | EPA HWN(s) |
|---|---|---|---|---|
| Vermiculite | Hydrated magnesium-aluminum-iron silicate used to absorb ethylene glycol, suspend oxide power samples, and waste/liquid packaging absorbent. | GPHS, P1, ME, PP, RO, WM | C035, M064, M154, M286, P098 | NA |
| Waste Lock 770 | Sodium polyacrylate absorbent material used during remediation/repackaging operations. | Various | C150, M154 | NA |
| WD-40 | Vessel handling and unloading. | VUL | M154, M189 | NA |
| Windex | Machining cleaner. | MA | C019, M154 | NA |
| Xylene | CLS, actinide R&D, and metallography operations reagent. Cement fixation contaminant. | ACL, APD, CF, CLS, CW, HP, ME, Various | C092, C094, D007, D032, D078, M164, P033 | NA |
| Yttrium metal/oxide | Mixed with plutonium in MWG processing and electrorefining reagent. | GPHS, P1, PP, SS | D076, D080, M029 | NA |
| Zeolite | Aluminosilicate mineral absorbent material used during pit disassembly and remediation/repackaging operations. | SRL, Various | D011, D029, M154 | NA |
| Zinc chloride | Pyroredox reagent salt. | RA | D002, P029 | NA |
| Zinc stearate | Fuel production anti-sticking reagent. | MOX | C102, D029 | NA |
| Zirconium metal/oxide | Electrorefining reagent and metal used in machining. | ME, SS, Various | D002, D009, D023, M029 | NA |

Notes :
Some of these chemicals may exhibit the characteristic of ignitability, corrosive, and/or reactivity in their pure form. However, potentially ignitable, corrosive, or reactive materials (e.g., liquids and pressurized containers) identified during RTR and/or VE will be remediated or removed from the waste container prior to shipment to the WIPP. In addition, based on an analysis of the generating operations and waste management practices, no pure or unused chemicals would have been introduced into the debris or homogeneous waste streams.

### 5.4.3.2 F-, K-, P-, and U-Listed Constituents

Based on review of AK relative to chemicals used or present in the facility and operations potentially contaminating the debris waste, LA-MHD01.001 may contain or be mixed with F-listed hazardous wastes from non-specific sources listed in 40 Code of Federal Regulations (CFR) 261.31, *Identification and Listing of Hazardous Waste* (Reference 15). As shown in Table 9, F001, F002, F003, and F005 listed solvents are utilized and could potentially contaminate the waste. F003 constituents, including acetone, n-butyl alcohol, ethyl ether, methanol, and xylene, are listed solely because these solvents are ignitable in the liquid form. The waste stream does not exhibit the characteristic of ignitability and therefore F003 is not assigned. Waste stream LA-MHD01.001 is assigned F-listed EPA HWNs F001, F002, and F005 for potential 1,1,1-trichloroethane, benzene, carbon tetrachloride, chlorobenzene, Freon TF (1,1,2-trichloro, 1,2,2-trifluoroethane), methylene chloride, methyl ethyl ketone, pyridine, tetrachloroethylene, toluene, and trichloroethylene contamination (References C121, C147, and M310).

Controlled
Copy



At one time, HWN P120 was applied to certain drums generated in 1998 because of the temporary use of vanadium pentoxide for about six months in that year. Based upon investigation into the way the material was handled, this code is not assigned to this waste stream. A P120 assignment would be used only if waste resulted from spillage of this material or from disposal of un-reacted/unspent material. No un-reacted/unspent material was disposed of in TRU waste drums. In addition, no significant spill of this material occurred. If a spill had occurred, suitable records would exist (e.g., incident reports, waste profile forms). The absence of such documentation, coupled with information obtained through interviews of people who worked with the material, indicates that a P120 assignment is not necessary (References C061, C147, M284, and M310).

Beryllium may be present in the waste stream, but does not meet the definition of a P015-listed waste. Available AK did not identify the use of beryllium powder as a constituent in this waste stream. During processing within P/S Codes PU and PUB, beryllium from Pu-Be sources is dissolved with the plutonium in acid, and after dissolution, the beryllium is either precipitated or in the contaminated solution is sent to the RLWTF at TA-50. The precipitate is not included in this waste stream. In some cases, Beryllium turnings are generated during machining operations. However, these turnings are a very low fraction of metal waste that is discarded. The material reclamation process identifies the processing and packaging of Pu-238/beryllium neutron source material. The amount of beryllium material was estimated at approximately two grams per neutron source prior to processing. Based on the description of the process, the beryllium contamination present in the final waste form is expected to be minimal. However, beryllium from metal operations may be present in this waste stream. Containers from these operations that contain greater than one weight percent beryllium will be appropriately identified (References 14, C121, C122, C147, C156, M283, and M310).

Hydrofluoric acid was used or present in the facility and operations potentially contaminating the debris waste; however, a U134 HWN assignment would only be applicable if the waste resulted from a spill or disposal of unused material. There is no documented spill of this material present. In addition, there is no record of unused hydrofluoric acid being disposed of in this waste stream (References C121, C155, D002, and D025).

Waste stream LA-MHD01.001 does not contain and is not mixed with a discarded commercial chemical product, an off-specification commercial chemical product, or a container residue or spill residue thereof. Constituents identified were further researched and a determination was made that waste does not meet the definition of a listed waste in 40 CFR 261.33 (Reference 15). The material in this waste stream is not hazardous from specific sources since it is not generated from any of the processes listed in 40 CFR 261.32 (Reference 15). Therefore, this waste stream is not a K-, P-, or U-listed waste stream (References C121 and C147).

5.4.3.3 Toxicity Characteristic Constituents

Based on review of AK relative to chemicals used or present in the facility and operations potentially contaminating the debris waste, LA-MHD01.001 may be contaminated with toxicity characteristic compounds as defined in 40 CFR 261.24 (Reference 15) as summarized in Table 9. Where a constituent is identified and there is no quantitative data available to demonstrate that the concentration of a constituent is below regulatory threshold levels, the applicable EPA HWN is added to the waste stream. The AK also identified the potential presence of organic toxicity characteristic compounds that are assigned the more specific F-listed EPA HWNs. Although these organic characteristic compounds are covered by the assignment of the F-listed EPA HWNs, the toxicity characteristic EPA HWNs are also assigned to the waste stream for consistency with historical site waste coding. Waste stream LA-MHD01.001 is assigned the following HWNs: D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040 (References C121, C147, and M310).

5.4.3.4 Ignitables, Corrosives, and Reactives

The debris material in waste stream LA-MHD01.001 does not meet the definition of ignitability as defined in 40 CFR 261.21 (Reference 15). Ignitable chemicals (e.g., acetone, hexane) are used or present in the facility and operations potentially contaminating this waste stream. However, D001 (ignitability) does not apply because: (a) the solid waste is not liquid, and verification that there are no prohibited liquids in the debris waste is performed prior to certification; (b) the solid waste does not spontaneously ignite at standard pressure and temperature through friction, absorption of moisture, or spontaneous chemical changes; (c) the solid waste is not an ignitable compressed gas; and (d) there are no oxidizers present that can stimulate combustion. Prior to 1992, some nitrate salts below the DL were not sent to cement fixation for immobilization but were packaged as waste. LANL has determined that these salts do not meet the definition of a DOT oxidizer (i.e., they would not stimulate combustion). However, the salts are being remediated/repackaged in the WCRR Facility with an inert absorbent material (e.g., zeolite, kitty litter). The minimum zeolite or kitty litter to nitrate salts mixture ratio is 1.5 to 1. LANL has determined that nitrate salts, when mixed with zeolite or kitty litter, would further support the managing of the waste as non-ignitable. This determination is based on the results of oxidizing solids testing performed by the Energetic Materials Research and Testing Center. The materials in the waste stream are therefore not ignitable wastes (D001) (References C121, C147, C201, C203, C230, C231, D083, D084, D089, D090, D091, P187, and P198).

The debris material in waste stream LA-MHD01.001 is not liquid and does not contain unreactive corrosive chemicals; therefore, it does not meet the definition of corrosivity as defined in 40 CFR 261.22 (Reference 15). Corrosive chemicals (e.g., hydrofluoric acid, nitric acid, potassium hydroxide, sodium hydroxide) are used or present in the facility and operations potentially contaminating this waste stream. However, D002

(corrosivity) does not apply because the solid waste is not a liquid, and verification that there are no prohibited liquids in the debris waste is performed prior to certification. The materials in the waste stream are therefore not corrosive wastes (D002) (References C121, C147, C194, C200, D071, P181, P182, and P190).

The debris material in waste stream LA-MHD01.001 does not meet the definition of reactivity as defined in 40 CFR 261.23 (Reference 15). Reactive chemicals (e.g., perchloric acid, sodium metal) are used or present in the facility and operations potentially contaminating this waste stream. However, D003 (reactivity) does not apply because the solid waste is stable and will not undergo violent chemical change without detonating. The waste will not react violently with water, form potentially explosive mixtures with water, or generate toxic gases, vapors, or fumes when mixed with water. The waste does not contain reactive cyanide or sulfide compounds. There is no indication that the waste contains explosive materials, and it is not capable of detonation or explosive reaction. The materials in the waste stream are therefore not reactive wastes (D003) (References C121, C147, C201, and C202).

Controls have also been in place to ensure the exclusion of ignitable, corrosive, and reactive constituents. The associated EPA HWNs do not apply to wastes in this waste stream for the following reasons (References D025, D037, D049, D083, P090, P091, P096, P097, P102, and P165):

- Liquids were prohibited from solid waste streams at LANL when the Plutonium Recovery Facility opened in January 1979. A waste management procedure written to cover operations at the new facility, *TA-55 Standard Operating Procedure* (SOP) stated that “Liquids are not permitted in any container of solid waste materials.” Currently, *TA-55 Waste Management,* requires that no liquids be disposed of as a solid waste unless the liquid has been absorbed into some media (like vermiculite) that does not carry a D001 code.

- Chemical Waste Disposal Requests (see Figure 6), introduced in June 1980, included check boxes that the waste generator was required to check if the waste contained corrosive acids or bases, or pyrophoric, flammable, corrosive, explosive, toxic, carcinogenic or highly reactive materials. The Certification Plan and related Generator Attachments were implemented in 1987. Waste generators are required to sign a statement on the WODF documenting that the waste contains “no free liquids, pyrophorics, explosives, compressed gases, powders or materials other than the indicated matrix.” Checkboxes are also present for indicating the presence or absence of corrosive chemicals. Full implementation of this generator statement occurred in May 1987.

- Waste management inspectors perform visual verification of the waste prior to its initial packaging, thus allowing the inspectors to verify the generator’s WODF statement.

- In addition to the above-mentioned prohibitions on explosives in waste, explosives were altogether prohibited until installation of the Impact Test Facility in the early 1990s. In case of a misfire or unconsumed explosives, a procedure is in place to ensure that explosives do not enter the waste stream.

- The Waste Profile Request Form (WPRF), which has been in use at LANL since 1991, includes a statement which is authenticated by the waste generator, that the waste is not ignitable, reactive, or corrosive.

- The Generator Attachments to the Certification Plan were updated in 1995, but the prohibition on liquids in the waste, and the waste management inspection, remained in effect.

- The LANL Project 2010 Certification Plan, and TWIDs prohibit liquids in waste and the absence of liquids is verified by LANL waste management.

- Solutions containing spent non-halogenated solvents are sent to the RLWTF if they are below the DL for plutonium.

- If above the DL, the solutions are sent to aqueous recovery as part of chloride or nitrate operations. Aqueous recovery steps include dissolution of any solid plutonium in hydrochloric or nitric acid, followed by plutonium recovery by ion exchange. The solutions are then below the DL and are either sent to the RLWTF or to the evaporator.

- Rags that are above the DL for plutonium are thermally decomposed, which destroys any organic component.

- Rags that are below the DL for plutonium are discarded as combustible debris, but headspace gas analyses support the contention that the solvents are below the limits established by the WIPP-WAC.

The absence of these prohibited items is verified through RTR and/or VE of each waste container. Any prohibited liquids are absorbed and discarded in an appropriate waste stream and containerized gases that are found to be present are removed before waste certification (Reference D083).

5.4.3.5 Polychlorinated Biphenyls (PCBs)

With the exception of suspect PCB fluorescent light ballasts, no other sources for PCBs in waste stream LA-MHD01.001 were identified in the AK source documents. In the cement fixation operation (P/S Codes CF and HP), oils are sometimes added to drums of cemented waste. They are added to the 55-gallon drums of cement in small quantities (maximum of six liters). The oils are primarily vacuum pump oils, along with

some oils used in heat-treating (cooking or silicone oils) or in grinding. None of these oils are known to contain PCBs. All transformers known to contain PCBs have been tracked from initiation of recovery operations. When any transformer oil is drained, the oil is handled by a subcontractor who is wholly responsible for its disposal; this oil does not enter the LANL disposal operations. Ballasts in fluorescent light fixtures could contain PCBs. These light fixtures are outside the gloveboxes and were not expected to have entered the TRU waste stream. However, characterization activities have identified the presence of light ballasts. Therefore, containers with PCB waste, identified during RTR or VE, will be managed as a Toxic Substances Control Act (TSCA) waste under 40 CFR 761, *Polychlorinated Biphenyls (PCBs) Manufacturing, Processing, Distribution in Commerce and use Prohibitions* (References 18, C096, C147, C157, C201, D080, D083, P012, and P162).

### 5.4.4 Prohibited Items

#### 5.4.4.1 Compressed Gases, Liquids, Nonradionuclide Pyrophorics, Sealed Containers >Four Liters In Volume, >1 Percent Radionuclide Pyrophorics, and >200 mrem/hr Waste

Most gases used at the PF-4 are stored outside the building and the gas is plumbed into the glovebox from outside the building (Reference C098). Occasionally, a lecture bottle is used for an operation inside the building, but these bottles are kept outside of the glovebox with the gas plumbed into the glovebox. Consequently, compressed gas cylinders or containers are not expected to be in any of the TRU waste streams (References C223 and D025).

Spray cans, especially WD-40, were in common use in gloveboxes until May 1992 (Reference C081). These were routinely discarded as noncombustible debris waste. From 1988 until May 1992, the protocol was to vent or puncture the spray cans inside the glovebox; venting was indicated by inserting a metal wire into the valve. After May 1992, spray cans are no longer used in gloveboxes (References C201, C206, D025, and D083).

Procedures for oxygen sparging and/or carbonate oxidation have been in use since May 1987 to ensure that potential pyrophorics associated with pyrochemical salt waste are oxidized. In addition, screening tests on similar pyrochemical salts and residues (which contained higher amounts of plutonium) at the former Rocky Flats Environmental Technology Site showed (1) no autoignition, (2) no spontaneous combustion, and (3) no sparking. Experimental results on the reactivity of DOR salt with water and the reactivity in air of heated calcium metal nodules from DOR salts indicate the absence of “dangerous when wet materials” and pyrophoricity in these salts (References C064, C065, C202, C203, D025, D084, P125, and P187).

Chemical Waste Disposal Requests dated as early as June 1980 included boxes that were required to be checked if the waste contained pyrophoric, flammable, corrosive, or explosive materials (see Figure 6) (Reference D083).

In addition, for wastes generated after the implementation of the 1987 Certification Plan, associated waste packaging procedures, and quality assurance systems, the waste generator has signed a statement on the WODF for each waste item stating that waste contains “no free liquids, pyrophorics, explosives, compressed gases, powders or materials other than the indicated matrix.” The Attachments to the Certification Plan describe how these restrictions are verified by waste management personnel (References D025 and P090).

The Project 2010 Certification Plan, and the TWIDS prohibit compressed gases, liquids, nonradionuclide pyrophorics, sealed containers greater than four liters in volume, or >1 percent radionuclide pyrophorics in waste and verified by waste management (Reference D025).

Based on interviews with site personnel performing VE and prohibited item disposition repackaging, internal cans (both shielded and unshielded) have been measured for dose rate during repackaging and found to contain waste with radiation levels exceeding 200 mrem/hr (References C135 and C136).

#### 5.4.4.2 Remediation of Prohibited Items

Prohibited items are known to be present. Procedures allowed containers greater than four liters, sealed with tape, to be used for waste packaging until WIPP certification procedures were implemented. The presence of containerized (e.g., butane lighter, lighter fluid can, unpunctured aerosol cans, vials) and uncontainerized liquids have also been observed. Lead shielding is often used to increase handling safety, and thick shielding can obscure RTR observations (References D025, D083, and DR029).

Prohibited items are detected by RTR or VE and reported with the characterization results. Waste containers with prohibited items are segregated then dispositioned appropriately and/or repackaged into new drums, during which time liquids are absorbed, sealed containers greater than four liters are opened, and other items removed and segregated if necessary prior to certification and shipment. Waste items with a high dose rate may be repackaged into a POC. Repackaged waste items that are placed into a new drum(s) or POC are from a single parent drum. Some secondary waste generated during remediation and repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., metal, plastic bags, plywood sheathing, rigid liner lids cut into pieces) (References C150, C177, D025, D083, M316, P154, P158, P159, P175, P192, and P203).

## 5.5 Waste Packaging

Waste packaging procedures for waste streams have been modified several times since the beginning of plutonium operations in PF-4 and containers in this waste stream include a variety of configurations with up to six layers of confinement. It is expected that debris waste from waste management operations generated between 1979 and 1995 would usually be packaged into a U.S. Department of Transportation (DOT) 7A, Type A 55-gallon steel drum, including either up to two 5-mil to 12-mil plastic liner bags closed with tape, or one 90-mil/125-mil rigid polyethylene liner with lid. Waste could also be packaged in vented 30-gallon drums or into in-line 30-gallon drums attached to a glovebox in the waste management room, and later overpacked into 55-gallon drums. Larger waste items and remediated/repackaged waste may be packaged in unlined SWBs with appropriate materials, such as Styrofoam sheets, wooden pallets, or plastic materials to prevent them from shifting (References C056, D025, P090, D084, P179, P188, P192, and P195).

Since 1995, several changes have been introduced to the packaging procedures. Up to two plastic liner bags could still be present, but they are typically closed by folding, not by taping. Waste can also be packaged in a rigid polyethylene drum liner contained in a bag-out bag which is then placed in a 55-gallon drum lined with plastic liner bag. All waste containers (i.e., 55-gallon drums, SWBs) are vented with approved filter vents prior to disposal (e.g., Nucfil-013). Since 1997, plastic bags with filters are typically used. Waste with the potential to tear the plastic bag, such as broken glass, is first placed in a metal container with a slip-top (also referred to as a slip-fit) lid, taped closed, and then placed into the plastic bag. Larger waste items with sharp edges are properly taped or otherwise rendered blunt. Waste with a dose rate greater than 75 mrem/hr is placed in a lead or a tin alloy shielded container prior to packaging. Waste could also be packaged or repackaged in a POC. Waste placed into a POC may be packaged into a single filtered plastic bag which may include a fiberboard liner/sleeve inside the plastic bag. POCs contain a pipe component in a standard 55-gallon steel drum that is lined with a punctured rigid liner with packing material between the pipe component and liner. POCs are closed once predetermined SNM or weight limits are met or when the pipe component is physically full.

Remediated/repackaged waste may be packaged with or without a single plastic liner bag with one of the following drum configurations depending on the remediation facility: no liner, a fiberboard liner, a POC, or a 90-/125-mil rigid polyethylene liner without lid (References C062, C149, D025, D084, D085, P091, P159, P164, P166, P167, P168, P169, P175, P178, P192, and P195).

This waste stream is primarily generated from operations performed in gloveboxes. The waste material is placed directly into bag-out bags (also called inner bags) through an opening in the glovebox where the bag is attached, and the bag is then closed and detached from the glovebox. Waste may also be packaged into a stainless-steel dressing jar, a slip-top can, and/or an unsealed metal container before it is placed into

Controlled
Copy



the bag-out bag. Once removed from the glovebox line, the bagged out container(s) may also be put into a secondary stainless-steel slip-top container. TRU waste is sometimes generated from “hot jobs” outside of the glovebox, such as valve changes, or from decontamination of spills or other releases. In these cases, the waste is placed directly into one (or possibly more) inner bag at the work area. All inner bag closures are by twist-and-tape method or the twist, tie, and tape method (References D025, D084, M074, M076, P155, P156, P157, and P160).

A minor source of waste in this waste stream is room trash that was originally considered to be LLW, which is collected in plastic bags inside cardboard boxes. Occasionally, when assayed, these boxes are determined to be TRU waste. These boxes may be sorted to remove the “hot” item, or the whole box may be bagged and sent to the TRU packaging area for placement in drums. When this occurs, the P/S Code WM is assigned to the waste. Due to the additional layers of plastic that may be present when this operation occurs, drums with the P/S Code WM are assumed to contain one more layer of internal packaging than other drums (References C056, C188, D025, and D084).

Generally, lesser quantities of homogeneous waste materials present in this waste stream are visually examined prior to waste packaging. If necessary, the material may be placed under a heat lamp, in a vacuum, on a hot plate, or in a furnace to further reduce the moisture content. TRU liquids are absorbed with an absorbent such as vermiculite prior to packaging. The minimum absorbent to liquid ratio is 3 to 1. After the liquid is absorbed in vermiculite, the waste is hand squeezed with a rubber glove. If any liquid is observed on the surface of the glove or the waste, more vermiculite is added and the hand squeezing is repeated until the waste appears dry. The homogeneous waste materials are then bagged out of the glovebox as described above (References M074, M076, P155, P156, P157, P161, and P162).

RTR and/or VE will confirm TRUCON code LA125/225. LA125/225 describes the broadest type of materials and bounds all waste packages in this waste stream. However, TRUCON codes LA115/215, LA116/216, LA117/217, LA118/218, LA119/219, LA122/222 (Reference P173), and LA123/223 have been identified as suitable TRUCON codes for individual containers in this waste stream. For high wattage drums, TRUCON codes LA154 or SQ154 may also be used for shipping. In addition, TRUCON code SQ133/233 is used for containers that include greater than one percent by weight beryllium. These TRUCON codes may be assigned for the eventual certification and transportation of payload containers in this waste stream pending further evaluation by the Waste Certification Official of container- specific information (References 9, 14, D025, D084, and M296).

Controlled
Copy



During waste management and drum storage activities following initial waste generation, 55-gallon drums have been overpacked into larger drums (i.e., 85-gallon drums or larger) or SWBs to correct/address external contamination, fissile gram equivalent (FGE) limits, and drum integrity problems such as pin hole corrosion, dents, etc. If drums are overpacked in an SWB (up to four 55-gallon drums), no closed liner bags are used in the SWB. In addition, CMBs may be modified, vented, and packaged into TDOPs (References D018, D024, D068, M222, P092, P098, P117, P158, P166, P167, P203, and P204).

This waste stream includes containers originally assigned to waste stream LA-CIN01.001 that contain greater than 50 percent debris material by volume (Reference DR044). Therefore, containers in this waste stream may be packaged in configurations described in Section 6.5 (e.g., packaged in lead shielded cans and drums).

Vent dates for individual containers are provided in the AK Tracking Spreadsheet (References C002 and M220).

## 6.0 REQUIRED WASTE STREAM INFORMATION: LA-CIN01.001

This section presents the mandatory waste stream AK required by the WIPP-WAP (Reference 1). Attachment 1 of CCP-TP-005 (Reference 8) provides a list of the TRU waste stream information required to be developed as part of the AK record.

### 6.1 Area and Building of Generation

All of the cemented TRU waste covered by this report originated from the TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations described in Section 4.4. Container-specific records are reviewed for each container to verify the physical composition and origin of the waste stream inventory (References C138, M222, M236, and M238).

### 6.2 Waste Stream Volume and Period of Generation

Waste stream LA-CIN01.001 is mixed cemented TRU waste generated from 1979 to present. Table 10, LA-CIN01.001 Approximate Waste Stream Volume, summarizes the current volume of this waste stream. Of the 2,828 containers in this waste stream, 78 are presently in below-grade retrievable storage at TA-54, Area G. The projected volume of retrievably stored below-grade containers may change based on the radiological characteristics and the condition of the containers. The future projection of additional generation of this waste stream is approximately 13 cubic meters per year. There is no projected end date for the termination of operations that generate this waste stream (References C138, C140, C180, C232, C234, D041, M236, and M238).

Table 10. LA-CIN01.001 Approximate Waste Stream Volume

| Containers | Volume (cubic meters) |
|---|---|
| 12 30-gallon drums | 1.36 |
| 2,086 55-gallon drums (includes POCs) | 438.06 |
| 718 85-gallon drums | 229.76 |
| 8 110-gallon drums | 3.36 |
| 2 SWB | 3.33 |
| 2 Other Containers | 0.84 |
| 2,828 Total | 677.11 |

## 6.3 Waste Generating Activities

Cemented TRU waste is generated by or originated from materials used during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations described in detail in Section 4.4 and includes (References D041 and D083):

- Preparing ultra-pure plutonium metals, alloys, and compounds
- Preparing (on a large scale) specific alloys, including casting and machining these materials into specific shapes
- Determining high-temperature thermodynamic properties of plutonium
- Reclaiming plutonium from scrap and residues produced by numerous feed sources
- Disassembling components for inspection and analysis
- Manufacturing of parts on a limited basis
- Processing mixtures of plutonium and uranium oxides for reactor fuels
- Pu-238 generator and heat source R&D, fabrication, testing, and recycling

## 6.4 Type of Wastes Generated

This section describes the process inputs, Waste Matrix Code assignment, WMPs, radionuclide contaminants, and RCRA hazardous waste determinations for waste stream LA-CIN01.001. The waste stream is characterized based on knowledge of the materials, knowledge of the operations generating the waste, and physical descriptions of the waste.

### 6.4.1 Material Input Related to Physical Form

Waste stream LA-CIN01.001 consists primarily of inorganic homogeneous solid waste (cemented TRU waste) generated in TA-55. The waste includes materials encased in Portland or gypsum cements such as aqueous and organic liquids from the six operational areas (e.g., nitrate operations), ash, calcium chloride salts, chloride solutions, evaporator bottoms and salts, filter aid, filter cakes (e.g., hydroxide cake), plutonium/uranium filings and fines, glovebox sweepings, graphite powder, HEPA filter media, leached ash residues, leached particulate solids (e.g., ash, sand, slag, and crucible parts), oxides (e.g., americium, metal, and uranium), miscellaneous oils (e.g., pump oil), silica solids, solvents, spent ion exchange resins, trioctyl

phosphineoxide and iodine in kerosene, and uranium solutions. A small fraction of debris waste (less than 50 percent by volume) including plastic packaging, metal packaging, and PPE (e.g., leaded gloves) may also be present. Finally, some secondary waste generated during remediation/repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770 [sodium polyacrylate]), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., metal, plastic bags, plywood sheathing, rigid liner lids cut into pieces) (References C150, C171, C177, DR043, D041, D050, D080, D083, and M316).

#### 6.4.1.1 Waste Matrix Code

Based on the evaluation of the materials contained in this waste stream and LANL waste management practices, this waste stream is comprised of greater than 50 percent by volume of cemented TRU waste. Therefore, Waste Matrix Code S3150, solidified homogeneous solid waste is assigned to waste stream LA-CIN01.001 (References 2, C138, D041, D083, M222, M236, and M238).

#### 6.4.1.2 Waste Material Parameters

The WMPs for waste stream LA-CIN01.001 were based on the descriptions of waste packaged into 2,470 containers. This waste stream is greater than 50 percent by volume of cemented TRU waste (References C138, D041, D083, and M222).

The WMPs for waste stream LA-CIN01.001 were estimated by reviewing the waste container inventory records for 2,470 containers packaged from 1979 through 2006. The waste container inventory provides a volume for waste materials packaged. By far the predominant WMP was solidified inorganic and organic material. However, from 1979 through 1987, the solidified matrix was packaged into one-gallon steel cans. These cans were considered mixing containers and not layers of confinement. Therefore, the cans were considered part of the waste. From 1988 through 2006, the concrete was mixed as a monolith in a rigid polyethylene liner inside the 55-gallon drum. As with the one-gallon cans, LANL considered the liner a mixing container and not a layer of confinement. Therefore, the liner was also considered part of the waste for WMP purposes. These calculations conclude that the relative waste weight percentages for organic waste materials (primarily rigid polyethylene liners) and inorganic waste materials (primarily solidified inorganic and organic materials and one-gallon cans) for waste stream LA-CIN01.001 are 0.61 percent and 99.39 percent, respectively. The results of the assessment are presented in Table 11, Waste Stream LA-CIN01.001 Waste Material Parameter Estimates.

The statistical analysis of the data is documented in a memorandum (included with Attachment 6) as required by CCP-TP-005 (Reference 8).

Table 11. Waste Stream LA-CIN01.001 Waste Material Parameter Estimates

| Waste Material Parameter | Avg. Weight Percent | Weight Percent Range |
|---|---|---|
| Iron-based Metals/Alloys | 3.43% | 0.0 – 97.29% |
| Aluminum-based Metals/Alloys | 0.00% | 0.0 – 0.0% |
| Other Metals | 0.00% | 0.0 – 0.0% |
| Other Inorganic Materials | 0.00% | 0.0 – 0.0% |
| Cellulosics | 0.00% | 0.0 – 0.0% |
| Rubber | 0.00% | 0.0 – 0.0% |
| Plastics (waste materials) | 0.61% | 0.0 – 3.31% |
| Organic Matrix | 0.00% | 0.0 – 0.0% |
| Inorganic matrix (solidified inorganic and organic materials) | 95.96% | 2.71 – 98.99% |
| Soils/Gravel | 0.00% | 0.0 – 0.0% |
| **Total Organic Waste Avg.** | **0.61%** | |
| **Total Inorganic Waste Avg.** | **99.39%** | |

### 6.4.2 Radiological Characterization

#### 6.4.2.1 Pu-238, Pu-239, Pu-240, Pu-241, and Pu-242

The primary plutonium material type inputs for the plutonium recovery process are listed in Section 5.4.2.2, Table 3. However, other MTs are occasionally introduced as feed material. The assignment of MTs is used to describe the isotopic composition of common blends of radioactive materials used within the DOE complex (References C186, C194, C209, C219, C222, D025, D073, D074, D076, D080, D083, M222, M283, M295, and M309).

Recovery operations are not expected to alter the plutonium isotopic ratios of the feed material. The material type used in the operation generating each waste item is documented on generator records; however, cross-contamination of equipment with different material types can lead to variable material types detected by radioassay (References D025, M222, M236, and M238).

The primary MT that feeds into the Pu-238 operations described in this report is heat source grade plutonium (MT 83), and these operations are not expected to alter the plutonium isotopic ratios of the feed material. Section 5.4.2.2, Table 3, identifies the isotopic distribution of MT 83 based on 100 isotopic analyses which were decay corrected assuming the material was not chemically separated for 45 years (References C125, C186, C194, C209, C219, C222, D073, D074, D076, D080, D083, M283, M295, and M309).

6.4.2.2 U-233, U-234, U-235, and U-238

U-233 and U-238 are not normally components of the plutonium MTs handled at PF-4. U-235 is present from the decay of Pu-239 only at 0.1 percent by weight of the total plutonium content. However, all three isotopes have been introduced as special material. In addition, uranium-plutonium oxide mixtures have been processed to recover the plutonium. Significant quantities of U-234 will be present from the decay of Pu-238 in waste originating from heat source plutonium operations (References C222, D025, and D076).

In general, uranium and its isotopes are expected to be present only at trace levels, if at all, if the feed material did not purposely contain uranium. However, some reactor fuel development, uranium-plutonium separation, and pit disassembly operations have uranium material as the feed material. The primary uranium MT inputs are listed in Section 5.4.2.2, Table 4 (Reference D080).

U-234 content must be estimated since this isotope cannot be reliably measured using NDA techniques (Reference C001). The MT provides the basis for estimating an upper bound for U-234 based on the rate of decay of the precursor, Pu-238, and the assumption that there is no other source of uranium in the waste material. The content of U-234 in the Pu-239 MTs is calculated as the sum of the contributions expected from decay of Pu-238 and from uranium input to the operation, with the value of 0.014 conservatively used for the ratio of abundances of U-234 to U-235 in typical uranium MTs. The standard uranium MTs provide an estimate of the ratio of U-234 to U-235 where one of the MTs listed in Section 5.4.2.2, Table 4, is an indicated MT in the waste container (References D025 and D083).

6.4.2.3 Am-241

AK on the MT inputs provides the basis for estimating an upper bound for Am-241 content based on the rate of decay of the precursor, Pu-241. The purpose of such bounding calculations is to provide a basis for identifying significant enrichment or depletion of Am-241 based on radioassay results for individual waste containers. The calculations assume that (a) none of these isotopes were initially present in the material, (b) the oldest plutonium material in inventory dates back to January 1, 1960, and (c) the legacy waste was packaged on January 1, 1996, making it 36 years old at that time. In general, wastes from the plutonium recovery process are enriched with Am-241, because a primary intent of the recovery process is to reduce the americium content of the retained plutonium (References C222, D025, and D083).

No correlation is expected among the different radioelements, Pu, Np, U, Pa, or Am. The differences in valence states and chemical affinities among these elements are expected to result in substantial fractionation during several recovery operations, including ion exchange, solvent extraction, hydroxide precipitation, and dissolution (References D025 and D083).

6.4.2.4 Other Radionuclides Present Due to Decay

Other radionuclides will be present in most of the wastes from the decay of a plutonium isotopic precursor or as a contaminant in the feed material. Refer to Section 5.4.2.4 for a discussion of Np-237, Am-243, Pa-231, and Ac-227 decay products (References C067, C073, C208, C209, D025, D080, and D083).

6.4.2.5 Cs-137 and Sr-90

Cs-137

Cs-137 is a product of the spontaneous fission of Pu-238, Pu-239, and especially Pu-240. Cs-137 is also a trace contaminant in purified plutonium from the production reactors (References C067 and C073). In the latter case, the remaining cesium could be on the order of 0.5 ng/g plutonium. In the former instance, the formation of Cs-137 due to spontaneous fission would lead to about 0.4 pg/g plutonium in plutonium that is ten years old. Because Cs-137 due to spontaneous fission is about a factor of a thousand less than that due to residual contamination from the original separation on the production fuel, the latter is the dominant source of cesium in waste (References C208, C209, D025, and D083).

Sr-90

Based on interviews with an SME, no spent nuclear fuel or other material containing Sr-90 were introduced into the TRU waste streams (Reference C076). No references or procedures related to spent fuel processing were located in the AK investigation of records. No generator documents (WODF, DWLS, TWSR, and WPF) identified spent fuel or Sr-90 as inputs or as present in the waste. During review of WPFs and database records from the waste storage facility (TA-54), use of material containing Sr-90 was not identified (References C139 and C208). However, because of the requirement that an estimate of Sr-90 content be made, the following approach is taken. In plutonium production runs, Cs-137 and Sr-90 are produced at approximately the same level. These two nuclides have very similar half-lives (~ 30 y) and will therefore be present at roughly the same activity level prior to commencement of any processing operations. If it is assumed that strontium and cesium are not fractionated from one another during chemical processing, Cs-137 may be used as a marker for Sr-90 activity at a ratio of 1:1 (References D025 and D083).

6.4.2.6 Other Radionuclides Introduced as Feed Material

Refer to Section 5.4.2.6 and Table 5 for a discussion of secondary radionuclides that are also present in this waste stream due to operations involving feed materials other than plutonium. The list of radionuclides includes Ac-227, Am-241, Am-243, Ce-144, Cm-244, Np-237, Pa-231, Pu-238, Th-230, Th-232, U-233, U-235, and U-238 (References C067, C076, C108, D025, and D083).

Controlled
Copy



#### 6.4.2.7 Estimated Predominant Isotopes and 95 percent Total Activity

Radionuclide data established by the PF-4 waste generator on a container basis and container data from the Area G waste storage records were evaluated to determine the relative radionuclide weight and activity for waste stream LA-CIN01.001. This evaluation was performed using the combined data for all containers in this waste stream. From this evaluation, the two predominant isotopes for the waste stream are Pu-239 and U-238, while over 95 percent of the total activity in the waste stream is from Am-241, Pu-238, Pu-239, and Pu-241. It should be noted that although U-238 is the most prevalent radionuclide by mass in the waste stream, U-238 was reported in only 204 containers. Table 12, Estimated Radionuclide Distribution in LA-CIN01.001, identifies the relative radionuclide weight and activity percent of expected radionuclides over the entire waste stream based on the container data evaluated. As illustrated in Table 12, the radionuclide weight percent of individual radionuclides varies greatly on a container-by-container basis. Because of this variability in container loadings, some containers will not contain the waste stream predominant radionuclides but may contain other radionuclides expected in this waste stream (References C133, C139, C180, C232, C234, D041, and M307).

#### 6.4.2.8 Use of Radionuclide Isotopic Ratios

For waste containers where direct measurement does not yield useable isotopic ratio information, AK may be used to supplement direct measurement data in accordance with the WIPP-WAC (Reference 3). The ratios that may be used are those identified in Section 5.4.2.2, Tables 3 and 4, in conjunction with the corresponding nuclear material type identified by the waste generator on a container basis. The specific use and confirmation of AK related to WIPP-certified assay measurements of containers in this waste stream is documented in the memorandum written in accordance with the requirements of CCP-TP-005 (Reference 8).

Table 12. Estimated Radionuclide Distribution in LA-CIN01.001

| Radionuclide | Total Nuclide Weight%[1,5] | Total Nuclide Curie%[2,5] | Nuclide Wt% Range for Individual Containers[3,5] | | | Nuclide Ci% Range for Individual Containers[4,5] | | | Expected Present |
|---|---|---|---|---|---|---|---|---|---|
| **WIPP Required Radionuclides** | | | | | | | | | |
| Am-241 | 0.60% | **31.62%** | 0 | - | 98.22% | 0 | - | 99.85% | Yes |
| Pu-238 | 0.01% | **3.61%** | 0 | - | 86.52% | 0 | - | 98.74% | Yes |
| Pu-239 | **9.82%** | **9.36%** | 0 | - | 96.42% | 0 | - | 37.04% | Yes |
| Pu-240 | 0.74% | 2.57% | 0 | - | 20.66% | 0 | - | 4.88% | Yes |
| Pu-242 | 0.08% | Trace | 0 | - | 92.08% | 0 | - | 0.21% | Yes |
| U-233 | Trace | Trace | 0 | - | 52.74% | 0 | - | 3.71% | Yes |
| U-234 | Trace | Trace | 0 | - | 0.74% | 0 | - | 0.09% | Yes |
| U-238 | **87.51%** | Trace | 0 | - | 99.68% | 0 | - | 0.10% | Yes |
| Sr-90 | Trace | Trace | 0 | - | Trace | 0 | - | Trace | Yes |
| Cs-137 | Trace | Trace | 0 | - | Trace | 0 | - | Trace | Yes |
| **Additional Radionuclides** | | | | | | | | | |
| Am-242 | Trace | 0.01% | 0 | - | Trace | 0 | - | 22.82% | Yes |
| Am-243 | Trace | Trace | 0 | - | 1.36% | 0 | - | 0.98% | Yes |
| Bk-249 | Trace | Trace | 0 | - | Trace | 0 | - | Trace | Yes |
| Cd-109[6] | Not Reported | | | | | | | | Yes |
| Ce-144[6] | Not Reported | | | | | | | | Yes |
| Cf-249 | Trace | Trace | 0 | - | Trace | 0 | - | Trace | Yes |
| Cm-244[6] | Not Reported | | | | | | | | Yes |
| Na-22[6] | Not Reported | | | | | | | | Yes |
| Np-237 | Trace | Trace | 0 | - | 4.63% | 0 | - | 0.01% | Yes |
| Np-239[6] | Not Reported | | | | | | | | Yes |
| Pa-231[6] | Not Reported | | | | | | | | Yes |
| Pu-241 | 0.03% | **52.83%** | 0 | - | 3.01% | 0 | - | 93.99% | Yes |
| Pu-244 | Trace | Trace | 0 | - | 0.02% | 0 | - | Trace | Yes |
| Th-228 | Trace | Trace | 0 | - | Trace | 0 | - | Trace | |
| Th-230[6] | Not Reported | | | | | | | | Yes |
| Th-232 | 0.83% | Trace | 0 | - | 94.84% | 0 | - | Trace | Yes |
| U-235 | 0.48% | Trace | 0 | - | 74.54% | 0 | - | Trace | Yes |
| U-236 | Trace | Trace | 0 | - | 0.35% | 0 | - | Trace | Yes |

1. This listing indicates the total weight percent of each radionuclide over the entire waste stream.
2. This listing indicates the total activity (curie) percent of each radionuclide over the entire waste stream.
3. This listing is the weight percent range of each radionuclide on a container-by-container basis.
4. This listing is the curie percent range of each radionuclide on a container-by-container basis.
5. “Trace” indicates <0.01 weight or activity percent for that radionuclide.
6. Radionuclides not reported but suspected present from secondary radionuclides or decay.

### 6.4.3 Chemical Content Identification – Hazardous Constituents

Waste stream LA-CIN01.001 has historically been managed in accordance with the generator site requirements and in compliance with the requirements of the New Mexico Environmental Department. Based on historical waste management and LANL's TRU Program (reference LANL waste stream LAMIN01-CIN), the containers in this waste stream were managed as hazardous and assigned the same EPA HWNs as the debris waste including arsenic (D004), barium (D005), cadmium (D006), benzene (D018), carbon tetrachloride (D019), chlorobenzene (D021), chloroform (D022), methyl ethyl ketone (D035), pyridine (D038), tetrachloroethylene (D039), trichloroethylene (D040), and F-listed solvents (F001, F002, F003, and F005). A review of available AK documentation has determined that this waste is hazardous for the above constituents, and with the exception of F003, the HWNs were retained. HWN F003 was not assigned because the waste stream does not exhibit the characteristic of ignitability. The following sections describe the characterization rationale for the assignment of EPA HWNs. Table 13, Waste Stream LA-CIN01.001 Hazardous Waste Characterization Summary, summarizes the EPA HWNs assigned to this waste stream. The HWN assignments have been applied on a waste stream basis; individual containers may not contain all of the hazardous materials listed for the waste stream as a whole (References C121, C147, and D083).

Table 13. Waste Stream LA-CIN01.001 Hazardous Waste Characterization Summary

| Waste Stream | EPA HWNs |
|---|---|
| LA-CIN01.001 | F001, F002, F005, D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040 |

Chemical constituents of inputs are compiled from chemical lists contained in procedures and from SME input. In this section, discussion of the chemical inputs is divided into the following categories (References C121, C147, and C197):

- Process feed materials
- Chemical Identification and Use

Section 5.4.3, Table 8, provides a summary of the special nuclear material feed materials processed by the operations described in this report.

#### 6.4.3.1 Chemical Inputs

To assign EPA HWNs, the available AK documentation is reviewed to assess chemical usage in the TA-55 PF-4 operations contributing to waste stream LA-CIN01.001, and potentially hazardous materials that may have been introduced into the waste stream. In addition, MSDSs are obtained for the commercial products to determine the presence of potentially regulated compounds. As described in Section 5.4.3.1, Table 9, several of

the HWNs are assigned due to lack of analytical evidence that these constituents have not exceeded the regulatory thresholds. The chemical inputs identified in Table 9 are used during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations. This waste is comprised of cemented liquids and residues that are generated by these operations. Therefore, these constituents have the potential to contaminate this waste stream.

6.4.3.2 F-, K-, P-, and U-Listed Constituents

Based on review of AK relative to chemicals used or present in the facility and operations potentially contaminating the cemented TRU waste, LA-CIN01.001 may contain or be mixed with F-listed hazardous wastes from non-specific sources listed in 40 CFR 261.31 (Reference 15). As shown in Section 5.4.3.1, Table 9, F001, F002, F003, and F005 listed solvents are utilized and could potentially contaminate the waste. F003 constituents, including acetone, n-butyl alcohol, ethyl ether, methanol, and xylene, are listed solely because these solvents are ignitable in the liquid form. The waste stream does not exhibit the characteristic of ignitability and therefore F003 is not assigned. Waste stream LA-CIN01.001 is assigned F-listed EPA HWNs F001, F002, and F005 for potential 1,1,1-trichloroethane, benzene, carbon tetrachloride, chlorobenzene, Freon TF (1,1,2-trichloro, 1,2,2-trifluoroethane), methylene chloride, methyl ethyl ketone, pyridine, tetrachloroethylene, toluene, and trichloroethylene contamination (References C121, C147, and D083).

At one time, HWN P120 was applied to certain drums generated in 1998 because of the temporary use of vanadium pentoxide for about six months in that year. Based upon investigation into the way the material was handled, this code is not assigned to this waste stream. A P120 assignment would be used only if waste resulted from spillage of this material or from disposal of un-reacted/unspent material. No un-reacted/unspent material was disposed of in TRU waste drums. In addition, no significant spill of this material occurred. If a spill had occurred, suitable records would exist (e.g., incident reports, waste profile forms). The absence of such documentation, coupled with information obtained through interviews of people who worked with the material, indicates that a P120 assignment is not necessary (References C061, C147, and D083).

Beryllium may be present in the waste stream, but does not meet the definition of a P015-listed waste. Available AK did not identify beryllium powder as a constituent in this waste stream. During processing within P/S Codes PU and PUB, beryllium from Pu-Be sources is dissolved with the plutonium in acid, and after dissolution, the beryllium is either precipitated or in the contaminated solution is sent to the RLWTF at TA-50. The precipitate is not included in this waste stream. Beryllium from metal operations, in general, is in the form of classified shapes and is therefore not in this waste stream. In some cases, beryllium turnings are generated during machining operations. However, these turnings are not expected to be in this homogeneous waste

stream. The beryllium contaminated waste from the material reclamation process was debris and would also not be in this waste stream. Individual containers in waste stream LA-CIN01.001 will contain less than one weight percent beryllium (References 14, C121, C122, C147, C156, and M283).

Hydrofluoric acid was used or present in the facility and operations potentially contaminating the cemented TRU waste; however, a U134 HWN assignment would only be applicable if the waste resulted from a spill or disposal of unused material. There is no documented spill of this material present. In addition, there is no record of unused hydrofluoric acid being disposed of in this waste stream (References C121, C155, D002, and D025).

Waste stream LA-CIN01.001 does not contain and is not mixed with a discarded commercial chemical product, an off-specification commercial chemical product, or a container residue or spill residue thereof. Constituents identified were further researched and a determination was made that waste does not meet the definition of a listed waste in 40 CFR 261.33 (Reference 15). The material in this waste stream is not hazardous from specific sources since it is not generated from any of the processes listed in 40 CFR 261.32 (Reference 15). Therefore, this waste stream is not a K-, P-, or U-listed waste stream (Reference C121).

#### 6.4.3.3 Toxicity Characteristic Constituents

Based on review of AK relative to chemicals used or present in the facility and operations potentially contaminating the cemented TRU waste, LA-CIN01.001 may be contaminated with toxicity characteristic compounds as defined in 40 CFR 261.24 (Reference 15) as summarized in Section 5.4.3.1, Table 9. Where a constituent is identified and there is no quantitative data available to demonstrate that the concentration of a constituent is below regulatory threshold levels, the applicable EPA HWN is added to the waste stream. The AK also identified the potential presence of organic toxicity characteristic compounds that are assigned the more specific F-listed EPA HWNs. Although these organic characteristic compounds are covered by the assignment of the F-listed EPA HWNs, the toxicity characteristic EPA HWNs are also assigned to the waste stream for consistency with historical site waste coding. Waste stream LA-CIN01.001 is assigned the following HWNs: D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040 (References C121, C147, D050, and D083).

#### 6.4.3.4 Ignitables, Corrosives, and Reactives

The homogeneous material in waste stream LA-CIN01.001 does not meet the definition of ignitability as defined in 40 CFR 261.21 (Reference 15). Ignitable chemicals (e.g., acetone, hexane) are used or present in the facility and operations potentially contaminating this waste stream. However, D001 (ignitability) does not apply to because: (a) the solid waste is not liquid, and verification that there are no prohibited

liquids in the waste is performed prior to certification; (b) the solid waste does not spontaneously ignite at standard pressure and temperature through friction, absorption of moisture, or spontaneous chemical changes; (c) the solid waste is not an ignitable compressed gas; and (d) there are no oxidizers present that can stimulate combustion. For example, evaporator salts (i.e., nitrate salts) solidified/stabilized in cement would not stimulate combustion and; therefore, would not meet the definition of an oxidizer. The materials in the waste stream are therefore not ignitable wastes (D001) (References C121, C147, C201, C203, D071, D083, P096, P102, and P187).

The homogeneous material in waste stream LA-CIN01.001 is not liquid and does not contain unreactive corrosive chemicals; therefore, it does not meet the definition of corrosivity as defined in 40 CFR 261.22 (Reference 15). Corrosive chemicals (e.g., hydrofluoric acid, nitric acid, potassium hydroxide, sodium hydroxide) are used or present in the facility and operations potentially contaminating this waste stream. However, D002 (corrosivity) does not apply because the solid waste is not a liquid, and verification that there are no prohibited liquids in the waste is performed prior to certification. The materials in the waste stream are therefore not corrosive wastes (D002) (References C121, C147, C194, D071, D083, P096, and P102).

The homogeneous material in waste stream LA-CIN01.001 does not meet the definition of reactivity as defined in 40 CFR 261.23 (Reference 15). Reactive chemicals (e.g., perchloric acid, sodium metal) are used or present in the facility and operations potentially contaminating this waste stream. However, D003 (reactivity) does not apply because the waste is stable and will not undergo violent chemical change without detonating. The waste will not react violently with water, form potentially explosive mixtures with water, or generate toxic gases, vapors, or fumes when mixed with water. The waste does not contain reactive cyanide or sulfide compounds. There is no indication that the waste contains explosive materials, and it is not capable of detonation or explosive reaction. The materials in the waste stream are therefore not reactive wastes (D003) (References, C121, C147, C201, C202, D071, and D083).

Controls have also been in place to ensure the exclusion of ignitable, corrosive, and reactive constituents. Section 5.4.3.4 provides a detailed list of TA-55 controls that apply to all waste streams. In addition, the absence of prohibited items is verified through RTR of each waste container (References D037, D041, D049, D083, P090, P096, P097, P102, and P165).

#### 6.4.3.5 Polychlorinated Biphenyls (PCBs)

Based on documentation in procedures reviewed during the AK investigation and summarized in lists of inputs documented in the TA-55 process reports, no sources of PCBs are introduced into waste stream LA-CIN01.001. In the cement fixation operation (P/S Codes CF and HP), oils are sometimes added to drums of cemented waste. They are added to the 55-gallon drums of cement in small quantities (maximum of six liters). The oils are primarily vacuum pump oils, along with some oils used in heat-treating

(cooking or silicone oils) or in grinding. None of these oils are known to contain PCBs. All transformers known to contain PCBs have been tracked from initiation of recovery operations. When any transformer oil is drained, the oil is handled by a subcontractor who is wholly responsible for its disposal; this oil does not enter the LANL disposal operations. Therefore, this waste stream is not regulated as a TSCA waste under 40 CFR 761 (References 18, C096, C147, C201, D080, D083, P012, and P162).

6.4.3.6 Flammable Volatile Organic Compounds

The cement fixation process immobilizes aqueous and organic liquids with low plutonium concentrations, evaporator bottoms, and salts in cement. Based on review of AK relative to chemicals used or present in TA-55, trace quantities of Flammable Volatile Organic Compounds (FVOCs) may be present in the materials prior to processing and therefore an evaluation of potential FVOC concentrations was performed.

The cement fixation process primarily immobilizes the materials listed above; however, historically filtered solids and fines were also sometimes cemented, but this is no longer done. Reagents used during this operation include cement accelerator, gypsum cement, nitric acid (pH adjustment), organic liquid emulsifier, Portland cement, silicone defoamer, sodium citrate retarder, sodium hydroxide, and phthalate and phosphate buffer solutions for pH meter calibration. The waste materials were adjusted to a specific pH and stirred directly with gypsum or Portland cement into a one-gallon can inside the glovebox or 55-gallon drum attached to the glovebox. The cement fixation process is performed in a closed system, which prevents any introduction of extraneous material such as flammable compounds (References C171, C200, D008, D036, and D078).

The estimated waste weight percentages for inorganic waste materials (solidified inorganic and organic materials and one-gallon cans) and organic waste materials (rigid polyethylene liners) for this waste stream are 99.39 percent and 0.61 percent, respectively. In addition, the results of available headspace gas sampling and analysis of 50 drums in this waste stream indicated that FVOCs are not present in significant amounts. The total FVOCs measured for each of the drums is well below 500 ppm. Based on the final waste form and sample data, containers in waste stream LA-CIN01.001 are not expected to exceed a total FVOC concentration of greater than or equal to 500 ppm (References 8 and C184).

6.4.4 Prohibited Items

6.4.4.1 Compressed Gases, Liquids, Nonradionuclide Pyrophorics, Sealed Containers > Four Liters In Volume, >1 Percent Radionuclide Pyrophorics, and >200 mrem/hr Waste

Refer to Section 5.4.4.1 for a detailed evaluation of compressed gases, liquids, nonradionuclide pyrophorics, sealed containers greater than four liters in volume, >1 percent radionuclide pyrophorics, and >200 mrem/hr waste in TA-55 waste streams.

#### 6.4.4.2 Remediation Of Prohibited Items

Prohibited items are known to be present. Procedures allowed containers greater than four liters, sealed with tape, to be used for waste packaging until WIPP certification procedures were implemented. In addition, the potential for prohibited quantities of liquid due to dewatering is anticipated. Lead shielding is used to increase handling safety, and thick shielding can obscure RTR observations (References C142, C143, D050, D083, and U005).

Prohibited items are detected by RTR and reported with the characterization results. Waste containers with prohibited items are segregated then dispositioned appropriately and/or repackaged, during which time liquids are absorbed, sealed containers greater than four liters are opened, and other items removed and segregated if necessary prior to certification and shipment. Some secondary waste generated during remediation and repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., plastic bags, plywood sheathing, rigid liner lids cut into pieces) (References C150, C177, D083, M316, P154, P158, and P203).

## 6.5 Waste Packaging

Waste packaging procedures for waste streams have been modified several times since the beginning of plutonium operations in PF-4 and containers in this waste stream include a variety of configurations with up to six layers of confinement. Historically cemented TRU waste could have been packaged in a vented 30-gallon drum. However, it is expected that cemented TRU waste from waste management operations would usually be packaged into a DOT 7A, Type A 55-gallon steel drum. Waste may be placed into plastic bags and mixed with cement (e.g., Portland cement) and water by hand-kneading. After cementation the bags were placed in cans and loaded into 55-gallon drums. Waste may be mixed with cement directly in cans and packaged into a 55-gallon drum with up to two plastic liner bags ranging from 5-mil to 12-mil. The typical arrangement of cans in the drum was five layers with each layer containing seven cans for a total of 35 cans. However, more or less cans could be present in a 55-gallon drum. The arrangement varied including placing inner cans with cement into larger cans and/or plastic bags. Cans with americium oxide were placed in the center of the drum. The inner cans were typically one-gallon in size; however, cans ranging in size from one quart to five gallon cans were used. The inner cans may include slip-top (also referred to as slip-fit) lids or tabbed pry-off lids with or without tape used to secure

the lid. The inner cans may or may not include shielding (e.g., lead liner). Waste may also be mixed with cement in a 90-mil/125-mil rigid polyethylene liner and packaged in a 55-gallon drum with up to two plastic liner bags. A cemented can of americium oxide could be included in the drum and it would be placed approximately midway down into the cement. However, personnel involved in the packaging of cemented waste believe this option was never used. When the drum was full the plastic liner bags were closed using the twist and tape method or the twist, tie, and tape method. The above packaging configurations typically, but not always, included 1/16-inch thick shielding (e.g., lead liner). The shielding (e.g., lead liner) consisted of two 1/16 inch thick discs, placed at the top and bottom of a 1/16-inch thick lead sheet fitted to the inside of the drum wall. If necessary, one or more 2-inch thick Styrofoam discs were placed on top of the outer plastic liner bag as bracing for the top circular lead disc (References C140, C226, C228, D041, D083, M252, P090, P152, P153, P179, P188, and U005).

Since 1995, several changes have been introduced to the packaging procedures. Liner bags could still be present, but they are typically closed by folding, not by taping. All waste packages (i.e., drums) are vented with approved filter vents prior to disposal (e.g., Nucfil-013). Since 1997, plastic bags with filters are typically used (References P091, P152, P153, P164, P166, P167, P168, P169, P178, and U005).

Beginning in 2006, several additional changes were introduced to the packaging procedures. The waste is still mixed with cement in a rigid polyethylene liner which is contained in a single plastic liner bag. A plastic bag skirt of the same material is attached to the rigid polyethylene liner on the inside of the drum-out bag for contamination control. The bag skirt is pushed down into the container once the mixing is complete to expose a clean drum-out bag. The drum-out bag is gathered into a tight bundle, sealed (e.g., with tape, plastic cable ties), and cut to remove the drum from the glovebox. Cemented waste is no longer packaged with a 1/16-inch thick shielding (e.g., lead liner) and Styrofoam discs. Remediated/repackaged waste may be packaged with or without a single plastic liner bag with one of the following drum configurations depending on the remediation facility: no liner, a fiberboard liner, a POC, or a 90-/125-mil rigid polyethylene liner without lid. Waste placed into a POC may be packaged into a single filtered plastic bag which may include a fiberboard liner/sleeve inside the plastic bag. POCs contain a pipe component in a 55-gallon drum that is lined with a punctured rigid liner with packing material between the pipe component and liner (References C164, P159, P171, P172, P175, and P195).

During waste management and drum storage activities following initial waste generation, 55-gallon drums have been overpacked larger drums (i.e., 85-gallon drums or larger) or SWBs to correct/address external contamination, FGE limits, and drum integrity problems such as pin hole corrosion, dents, etc. If drums are overpacked in an SWB (up to four 55-gallon), no closed liner bags are used in the SWB (References C138, D018, D024, D068, M222, P092, P098, P117, P158, P166, and P167).

Controlled
Copy



RTR will confirm waste stream TRUCON code LA126/226. However, TRUCON code LA114/214 has been identified as suitable for individual containers in this waste stream. This TRUCON code may be assigned for the eventual certification and transportation of payload containers in this waste stream pending further evaluation by the Waste Certification Official of container-specific information. Vent dates for individual containers are provided in the AK Tracking Spreadsheet (References 9, 14, C002, C138, and M296).

## 7.0 REQUIRED WASTE STREAM INFORMATION: LA-MIN02-V.001

This section presents the mandatory waste stream AK required by the WIPP-WAP (Reference 1). Attachment 1 of CCP-TP-005 (Reference 8) provides a list of the TRU waste stream information required to be developed as part of the AK record.

### 7.1 Area and Building of Generation

All of the absorbed waste covered by this report originated from TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations described in Section 4.4. Container-specific records are reviewed for each container to verify the physical composition and origin of the waste stream inventory (References C154, C181, M222, and M242).

### 7.2 Waste Stream Volume and Period of Generation

Waste stream LA-MIN02-V.001 is mixed absorbed waste generated from 1980 to present. Table 14, LA-MIN02-V.001 Approximate Waste Stream Volume, summarizes the current volume of this waste stream. The future projection of additional generation of this waste stream is approximately 0.21 cubic meters per year. There is no projected end date for the termination of operations that generate this waste stream (References C152, C154, C181, C232, C235, D041, M222, and M242).

Table 14. LA-MIN02-V.001 Approximate Waste Stream Volume

| Containers | Volume (cubic meters) |
|---|---|
| 450 55-gallon drums (includes POCs) | 94.5 |
| 4 85-gallon drums | 1.28 |
| 1 SWB | 1.88 |
| 455 Total | 97.66 |

### 7.3 Waste Generating Activities

Absorbed waste is generated by or originated from materials used during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations described in detail in Section 4.4 and includes (References D041 and D083):

- Preparing ultra-pure plutonium metals, alloys, and compounds
- Preparing (on a large scale) specific alloys, including casting and machining these materials into specific shapes

- Determining high-temperature thermodynamic properties of plutonium
- Reclaiming plutonium from scrap and residues produced by numerous feed sources
- Disassembling components for inspection and analysis
- Manufacturing of parts on a limited basis
- Processing mixtures of plutonium and uranium oxides for reactor fuels
- Pu-238 generator and heat source R&D, fabrication, testing, and recycling

## 7.4 Type of Wastes Generated

This section describes the process inputs, Waste Matrix Code assignment, WMPs, radionuclide contaminants, and RCRA hazardous waste determinations for waste stream LA-MIN02-V.001. The waste stream is characterized based on knowledge of the materials, knowledge of the operations generating the waste, and physical descriptions of the waste.

### 7.4.1 Material Input Related to Physical Form

Waste stream LA-MIN02-V.001 consists primarily of inorganic particulate waste generated in TA-55. The waste is largely comprised of TRU waste such as liquids and solids absorbed or mixed with absorbent (e.g., Ascarite II [sodium hydroxide coated silicate], diatomaceous earth [silica and quartz], kitty litter [clay], vermiculite [hydrated magnesium aluminum iron silicate], and/or zeolite [aluminosilicate mineral]). Examples of absorbed liquids include acids (e.g., hydrochloric acid, hydrofluoric acid, and nitric acid); carbon tetrachloride; ethylene glycol; kerosene; methanol; methylene chloride; silicone based liquids (e.g., silicone oil); tetrachloroethylene; tributyl phosphate; trichloroethylene; and various types of oils including hydraulic, vacuum pump, grinding, and lapping (mixture of mineral oil and lard). Solids mixed with absorbents are typically evaporator salts (i.e., nitrate salts). The waste is also expected to contain heavy metals such as cadmium, chromium, and lead. Liquids and solids not absorbed or mixed with absorbent are often cemented and disposed of separately in waste stream LA-CIN01.001. A small fraction of debris waste (less than 50 percent by volume) including plastic packaging, metal packaging, lead (e.g., shielding), PPE, and metal fines may also be present. Finally, some secondary waste generated during remediation/repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770 [sodium polyacrylate]), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., metal, plastic bags, plywood sheathing, rigid liner lids cut into pieces)

(References C005, C035, C080, C094, C150, C177, C232, D007, D025, D032, D036, D041, D080, D083, M064, M142, M242, M286, and M316).

7.4.1.1 Waste Matrix Code

Based on the evaluation of the materials contained in this waste stream and LANL waste management practices, this waste stream is comprised of greater than 50 percent by volume of absorbed waste. Therefore, Waste Matrix Code S3110, Inorganic Particulate Waste, is assigned to waste stream LA-MIN02-V.001 (References 2, C154, D041, D083, M222, and M242).

7.4.1.2 Waste Material Parameters

The WMPs for waste stream LA-MIN02-V.001 were based on the descriptions of waste packaged into 339 containers. This waste stream is greater than 50 percent by volume of absorbed waste (References C154, C232, D041, D083, M222, and M242).

The WMPs for 49 containers were calculated assuming that approximately one gallon of absorbed waste was placed into either a 5-mil plastic bag or a one-gallon can, and subsequently placed in a bag-out bag prior to being placed in a drum. A conservative approach was taken with respect to the absorbed liquid. Unless specified otherwise, the liquid absorbed was assumed to be an organic matrix. Vermiculite, for example, is known to absorb approximately 250 percent of its weight in liquid; therefore, the vermiculite/organic matrix would be considered to be greater than 50 percent organic matrix. The WMPs for 290 containers were calculated assuming a 1 to 1.5 ratio of evaporator salts (i.e., nitrate salts) mixed with an inorganic absorbent material (e.g., zeolite, kitty litter). The average weights of absorbed waste, metal cans, and bag-out bags were used in the calculations. Average, minimum, and maximum WMP weight percentages were calculated using this data. These calculations conclude that the relative waste weight percentages for organic waste materials (primarily absorbed organic liquids and plastic bags) and inorganic waste materials (primarily absorbed inorganic solids and steel cans for waste stream LA-MIN02-V.001 are 15.13 percent and 84.87 percent, respectively. The results of the assessment are presented in Table 15, Waste Stream LA-MIN02-V.001 Waste Material Parameter Estimates.

The statistical analysis of the data is documented in a memorandum (included with Attachment 6) as required by CCP-TP-005 (Reference 8).

Table 15. Waste Stream LA-MIN02-V.001 Waste Material Parameter Estimates

| Waste Material Parameter | Avg. Weight Percent | Weight Percent Range |
|---|---|---|
| Iron-based Metals/Alloys | 4.65% | 0.00% – 9.17% |
| Aluminum-based Metals/Alloys | 0.00% | 0.00% – 0.00% |
| Other Metals | 0.00% | 0.00% – 0.00% |
| Other Inorganic Materials | 0.00% | 0.00% – 0.00% |
| Cellulosics | 0.00% | 0.00% – 0.00% |
| Rubber | 0.00% | 0.00% – 0.00% |
| Plastics (waste materials) | 4.57% | 2.90% – 14.37% |
| Organic Matrix | 10.56% | 0.00% – 73.09% |
| Inorganic Matrix | 80.22% | 0.00% – 93.20% |
| Soils/Gravel | 0.00% | 0.00% – 0.00% |
| **Total Organic Waste Avg.** | **15.13%** | |
| **Total Inorganic Waste Avg.** | **84.87%** | |

### 7.4.2 Radiological Characterization

#### 7.4.2.1 Pu-238, Pu-239, Pu-240, Pu-241, and Pu-242

The primary plutonium material type inputs for the plutonium recovery process are listed in Section 5.4.2.2, Table 3. However, other MTs are occasionally introduced as feed material. The assignment of MTs is used to describe the isotopic composition of common blends of radioactive materials used within the DOE complex (References C186, C194, C209, C219, C222, D025, D073, D074, D076, D080, D083, M222, M283, M295, and M309).

Recovery operations are not expected to alter the plutonium isotopic ratios of the feed material. The material type used in the operation generating each waste item is documented on generator records; however, cross-contamination of equipment with different material types can lead to variable material types detected by radioassay (References D025, M222, and M242).

The primary MT that feeds into the Pu-238 operations described in this report is heat source grade plutonium (MT 83), and these operations are not expected to alter the plutonium isotopic ratios of the feed material. Section 5.4.2.2, Table 3, identifies the isotopic distribution of MT 83 based on 100 isotopic analyses which were decay corrected assuming the material was not chemically separated for 45 years (References C125, C186, C194, C209, C219, C222, D073, D074, D076, D080, D083, M283, M295, and M309).

7.4.2.2 U-233, U-234, U-235, and U-238

U-233 and U-238 are not normally components of the plutonium MTs handled at PF-4. U-235 is present from the decay of Pu-239 only at 0.1 percent by weight of the total plutonium content. However, all three isotopes have been introduced as special material. In addition, uranium-plutonium oxide mixtures have been processed to recover the plutonium. Significant quantities of U-234 will be present from the decay of Pu-238 in waste originating from heat source plutonium operations (References C222, D025, and D076).

In general, uranium and its isotopes are expected to be present only at trace levels, if at all, if the feed material did not purposely contain uranium. However, some reactor fuel development, uranium-plutonium separation, and pit disassembly operations have uranium material as the feed material. The primary uranium MT inputs are listed in Section 5.4.2.2, Table 4 (Reference D080).

U-234 content must be estimated since this isotope cannot be reliably measured using NDA techniques (Reference C001). The MT provides the basis for estimating an upper bound for U-234 based on the rate of decay of the precursor, Pu-238, and the assumption that there is no other source of uranium in the waste material. The content of U-234 in the Pu-239 MTs is calculated as the sum of the contributions expected from decay of Pu-238 and from uranium input to the operation, with the value of 0.014 conservatively used for the ratio of abundances of U-234 to U-235 in typical uranium MTs. The standard uranium MTs provide an estimate of the ratio of U-234 to U-235 where one of the MTs listed in Section 5.4.2.2, Table 4, is an indicated MT in the waste container (References D025 and D083).

7.4.2.3 Am-241

AK on the MT inputs provides the basis for estimating an upper bound for Am-241 content based on the rate of decay of the precursor, Pu-241. The purpose of such bounding calculations is to provide a basis for identifying significant enrichment or depletion of Am-241 based on radioassay results for individual waste containers. The calculations assume that (a) none of these isotopes were initially present in the material, (b) the oldest plutonium material in inventory dates back to January 1, 1960, and (c) the legacy waste was packaged on January 1, 1996, making it 36 years old at that time. In general, wastes from the plutonium recovery process are enriched with Am-241 because a primary intent of the recovery process is to reduce the americium content of the retained plutonium (References C222, D025, and D083).

No correlation is expected among the different radioelements, Pu, Np, U, Pa, or Am. The differences in valence states and chemical affinities among these elements are expected to result in substantial fractionation during several recovery operations, including ion exchange, solvent extraction, hydroxide precipitation, and dissolution (References D025 and D083).

7.4.2.4 Other Radionuclides Present Due to Decay

Other radionuclides will be present in most of the wastes from the decay of a plutonium isotopic precursor or as a contaminant in the feed material. Refer to Section 5.4.2.4 for a discussion of Np-237, Am-243, Pa-231, and Ac-227 decay products (References C067, C073, C208, C209, D025, D080, and D083).

7.4.2.5 Cs-137 and Sr-90

Cs-137

Cs-137 is a product of the spontaneous fission of Pu-238, Pu-239, and especially Pu-240. Cs-137 is also a trace contaminant in purified plutonium from the production reactors (References C067 and C073). In the latter case, the remaining cesium could be on the order of 0.5 ng/g plutonium. In the former instance the formation of Cs-137 due to spontaneous fission would lead to about 0.4 pg/g plutonium in plutonium that is 10 years old. Because Cs-137 due to spontaneous fission is about a factor of a thousand less than that due to residual contamination from the original separation on the production fuel, the latter is the dominant source of cesium in waste (References C208, C209, D025 and D083).

Sr-90

Based on interviews with an SME, no spent nuclear fuel or other material containing Sr-90 were introduced into the TRU waste streams (Reference C076). No references or procedures related to spent fuel processing were located in the AK investigation of records. No generator documents (i.e., WODF, DWLS, TWSR, and WPF) identified spent fuel or Sr-90 as inputs or as present in the waste. During review of WPFs and database records from the waste storage facility (TA-54), use of material containing Sr-90 was not identified (References C154 and C208). However, because of the requirement that an estimate of Sr-90 content be made, the following approach is taken. In plutonium production runs, Cs-137 and Sr-90 are produced at approximately the same level. These two nuclides have very similar half-lives (~ 30 y) and will therefore be present at roughly the same activity level prior to commencement of any processing operations. If it is assumed that strontium and cesium are not fractionated from one another during chemical processing, Cs-137 may be used as a marker for Sr-90 activity at a ratio of 1:1 (References D025 and D083).

7.4.2.6 Other Radionuclides Introduced as Feed Material

Refer to Section 5.4.2.6 and Table 5 for a discussion of secondary radionuclides that are also present in this waste stream due to operations involving feed materials other than plutonium. The list of radionuclides includes Ac-227, Am-241, Am-243, Ce-144, Cm-244, Np-237, Pa-231, Pu-238, Th-230, Th-232, U-233, U-235, and U-238 (References C067, C076, C108, D025, and D083).

#### 7.4.2.7 Estimated Predominant Isotopes and 95 percent Total Activity

Radionuclide data established by the PF-4 waste generator on a container basis and container data from the Area G waste storage records were evaluated to determine the relative radionuclide weight and activity for waste stream LA-MIN02-V.001. This evaluation was performed using the data for the containers in this waste stream (if a container was repackaged, then the data from the parent container was used). From this evaluation, the two predominant isotopes for the waste stream are Pu-239 and U-238 while over 95 percent of the total activity is from Pu-239, Pu-240, and Pu-241. It should be noted that although U-238 is the most prevalent radionuclide by mass in the waste stream, U-238 was reported in only 12 containers. Table 16, Estimated Radionuclide Distribution in LA-MIN02-V.001, identifies the relative radionuclide weight and activity percent of expected radionuclides over the entire waste stream based on the container data evaluated. Radiological data was available for all of the waste in this waste stream. However, some of the containers list “zero” assay values. It is not known why the zero assay values are listed. This could indicate that assay was not performed on these containers although they were managed as TRU waste. It could also indicate low assay containers that did not contain activity levels above the lower limit of detection. Finally, it could indicate measured or estimated plutonium mass values below 0.5 grams. As illustrated in Table 16, the radionuclide weight percent of individual radionuclides varies on a container-by-container basis. Because of this variability in container loadings, some containers will not contain the waste stream predominant radionuclides but may contain other radionuclides expected in this waste stream (References C154, C181, C232, C235, D041, M242, and M307).

#### 7.4.2.8 Use of Radionuclide Isotopic Ratios

For waste containers where direct measurement does not yield useable isotopic ratio information, AK may be used to supplement direct measurement data in accordance with the WIPP-WAC (Reference 3). The ratios that may be used are those identified in Section 5.4.2.2, Tables 3 and 4, in conjunction with the corresponding nuclear material type identified by the waste generator on a container basis. The specific use and confirmation of AK related to WIPP-certified assay measurements of containers in this waste stream is documented in the memorandum written in accordance with the requirements of CCP-TP-005 (Reference 8).

Table 16. Estimated Radionuclide Distribution in LA-MIN02-V.001

| Radionuclide | Total Nuclide Weight%[1,5] | Total Nuclide Curie%[2,5] | Nuclide Wt% Range for Individual Containers[3,5] | Nuclide Ci% Range for Individual Containers[4,5] | Expected Present |
|---|---|---|---|---|---|
| **WIPP Required Radionuclides** | | | | | |
| Am-241 | Trace | 0.05% | 0 - 7.64% | 0 - 2.43% | Yes |
| Pu-238 | 0.01% | 1.14% | 0 - 83.75% | 0 - 97.63% | Yes |
| Pu-239 | **23.19%** | **17.32%** | 0 - 95.29% | 0 - 25.16% | Yes |
| Pu-240 | 1.63% | **4.45%** | 0 - 16.49% | 0 - 4.88% | Yes |
| Pu-242 | 0.04% | Trace | 0 - 35.97% | 0 - 0.17% | Yes |
| U-233[6] | Not Reported | | | | |
| U-234 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| U-238 | **74.80%** | Trace | 0 - 99.32% | 0 - Trace | Yes |
| Sr-90 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| Cs-137 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| **Additional Radionuclides** | | | | | |
| Np-237 | Trace | Trace | 0 - 1.45% | 0 - Trace | Yes |
| Pu-241 | 0.06% | **77.04%** | 0 - 1.18% | 0 - 92.46% | Yes |
| Pu-244 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |
| U-235 | 0.26% | Trace | 0 - 21.07% | 0 - Trace | Yes |
| U-236 | Trace | Trace | 0 - Trace | 0 - Trace | Yes |

1. This listing indicates the total weight percent of each radionuclide over the entire waste stream.
2. This listing indicates the total activity (curie) percent of each radionuclide over the entire waste stream.
3. This listing is the weight percent range of each radionuclide on a container-by-container basis.
4. This listing is the curie percent range of each radionuclide on a container-by-container basis.
5. "Trace" indicates <0.01 weight or activity percent for that radionuclide.
6. Radionuclides not reported but suspected present from secondary radionuclides or decay.

### 7.4.3 Chemical Content Identification – Hazardous Constituents

Waste stream LA-MIN02-V.001 has historically been managed in accordance with the generator site requirements and in compliance with the requirements of the New Mexico Environmental Department. Based on historical waste management and LANL's TRU Program (Reference LANL waste stream LA-MIN02-V), the containers in this waste stream were managed as hazardous and assigned the same EPA HWNs as the debris waste stream (except for HWN D028 discussed below) including arsenic (D004), (D004), barium (D005), cadmium (D006), chromium (D007), lead (D008), mercury (D009), selenium (D010), silver (D011), benzene (D018), carbon tetrachloride (D019), chlorobenzene (D021), chloroform (D022), 1,2-dichloroethane (D028), methyl ethyl ketone (D035), pyridine (D038), tetrachloroethylene (D039), trichloroethylene (D040), and F-listed solvents (F001, F002, F003, and F005). A review of available AK documentation has determined that this waste is hazardous for the above constituents, and with the exception of D028 and F003, the HWNs were retained. An evaluation was performed of existing TA-55 AK source documentation and no use of 1,2-dichloroethane (D028) was identified. This HWN is also not assigned to any other TA-55 waste streams. LANL waste stream LA-MIN02-V originally included containers from the CMR

Facility at TA-3 and HWN D028 is believed to be associated with this facility only. HWN F003 was not assigned because the waste stream does not exhibit the characteristic of ignitability. The following sections describe the characterization rationale for the assignment of EPA HWNs. Table 17, Waste Stream LA-MIN02-V.001 Hazardous Waste Characterization Summary, summarizes the EPA HWNs assigned to this waste stream. The HWN assignments have been applied on a waste stream basis; individual containers may not contain all of the hazardous material listed for the waste stream as a whole (Reference C121, C155, and D083).

Table 17. Waste Stream LA-MIN02-V.001 Hazardous Waste Characterization Summary

| Waste Stream | EPA HWNs |
|---|---|
| LA-MIN02-V.001 | F001, F002, F005, D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040 |

Chemical constituents of inputs are compiled from chemical lists contained in procedures and from SME input. In this section, discussion of the chemical inputs is divided into the following categories (References C121, C155, and C197):

- Process feed materials
- Chemical Identification and Use

Section 5.4.3, Table 8, provides a summary of the special nuclear material feed materials processed by the operations described in this report.

#### 7.4.3.1 Chemical Inputs

To assign EPA HWNs, the available AK documentation is reviewed to assess chemical usage in the TA-55 PF-4 operations contributing to waste stream LA-MIN02-V.001, and potentially hazardous materials that may have been introduced into the waste stream. In addition, MSDSs are obtained for the commercial products to determine the presence of potentially regulated compounds. As described in Section 5.4.3.1, Table 9, several of the HWNs are assigned due to lack of analytical evidence that these constituents have not exceeded the regulatory thresholds. The chemical inputs identified in Table 9 are used during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations. This waste is largely comprised of liquids and solids generated or contaminated from these operations absorbed or mixed with absorbent. Therefore, these constituents have the potential to contaminate this waste stream.

7.4.3.2 F-, K-, P-, and U-Listed Constituents

Based on review of AK relative to chemicals used or present in the facility and operations potentially contaminating the absorbed waste, LA-MIN02-V.001 may contain or be mixed with F-listed hazardous wastes from non-specific sources listed in 40 CFR 261.31 (Reference 15). As shown in Section 5.4.3.1, Table 9, F001, F002, F003, and F005 listed solvents are utilized and potentially contaminate the waste. F003 constituents, including acetone, n-butyl alcohol, ethyl ether, methanol, and xylene, are listed solely because these solvents are ignitable in the liquid form. The waste stream does not exhibit the characteristic of ignitability and therefore F003 is not assigned. Waste stream LA-MIN02-V.001 is assigned F-listed EPA HWNs F001, F002, and F005 for potential 1,1,1-trichloroethane, benzene, carbon tetrachloride, chlorobenzene, Freon TF (1,1,2-trichloro, 1,2,2-trifluoroethane), methylene chloride, methyl ethyl ketone, pyridine, tetrachloroethylene, toluene, and trichloroethylene contamination (References C121, C155, and D083).

At one time, HWN P120 was applied to certain TRU drums generated in 1998 because of the temporary use of vanadium pentoxide for about six months in that year. Based upon investigation into the way the material was handled, this code is not assigned to this waste stream. A P120 assignment would be used only if waste resulted from spillage of this material or from disposal of un-reacted/unspent material. No un-reacted/unspent material was disposed of in TRU waste drums. In addition, no documented spill of this material occurred. If a spill had occurred, suitable records would exist (e.g., incident reports, waste profile forms). The absence of such documentation, coupled with information obtained through interviews of people who worked with the material, indicates that a P120 assignment is not necessary (References C061, C155, and D083).

Beryllium may be present in the waste stream, but does not meet the definition of a P015-listed waste. Available AK did not identify beryllium powder as a constituent of this waste stream. During processing within P/S Codes PU and PUB, beryllium from Pu-Be sources is dissolved with the plutonium in acid, and after dissolution, the beryllium is either precipitated or the contaminated solution is sent to the RLWTF at TA-50. The precipitate is not included in this waste stream. Beryllium from metal operations, in general, would be in the form of classified shapes and would therefore not be in this waste stream. In some cases, beryllium turnings are generated during machining operations. However, these turnings are not expected to be in this homogeneous waste stream. The beryllium contaminated waste from the material reclamation process was debris and would also not be in this waste stream. Individual containers in waste stream LA-MIN02-V.001 will contain less than one weight percent beryllium (References 14, C121, C122, C155, C156, and M283).

Hydrofluoric acid was used or present in the facility and operations potentially contaminating the absorbed waste; however, a U134 HWN assignment would only be applicable if the waste resulted from a spill or disposal of unused material. There is no documented spill of this material present. In addition, there is no record of unused hydrofluoric acid being disposed of in this waste stream (References C121, C155, D002, and D025).

Waste stream LA-MIN02-V.001 does not contain and is not mixed with a discarded commercial chemical product, an off-specification commercial chemical product, or a container residue or spill residue thereof. Constituents identified were further researched and a determination was made that waste does not meet the definition of a listed waste in 40 CFR 261.33 (Reference 15). The material in this waste stream is not hazardous from specific sources since it is not generated from any of the processes listed in 40 CFR 261.32 (Reference 15). Therefore, this waste stream is not a K-, P-, or U-listed waste stream (References C121 and C155).

#### 7.4.3.3 Toxicity Characteristic Constituents

Based on review of AK relative to chemicals used or present in the facility and operations potentially contaminating the absorbed waste, LA-MIN02-V.001 may be contaminated with toxicity characteristic compounds as defined in 40 CFR 261.24 (Reference 15) as summarized in Section 5.4.3.1, Table 9. Where a constituent is identified and there is no quantitative data available to demonstrate that the concentration of a constituent is below regulatory threshold levels, the applicable EPA HWN is added to the waste stream. The AK also identified the potential presence of organic toxicity characteristic compounds that are assigned the more specific F-listed EPA HWNs. Although these organic characteristic compounds are covered by the assignment of the F-listed EPA HWNs, the toxicity characteristic EPA HWNs are also assigned to the waste stream for consistency with historical site waste coding. Waste stream LA-MIN02-V.001 is assigned the following HWNs: D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040 (References C121, C155, and D083).

#### 7.4.3.4 Ignitables, Corrosives, and Reactives

The homogeneous waste in waste stream LA-MIN02-V.001 does not meet the definition of ignitability as defined in 40 CFR 261.21 (Reference 15). Ignitable chemicals (e.g., acetone, hexane) are used or present in the facility and operations potentially contaminating this waste stream. However, D001 (ignitability) does not apply because: (a) the solid waste is not liquid, and verification that there are no prohibited liquids in the waste is performed prior to certification; (b) the solid waste does not spontaneously ignite at standard pressure and temperature through friction, absorption of moisture, or spontaneous chemical changes; (c) the solid waste is not an ignitable compressed gas; and (d) there are no oxidizers present that can stimulate combustion. Prior to 1992, some nitrate salts below the DL were not sent to cement fixation for immobilization but

were packaged as waste. LANL has determined that these salts do not meet the definition of a DOT oxidizer (i.e., they would not stimulate combustion). However, the salts are being remediated/repackaged in the WCRR Facility with an inert absorbent material (e.g., zeolite, kitty litter). The minimum inert absorbent material to nitrate salts mixture ratio is 1.5 to 1. LANL has determined that nitrate salts, when mixed with inert absorbent material, would further support the managing of the waste as non-ignitable. This determination is based on the results of oxidizing solids testing performed by the Energetic Materials Research and Testing Center. The materials in the waste stream are therefore not ignitable wastes (D001) (References C121, C155, C201, C203, C230, C231, D071, D083, D089, D090, D091, P096, P102, P187, and P198).

The homogeneous material in waste stream LA-MIN02-V.001 is not liquid and does not contain unreactive corrosive chemicals; therefore, it does not meet the definition of corrosivity as defined in 40 CFR 261.22 (Reference 15). Corrosive chemicals (e.g., hydrofluoric acid, nitric acid, potassium hydroxide, sodium hydroxide) are used or present in the facility and operations potentially contaminating this waste stream. However, D002 (corrosivity) does not apply because the solid waste is not a liquid, and verification that there are no prohibited liquids in the waste is performed prior to certification. The materials in the waste stream are therefore not corrosive wastes (D002) (References C121, C155, C194, D071, D083, P096, and P102).

The homogeneous waste in waste stream LA-MIN02-V.001 does not meet the definition of reactivity as defined in 40 CFR 261.23 (Reference 15). Reactive chemicals (e.g., perchloric acid, sodium metal) are used or present in the facility and operations potentially contaminating this waste stream. However, D003 (reactivity) does not apply because the waste is stable and will not undergo violent chemical change without detonating. The waste will not react violently with water, form potentially explosive mixtures with water, or generate toxic gases, vapors, or fumes when mixed with water. The waste does not contain reactive cyanide or sulfide compounds. There is no indication that the waste contains explosive materials, and it is not capable of detonation or explosive reaction. The materials in the waste stream are therefore not reactive wastes (D003) (References 15, C121, C155, C201, C202, D071, and D083).

Controls have also been in place to ensure the exclusion of ignitable, corrosive, and reactive constituents. Section 5.4.3.4 provides a detailed list of TA-55 controls that apply to all waste streams. In addition, the absence of prohibited items is verified through RTR of each waste container (References D037, D041, D049, D083, P090, P096, P097, P102, and P165).

#### 7.4.3.5 Polychlorinated Biphenyls (PCBs)

Based on documentation in procedures reviewed during the AK investigation and summarized in lists of inputs documented in the TA-55 process reports, no sources of PCBs are introduced into waste stream LA-MIN02-V.001. In the cement fixation operation (P/S Codes CF and HP), oils are sometimes added to drums of cemented

waste. They are added to the 55-gallon drums of cement in small quantities (maximum of six liters). The oils are primarily vacuum pump oils, along with some oils used in heat-treating (cooking or silicone oils) or in grinding. None of these oils are known to contain PCBs. All transformers known to contain PCBs have been tracked from initiation of recovery operations. When any transformer oil is drained, the oil is handled by a subcontractor who is wholly responsible for its disposal; this oil does not enter the LANL disposal operations. Therefore, this waste stream is not regulated as a TSCA waste under 40 CFR 761 (References 18, C096, C155, C201, D080, D083, P012, and P162).

### 7.4.4 Prohibited Items

#### 7.4.4.1 Compressed Gases, Liquids, Nonradionuclide Pyrophorics, Sealed Containers > Four Liters In Volume, >1 Percent Radionuclide Pyrophorics, and >200 mrem/hr Waste

Refer to Section 5.4.4.1 for a detailed evaluation of compressed gases, liquids, nonradionuclide pyrophorics, sealed containers greater than four liters in volume, >1 percent radionuclide pyrophorics, and >200 mrem/hr waste in TA-55 waste streams.

#### 7.4.4.2 Remediation Of Prohibited Items

Prohibited items are not expected to be present. However, the presence of prohibited quantities of liquid due to dewatering or incomplete absorption is possible. Procedures also allowed containers greater than four liters, sealed with tape, to be used for waste packaging until WIPP certification procedures were implemented. Lead shielding was used to increase handling safety, and thick shielding can obscure RTR observations (References D025 and D083).

Prohibited items are detected by RTR and reported with the characterization results. Waste containers with prohibited items are segregated then dispositioned appropriately and/or repackaged, during which time sealed containers greater than four liters are opened, and other items removed and segregated if necessary prior to certification and shipment. Some secondary waste generated during remediation and repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., plastic bags, plywood sheathing, rigid liner lids cut into pieces) (References C150, C177, D083, M316, P154, P158, and P203).

Controlled
Copy



## 7.5 Waste Packaging

Waste packaging procedures for waste streams have been modified several times since the beginning of plutonium operations in PF-4 and containers in this waste stream include a variety of configurations with up to four layers of confinement. Radioactively contaminated liquid wastes are examined to establish nuclear material content and are often treated or filtered prior to waste packaging. If the liquid is TRU and determined to be waste, it is immobilized with an absorbent (e.g., vermiculite). The minimum absorbent to liquid ratio is 3 to 1. After the liquid is absorbed, the waste is hand squeezed with a rubber glove. If any liquid is observed on the surface of the glove or the waste, more absorbent is added and the hand squeezing is repeated until the waste appears dry. Solids, typically evaporator salts (i.e., nitrate salts), are also mixed with absorbents (e.g., zeolite, kitty litter). The minimum absorbent to nitrate salts mixture ratio is 1.5 to 1. The absorbed waste is then typically placed into a plastic bag, an unsealed metal can, and/or a bottle and transferred directly into a bag-out bag (also called an inner bag) through an opening in the glovebox where the bag is attached, and the bag is then closed and detached from the glovebox. All bag closures are by the twist-and-tape method or the twist, tie, and tape method. Bagged out items are placed into a DOT 7A, Type A 55-gallon steel drum lined with either up to two 5-mil to 12-mil plastic liner bags closed with tape or one 90-mil/125-mil rigid polyethylene liner with lid (References D024, D025, D041, D083, M018, P090, P160, P161, P162, P163, P179, and P198).

Since 1995, several changes have been introduced to the packaging procedures. Up to two plastic liner bags could still be present, but they are typically closed by folding, not by taping. Waste can also be packaged in a rigid polyethylene drum liner contained in a bag-out bag which is then placed in a 55-gallon drum lined with a plastic liner bag. All waste packages (i.e., drums, SWBs) are vented with approved vents prior to disposal (e.g., Nucfil-013). Since 1997, plastic bags with filters are typically used. In addition, waste with a dose rate greater than 75 mrem/hr is placed in a lead or a tin alloy shielded container prior to packaging. Remediated/repackaged waste may be packaged with or without a single plastic liner bag with one of the following drum configurations depending on the remediation facility: no liner, a fiberboard liner, a POC, or a 90-/125-mil rigid polyethylene liner without lid. Waste placed into a POC may be packaged into a single filtered plastic bag which may include a fiberboard liner/sleeve inside the plastic bag. POCs contain a pipe component in a 55-gallon drum that is lined with a punctured rigid liner with packing material between the pipe component and liner (References C062, D025, D084, D085, P091, P159, P164, P166, P167, P168, P169, P175, P178, P195, and P198).

Controlled
Copy



During waste management and drum storage activities following initial waste generation, 55-gallon drums have been overpacked into larger drums (i.e., 85-gallon drums or larger) or SWBs to correct/address external contamination, FGE limits, and drum integrity problems such as pin hole corrosion, dents, etc. If drums are overpacked in an SWB (up to four 55-gallon drums), no closed liner bags are used in the SWB (References C154, D018, D024, D068, M222, P092, P098, P117, P158, P166, and P167).

RTR will confirm waste stream TRUCON code LA112/212. However, TRUCON codes LA126/226, SQ112/212, SQ113/213, and SQ129/229 have been identified as suitable for individual containers in this waste stream. These TRUCON codes may be assigned for the eventual certification and transportation of payload containers in this waste stream pending further evaluation by the Waste Certification Official of container-specific information. Vent dates for individual containers are provided in the AK Tracking Spreadsheet (References 9, 14, C002, C154, D041, and M242).

## 8.0 REQUIRED WASTE STREAM INFORMATION: LA-MIN04-S.001

This section presents the mandatory waste stream AK required by the WIPP-WAP (Reference 1). Attachment 1 of CCP-TP-005 (Reference 8) provides a list of the TRU waste stream information required to be developed as part of the AK record.

### 8.1 Area and Building of Generation

All of the salt waste covered by this report originated from TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations described in Section 4.4. Container-specific records are reviewed for each container to verify the physical composition and origin of the waste stream inventory (References C172, C182, M222, and M279).

### 8.2 Waste Stream Volume and Period of Generation

Waste stream LA-MIN04-S.001 is salt waste generated from 1979 to present. Table 18, LA-MIN04-S.001 Approximate Waste Stream Volume, summarizes the current volume of this waste stream. The future projection of additional generation of this waste stream is approximately 22 cubic meters per year. There is no projected end date for the termination of operations that generate this waste stream (References C172, C174, C182, C236, D041, M222, and M279).

Table 18. LA-MIN04-S.001 Approximate Waste Stream Volume

| Containers | Volume (cubic meters) |
|---|---|
| 141 55-gallon drums (includes POCs) | 29.61 |

### 8.3 Waste Generating Activities

Salt waste is generated during the purification of plutonium metal and scrap that is recovered or generated by recovery, during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations described in detail in Section 4.4 and includes (References D041 and D083):

- Preparing ultra-pure plutonium metals, alloys, and compounds
- Preparing (on a large scale) specific alloys, including casting and machining these materials into specific shapes
- Determining high-temperature thermodynamic properties of plutonium

- Reclaiming plutonium from scrap and residues produced by numerous feed sources
- Disassembling components for inspection and analysis
- Manufacturing of parts on a limited basis
- Processing mixtures of plutonium and uranium oxides for reactor fuels
- Pu-238 generator and heat source R&D, fabrication, testing, and recycling

## 8.4 Type of Wastes Generated

This section describes the process inputs, Waste Matrix Code assignment, WMPs, radionuclide contaminants, and RCRA hazardous waste determinations for waste stream LA-MIN04-S.001. The waste stream is characterized based on knowledge of the materials, knowledge of the operations generating the waste, and physical descriptions of the waste.

### 8.4.1 Material Input Related to Physical Form

Waste stream LA-MIN04-S.001 consists primarily of inorganic homogeneous solid waste (salt waste) generated in TA-55. The waste is largely comprised of salts which are a byproduct from a variety of plutonium metal purification operations including electrorefining, molten salt extraction, salt stripping, fluoride reduction, and direct oxide reduction. Salts serve as a transportation vehicle for plutonium ions and provide a trap for impurities that are driven or extracted out during the purification process. Salt waste can include varying mixtures of calcium chloride, cesium chloride, lithium chloride, magnesium chloride, potassium chloride, sodium chloride, zinc chloride, residual entrained calcium and zinc metal, and various plutonium and americium compounds. The waste may also be contaminated with solvent metals and reagent materials such as barium, bismuth, cadmium, calcium carbonate, gallium, lead, molybdenum, niobium, tantalum, titanium, tungsten, vanadium, yttrium, and zirconium. Salts can be cemented and disposed of separately in waste stream LA-CIN01.001. A small fraction of debris waste (less than 50 percent by volume) including plastic packaging, metal packaging, PPE, and MgO crucible pieces may also be present. Finally, some secondary waste generated during remediation/repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770 [sodium polyacrylate]), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., metal, plastic bags, plywood sheathing, rigid liner lids cut into pieces) (References C150, C177, D011, D025, D028, D032, D055, D078, D080, D083, M028, M029, M130, M316, and P157).

Controlled
Copy



#### 8.4.1.1 Waste Matrix Code

Based on the evaluation of the materials contained in this waste stream and LANL waste management practices, this waste stream is comprised of greater than 50 percent by volume of salt waste. Therefore, Waste Matrix Code S3140, Salt Waste, is assigned to waste stream LA-MIN04-S.001 (References 2, C172, D041, D083, M222, and M279).

#### 8.4.1.2 Waste Material Parameters

To estimate the WMPs for waste stream LA-MIN04-S.001, batch data reports (BDRs) were obtained from the CCP at LANL. This waste stream is greater than 50 percent by volume material that meets the criteria for salt waste (References C172 and M279).

The WMPs for waste stream LA-MIN04-S.001 were estimated by reviewing the RTR data documented in the BDRs for 35 containers packaged from February 1985 to May 2008. The RTR data provides a weight for packaged waste materials, which were categorized into one or more of the following WMPs: iron based metals/alloys, other metals/alloys, other inorganic materials (which were included under inorganic matrix), plastics, and inorganic matrix. Average, minimum, and maximum WMP weight percentages were calculated using this data. These calculations conclude that the relative waste weight percentages for organic waste materials (plastic debris) and inorganic waste materials (primarily salt and metal debris) for waste stream LA-MIN04-S.001 are 11.0 percent and 89.0 percent, respectively. The results of the assessment are presented in Table 19, Waste Stream LA-MIN04-S.001 Waste Material Parameter Estimates.

The statistical analysis of the data is documented in a memorandum (included with Attachment 6) as required by CCP-TP-005 (Reference 8).

Table 19. Waste Stream LA-MIN04-S.001 Waste Material Parameter Estimates

| Waste Material Parameter | Avg. Weight Percent | Weight Percent Range |
|---|---|---|
| Iron-based Metals/Alloys | 21.0% | 0.0 – 58.3% |
| Aluminum-based Metals/Alloys | 0.0% | 0.0 – 0.0% |
| Other Metals | 1.3% | 0.0 – 3.2% |
| Other Inorganic Materials | 0.0% | 0.0 – 0.0% |
| Cellulosics | 0.0% | 0.0 – 0.0% |
| Rubber | 0.0% | 0.0 – 0.0% |
| Plastic (waste materials) | 11.0% | 0.6 – 55.6% |
| Organic Matrix | 0.0% | 0.0 – 0.0% |
| Inorganic Matrix | 66.7% | 0.0 – 96.2% |
| Soils/Gravel | 0.0% | 0.0 – 0.0% |
| **Total Organic Waste Avg.** | **11.0%** | |
| **Total Inorganic Waste Avg.** | **89.0%** | |

### 8.4.2 Radiological Characterization

#### 8.4.2.1 Pu-238, Pu-239, Pu-240, Pu-241, and Pu-242

The primary plutonium material type inputs for the plutonium recovery process are listed in Section 5.4.2.2, Table 3. However, other MTs are occasionally introduced as feed material. The assignment of MTs is used to describe the isotopic composition of common blends of radioactive materials used within the DOE complex (References C186, C194, C209, C219, C222, D025, D073, D074, D076, D080, D083, M222, M283, M295, and M309).

Recovery operations are not expected to alter the plutonium isotopic ratios of the feed material. The material type used in the operation generating each waste item is documented on generator records; however, cross-contamination of equipment with different material types can lead to variable material types detected by radioassay (References D025, M222, and M279).

The primary MT that feeds into the Pu-238 operations described in this report is heat source grade plutonium (MT 83), and these operations are not expected to alter the plutonium isotopic ratios of the feed material. Section 5.4.2.2, Table 3, identifies the isotopic distribution of MT 83 based on 100 isotopic analyses and were decay corrected assuming the material was not chemically separated for 45 years (References C125, C186, C194, C209, C219, C222, D073, D074, D076, D080, D083, M283, M295, and M309).

8.4.2.2 U-233, U-234, U-235, and U-238

U-233 and U-238 are not normally components of the plutonium MTs handled at PF-4. U-235 is present from the decay of Pu-239 only at 0.1 percent by weight of the total plutonium content. However, all three isotopes have been introduced as special material. In addition, uranium-plutonium oxide mixtures have been processed to recover the plutonium. Significant quantities of U-234 will be present from the decay of Pu-238 in waste originating from heat source plutonium operations (References C222, D025, and D076).

In general, uranium and its isotopes are expected to be present only at trace levels, if at all, if the feed material did not purposely contain uranium. However, some reactor fuel development, uranium-plutonium separation, and pit disassembly operations have uranium material as the feed material. The primary uranium MT inputs are listed in Section 5.4.2.2, Table 4 (Reference D080).

U-234 content must be estimated since this isotope cannot be reliably measured using NDA techniques (Reference C001). The MT provides the basis for estimating an upper bound for U-234 based on the rate of decay of the precursor, Pu-238, and the assumption that there is no other source of uranium in the waste material. The content of U-234 in the Pu-239 MTs is calculated as the sum of the contributions expected from decay of Pu-238 and from uranium input to the operation, with the value of 0.014 conservatively used for the ratio of abundances of U-234 to U-235 in typical uranium MTs. The standard uranium MTs provide an estimate of the ratio of U-234 to U-235 where one of the MTs listed in Section 5.4.2.2, Table 4, is an indicated MT in the waste container (References D025 and D083).

8.4.2.3 Am-241

AK on the MT inputs provides the basis for estimating an upper bound for Am-241 content based on the rate of decay of the precursor, Pu-241. The purpose of such bounding calculations is to provide a basis for identifying significant enrichment or depletion of Am-241 based on radioassay results for individual waste containers. The calculations assume that (a) none of these isotopes were initially present in the material, (b) the oldest plutonium material in inventory dates back to January 1, 1960, and (c) the legacy waste was packaged on January 1, 1996, making it 36 years old at that time. In general, wastes from the plutonium recovery process are enriched with Am-241, because a primary intent of the recovery process is to reduce the americium content of the retained plutonium (References C222, D025, and D083).

No correlation is expected among the different radioelements, Pu, Np, U, Pa, or Am. The differences in valence states and chemical affinities among these elements are expected to result in substantial fractionation during several recovery operations, including ion exchange, solvent extraction, hydroxide precipitation, and dissolution (References D025 and D083).

8.4.2.4 Other Radionuclides Present Due to Decay

Other radionuclides will be present in most of the wastes from the decay of a plutonium isotopic precursor or as a contaminant in the feed material. Refer to Section 5.4.2.4 for a discussion of Np-237, Am-243, Pa-231, and Ac-227 decay products (References C067, C073, C208, C209, D025, D080, and D083).

8.4.2.5 Cs-137 and Sr-90

Cs-137

Cs-137 is a product of the spontaneous fission of Pu-238, Pu-239, and especially Pu-240. Cs-137 is also a trace contaminant in purified plutonium from the production reactors (References C067 and C073). In the latter case, the remaining cesium could be on the order of 0.5 ng/g plutonium. In the former instance the formation of Cs-137 due to spontaneous fission would lead to about 0.4 pg/g plutonium in plutonium that is 10 years old. Because Cs-137 due to spontaneous fission is about a factor of a thousand less than that due to residual contamination from the original separation on the production fuel, the latter is the dominant source of cesium in waste (References C208, C209, D025, and D083).

Sr-90

Based on interviews with an SME, no spent nuclear fuel or other material containing Sr-90 were introduced into the TRU waste streams (Reference C076). No references or procedures related to spent fuel processing were located in the AK investigation of records. No generator documents (i.e., WODF, DWLS, TWSR, and WPF) identified spent fuel or Sr-90 as inputs or as present in the waste. During review of WPFs and database records from the waste storage facility (TA-54), use of material containing Sr-90 was not identified (References C172 and C208). However, because of the requirement that an estimate of Sr-90 content be made, the following approach is taken. In plutonium production runs, Cs-137 and Sr-90 are produced at approximately the same level. These two nuclides have very similar half-lives (~ 30 y) and will therefore be present at roughly the same activity level prior to commencement of any processing operations. If it is assumed that strontium and cesium are not fractionated from one another during chemical processing, Cs-137 may be used as a marker for Sr-90 activity at a ratio of 1:1 (References D025 and D083).

8.4.2.6 Other Radionuclides Introduced as Feed Material

Refer to Section 5.4.2.6 and Table 5 for a discussion of secondary radionuclides that are also present in this waste stream due to operations involving feed materials other than plutonium. The list of radionuclides includes Ac-227, Am-241, Am-243, Ce-144, Cm-244, Np-237, Pa-231, Pu-238, Th-230, Th-232, U-233, U-235, and U-238 (References C067, C076, C108, D025, and D083).

#### 8.4.2.7 Estimated Predominant Isotopes and 95 percent Total Activity

Radionuclide data established by the PF-4 waste generator on a container basis and container data from the Area G waste storage records were evaluated to determine the relative radionuclide weight and activity for waste stream LA-MIN04-S.001. From this evaluation, the two predominant isotopes for the waste stream are Pu-239 and U-238, while over 95 percent of the total activity in the waste stream is from Pu-239, Pu-240, and Pu-241. It should be noted that although U-238 is the second most predominant isotope by mass in the waste stream, it was only reported in a small percentage of containers. The predominant isotopes for most containers in this waste stream are Pu-239 and Pu-240. Table 20, Estimated Radionuclide Distribution in LA-MIN04-S.001, identifies the relative radionuclide weight and activity percent of expected radionuclides over the entire waste stream based on the container data evaluated. As illustrated in Table 20, the radionuclide weight percent of individual radionuclides varies on a container-by-container basis. Because of this variability in container loadings, some containers will not contain the waste stream predominant radionuclides but may contain other radionuclides expected in this waste stream (References C172, C182, C224, C232, C236, D041, M279, M307, and M317).

#### 8.4.2.8 Use of Radionuclide Isotopic Ratios

For waste containers where direct measurement does not yield useable isotopic ratio information, AK may be used to supplement direct measurement data in accordance with the WIPP-WAC (Reference 3). The ratios that may be used are those identified in Section 5.4.2.2, Tables 3 and 4, in conjunction with the corresponding nuclear material type identified by the waste generator on a container basis. The specific use and confirmation of AK related to WIPP-certified assay measurements of containers in this waste stream is documented in the memorandum written in accordance with the requirements of CCP-TP-005 (Reference 8).

Table 20. Estimated Radionuclide Distribution in LA-MIN04-S.001

| Radionuclide | Total Nuclide Wt%[1] | Total Nuclide Ci%[2,5] | Nuclide Wt% Range for Individual Containers[3,5] | Nuclide Ci% Range for Individual Containers[4,5] | Expected Present |
|---|---|---|---|---|---|
| **WIPP Required Radionuclides** | | | | | |
| Am-241 | 0.14% | 1.81% | 0.00% - 15.50% | 0.00% - 69.26% | Yes |
| Pu-238 | 0.01% | 0.95% | 0.00% - 0.68% | 0.00% - 7.05% | Yes |
| Pu-239 | **72.55%** | **16.94%** | 0.00% - 96.71% | 0.00% - 40.51% | Yes |
| Pu-240 | 4.98**%** | **4.25%** | 0.00% - 16.19% | 0.00% - 4.88% | Yes |
| Pu-242 | 0.72% | 0.01% | 0.00% - 92.16% | 0.00% - 0.21% | Yes |
| U-233[6] | Not Reported | | | | Yes |
| U-234 | Trace | Trace | 0.00% - Trace | 0.00% - Trace | Yes |
| U-238 | **21.34%** | Trace | 0.00% - 95.95% | 0.00% - Trace | Yes |
| Sr-90 | Trace | Trace | 0.00% - Trace | 0.00% - Trace | Yes |
| Cs-137 | Trace | Trace | 0.00% - Trace | 0.00% - Trace | Yes |
| **Additional Radionuclides** | | | | | |
| Np-237 | Trace | Trace | 0.00% - Trace | 0.00% - Trace | Yes |
| Pu-241 | 0.24% | **76.04%** | 0.08% - 1.58% | 43.11% - 93.06% | Yes |
| Pu-244 | Trace | Trace | 0.00% - 0.02% | 0.00% - Trace | Yes |
| U-235 | 0.05% | Trace | 0.00% - 0.24% | 0.00% - Trace | Yes |

1. This listing indicates the total weight percent of each radionuclide over the entire waste stream.
2. This listing indicates the total activity (curie) percent of each radionuclide over the entire waste stream.
3. This listing is the weight percent range of each radionuclide on a container-by-container basis.
4. This listing is the curie percent range of each radionuclide on a container-by-container basis.
5. "Trace" indicates <0.01 weight or activity percent for that radionuclide.
6. Radionuclides not reported but suspected present from secondary radionuclides or decay.

### 8.4.3 Chemical Content Identification – Hazardous Constituents

Waste stream LA-MIN04-S.001 historically been managed in accordance with the generator site requirements and in compliance with the requirements of the New Mexico Environmental Department. Based on historical waste management and LANL's TRU Program (Reference LANL waste stream LA-MIN04-S), the containers in this waste stream were managed as hazardous and assigned the same EPA HWNs as the debris waste stream including arsenic (D004), barium (D005), cadmium (D006), chromium (D007), lead (D008), mercury (D009), selenium (D010), silver (D011), benzene (D018), carbon tetrachloride (D019), chlorobenzene (D021), chloroform (D022), methyl ethyl ketone (D035), pyridine (D038), tetrachloroethylene (D039), trichloroethylene (D040), and F-listed solvents (F001, F002, F003, and F005). A review of available AK documentation has determined that this waste is hazardous for the above constituents, and with the exception of F003, the HWNs were retained. HWN F003 was not assigned because the waste stream does not exhibit the characteristic of ignitability. The following sections describe the characterization rationale for the assignment of EPA HWNs. Table 21, Waste Stream LA-MIN04-S.001 Hazardous Waste Characterization Summary, summarizes the EPA HWNs assigned to this waste stream. The HWN

assignments have been applied on a waste stream basis; individual containers may not contain all of the hazardous material listed for the waste stream as a whole (References C121, C173, and D083).

Table 21. Waste Stream LA-MIN04-S.001 Hazardous Waste Characterization Summary

| Waste Stream | EPA HWNs |
|---|---|
| LA-MIN04-S.001 | F001, F002, F005, D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040 |

Chemical constituents of inputs are compiled from chemical lists contained in procedures and from SME input. In this section, discussion of the chemical inputs is divided into the following categories (References C121, C173, and C197):

- Process Feed Materials
- Chemical Identification and Use

Section 5.4.3, Table 8, provides a summary of the special nuclear material feed materials processed by the operations described in this report.

8.4.3.1 Chemical Inputs

To assign EPA HWNs, the available AK documentation is reviewed to assess chemical usage in the TA-55 PF-4 operations contributing to waste stream LA-MIN04-S.001, and potentially hazardous materials that may have been introduced into the waste stream. In addition, MSDSs are obtained for the commercial products to determine the presence of potentially regulated compounds. As described in Section 5.4.3.1, Table 9, several of the HWNs are assigned due to lack of analytical evidence that these constituents have not exceeded the regulatory thresholds. The chemical inputs identified in Table 9 are used during TA-55 R&D/fabrication and associated recovery, facility and equipment maintenance, D&D, waste repackaging, and below-grade retrieval operations. This waste is largely comprised of salt waste from plutonium metal purification operations that received plutonium metal and scrap that is recovered or generated by these various operations. Therefore, these constituents have the potential to contaminate this waste stream.

8.4.3.2 F-, K-, P-, and U-Listed Constituents

Based on review of AK relative to chemicals used or present in the facility and operations potentially contaminating the salt waste, LA-MIN04-S.001 may contain or be mixed with F-listed hazardous wastes from non-specific sources listed in 40 CFR 261.31 (Reference 15). As shown in Section 5.4.3.1, Table 9, F001, F002, F003, and F005 listed solvents are utilized and potentially contaminate the waste. F003

constituents, including acetone, n-butyl alcohol, ethyl ether, methanol, and xylene, are listed solely because these solvents are ignitable in the liquid form. The waste stream does not exhibit the characteristic of ignitability and therefore F003 is not assigned. Waste stream LA-MIN04-S.001 is assigned F-listed EPA HWNs F001, F002, and F005 for potential 1,1,1-trichloroethane, benzene, carbon tetrachloride, chlorobenzene, Freon TF (1,1,2-trichloro, 1,2,2-trifluoroethane), methylene chloride, methyl ethyl ketone, pyridine, tetrachloroethylene, toluene, and trichloroethylene contamination (References C121, C173, and D083).

At one time, HWN P120 was applied to certain TRU drums generated in 1998 because of the temporary use of vanadium pentoxide for about six months in that year. Based upon investigation into the way the material was handled, this code is not assigned to this waste stream. A P120 assignment would be used only if waste resulted from spillage of this material or from disposal of un-reacted/unspent material. No un-reacted/unspent material was disposed of in TRU waste drums. In addition, no documented spill of this material occurred. If a spill had occurred, suitable records would exist (e.g., incident reports, waste profile forms). The absence of such documentation, coupled with information obtained through interviews of people who worked with the material, indicates that a P120 assignment is not necessary (References C061, C173, and D083).

Beryllium may be present in the waste stream, but does not meet the definition of a P015-listed waste. Available AK did not identify the use of beryllium powder. During processing within P/S Codes PU and PUB, beryllium from Pu-Be sources is dissolved with the plutonium in acid, and after precipitation, the beryllium is either precipitated or remained in solution that is sent to the RLWTF at TA-50, and the precipitate is not included in this waste stream. Beryllium from metal operations, in general, is in the form of classified shapes and is therefore not in this waste stream. In some cases, beryllium turnings are generated during machining operations. However, these turnings are not expected to be in this homogeneous waste stream. Individual containers in waste stream LA-MIN04-S.001 will contain less than one weight percent beryllium (References 14, C121, C122, C173, and M283).

Waste stream LA-MIN04-S.001 does not contain and is not mixed with a discarded commercial chemical product, an off-specification commercial chemical product, or a container residue or spill residue thereof. Constituents identified were further researched and a determination was made that waste does not meet the definition of a listed waste in 40 CFR 261.33 (Reference 15). The material in this waste stream is not hazardous from specific sources since it is not generated from any of the processes listed in 40 CFR 261.32 (Reference 15). Therefore, this waste stream is not a K-, P-, or U-listed waste stream (References C121 and C173).

Hydrofluoric acid was used or present in the facility and operations potentially contaminating the salt waste; however, a U134 HWN assignment would only be applicable if the waste resulted from a spill or disposal of unused material. There is no

documented spill of this material present. In addition, there is no record of unused hydrofluoric acid being disposed of in this waste stream (References C121, C155, D002, and D025).

8.4.3.3 Toxicity Characteristic Constituents

Based on review of AK relative to chemicals used or present in the facility and operations potentially contaminating the salt waste, LA-MIN04-S.001 may be contaminated with toxicity characteristic compounds as defined in 40 CFR 261.24 (Reference 15) as summarized in Section 5.4.3.1, Table 9. Where a constituent is identified and there is no quantitative data available to demonstrate that the concentration of a constituent is below regulatory threshold levels, the applicable EPA HWN is added to the waste stream. The AK also identified the potential presence of organic toxicity characteristic compounds that are assigned the more specific F-listed EPA HWNs. Although these organic characteristic compounds are covered by the assignment of the F-listed EPA HWNs, the toxicity characteristic EPA HWNs are also assigned to the waste stream for consistency with historical site waste coding. Waste stream LA-MIN04-S.001 is assigned the following HWNs: D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D035, D038, D039, and D040 (References C121, C173, and D083).

8.4.3.4 Ignitables, Corrosives, and Reactives

The homogeneous material in waste stream LA-MIN04-S.001 does not meet the definition of ignitability as defined in 40 CFR 261.21 (Reference 15). Ignitable chemicals (e.g., acetone, hexane) are used or present in the facility and operations potentially contaminating this waste stream. However, D001 (ignitability) does not apply because: (a) the solid waste is not liquid, and verification that there are no prohibited liquids in the waste is performed prior to certification; (b) the solid waste does not spontaneously ignite at standard pressure and temperature through friction, absorption of moisture, or spontaneous chemical changes; (c) the solid waste is not an ignitable compressed gas; and (d) there are no oxidizers present except as trace contaminants. Nitrate salts are solidified/stabilized in cement or absorbent and are not included in this waste stream. The materials in the waste stream are therefore not ignitable wastes (D001) (References C121, C173, C201, C202, C203, D071, D083, P096, P102, and P187).

The homogeneous material in waste stream LA-MIN04-S.001 is not liquid and does not contain unreactive corrosive chemicals; therefore, it does not meet the definition of corrosivity as defined in 40 CFR 261.22 (Reference 15). Corrosive chemicals (e.g., hydrofluoric acid, nitric acid, potassium hydroxide, sodium hydroxide) are used or present in the facility and operations potentially contaminating this waste stream. However, D002 (corrosivity) does not apply because the solid waste is not a liquid, and verification that there are no prohibited liquids in the waste is performed prior to

certification. The materials in the waste stream are therefore not corrosive wastes (D002) (References C121, C173, C194, D071, D083, P091, P096, and P102).
The homogeneous material in waste stream LA-MIN04-S.001 does not meet the definition of reactivity as defined in 40 CFR 261.23 (Reference 15). Reactive chemicals (e.g., perchloric acid, sodium metal) are used or present in the facility and operations potentially contaminating this waste stream. However, D003 (reactivity) does not apply because the waste is stable and will not undergo violent chemical change without detonating. The waste will not react violently with water, form potentially explosive mixtures with water, or generate toxic gases, vapors, or fumes when mixed with water. The waste does not contain reactive cyanide or sulfide compounds. There is no indication that the waste contains explosive materials, and it is not capable of detonation or explosive reaction. The materials in the waste stream are therefore not reactive wastes (D003) (References 15, C121, C173, C201, D071, and D083).

Controls have also been in place to ensure the exclusion of ignitable, corrosive, and reactive constituents. Section 5.4.3.4 provides a detailed list of TA-55 controls that apply to all waste streams. In addition, the absence of prohibited items is verified through RTR of each waste container (References D037, D041, D049, D083, P090, P096, P097, P102, and P165).

#### 8.4.3.5 Polychlorinated Biphenyls (PCBs)

Based on documentation in procedures reviewed during the AK investigation and summarized in lists of inputs documented in the TA-55 process reports, no sources of PCBs are introduced into waste stream LA-MIN04-S.001. All transformers known to contain PCBs have been tracked from initiation of recovery operations. When any transformer oil is drained, the oil is handled by a subcontractor who is wholly responsible for its disposal; this oil does not enter the LANL disposal operations. Suspect PCB fluorescent light ballasts occasionally found in heterogeneous debris would not be present in this waste stream. PCB containing waste is identified during characterization activities and those containers are managed in accordance with the CCP waste certification program (i.e., removed from this waste stream). Therefore, this waste stream is not regulated as a TSCA waste under 40 CFR 761 (References 18, C096, C173, C201, D080, D083, P012, and P162).

### 8.4.4 Prohibited Items

#### 8.4.4.1 Compressed Gases, Liquids, Nonradionuclide Pyrophorics, Sealed Containers Greater Than Four Liters In Volume, >1 Percent Radionuclide Pyrophorics, and >200 mrem/hr Waste

Refer to Section 5.4.4.1 for a detailed evaluation of compressed gases, liquids, nonradionuclide pyrophorics, sealed containers greater than four liters in volume, >1 percent radionuclide pyrophorics, and >200 mrem/hr waste in TA-55 waste streams.

#### 8.4.4.2 Remediation of Prohibited Items

Prohibited items are not expected to be present. However, procedures allowed containers greater than four liters, sealed with tape, to be used for waste packaging until WIPP certification procedures were implemented. Lead shielding is used to increase handling safety, and thick shielding can obscure RTR observations (References D025 and D083).

Prohibited items are detected by RTR and reported with the characterization results. Waste containers with prohibited items are segregated then dispositioned appropriately and/or repackaged, during which time sealed containers greater than four liters are opened, and other items removed and segregated if necessary prior to certification and shipment. Some secondary waste generated during remediation and repackaging operations may be added to the waste containers, including but not limited to: absorbent (e.g., Waste Lock 770), alkaline batteries, Fantastik bottles used during decontamination, miscellaneous hand tools, paper/plastic tags and labels, plastic/metal wire ties, PPE, plastic sheeting used for contamination control, rags and wipes (Kimwipes), and original packaging material (e.g., plastic bags, plywood sheathing, rigid liner lids cut into pieces) (References C150, C177, D083, M316, P154, P158, and P203).

## 8.5 Waste Packaging

Waste packaging procedures for waste streams have been modified several times since the beginning of plutonium operations in PF-4 and containers in this waste stream include a variety of configurations with up to four layers of confinement. Typically, salts are generated after multiple plutonium purification runs involving the heating and cooling of various salt and metal mixtures. Once the salt and metal mixtures are separated, the salts are placed into a tin or stainless-steel can/dressing jar and transferred directly into a bag-out bag (also called an inner bag) through an opening in the glovebox where the bag is attached. The bag is then closed and detached from the glovebox. Waste may also be packaged in either an unsealed metal can within a single filtered plastic bag or directly into one filtered plastic bag. All bag closures are by the twist-and-tape method or the twist, tie, and tape method. Bagged out items are placed into a 55-gallon DOT 7A, Type A 55-gallon steel drum lined with either two 5-mil or greater plastic liner bags closed with tape, or one 90-mil/125-mil rigid polyethylene liner with lid. In addition, salt waste may be packaged into a POC. In this configuration the salt waste is placed directly into a metal can and then placed into a pipe component. The metal can may also be bagged out and/or placed into a secondary can. Waste placed into a POC may also be packaged into a single filtered plastic bag which may include a fiberboard liner/sleeve inside the plastic bag. Once the material is placed into the pipe component, the lid with filter is bolted on. The pipe component is contained in a standard 55-gallon steel drum that is lined with a punctured rigid liner with packaging material between the pipe component and liner (References D024, D025, D041, D083, D084, P090, P157, P159, P160, P161, P162, P163, P175, P177, P179, and P188).

Controlled
Copy



Since 1995, several changes have been introduced to the packaging procedures. Up to two plastic liner bags could still be present, but they are typically closed by folding, not by taping. Waste can also be packaged in a rigid polyethylene drum liner contained in a bag-out bag which is then placed in a 55-gallon drum lined with a 5-mil plastic liner bag. All waste packages (i.e., drums) are vented with approved filter vents prior to disposal (e.g., Nucfil-013). Since 1997, plastic bags with filters are typically used. In addition, waste with a dose rate greater than 75 mrem/hr is placed in a lead or a tin alloy shielded container prior to packaging. Remediated/repackaged waste may be packaged with or without a single plastic liner bag with one of the following drum configurations depending on the remediation facility: no liner, a fiberboard liner, a POC, or a 90-/125-mil rigid polyethylene liner without lid (References C062, D025, D084, D085, P091, P159, P164, P166, P167, P168, P169, P175, P178, and P195).

During waste management and drum storage activities following initial waste generation, 55-gallon drums may be overpacked into larger drums (i.e., 85-gallon drums or larger) or SWBs to correct/address external contamination, FGE limits, and drum integrity problems such as pin hole corrosion, dents, etc. If drums are overpacked in an SWB (up to four 55-gallon drums), no closed liner bags are used in the SWB (References D018, D024, D041, D068, M222, M279, P092, P098, P117, P158, P166, and P167).

RTR will confirm waste stream TRUCON code LA124/224. Vent dates for individual containers are provided in the AK Tracking Spreadsheet (References 9, 14, C002, D041, and M279).

Controlled
Copy



# 9.0 CONTAINER-SPECIFIC INFORMATION

Several data sources were reviewed relating container-specific information about the radiological, physical, and chemical characterization of containers in these waste streams including archived and active site database information and generator records. The list of containers included in these waste streams is provided in the current AK Tracking Spreadsheet.

## 10.0 REFERENCES

1. *Waste Isolation Pilot Plant Hazardous Waste Facility Permit, Waste Analysis Plan,* New Mexico Environment Department, Santa Fe, New Mexico

2. DOE/LLW-217, *DOE Waste Treatability Group Guidance*, Idaho Falls, Idaho, INEL-Lockheed Idaho Technologies

3. DOE/WIPP-02-3122, *Transuranic Waste Acceptance Criteria for the Waste Isolation Pilot Plant*, Carlsbad, New Mexico, U.S. DOE, 2004

4. *Interim Guidance on Ensuring that Waste Qualifies for Disposal at the Waste Isolation Pilot Plant*, U.S. DOE, Carlsbad, 1997

5. Public Law 102-579, *The Waste Isolation Pilot Plant Land Withdrawal Act* (as amended)

6. DOE/TRU-13-3425, *Annual Transuranic Waste Inventory Report – 2013*, Carlsbad, New Mexico, U.S. DOE, Carlsbad Field Office

7. CCP-PO-001, *CCP Transuranic Waste Characterization Quality Assurance Project Plan*, Carlsbad, New Mexico, Nuclear Waste Partnership, LLC.

8. CCP-TP-005, *CCP Acceptable Knowledge Documentation*, Carlsbad, New Mexico, Nuclear Waste Partnership, LLC.

9. DOE/WIPP 01-3194, TRUPACT-ll Content Codes (TRUCON)

10. U.S. Atomic Energy Commission AEC Manual: Chapter 0511, *Radioactive Waste Management*, AEC, 1973

11. DOE Order 435.1, *Radioactive Waste Management*, U.S. DOE, Environmental Management, 2001

12. DOE Order 5820.1, *Management of Transuranic Contaminated Materials* and DOE Order 5820.2A, *Radioactive Waste Management*, U.S. DOE, 9/30/82 and 2/6/84

13. CCP-AK-LANL-005, *Central Characterization Project Acceptable Knowledge Summary Report For Los Alamos National Laboratory TA-55 Non-Hazardous Heterogeneous Debris, Waste Stream: LA-NHD01.001*

14. CCP-PO-003, *CCP Transuranic Authorized Methods for Payload Control (CCP CH-TRAMPAC), Carlsbad, New Mexico, Nuclear Waste Partnership, LLC.*

15. Title 40 CFR, Part 261, *Identification and Listing of Hazardous Waste*

16. CCP-PO-002, *CCP Transuranic Waste Certification Plan,* Carlsbad, New Mexico, Nuclear Waste Partnership, LLC.

17. CCP-AK-LANL-009, *Central Characterization Program Acceptable Knowledge Summary Report For Los Alamos National Laboratory Chemistry and Metallurgy Research (CMR) Facility Waste Streams*: *LA-MHD03.001, LA-CIN03.001, LA-MIN05-V.001,* Nuclear Waste Partnership, Carlsbad, New Mexico

18. Title 40 CFR, Part 761, *Polychlorinated Biphenyls (PCBs) Manufacturing, Processing, Distribution in Commerce, and use Prohibitions*

19. 42 U.S. Code 10101, *Nuclear Waste Policy Act of 1982,* U.S. Congress

20. CCP-AK-LANL-007*, Los Alamos National Laboratory Pu-238 Contaminated Mixed Heterogeneous Debris, Waste Stream LA-MHD02.001*

## 11.0 AK SOURCE DOCUMENTS

| Source Document Tracking Number | Title |
|---|---|
| C001 | Assay of U-234 |
| C002 | Vent and Closure dates for TWISP containers submitted to WWIS |
| C005 | TA-55 Pu-238 Processes Issues and SMEs (Acceptable Knowledge Personnel Interview Form) |
| C009 | Electronic Communication from the Author |
| C010 | Interview with R. Gutierrez, SME, re: P/S Code PE |
| C011 | Interview with Dale Soderquist, SME re: P/S Code DA |
| C014 | Interview with J. Milewski, SME, re: P/S Code ELW |
| C017 | Interview with B. Martinez, SME, re: P/S Codes RAP, RAP2, FSPF, PF, JA, and BC |
| C018 | Interview with J. Simpson, SME, re: P/S Code RL |
| C019 | Interview with G. Zaker, SME, re: P/S Code MA and Chemicals Used in Machining |
| C020 | Interview with G. Zaker, SME, re: P/S Code CA |
| C023 | Interview with G. Jarvinen re: P/S Codes AD, APD |
| C026 | Interview with L. Avens re: P/S Codes MAS, SA |
| C027 | Interview with B. Zwick and J. Byrd re: P/S Codes AC1 and AC2 |
| C031 | Interview with C. Davis re: P/S Code SMP |
| C033 | Interview with J. Foxx re: P/S Codes RD, NCD, WM, and XO/XO |
| C035 | Interview with R. Masen re: P/S Code ME |
| C037 | Interview with D. Wulff re: P/S Code XO/XO |
| C038 | Interview with John Musgrave – TA-55 Miscellaneous Operations, RD&D Processes |
| C039 | Interview with J. Foxx re: Process inputs to P/S Code AD |
| C040 | Interview with J. Foxx re: P/S Codes PB, PuBe, CC, MB, MS, FF, BF, and other issues |
| C041 | Interview with J. Foxx re: Use of Lead in P/S Codes DOP |
| C047 | Interview with F. Hampel re: Metal Operations Process AK; Information on Chemical Use in P/S Code FF |
| C054 | Air Sparging to Eliminate Pyrophoric Sodium |
| C056 | Layers of Packaging in TA-55 Combustible TRU Waste |
| C057 | Commingling of Defense and Nondefense TRU Waste |
| C061 | Interview with J. Foxx re: Vanadium, Vanadium Pentoxide, TA-55-19, TA-55-30 |
| C062 | Wire Twist-Tie and Plastic Electrical Tie Bag Closure |
| C064 | Air Sparging to Eliminate Pyrophoric Sodium |
| C065 | WACCC Audit Finding #1 (April 27-May 1, 1987) |
| C066 | Interview with F. Hampel re: Information on Chemical Use in P/S Code FF |
| C067 | Interview with J. Foxx re: Sources of Cs-137, Pa-231, and Cm-244 in TA-55 waste |
| C068 | Interview with J. Foxx re: Timeline for disposal of TA-55 waste with P120 |
| C069 | Ac-227 Drums |
| C073 | Interview of J. Foxx re: Sources of Cs-137 and Pa-231 in TA-55 Waste |
| C076 | Memo to P. Rogers re: “Secondary Radionuclides and Toxic Metals in TA-55 TRU Waste” |
| C079 | Interview of J. Foxx re: P/S Codes PPD, UA, VD, IN, and WE |

| Source Document Tracking Number | Title |
|---|---|
| C080 | Collection of Correspondence, Comments, and AK Summaries |
| C081 | Interview with J. Foxx re: P/S Code DO |
| C082 | Interview with J. Foxx and Supporting Documentation re: Defense Relationship of TA-55 Waste |
| C083 | Interview with J. Foxx, SME re: P/S Codes |
| C085 | Interview with M. West of NMT-2 and G. Bird of NMT-2 re: P/S Codes SBB and SCB |
| C087 | Answers to Questions About Pyrochemical Processes |
| C089 | Interview with J. Foxx re: Pu-238 and Effluent to TA-50 |
| C092 | Interview with J. Foxx re: CLS-1 Solvents |
| C094 | Interview with T. Hayes of TA-55 Nitrate Operations re: Draft AK Summary for TA-55 Nitrate Operations, 12-19-99 (attached) |
| C095 | Comments from T. Hayes and J. Foxx on the Acceptable Knowledge Summary for TA-55 Nitrate Operations |
| C096 | Response to comments on the AK Summary for TA-55 Nitrate Operations |
| C098 | Interview with J. Foxx re: P/S Code PY |
| C100 | Memo with Attachments to K. Dziewinski re: Material Type Isotopic Compositions |
| C101 | AK Isotopic Files for Input to NDA Radioassay Spreadsheets |
| C102 | Interview with R. Simpson re: P/S Codes CN, CO, CT, EL, FF, ID, OB, OM, MOX, RS |
| C104 | Interview with J. Foxx re: P/S UA |
| C105 | Interview with J. Foxx re: P/S Codes AO, EVAC and WLT |
| C108 | Interview with J. Foxx re: Secondary radionuclides used in P/S Code PI |
| C113 | AK Interview with Jim Foxx re: P/S Code FF, Use of Kynar, Portland Cement, Code HRA, 40 mm Gun |
| C117 | A Few Issues |
| C121 | Detailed Chemical Evaluation MHD01.001 |
| C122 | Be Contamination |
| C124 | Interview with Jim Fox Regarding Material Type 83 used at TA-55 |
| C125 | Decay Corrected Values for LANL Heat Source Plutonium |
| C129 | Jim Foxx's Review and Comments on CCP-AK-LANL-006 |
| C130 | Jim Foxx's Review and Comments on Nitrate and Pyrochemical/Chloride Operations Process Flow Diagrams |
| C131 | Jim Foxx's Review and Comments on Draft Process Flow Diagrams |
| C132 | Pu-239 Operations Detailed Process Flow Diagrams |
| C133 | Radiological Evaluation of Waste Stream LA-MHD01.001 Based on the Addition of Waste Stream LA-MHD02.01 |
| C135 | Interview with Site Personal Performing VE and PID Repackaging Regarding Potential for High Dose Rate Waste from TA-55 |
| C136 | Interview with Dennis Wulff Regarding Potential for High Dose Rate Waste from TA-55 |
| C138 | Addition of Mixed Inorganic and Organic Process Solids (Waste Stream # LA-CIN01.001) to Acceptable Knowledge Report AK6 |
| C139 | Calculation of Individual and Total Radionuclide Masses and Activities for Waste Stream # LA-CIN01.001 |
| C140 | Interview with Gerry Veazey Regarding the TA-55 Cement Fixation Process |
| C142 | Opening of Drum (#8260) of Retrieved TA-55 Cement Waste |

| Source Document Tracking Number | Title |
|---|---|
| C143 | Documentation Re Evaluation of TRU Waste Can Drums Retrieved from TA-54, Area G |
| C144 | Interview with Dennis Wulff Regarding the Packaging of Pu-238 Waste at TA-55 |
| C145 | Evaluation of LANL Pu-238 Waste Management Practices |
| C147 | RCRA and Chemical Evaluation for LANL Waste Streams LA-MHD01.001 and LA-CIN01.001 |
| C149 | Fiberboard Drum Liners Used During Repackaging |
| C150 | Secondary Waste Discussions to be Added to AK4 and AK6 |
| C152 | Interview with J. Foxx re: Future Waste Generation for Waste Streams LA-MHD01.001 and LA-MIN02-V.001 |
| C153 | Evaluation of Volume, Period Generation, and Calculation of Individual and Total Radionuclide Masses and Activities for Waste Stream LA-MHD01.001 |
| C154 | Evaluation of Volume, Period Generation, and Calculation of Individual and Total Radionuclide Masses and Activities for Waste Stream LA-MIN02-V.001 |
| C155 | RCRA and Chemical Evaluation for LANL Waste Stream LA-MIN02-V.001 |
| C156 | Email to M. J. Papp re: Material Reclamation Project |
| C157 | Prohibition on PCB waste lifted from LANL |
| C163 | Change of LA Waste Stream Designation For TRU Oversize Crates at TA-54 |
| C164 | Information on Packaging Changes |
| C165 | Decontamination and Volume Reduction System (DVRS) Information |
| C171 | Homogeneity of LANL Waste Stream LA-CIN01.001 |
| C172 | Evaluation of Volume, Period Generation, and Calculation of Individual and Total Radionuclide Masses and Activities for Waste Stream LA-MIN04-S.001 |
| C173 | RCRA and Chemical Evaluation for LANL Waste Stream LA-MIN04-S.001 |
| C174 | Projected Future Waste Generation for Waste Stream LA-MIN04-S.001 |
| C175 | Evaluation of Volume, Period Generation, and Calculation of Individual and Total Radionuclide Masses and Activities for Waste Stream LA-MHD01.001 |
| C176 | Email from Kapil Goyal Regarding Compact Fluorescent Bulbs |
| C177 | Secondary Waste Generated by the Remediation/Repackaging Processes at Dome 231 and WCRRF |
| C178 | Drum Washing of Drums Retrieved from Below-Grade |
| C179 | Evaluation of Volume and Calculation of Individual and Total Radionuclide Masses and Activities for Waste Stream LA-MHD01.001 |
| C180 | Evaluation of Volume and Calculation of Individual and Total Radionuclide Masses and Activities for Waste Stream LA-CIN01.001 |
| C181 | Evaluation of Volume and Calculation of Individual and Total Radionuclide Masses and Activities for Waste Stream LA-MIN02-V.001 |
| C182 | Evaluation of Volume and Calculation of Individual and Total Radionuclide Masses and Activities for Waste Stream LA-MIN04-S.001 |
| C184 | Determination of Flammable VOCs For LANL TA-55 Mixed Transuranic Waste, Waste Stream LA-CIN01.001 |
| C185 | TA-54 Building 412 vs. DVRS Facility |
| C186 | Letter on Material Type Isotopic Composition |
| C187 | Memorandum to Pamela Rogers, Transuranic Database Modifications |
| C188 | Memorandum to Pam Rogers; Layers of Packaging in TA-55 Combustible TRU Waste |

| Source Document Tracking Number | Title |
|---|---|
| C189 | Secondary Radionuclides and Toxic Metals in TA-55 TRU Waste |
| C190 | Memo to TWCP Records Center: Commingling of Defense and Nondefense TRU Waste |
| C192 | Memorandum to Pamela Rogers; Acceptable Knowledge of Pu-238 Waste Generated at the Los Alamos Plutonium Facility, TA-55 |
| C194 | Comments from Jim Foxx on the Draft Pu-238 AK Summary Report (dated November 1999) |
| C195 | Interview with Jim Foxx: Pu-238 and Effluent to TA-50 |
| C196 | Email from Jim Foxx: RCRA Codes for Pu-238 |
| C197 | Interview with Jim Foxx and Gary Rinehart Relating to the RCRA Characterization and Management of Pu-238 Liquids and P/S Code Operations |
| C198 | Interview with Jim Foxx Regarding P/S Code PI |
| C199 | Interview with Gordon Jarvinen Regarding TA-55 Miscellaneous Operations – RD&D Processes |
| C200 | Jim Foxx's comments on Draft Acceptable Knowledge Summary for TA-55 Nitrate Operations |
| C201 | Comment Resolution for Nitrates AK Summary Report (dated 2/25/00) |
| C202 | Memorandum to B.T. Reich: Air Sparging to Eliminate Pyrophoric Sodium |
| C203 | Memorandum to B.T. Reich: Experimental data on calcium pyrophoricity in salts |
| C204 | Interview with Jim Foxx; Segregation of non-defense wastes from defense wastes |
| C205 | Interview with Jim Foxx; Answers to questions of use of Ag, disposal of ash and resins, and use of gases |
| C206 | Acceptable Knowledge Personnel Interview with Jim Foxx: Disposal of Spray Cans Used in Gloveboxes |
| C207 | Interview with Jim Foxx re: Volatile RCRA-Listed Metals |
| C208 | Acceptable Knowledge Personnel Interview with Jim Foxx: Sources of Cs-137 and Pa-231 in TA-55 TRU Waste |
| C209 | Interview with J. Foxx re: Sources of Cs-137, Pa-231, and Cm-244 in TA-55 TRU Waste |
| C210 | AK Personnel Interview of Lisa Pansoy-Hjelvik, Description of P/S Code ASP |
| C211 | Interview with Gary Rinehart regarding P/S code WS Operations |
| C212 | Memorandum to Ed Wilmont, Pu-238 Waste at TA-55 |
| C213 | AK Personnel Interview with Jim Foxx: Information on P/S Codes PPD, UA, VD, IN, and WE |
| C214 | AK Personnel Interview with Jim Foxx: RD&D Processes (RD, NCD, WM) |
| C215 | Email From Wayne Punjak to Pamela Rogers: Ac-227 Drums |
| C216 | Memorandum to RMDC; Vent and Closure dates for TWISP containers submitted to WWIS |
| C219 | Interview with Jim Foxx: Material Type 83 used at TA-55 |
| C220 | Jim Foxx's Review and Comments on Draft Process Flow Diagrams |
| C221 | Detailed Pu-238 Operations Process Flow Diagrams |
| C222 | Decay Corrected Values for LANL Heat Source Plutonium |
| C223 | Record of Communication for interview with Jim Foxx: All Process Wastes |
| C224 | Addition of 7 Containers to Waste Stream LA-MIN04-S.001 |
| C225 | Evaluation of Additional Containers for waste stream LA-MHD01.001 |

| Source Document Tracking Number | Title |
|---|---|
| C226 | Waste Packaging Issues with CCP-AK-LANL-006, Waste Stream LA-CIN01.001 (TA-55 cemented waste packaged in cans and monoliths) |
| C228 | Evaluation of Los Alamos National Laboratory Circumferentially Taped Slip-Lid Cans (>4 Liters) |
| C230 | Memo: Legacy TA-55 Nitrate Salt Wastes at TA-54 - Potential Applicability of RCRA D001/D002/D003 Waste Codes |
| C231 | Email RE: Nitrate Salt Processing Guidance |
| C232 | Evaluation of Volumes and Calculations of Individual and Total Radionuclide Masses and Activities for Waste Streams LA-MHD01.001, LA-CIN01.001, LA-MIN02-V.01, and LA-MIN04-S.001 |
| C233 | Evaluation of Additional Repackaged Containers for Waste Stream LA-MHD01.001 |
| C234 | Evaluation of Additional Containers for Waste Stream LA-CIN01.001 |
| C235 | Evaluation of Additional Containers for waste stream LA-MIN02-V.001 |
| C236 | Evaluation of Additional Containers for waste stream LA-MIN04-S.001 |
| C237 | Containment Vessel Weight Analysis and Acceptable Knowledge Document |
| C238 | Memorandum of Understanding - Roles and Responsibilities for Transuranic Material Experiments on the Z Machine |
| C239 | Email RE: # of Shots |
| C240 | Email Re: Future Projected Volume for LA-MHD01.001 |
| D002 | Acceptable Knowledge Report for Legacy Debris TA-55 Waste Streams Containing Pu-239 |
| D003 | Hazardous Waste Facility Contract with DOE, University of California & Summary of Modifications |
| D004 | Attachment A (Waste Analysis Plan) of the LANL Hazardous Waste Permit |
| D007 | Process Acceptable Knowledge Report for Chloride Operations at TA-55 |
| D008 | Acceptable Knowledge Report for Newly Generated Waste from Nitrate Operations at TA-55 |
| D009 | Acceptable Knowledge Report for Newly Generated Waste from Miscellaneous Operations at TA-55 |
| D010 | Acceptable Knowledge Report for Newly Generated Waste from Special Processing Operations at TA-55 |
| D011 | Acceptable Knowledge Report for Newly Generated Waste from Metal/Pyrochemical Operations at TA-55 |
| D013 | Los Alamos National Laboratory Transuranic Waste Characterization Acceptable Knowledge Information Summary (AKIS) |
| D014 | TA-55 Facility Safety Analysis Report (FSAR), Excerpt (Chapter 1 missing) |
| D017 | Draft Acceptable Knowledge (Report) for TA-55 Nitrate Operations (and Interview comments from Tim Hayes) |
| D018 | Transuranic Waste Interface Document for the Waste Characterization, Reduction, and Repackaging Facility and the Radioactive Materials Research, Operations, and Demonstration Facility |
| D019 | Waste Management Plan for the 40-mm Powder Breach Project |
| D023 | TA-55 Plutonium Facility Acceptable Knowledge Report |
| D024 | TA-55 Transuranic Waste Interface Document |
| D025 | Acceptable Knowledge Report for Debris Waste Streams Containing Pu-239 |
| D026 | Acceptable Knowledge Information Summary For LANL Transuranic Waste Streams |

| Source Document Tracking Number | Title |
|---|---|
| D028 | Process Acceptable Knowledge Report for Pyrochemical Processes at TA-55 |
| D029 | Process Acceptable Knowledge Report for Metal Operation Processes at TA-55 |
| D030 | Process Acceptable Knowledge Report for Special Processing at TA-55 |
| D032 | Process Acceptable Knowledge Report for Miscellaneous Operations at TA-55 |
| D034 | Waste Management Site Plan |
| D036 | Process Knowledge Report for Nitrate Operations at TA-55 |
| D037 | Los Alamos TRU Waste Certification Plan for Newly Generated TRU Waste |
| D041 | Acceptable Knowledge Information Summary for LANL Transuranic Waste Streams |
| D044 | Lightweight Radioisotope Heater Unit (LWRHU) Production for the Cassini Mission |
| D045 | Final Safety Analysis Report for TA-55 NMT |
| D048 | Wastes from Plutonium Conversion and Scrap Recovery Operations |
| D049 | 40-mm Powder Breech Project, TA-55 Bldg PF-4, Waste Management Plan |
| D050 | Waste-form Development for Conversion to Portland Cement at LANL Technical Area 55 |
| D055 | Rocky Flats Environmental Technology Site Backlog Waste Reassessment Baseline Book – Waste Form 34 Pyrochemical Salts |
| D056 | TWISP Final Report |
| D057 | Processing Waste Acceptance Criteria Exception Forms |
| D058 | Review and Completion of the TWSR |
| D059 | Environmental Protection: Managing Waste; Air Quality; Ecological and Cultural Resources |
| D060 | Repackaging Plutonium-238 High Dose Rate Material for Waste Disposal |
| D062 | Upgrade and Performance Testing for the LINC Systems at TA-54 Area G |
| D063 | Project Management Objectives for Pit 9 TRU Waste Retrieval |
| D064 | Retrieval Plan for TA-54, Area G TRU Waste for Pit 9 |
| D065 | TA-54, Area G Pit 9 Waste Description |
| D066 | TA-54, Area G Pit 9 Waste Description |
| D067 | TA-54, Area G Trenches A-D Waste Description |
| D068 | TA-54 Area G Documented Safety Analysis |
| D070 | Wastes from Plutonium Conversion and Scrap Recovery Operations |
| D071 | Final Safety Analysis Report for TA-55 NMT |
| D073 | Lightweight Radioisotope Heater Unit (LWRHU) Production for the Galileo Mission |
| D074 | Lightweight Radioisotope Heater Unit (LWRHU) Production for the Cassinni Mission |
| D075 | Sampling and Analysis Project Validates Acceptable Knowledge on TA-55-43, Lot No. 01 |
| D076 | Acceptable Knowledge Summary Report for Waste Streams TA-55-43, TA-55-44, TA-55-45, TA-55-46, TA-55-47 |
| D077 | Process Acceptable Knowledge Report for Miscellaneous Operations at TA-55 |
| D078 | Process Acceptable Knowledge Report for Nitrate Operations at TA-55 |
| D079 | Process Acceptable Knowledge Report for Special Processing at TA-55 |
| D080 | Process Acceptable Knowledge Summary Report for Plutonium-238 Operations at TA-55 |
| D081 | AK Report for NG Waste from Metal/Pyrochemical Operations at TA-55 |
| D082 | Institutional Plan FY2002-FY2007 |

| Source Document Tracking Number | Title |
|---|---|
| D083 | Acceptable Knowledge Information Summary for LANL Transuranic Waste Streams |
| D084 | Acceptable Knowledge Report for Debris Waste Streams Containing Pu-239 |
| D085 | Determination of H2 Diffusion Rates through Various Closure on TRU Waste Bag-Out Bags |
| D089 | Amount of Zeolite Required to Meet the Constraints Established by the EMRTC Report RF 10-13: Application to LANL Evaporator Nitrate Salts |
| D090 | Results of Oxidizing Solids Testing - EMRTC Report FR 10-13 |
| D091 | Solution Package Scope Definition REPORT-72, Salt Waste (SP #72) Rev 1 |
| D092 | Generator Knowledge Report for the Plutonium Isentropic Compression Experiments Containment Systems |
| D093 | Preparing Samples for Materials Characterization |
| D094 | Panel Preparation for Z Experiments |
| DR001 | Discrepancy Resolution Waste Stream Assignment |
| DR004 | Discrepancy Resolution Non-Mixed TA-55 Pu-239 Debris Drums |
| DR005 | Acceptable Knowledge Source Document Discrepancy Resolution - Homogeneous Solids in Containers S818280, S818308, S822622, S818309, S832485, S862359, S802994, and S811632 |
| DR007 | Acceptable Knowledge Source Document Discrepancy Resolution – Layers of Confinement |
| DR008 | Acceptable Knowledge Source Document Discrepancy Resolution – TA-55 Homogeneous Solids Containing Greater Than 50% Heterogeneous Debris |
| DR029 | Acceptable Knowledge Source Document Discrepancy Resolution – Drum No. 86309 Contained a Small Lighter Fluid Can with ~ 65 ml of liquid |
| DR043 | Miscellaneous Debris Items in LA-CIN01.001 (cemented) Container No. 53706 |
| DR044 | Removal of 114 Heterogeneous Drums from Cemented Waste Stream (LA-CIN01.001) |
| DR048 | Acceptable Knowledge Source Document Discrepancy Resolution – Waste Stream LA-MHD01.001 Radiological Characterization |
| M002 | Review of Headspace Gas Data from Pre-WAP Analyses for Additions to AK |
| M006 | Pit Production |
| M011 | Waste Determination Report for Waste Stream TA-55-43 Lot No. 01 |
| M012 | Waste Profile Form Guidance |
| M013 | Waste Generator Guidance for Completing the TRU Waste Storage Record (TWSR) |
| M014 | General Waste Management Requirements |
| M015 | Managing Radioactive Waste |
| M016 | Hazardous and Mixed Waste |
| M017 | Final Documentation for RadWaste ORACLE Database's List of Acceptable Radioisotopes, Specific Activities, Categories and Regulatory Limits |
| M018 | Los Alamos National Laboratory Waste Profile System Forms |
| M019 | Generator Documentation |
| M023 | Procedure Review Sheets for 410-MPP, "Electrorefining of Plutonium Metal-Crac Cell" |
| M024 | Procedure Review Sheets for 435-MPP, "Reverse Cell Electrorefining (R&D Project)" |
| M026 | Coalesence of Plutonium Metal (Excerpts) and Procedure Review Sheets |
| M028 | Procedure Review Sheets and Excerpts from Salt Stripping of Electrorefining Salts Using Oxygen/Argon |

| Source Document Tracking Number | Title |
|---|---|
| M029 | Procedure Review Sheets and Excerpts from Electrorefining of Plutonium Metal, Nominal Six Kilogram Scale |
| M030 | Measuring Physical Properties (Excerpt) |
| M032 | Acceptable Knowledge Personnel Interview Form - Metal Operations |
| M037 | Multiple-Cycle Direct Oxide Reduction |
| M041 | Procedure Review Sheets for Revs 0-5 of "Electrorefining of Plutonium Metal," Doc. # 258-MPP-R00 |
| M043 | Procedure Review Sheet for Procedure 290-MPP-R02 |
| M044 | Procedure Review Sheets for Procedure 216-MPP-R01 "Oxalate Precipitation of Ion-Exchange Eluates" |
| M045 | Procedure Review Sheets for Procedure 215-MPP-R01, "Oxalate Precipitation of Plutonium from Nitrate Solutions" |
| M048 | Procedure Review Sheets for Procedure 230-MPP-R01, "Hydroxide Precipitation for Oxalate Filtrates" |
| M050 | Procedure Review Sheet for 474-REC-R01, "Process Research and Development Facilities" |
| M053 | Procedure Review Sheet for 426-REC-R00, "Residue Leaching" |
| M054 | Procedure Review Sheet for 461-REC-R00, "Nitrate Anion Exchange" |
| M057 | Procedure Review Sheet for 431-REC, "Procedure for Disposal of Oils Containing Recoverable Amounts of Pu in the Form of (U, Pu) Carbides" |
| M061 | Process Review Sheet for RAB-MS-2000, "Carbothermic Process Material Specification for Uranium Oxide Powder (Depleted)" |
| M064 | Process Accountability Flow Documents for Various Nitrate Processes |
| M067 | Procedure Review Sheet for 430-REC, "Recovery of Contaminated Platinum" |
| M069 | Procedure Review Sheet for 420-REC, "Processing of Contaminated Solids" |
| M072 | Procedure Review Sheets for 444-REC, "Dissolving Chloride Melt Portion of Electrorefining Residues" |
| M074 | Procedure 474-CLO, Hydroxide Precipitation of Chloride Waste Streams |
| M076 | Hydroxide Precipitation of the Plutonium in Chloride Waste Streams |
| M080 | Interview with J. Foxx re: Solvent Extraction Developmental Work |
| M084 | Procedure 437-REC, "Polystyrene Cube Processing" |
| M085 | Procedure 445-REC, "Preferential Dissolution of Uranium Oxides from a Uranium-Plutonium Oxide Mixture" |
| M086 | Procedure 490-REC, "Catalyzed Electrochemical Plutonium Oxide Dissolver (CEPOD)" |
| M088 | Procedure 423-REC, "Ash Leaching" |
| M089 | Procedure 431-REC, "Leaching of Contaminated Metals in Nitric Acid" |
| M090 | Procedure 421-REC, "Pickling or Surface Leaching" and "Leaching of Noncombustible Materials in Nitric Acid" |
| M092 | Procedure 490-REC, "Mediated Electro-Oxidation of Low-Level Organic Waste" and "Catalyzed Electrochemical Plutonium Oxide Dissolver" |
| M093 | Procedure 427-REC, "Incinerator Ash R&D Facility" |
| M095 | Procedure 447-REC, "Dissolution of Impure Plutonium Dioxides, Filter Residues, and Glovebox Sweepings in Hot HNO3-HF" |
| M096 | Procedure 472-REC, "Nitrate Anion Exchange for the Rich Column Material System" |
| M097 | Procedure 471-REC, "Nitrate Anion Exchange for the Lean Residue System" |

| Source Document Tracking Number | Title |
|---|---|
| M098 | Procedure 470-REC, "Nitrate Anion Exchange for the Rich Residues Ion Exchange Column" |
| M099 | Procedure 473-REC, "Nitrate Anion Exchange for the Dissolved Solids (DS) System" |
| M103 | Procedure 480-REC, "Peroxide Precipitation" |
| M112 | Procedure 407-MPP, Chlorination of Plutonium Compounds |
| M113 | Procedure 420-MPP, Reduction of $PuO_2$ to metal |
| M116 | Review Sheet for Procedure 445-MPP, "Coalescence of Plutonium Metal" |
| M118 | Review Sheet for Procedure 209-MPP, "Pickling, Leaching, and Dissolution" |
| M123 | Procedure 213-MPP, Conversion of Plutonium Oxalate to Oxide using heat lamp and hot plate |
| M125 | Procedure 217-MPP, Peroxide precipitation |
| M126 | Procedure 226-MPP, Dissolving Chloride Melt Portion of Electrorefining Residues |
| M127 | Procedure 232-MPP, Oxalate Precipitation of Pu from Hydrochloric solutions |
| M129 | Procedure 224-MPP, Chlorination of Plutonium Compounds |
| M130 | Procedure 251-MPP, Multiple-cycle Direct Oxide Reduction |
| M131 | Procedure 273-CLO, Purifying and Recovering Pu by Chloride anion exchange |
| M132 | Procedure 242-MPP, Precipitation of Plutonium Oxalate in Hydrochloric Acid |
| M134 | Direct Oxide Reduction R&D |
| M137 | Procedure HS-NMT9-PP-42, "Particle Size Analysis of Oxide Powders Procedure" |
| M142 | Procedure 435-REC, "Processing Lapping Oil and Similar Organics" |
| M144 | Procedure 491-REC, "Advanced Testing Line for Actinide Separations (ATLAS) Unit Operations" |
| M151 | Procedure 464-Rec, "Peroxide Precipitation" |
| M153 | Development of Control Charts for the Evaporator Bottoms Newly Generated Waste Stream from TA-55 |
| M154 | Miscellaneous MSDSs |
| M156 | Project 2010 Container Specific Database Information for LA-MHD01.001 |
| M157 | Project 2010 Database Summary of Waste Codes from LA-MHD01.001 |
| M158 | Project 2010 Database Information Waste Item Descriptions Summary |
| M159 | Project 2010 Container Specific Database Information - Area G Reported Radionuclides |
| M160 | LANL Project 2010 Summary of AK Discrepancies |
| M164 | Procedure Review Sheet for Identification of Potential Hazards Associated with Metallographic Operations in Rooms G104 and G107 |
| M169 | Procedure Review Sheet - Comminution and Nickel Addition Procedures for Uranium Carbide or Uranium-Plutonium Carbide |
| M172 | Procedure Review Sheet for Manual Pellet Pressing Procedure for Uranium Carbide or Uranium-Plutonium Carbide Powders |
| M174 | Procedure Review Sheet for Procedure for Measuring the Density of Sintered Fuel or Insulator Pellets by a Water Immersion Technique |
| M180 | Procedure Review Sheet - Hydroxide Precipitation of Chloride Solutions Containing Organic Chemicals |
| M181 | Procedure Review Sheet - Oxalate Precipitation of Plutonium from Chloride Solutions |
| M182 | Procedure Review Sheet - Purification and Recovery of Plutonium by Chloride Anion Exchange |

| Source Document Tracking Number | Title |
|---|---|
| M184 | Procedure Review Sheet - Dicesium Hexachloro Plutonate (DCHP) |
| M185 | Procedure Review Sheet - Head End Processing of Aqueous Chloride Plutonium |
| M186 | Procedure Review Sheet - Plutonium Recovery from Chloride Solutions by Oxalate |
| M189 | Procedure Review Sheet - Vessel Handling and Unloading |
| M200 | Plutonium Electrorefining |
| M202 | Preparation of Pu Metal by the Fluoride Reduction Process |
| M206 | Procedure Review Sheet - Salt Stripping of Electrorefining Salts |
| M212 | Procedure Review Sheet - Six Foot Sphere Handling and Unloading |
| M215 | LANL Hard Copy TWSRs for LA-MHD01 and LA-MHD02 from 2500 Set |
| M216 | LANL Hard Copy TWSRs for LA-MHD01 and LA-MHD02 from AK6 Remaining Set |
| M217 | LANL Hard Copy TWSRs for LA-MHD01 and LA-MHD02 from AK7 Remaining Set |
| M218 | LANL Hard Copy TWSRs for LA-MHD01 and LA-MHD02 from Imagic Printout Set |
| M219 | Electronic image of TWSRs and RSWD Forms from Imagic Software |
| M220 | Vent Date Information Sources |
| M222 | CONCERT Database |
| M223 | Design of Hydrothermal Waste Treatment Units for Operation at Pressures from 1 to 1,000 Bar |
| M224 | LANL Hard Copy RSWDs and TWSRs for LA-MHD01 and LA-MHD02 |
| M226 | LANL Hard Copy RSWDs and TWSRs for LA-MHD01 and LA-MHD02 |
| M236 | TA-55 Cemented RSWDs/TWSRs |
| M238 | NUGEN Drum TWSRs |
| M241 | Drum Spreadsheet for Additional LA-MHD01.001 Containers |
| M242 | TA-55 Waste Stream LA-MIN02-V.001 RSWDs/TWSRs and Drum Spreadsheet |
| M252 | TA-55 Cement Fixation Drum Logbook |
| M273 | LA-MHD01.001 TWSRs |
| M274 | TWSRs for Containers 8000 Series |
| M275 | TA-55 NUGEN TWSRs |
| M276 | TA-55 VE NUGEN TWSRs |
| M279 | TA-55 Waste Stream LA-MIN04-S.001 RSWDs/TWSRs, Drum Spreadsheet, and BDRs |
| M280 | Pit 9 Waste Information |
| M281 | Trenches A-D logbook |
| M283 | Assembled Tables taken from Milliwatt Generator Project Progress Reports |
| M284 | MSDSs for Pu-238 Operations |
| M285 | Process Flow Diagram for Routine Pu-238 Heat Source Production - Fuel Fabrication |
| M286 | Particle Size Analysis of Oxide Powders |
| M287 | Process Flow Diagram for Metallography |
| M288 | Process Flow Diagram for Pu-238 Scrap Processing |
| M289 | Introductory Glovebox Transfer of an EP-60 into and EP-61 |
| M290 | Decontamination of Ir Using Molten MgCl2 |
| M291 | Process Flow Diagram for Recovery of Pu-238 Oxide from Contaminated Iridium |
| M292 | Dissolution of Ir by Electrochemical Methods |
| M293 | Process Flow Diagram for Pu-238 Waste Solidification |

| Source Document Tracking Number | Title |
|---|---|
| M294 | Recovery of Plutonium-238 from Sucrose Solutions |
| M295 | Documentation for RadWaste ORACLE Database's List of Acceptable Radioisotopes, Specific Activities, Categories and Regulatory Limits |
| M296 | Generator Documentation (RSWD/TWSRs) |
| M298 | Concert Database Query, Physical Parameter Inventory Analysis for Waste Stream LA-MHD02.002 |
| M299 | Thermal Decomposition of Cellulose Items |
| M300 | General Waste Management Requirements |
| M301 | Hazardous and Mixed Waste |
| M302 | Managing Radioactive Waste |
| M303 | Waste Profile Form Guidance |
| M304 | Waste Generator Guidance for Completing the TRU Waste Storage Record (TWSR) |
| M306 | The Actinide Research Quarterly, Magnetic Levitation Results in High-Purity Plutonium Metal. |
| M307 | Acceptable Knowledge Isotopic Ratios (AKIR) database, Versions 2.0 and 2.1 |
| M308 | Pu-238 Defense Determination Resolution |
| M309 | Radiological Discrepancy Report |
| M310 | RCRA EPA Hazardous Waste Code Assignment Discrepancy Report |
| M312 | CCP-AK-LANL-007 Document Conversion To CCP-AK-LANL-006 Source Documents |
| M316 | Record of Communication - Secondary Waste Added During Remediation and Repackaging Operations |
| M317 | Waste Stream LA-MIN04-S.001 Radionuclide Calculations |
| P001 | Nitric Acid Process Evaporator |
| P005 | Thorium Fluoride Precipitation |
| P008 | Cement Fixation of Process Residues in 55-Gallon Drums (Excerpts) |
| P011 | Cement Fixation of Process Residues in One-Gallon Cans (Excerpts) |
| P012 | Organic Liquid Emulsification |
| P014 | Casing Enriched Plutonium |
| P024 | Nitrate Anion Exchange |
| P025 | Dissolution and/or Leaching of Various Materials in Hydrochloric Acid |
| P026 | Oxalate Precipitation of Plutonium from Hydrochloric Acid Solutions |
| P027 | Purification and Recovery of Plutonium by Chloride Anion Exchange |
| P028 | Hydroxide Precipitation |
| P029 | Procedure for Pyroredox Processing of Spent Electrorefining Anodes (P/S RA) |
| P033 | Procedure "Cleaning Requirements for Large Components" P/S EL |
| P034 | Procedure "Cleaning for Small Components" |
| P036 | Procedure "Fabrication and Inspection of He-Bonded Fuel Elements" P/S EL |
| P042 | Procedure "Sodium Bonding" P/S EL |
| P044 | Procedure "Encapsulation of Radioactive Isotopes" P/S WE |
| P045 | Procedure "Plasma Chemical Reactor" P/S PCH |
| P046 | Procedure "Safe Operating Procedure for Pit Disassembly" P/S MW, PD, SRL |
| P049 | Procedure "Ultrasonic Degreaser" P/S MA |
| P051 | Procedure "Operating the Autoclave Hot Isostatic Press" P/S BA |

| Source Document Tracking Number | Title |
|---|---|
| P052 | Procedure "Cleaning of SP-100 Fuel Pin Components" |
| P053 | Procedure "Pit Disassembly" P/S SRL |
| P056 | Procedure "Heat Treatment of SP-100 Components" |
| P064 | Procedure "Hydrothermal Processing" |
| P065 | Procedure "Superacid Research and Development" |
| P067 | Procedure "Room 208 Purification Process Development" |
| P069 | Procedure "Super Oxidizer Fluorination of Ash" |
| P070 | Procedure "Operation of the Plutonium FOOF Loop" |
| P071 | Procedure "Operation of the Plutonium Fluorination Loop" |
| P076 | Procedure "Research, Development, and Demonstration Facilities" |
| P077 | Procedure "Research, Development, and Demonstration Facilities" |
| P078 | Procedure "Sensors and Instrumentation Development" |
| P080 | Procedure "Organoactinide R&D" |
| P081 | Procedure "Actinide Chemistry Research and Development" |
| P083 | Procedure "Plutonium Chlorination" |
| P085 | Procedure "Developmental Chloride Solvent Extraction Process" |
| P090 | TA-55 Generator Attachment to the Los Alamos TRU Waste Certification Plan |
| P091 | Attachment 3 to the TRU Waste Certification Plan, R05 |
| P092 | TA-55 Transuranic Waste Interface Document for Debris Waste |
| P094 | Documenting Acceptable Knowledge For Legacy Waste Items |
| P095 | Inspecting, Packaging, Rejecting, and Remediating Transuranic Waste for WIPP and for TA-54 Safe Storage |
| P096 | TA-55 Waste Management, TWCP-351 |
| P097 | Performing Visual Inspections of TRU Waste |
| P098 | Packing TRU Waste Containers |
| P102 | Procedure 406-GEN, "Standard Operating Procedure for the Waste Management at TA-55, CMB-11 Facility"; also LA-UR-01-6170 |
| P103 | Thorium Fluoride Precipitation |
| P104 | Electrorefining of Plutonium Metal, Nominal Six Kg Scale |
| P105 | Chloride Melt Preparation for Electrorefining and Fused Salt Extraction |
| P109 | Acceptable Knowledge Personnel Interview Form re: Pyrochemical waste stream |
| P110 | Acceptable Knowledge Personnel Interview Form re: Pyrochemical waste stream |
| P117 | Waste Visual Examination and Packaging |
| P118 | Acceptable Knowledge Documentation |
| P125 | Characterization of Direct Oxide Salts |
| P147 | Electrochemical Systems Operations, NMT-15 Hazard Control Plan |
| P148 | Machining of Special Nuclear Materials in Glovebox Enclosures, NMT-15 Hazard Control Plan |
| P152 | Cement Fixation of Process Residues in One-Gallon Cans |
| P153 | Cement Fixation of Process Residues in 55-Gallon Drums |
| P154 | Standard Waste Visual Examination and Prohibited Item Disposition |
| P155 | Pu-238 Residue Solidification |
| P156 | Thermal Decomposition of Cellulose Items Contaminated with Plutonium-238 |

| Source Document Tracking Number | Title |
|---|---|
| P157 | Direct Oxide Reduction of Pu-238 Oxide |
| P158 | Prohibited Items Disposition Dome 231 Permacon |
| P159 | Processing Waste in the Waste Characterization Glovebox |
| P160 | Introducing and Removing Items and Samples from the Glovebox Systems in PF-4 |
| P161 | TA-55 Waste Management |
| P162 | TA-55 Waste Management Requirements |
| P163 | Nuclear Materials Packaging |
| P164 | Inspecting, Labeling, and Preparing TRU Waste Containers |
| P165 | Performing Visual Inspections of TRU Waste |
| P166 | Packing TRU Waste Containers |
| P167 | Packing TRU Waste Containers |
| P168 | Sealing TRU Waste Containers |
| P169 | Sealing TRU Waste Containers |
| P170 | Material Reclamation |
| P171 | Inspecting and Preparing a Drum |
| P172 | Inspecting the Cement and Performing the Drum-in and Drum-out |
| P173 | Waste Generating Instruction for Heat-Source Plutonium Solid TRU Waste |
| P174 | Trenches A – D Retrieval Operations |
| P175 | Sort, Segregate, Size Reduction, and Repackaging Activities |
| P177 | TA-55 Waste Management |
| P178 | Attachment 3 to the Los Alamos TRU Waste Certification Plan for Newly Generated TRU Waste |
| P179 | TA-55 Generator Attachment to the Los Alamos TRU Waste Certification Plan |
| P180 | Sampling PuO2 Procedure |
| P181 | Ceramography of 238 PuO2 Fuel Samples |
| P182 | 238 Pu Waste Solidification |
| P183 | Cement Fixation of Process Residues in 55-Gallon Drums |
| P185 | Cement Fixation of Process Residues in One-Gallon Cans |
| P186 | Organic Liquid Emulsification |
| P187 | Characterization of Direct Oxide Salts |
| P188 | Standard Operating Procedure for the Waste Management at TA-55 |
| P189 | Direct Oxide Reduction of 238 PuO2 |
| P190 | Advanced Testing Line for Actinide Separations (ATLAS) Unit Operations |
| P192 | TA-54 Area G TRU Crate SSSR Activities |
| P194 | TA-54-231 PermaCon Upgrades |
| P195 | Sort, Segregate, Size Reduction, and Repackaging Activities |
| P196 | TA-54 Area G Sludge Remediation Activities |
| P197 | TA-54 Area G TRU Crate SSSR Activities |
| P198 | WCRRF Waste Characterization Glovebox Operations |
| P199 | TA-54-375 TRU Oversized Box Processing Capability Project |
| P203 | TA-54 Area G TRU Corrugated Metal Box SSSR Activities |
| P204 | TA-54 Area G Ten-Drum Overpack Container Operations |

Controlled
Copy



| Source Document Tracking Number | Title |
|---|---|
| U002 | Review of RTR Data From Pre-WAP Analysis For AK |
| U004 | Process Status Data from Area 55 WMD & Cert. Database |
| U005 | Twenty-Five Years of Radioactive Waste Cementation at Los Alamos National Laboratory |
| U007 | Review of RTR Data From Pre-WAP Analysis for AK |

Controlled
Copy



Figure 1. Location of LANL Site



Controlled
Copy



Figure 2. Location of the PF-4 at TA-55 LANL Site



Controlled
Copy



Figure 3. RSWD Code Descriptions Table

| RSWD Code | Definition | Waste Stream |
|---|---|---|
| A10 | Graphite | LA-MHD01.001 |
| A14 | Combustible Decon Waste | LA-MHD01.001 |
| A15 | Cellulosics | LA-MHD01.001 |
| A16 | Plastics | LA-MHD01.001 |
| A17 | Rubber Materials | LA-MHD01.001 |
| A18 | Combustible Lab Trash | LA-MHD01.001 |
| A19 | Combined Combustible/Non-Combustible Lab Trash | LA-MHD01.001 |
| A20 | Hydrocarbon Oil – Liquid (Absorbed) | LA-MIN02-V.001 |
| A21 | Silicon-Based – Liquid (Absorbed) | LA-MIN02-V.001 |
| A25 | Leached Process Residues | LA-CIN01.001 |
| A26 | Evaporator Bottoms/Salts | LA-CIN01.001 |
| A27 | Nitrate Salts | LA-MIN04-S.001 |
| A28 | Chloride Salts | LA-MIN04-S.001 |
| A30 | Property Number Equipment | LA-MHD01.001 |
| A31 | Non-Property Number Equipment | LA-MHD01.001 |
| A35 | Combustible Building Debris | LA-MHD01.001 |
| A36 | Noncombustible Building Debris | LA-MHD01.001 |
| A47 | Slag and Porcelain | LA-MHD01.001 |
| A50 | Metal Crucibles, Scrap, Dies | LA-MHD01.001 |
| A51 | Precious Metal | LA-MHD01.001 |
| A52 | Scrap Metal | LA-MHD01.001 |
| A55 | Filter Media | LA-MHD01.001 |
| A60 | Other Combustibles | LA-MHD01.001 |
| A61 | Other Non-combustibles | LA-MHD01.001 |
| A70 | Chemical Waste | LA-MIN02-V.001 |
| A77 | Vermiculite (Before 1985) | LA-MIN02-V.001 |
| A95 | Glass | LA-MHD01.001 |

Controlled
Copy



Figure 4. Item Description Codes (IDC) Table

| Item Description Code | Definition | Description |
|---|---|---|
| 001 | Mixed metal scrap and combustibles (primarily metals or metal equipment along with its combustible components and combustibles generated during decommissioning, sectioning equipment, or packaging) | IDC 001 waste is comprised of several types of metal scrap and incidental combustibles generated at various TAs and size reduced at the WCRR Facility. The waste consists mostly of metals or metal equipment, either whole or sectioned, and lesser amounts of combustible components. In addition, small volumes of combustibles generated during decommissioning, sectioning, and packaging are present. The waste forms primarily include gloveboxes, process equipment, and ductwork from decommissioning operations. Gloveboxes may include gloves, wiring, plastic, glass windows, plastic wrapping, and lead shielding. |
| 004 | Combustible solids (may contain small fraction of noncombustible solids) | IDC 004 waste is comprised of combustible waste such as paper, rags, plastic, and rubber, including plastic-based and cellulose-based waste generated at the TA-55 Plutonium Facility. Plastic-based waste includes, but may not be limited to, tape, polyethylene, and vinyl; gloves; plastic vials; polystyrene; Tygon tubing; polyvinyl chloride plastic; Teflon products; Plexiglas; and dry box gloves (unleaded Neoprene base). Cellulose-based waste includes, but may not be limited to, rags, wood, paper, cardboard, laboratory counts and coveralls, booties, and cotton gloves, and similar miscellaneous materials. IDC 004 waste may also contain a small fraction of noncombustible solids (e.g., scrap metals, metal lids). |
| 005 | Noncombustible scrap (may contain small fraction of combustible solids) | IDC 005 waste includes metals and non-metals. The non-metal wastes included glass, fiberglass heating mantles, porcelain crucibles, ceramic furnace tube inserts, and leaded glovebox gloves. Discarded HEPA filters are identified as IDC 005 waste. This waste is generated in PF-4 at TA-55. A small fraction of combustible waste, such as plastics (mainly packaging), may also be present. |

Controlled
Copy



Figure 4. Item Description Codes (IDC) Table (Continued)

| Item Description Code | Definition | Description |
|---|---|---|
| 005(P1) | Leaded rubber and metal waste | IDC 005(P1) consists of leaded rubber waste and metal waste, including lead-lined glovebox gloves discarded along with metal waste, such as motors and tools. |
| 005(P2S) | Salt waste | IDC 005(P2S) waste consists of used salts from pyrochemical processes such as electrorefining, molten salt extraction, salt stripping, fluoride reduction, and direct oxide reduction carried out at PF-4 at TA-55. A small fraction of combustible waste, such as plastics (mainly packaging), may also be present. |
| 006 | Cemented process residues (process-leached solids, filter cakes, evaporator bottoms, etc., stabilized in Portland cement) | IDC 006 waste includes solidified inorganic and organic process solids generated from facility and equipment operations and maintenance. This waste may include process leached solids, ash, filter cakes, salts, metal oxides, fines, evaporated bottoms, or up to six liters of emulsified solvents and oils stabilized in Portland or gypsum cement. This waste also includes spent samples received from TA-3, CMR Building. |

Figure 5. TA-55 Process/Status Code Index Table

| P/S Code | P/S Name | Operations Process Report in which this P/S Code is Described* |
|---|---|---|
| AAP | Accelerated Aging of Plutonium | Metal Operations |
| AC | Actinide chemistry, R&D | Miscellaneous Operations |
| AC1 | Actinide chemistry, R&D | Miscellaneous Operations |
| AC2 | Actinide chemistry, R&D | Miscellaneous Operations |
| AC3 | Actinide chemistry, R&D | Miscellaneous Operations |
| ACC | Ammonium chloride conversion | Special Processing Operations |
| ACD | Cascade dissolver | Special Processing Operations |
| ACL | Analytical chemistry laboratory | Miscellaneous Operations |
| AD | Actinide processing demonstration | Miscellaneous Operations |
| AL | Ash leach | Nitrate Operations |
| AO | Assembly operation | Metal Operations |
| AO | Americium processing calcination | Nitrate Operations |
| AP | Americium purification | Nitrate Operations |
| APD | Actinide processing demonstration | Miscellaneous Operations |
| ARI | ARIES | Metal Operations |
| AS | Anode heel dissolution | Nitrate Operations |
| ASP | Aqueous Scrap Processing | Pu-238 Operations |
| AT | Ash testing | Nitrate Operations |
| ATL | Advanced test line for actinide separation RD&D | Nitrate Operations |
| AX | Solution assay | Miscellaneous Operations |
| BA | Basement isopress | Metal Operations |
| BAC | Bacterial decomposition of cellulose items | Nitrate Operations |
| BC | Physical properties | Metal Operations |
| BF | Unknown name for P/S Code | Nitrate Operations |
| BL | Blending | Nitrate Operations |
| BM | Burning metal | Nitrate Operations |
| BT | Burst testing | Metal Operations |

Figure 5. Process/Status Code Index Table (Continued)

| P/S Code | P/S Name | Operations Process Report in which this P/S Code is Described* |
|---|---|---|
| BU | Button burning | Nitrate Operations |
| C1 | Pu-238 Heat Source Calorimetry | Pu-238 Operations |
| CA | Casting | Metal Operations |
| CC | Calcination | Nitrate Operations |
| CD | Hydroxide cake dissolution | Nitrate Operations |
| CF | Cement fixation | Nitrate Operations |
| CH | Characterization | Nitrate Operations |
| CK | RD&D volatile fluoride Pu recovery | Miscellaneous Operations |
| CL | Crucible processing | Chloride Operations |
| CLRD | Aqueous chloride R&D | Chloride Operations |
| CLS | Accountable CLS chloride solutions | Chloride Operations |
| CN | C-N-O analysis | Metal Operations |
| CO | Comminution | Metal Operations |
| COD | Chlorinated oxide dissolution | Nitrate Operations |
| COL | Chlorinated oxide leach | Nitrate Operations |
| CP | Chloride processing | Special Operations |
| CPOD | Catalyzed electrochemical plutonium oxide dissolver | Nitrate Operations |
| CR | Crushing and pulverizing | Nitrate Operations |
| CRD | Chlorination/reduction RD&D | Pyrochemical Operations |
| CS | Chloride solutions | Chloride Operations |
| CSE | Chloride solvent extraction | Chloride Operations |
| CT | Compatibility testing | Metal Operations |
| CV | RD&D experimental chlorination processes | Miscellaneous Operations |
| CW | Caustic waste | Chloride Operations |
| CX | Chloride anion exchange | Chloride Operations |
| CXL | Experimental chloride extraction line | Chloride Operations |

Figure 5. Process/Status Code Index Table (Continued)

| P/S Code | P/S Name | Operations Process Report in which this P/S Code is Described* |
|---|---|---|
| DA | Alloy development Pu items | Metal Operations |
| DF | DS furnace and oxide preparation | Nitrate Operations |
| DO | Dissolution of oxide | Special Processing Operations |
| DOP | Detector oxide preparation | Metal Operations |
| DP | Dry processing | Nitrate Operations |
| DS | Ion exchange | Nitrate Operations |
| DT | John Ward R&D | Metal Operations |
| ECHM | Electrochemistry | Miscellaneous Operations |
| ED | Cascade dissolver | Nitrate Operations |
| EDC | Electrolytic decontamination | Miscellaneous Operations |
| EL | Element loading | Metal Operations |
| ELW | Experimental laser welding | Metal Operations |
| EM | Electron microscopy | Metal Operations |
| EOC | Experimental oxide characterization | Miscellaneous Operations |
| ER | Electrorefining | Pyrochemical Operations |
| ETD | Experimental thermal decomposition | Nitrate Operations |
| EV | Evaporator | Nitrate Operations |
| EVAC | Evacuation and bake out | Metal Operations |
| EXT | Extraction RD&D | Miscellaneous Operations |
| FA | Americium processing | Nitrate Operations |
| FC | Canning | Nitrate Operations |
| FDL | FOOF demonstration loop | Miscellaneous Operations |
| FF | Fuel fabrication | Metal Operations |
| FLU | Fluorination RD&D | Miscellaneous Operations |
| FSPF | Special furnace operations | Metal Operations |
| FX | Cement to drum | Nitrate Operations |
| GI | Pellet grinding & inspection | Metal Operations |

Figure 5. Process/Status Code Index Table (Continued)

| P/S Code | P/S Name | Operations Process Report in which this P/S Code is Described* |
|---|---|---|
| GMS | Open gradient magnetic separation | Nitrate Operations |
| GPHS | General Purpose Heat Source (GPHS) | Pu-238 Operations |
| HC | Calcination | Nitrate Operations |
| HCD | Hydroxide cake dissolution | Nitrate Operations |
| HD | Hydroxide cake dissolution | Nitrate Operations |
| HG | Pu removal by mercury | Metal Operations |
| HGMS | High gradient magnetic separation | Nitrate Operations |
| HP | Cement fixation | Nitrate Operations |
| HRA | Hanford Reservation Material | Nitrate Operations |
| HRS | High resolution spectroscopy | Miscellaneous Operations |
| IA | Impure americium holding for discard | Nitrate Operations |
| IAM | Inspection and measurement | Special Processing Operations |
| IB | Matrix study of pyrochemical salts | Miscellaneous Operations |
| ICP | ICP-AES analysis | Miscellaneous Operations |
| ID | Immersion density | Metal Operations |
| IE | Isotope enrichment | Miscellaneous Operations |
| IHL | Induction Heating and Levitation | Pu-238 Operations |
| IN | Inspection | Metal Operations |
| IS | Incinerator | Nitrate Operations |
| ITF | Impact test facility | Metal Operations |
| ITF4 | Impact test facility | Metal Operations |
| ITF7 | Impact test facility | Metal Operations |
| IX | Ion exchange | Special Processing Operations |
| JA | Gas isostatic press | Metal Operations |
| KBTF | Kolsky bar test facility | Metal Operations |
| LC | Uranium plutonium processing | Nitrate Operations |

Figure 5. Process/Status Code Index Table (Continued)

| P/S Code | P/S Name | Operations Process Report in which this P/S Code is Described* |
|---|---|---|
| LD | Chloride leach & dissolution | Chloride Operations |
| LG1 | Non combustible leach | Nitrate Operations |
| LG2 | Hydroxide cake dissolution | Nitrate Operations |
| LI | XF6 experimental measurements | Miscellaneous Operations |
| LIBS | Laser-induced breakdown spectroscopy system | Miscellaneous Operations |
| LR | Ion exchange | Nitrate Operations |
| M1, M2, MM, M4 | Materials Management | Miscellaneous Operations |
| MA | Machining | Metal Operations |
| MAG | Magnetic separation | Nitrate Operations |
| MAS | RD&D experimental processes | Nitrate Operations |
| MB | Nitric dissolution of molten salts | Chloride Operations<br>Nitrate Operations |
| MBC | Crystal | Metal Operations |
| ME | Metallography | Miscellaneous Operations |
| MELL | Mediated electro-oxidation of LLW | Nitrate Operations |
| MF | Metals furnace | Nitrate Operations |
| MIS | Material identification and surveillance | Miscellaneous Operations |
| ML | Non-Pu metal leach | Nitrate Operations |
| MO | Metal oxidation, room 429 | Pyrochemical Operations |
| MOX | Mixed oxide fuel production | Metal Operations |
| MP | Metal preparation | Pyrochemical Operations |
| MPD | Cascade dissolver | Nitrate Operations |
| MR | Material Reclamation | Pu-238 Operations |
| MS | Molten salts purification dissolution | Chloride Operations |
| MTL | Metallography-Plutonium-238 Operations | Pu-238 Operations |
| MW | Metal working | Metal Operations |
| NC | Noncombustible leach | Nitrate Operations |

Figure 5. Process/Status Code Index Table (Continued)

| P/S Code | P/S Name | Operations Process Report in which this P/S Code is Described* |
|---|---|---|
| NCD | Nonconforming drums | Miscellaneous Operations |
| NEPTUNIUM | Neptunium | Pyrochemical Operations |
| NL | Noncombustible leach | Nitrate Operations |
| NP | Nitrate processing | Special Operations |
| NR | Nitrate recovery | Nitrate Operations |
| OB | Oxide blending | Metal Operations |
| OD | Oxide dissolution | Nitrate Operations |
| OH | Hydroxide precipitation | Nitrate Operations |
| OM | Oxygen to metal ratio determination | Metal Operations |
| OR | Direct oxide reduction | Pyrochemical Operations |
| OY | Oxalate precipitation | Nitrate Operations |
| P1 | Routine Pu-238 Heat Source | Pu-238 Operations |
| PA | Passivation | Nitrate Operations |
| PAF | Passivation furnaces | Nitrate Operations |
| PB | Pu-beryllium source recovery | Chloride Operations |
| PCH | Plasma chemistry | Metal Operations |
| PD | Pit disassembly | Metal Operations |
| PE | Sputtering process | Metal Operations |
| PF | Plutonium surfaces | Metal Operations |
| PH | Thermal hydride/dehydride | Metal Operations |
| PI | Preparation of isotopes | Special Processing Operations |
| PIG | Welding | Metal Operations |
| PK | Pickling and nitrate holding | Pyrochemical Operations |
| POSM | Processing out-of-specification material | Special Operations |
| PP | Pellet Production | Pu-238 Operations |
| PPD | Pu pellet dissolution | Special Operations |
| PR | Peroxide precipitation | Nitrate Operations |
| PRR | Pyrochemical residue recovery | Chloride Operations |
| PS | Peroxide precipitation of MSE salts | Nitrate Operations |

Figure 5. Process/Status Code Index Table (Continued)

| P/S Code | P/S Name | Operations Process Report in which this P/S Code is Described* |
|---|---|---|
| PSE | Plutonium standards extrusion | Metal Operations |
| PT | Plutonium-thorium separation | Nitrate Operations |
| PTP | Plutonium trichloride preparation | Pyrochemical Operations |
| PTS | RD&D pretreatment study | Nitrate Operations |
| PUB | Pu/Be source recovery | Chloride Operations |
| PX | Pyrochemical R&D | Special Operations |
| R8 | Routine Pu-238 Solidification/Recovery of Pu-238 from Sucrose | Pu-238 Operations |
| RA | Recovery of anodes | Pyrochemical Operations |
| RAP | Research alloy preparation | Metal Operations |
| RAP2 | Research alloy preparation | Metal Operations |
| RASS/RSS | Raman spectroscopy system | Miscellaneous Operations |
| RB | Roasting and blending | Nitrate Operations |
| RBJ | Roasting and blending Jr | Nitrate Operations |
| RC | Rotary calciner | Nitrate Operations |
| RCI | Recovery of Pu-238 from contaminated Iridium | Pu-238 Operations |
| RCM | Rich column material ion exchange | Nitrate Operations |
| RD | Repackaging into retrievable drums | Miscellaneous Operations |
| RFX | Ion exchange | Nitrate Operations |
| RL | Radiochemical coating | Metal Operations |
| RM | Reduction to metal | Special Processing Operations |
| RO | Oil recovery | Nitrate Operations |
| RR | Ion exchange | Nitrate Operations |
| RS | Pellet sintering | Metal Operations |
| SA | Super acid RD&D | Miscellaneous Operations |
| SB | Scrap burning | Special Processing Operations |
| SBB | Ca/Al scrubbing RD&D | Special Processing Operations |

Controlled
Copy



Figure 5. Process/Status Code Index Table (Continued)

| P/S Code | P/S Name | Operations Process Report in which this P/S Code is Described* |
|---|---|---|
| SC | Cascade dissolver, G437 | Nitrate Operations |
| SCB | Chlorination Ca/Al scrubbing RD&D | Pyrochemical Operations |
| SCP | Routine Pu-238 Scrap Processing | Pu-238 Operations |
| SD | Salt distillation | Pyrochemical Operations |
| SE | Solvent extraction | Chloride Operations |
| SL | Scrap leaching | Special Processing Operations |
| SMA | Surveillance machining | Metal Operations |
| SMIS | Long-Term Storage/Compatibility Testing | Miscellaneous Operations |
| SMP | SP mounting preparation | Miscellaneous Operations |
| SO | Super oxidizer, FOOF program | Miscellaneous Operations |
| SP | Scrap dissolution, G438 | Nitrate Operations |
| SRL | Special recovery line | Metal Operations |
| SS | Salt stripping | Pyrochemical Operations |
| SSD | Special scrap dissolution | Nitrate Operations |
| SSMD | SS material development | Pyrochemical Operations |
| STF | Standard fabrication | Miscellaneous Operations |
| SURF | Plutonium surfaces | Metal Operations |
| SX | Americium processing silicon removal | Nitrate Operations |
| TDC | Thermal decomposition of cellulose items | Nitrate Operations |
| TSC | Thermal stabilization of cellulosic material | Nitrate Operations |
| TIGR | Thermally induced gallium removal | Metal Operations |
| UA | Uranium fabrication | Metal Operations |
| UCON | Uranium conversion | Metal Operations |
| UPS | Uranium/plutonium separation | Nitrate Operations |

Figure 5. Process/Status Code Index Table (Continued)

| P/S Code | P/S Name | Operations Process Report in which this P/S Code is Described* |
|---|---|---|
| US | Uranium separation for solid solution feed | Nitrate Operations |
| US2 | Uranium separation for non-solid solutions feed | Nitrate Operations |
| VC | Variable CSMO scrap dissolution | Nitrate Operations |
| VD | Vapor degreaser and sand blasting | Metal Operations |
| VP1 | CSMO scrap dissolution | Nitrate Operations |
| VP2 | Polycube processing | Nitrate Operations |
| VP3 | Hydroxide precipitation | Nitrate Operations |
| VS | Confirmation, inspection & sampling | Miscellaneous Operations |
| VU | Vessel unloading | Special Processing Operations |
| VUL | Vessel unloading | Nitrate Operations |
| WD | Welding and Decontamination for GPHS | Pu-238 Operations |
| WE | Welding | Metal Operations |
| WLT | Welding leak test | Metal Operations |
| WM | Waste management | Miscellaneous Operations |
| WS | Pu-238 Direct Oxide Reduction | Pu-238 Operations |
| X0 | Inactive or unspecified P/S material | Miscellaneous Operations |
| XES | X-ray energy spectroscopy | Miscellaneous Operations |
| XO | Inactive or unspecified P/S material | Miscellaneous Operations |
| XP | RD&D experimental processes | Miscellaneous Operations |
| ZD | Scrap oxide dissolution | Nitrate Operations |

*Operations Process Reports: Chloride Operations (Reference D007), Metal Operation Processes (References D011 and D029), Miscellaneous Operations (References D009 and D032), Nitrate Operations (References D008 and D036), Pyrochemical Operations (References D011 and D028), Special Processing Operations (References D010 and D030), and Pu-238 Operations (Reference D080). Timelines for the P/S Codes can be found in these Operations Process Reports.

Controlled
Copy



Figure 6. Example Generator Container Specific Documentation

PLEASE READ INSTRUCTIONS ON BACK CAREFULLY

LASL RADIOACTIVE SOLID WASTE
DISPOSAL RECORD FORM

H-7 Waste Management
Ext 6095 MS 882

1. FORM NUMBER: S B 13597

2. DATE (M M D D Y Y): 05 26 81

3. RETRIEVABLE SERIAL NO.: 000148

4. ORIGIN OF WASTE: GROUP CMB11; TA 55; BLDG PF4; WING 206; ROOM 432

5. WASTE CODE: A60

6. WASTE DESCRIPTION: Combustible

7. NUMBERS OF WASTE PACKAGES: PLASTIC BAGS; CARD BOARD BOXES; DRUMS NO. GAL; WOODEN CRATES NO. VOLUME ft³: 1 55

8. GROSS VOLUME: 2 M (UNITS: M - METER³, F - FEET³, G - GALLON)

9. PACKAGE RADIATION AT: SURFACE MR/HR 0; 1 METER MR/HR 0

10. GROSS WEIGHT: 47.8 K (UNITS: K - KILOGRAM, P - POUND, T - TON)

11. ADDITIONAL DESCRIPTION OF PACKAGING AND PACKAGING MATERIALS

12. RADIONUCLIDE CONTENT (UNITS: C - CURIE, M - GRAM)

| NUCLIDE | AMOUNT | ± | UNITS | CHROMIUM AMOUNT | ± | AMOUNT DETERMINED BY (A - ANALYSIS, M - MEASUREMENT, E - ESTIMATE) | SS MATERIALS WRITEOFF ACCOUNT | PROJECT CODE |
|---|---|---|---|---|---|---|---|---|
| PU 83 | | E | +DM | | E | M | 741 | 309 |
| | | E | | | E | | | |
| | | E | | | E | | | |
| | | E | | | E | | | |
| | | E | | | E | | | |
| | | E | | | E | | | |

Arnold T. Cubitt
WASTE GENERATOR
Signature certifies that waste is in accordance with all applicable disposal requirements

H-1 AREA REPRESENTATIVE
Signature certifies that waste package or shipment is safe to handle and transport

Faye Hsu
CHIEF (OR DEPUTY) H-1 REPRESENTATIVE

13. DATE DISPOSED (M M D D Y Y)

14. DISPOSAL/STORAGE LOCATION: AREA; SHAFT; PIT; POSITION; LAYER; SOS

15. SHAFT SURFACE DOSE: MR/HR

H-7 WASTE MANAGEMENT REPRESENTATIVE

HS-E 7-1A(10/80)

Controlled
Copy



Figure 6. Example Generator Container Specific Documentation (Continued)



**Discardable Waste Log Sheet** **DrumID: 000148**

| Item# | ItemID | Net (kg) | Matrix | M Code | NM | MT | Auth | Remarks |
|---|---|---|---|---|---|---|---|---|
| 1 | TRASH | 4.1 | COMB | 0 | 85 | | | |
| | | 4.1 kg | | | | | | |

Figure 6. Example Generator Container Specific Documentation (Continued)

Los Alamos
NATIONAL LABORATORY

TRU WASTE STORAGE RECORD

LA00000057745

1. GENERATOR'S PRE-USE VISUAL INSPECTION

| | | | |
|---|---|---|---|
| Purchase Order # 2328415 | Inspected Items | | |
| *This container has been visually inspected according to approved procedures and has been found to be free of damage that would make it unsuitable for TRU waste packaging.* | [X] Ring, Bolt, and Nut | [X] Chime | [X] Dents |
| | [X] Lid and Gasket | [X] Gouges | [X] Paint |
| Name | Znumber 091564 | Date NOV 23 1998 | |

2. GENERATOR'S PACKAGE INFORMATION

| | | | | |
|---|---|---|---|---|
| Group NMT-7 | Technical Area 55 | Building PF-4 | Program Code 8J0700 KG19 2000 1000 | [ ] Off-Normal |
| Additional Information TID | | | | |

| CONTAINER | LINER |
|---|---|
| [X] Steel Drum (*55 gal.*) | [X] None |
| [ ] Steel Drum (*85 gal.*) | [ ] 90 mil liner |
| [ ] Standard Waste Box | [ ] 125 mil liner |
| [ ] RH Canister | INTERNAL SHIELDING |
| [ ] Other (*Call TWCO*) | [X] None |
| [ ] Overpack | Type / Thickness (*in.*) |
| Carbon Filter ID 01 2080 / 02 | |

RADIONUCLIDE CONTENT

| Nuclide | Amount | Uncertainty | C=Curie M=Gram |
|---|---|---|---|
| PU-238 | 4.040E-3 | 1.867E-4 | M |
| PU-239 | 3.788E+1 | 1.751E+0 | M |
| PU-240 | 2.424E+0 | 1.120E-1 | M |
| PU-241 | 8.079E-2 | 3.734E-3 | M |
| PU-242 | 8.079E-3 | 3.734E-4 | M |
| AM-241 | 6.423E-2 | 2.969E-3 | M |

| | |
|---|---|
| Waste Profile Request Number | 20283 |
| Process Batch Code | NA |
| Gross Weight (*lb.*) | 2.21E+2 |
| Net Weight (*lb.*) | 1.60E+2 |
| Shipping Category | 2001700110 |
| LANL Waste Stream ID | TA-55-5 |
| TRUCON Code | 117C |
| Date Closed (*MMDDYY*) | DEC 2 1998 |

[ ] PDP Program Tracking No:

NONRADIOACTIVE HAZARDOUS MATERIALS

| Name | EPA Code | Quantity (*g*) |
|---|---|---|
| None | | |

Accumulation Start Date (*MMDDYY*)

*The data in this section were collected, and the waste described herein was packaged and labeled according to approved procedures.*

Name [redacted] Znumber [redacted] Date DEC 8 1998

3. GENERATOR SITE HEALTH PHYSICS INFORMATION

| | | Survey Date | Survey Meter Model | Property | Calibration Void Date |
|---|---|---|---|---|---|
| Gamma Dose Rate (*mrem/h*) (contact) | 4.2E+0 | DEC 8 1998 | RO20 | 006469 | APR 14 1999 |
| Neutron Dose Rate (*mrem/h*) (contact) | 5.0E-1 | DEC 8 1998 | PNR-4 | Property Number 004904 | APR 28 1999 |
| Total Dose Rate (*mrem/h*) (contact) | 4.7E+0 | | | | |
| Total Dose Rate (*mrem/h*) (1 meter) | 2.0E-1 | | | | |
| Alpha Contamination (*dpm/100cm*$^2$) (*rem*) | 0.0E+0 | | | | |
| Beta-Gamma Cont. (*dpm/100cm*$^2$) (*rem*) | 0.0E+0 | | | | |

*The data in this section were collected according to approved procedures.*

Name

Znumber [redacted] Date DEC 8 1998

Form 1562E (7/97) Printed FEB 12 99 11:04:08 by Page 1 of 2

Modifications to Computer Generated Data Invalidate this Form

Controlled
Copy



Figure 6. Example Generator Container Specific Documentation (Continued)

Los Alamos
NATIONAL LABORATORY

DISCARDABLE WASTE
LOG SHEET

| Item ID | Matrix | Pkg Wt (kg) | Qty | Volume (l) | MT | SNM(g) | Uncert(g) | Pg/Section/Ln OR Memo |
|---|---|---|---|---|---|---|---|---|
| [redacted] | Metal (Non-Pu Scrap) | 8.49 | | | 52 | 10.697 | 1.558 | 8/14 |
| | Metal (Non-Pu Scrap) | 3.18 | | | 52 | 0.760 | 0.480 | 8/14 |
| | Metal (Non-Pu Scrap) | 10.28 | | | 52 | 0.775 | 0.423 | 8/14 |
| | Metal (Non-Pu Scrap) | 5.05 | | | 52 | 0.635 | 0.329 | 8/14 |
| | Metal (Non-Pu Scrap) | 23.42 | | | 52 | 1.035 | 0.290 | 8/14 |
| | Metal (Non-Pu Scrap) | 20.94 | | | 52 | 21.226 | 0.725 | 8/14 |
| | MgO Crucible (Chloride) | 0.59 | | | 52 | 1.901 | 0.026 | 8/21 |
| | MgO Crucible (Chloride) | 0.64 | | | 52 | 3.366 | 0.033 | 8/21 |

| MT | Total SNM | Total Uncert |
|---|---|---|
| 52 | 40.395000 | 3.784000 |

| | |
|---|---|
| Total Pkg Wt (lbs) | 160.03 |
| Drum Tare (lbs) | 60.96 |
| Calc Gross Wt (lbs) | 220.99 |
| Meas Gross Wt (lbs) | 221.08 |

Controlled
Copy



Figure 6. Example Generator Container Specific Documentation (Continued)

## TRU Waste Origination & Disposition Information

| | | | | | | |
|---|---|---|---|---|---|---|
| Itemid [redacted] | | Matrix Metal (Non-Pu Scrap) | | | | Date NOV 19 1998 |
| Quantity | Gross Wt (kg) 7.50 | Tare Wt | Net Wt (kg) 7.50 | Volume (l) | | Process Status BM |
| Generator | | | | Znumber [redacted] | Room 208 | Phone 7-2547 |
| Waste Process Solid Waste Processing | | Assay NDA Laboratory | | Combined into | Drumid LA00000057745 | |

| | | | | | |
|---|---|---|---|---|---|
| Beryllium | NO | Explosives | NO | PCB's | NO |
| Compressed Gases | NO | Free Liquids | NO | Particulates | NO |
| Corrosive | NO | Hazardous | NO | Pyrophorics | NO |

Comments
bagout filter#249

### Assay Information

| Isotope | MT | SNM (g) | Uncert (g) | Mcode | Limit | SNM (g)/unit | Date | By |
|---|---|---|---|---|---|---|---|---|
| PU-239 | 52 | 10.697000 | 1.558000 | N02 | 3.31 | 1.426 | NOV 24 1998 | |

### Justification Memos

| Memo ID |
|---|
| NONE |

### Hazardous Materials

| EPA Code | Material | Wt (g) |
|---|---|---|
| NONE | | |

### History

| Date | Name | Event | | Comments |
|---|---|---|---|---|
| NOV 19 1998 | | CERTIFIED | | |
| NOV 24 1998 | | PACKED | LA00000057745 | |
| NOV 24 1998 | | CERTIFIED | added bagout filter # | |

Figure 6. Example Generator Container Specific Documentation (Continued)

## TRU Waste Origination & Disposition Information

| | | | | | | |
|---|---|---|---|---|---|---|
| Itemid [redacted] | | Matrix Metal (Non-Pu Scrap) | | | | Date NOV 23 1998 |
| Quantity | Gross Wt (kg) 2.80 | Tare Wt | Net Wt (kg) 2.80 | Volume (l) | | Process Status EOC |
| Generator | | | | Znumber [redacted] | Room 208 | Phone 7-2547 |
| Waste Process Solid Waste Processing | | Assay NDA Laboratory | | Combined into | | Drumid LA00000057745 |

| | | | | | |
|---|---|---|---|---|---|
| Beryllium | NO | Explosives | NO | PCB's | NO |
| Compressed Gases | NO | Free Liquids | NO | Particulates | NO |
| Corrosive | NO | Hazardous | NO | Pyrophorics | NO |

Comments
scrap metal Filter 497

### Assay Information

| Isotope | MT | SNM (g) | Uncert (g) | Mcode | Limit | SNM (g)/unit | Date | By |
|---|---|---|---|---|---|---|---|---|
| PU-239 | 52 | 0.760000 | 0.400000 | N02 | 3.31 | 0.271 | NOV 30 1998 | |

### Justification Memos

| Memo ID |
|---|
| NONE |

### Hazardous Materials

| EPA Code | Material | Wt (g) |
|---|---|---|
| NONE | | |

### History

| Date | Name | Event | | Comments |
|---|---|---|---|---|
| NOV 23 1998 | | CERTIFIED | | |
| DEC 1 1998 | | PACKED | LA00000057745 | |
| DEC 1 1998 | | CERTIFIED | add fil | |

Controlled
Copy



Figure 6. Example Generator Container Specific Documentation (Continued)

## TRU Waste Origination & Disposition Information

| | | | | | |
|---|---|---|---|---|---|
| Itemid [redacted] | Matrix Metal (Non-Pu Scrap) | | | | Date NOV 23 1998 |
| Quantity / Gross Wt (kg) 4.64 | Tare Wt | Net Wt (kg) 4.64 | Volume (l) | | Process Status OM |
| Generator | | | Znumber [redacted] | Room 126 | Phone 7-2370 |
| Waste Process Solid Waste Processing | Assay NDA Laboratory | | Combined into | Drumid LA00000057745 | |

| | | | | | |
|---|---|---|---|---|---|
| Beryllium | NO | Explosives | NO | PCB's | NO |
| Compressed Gases | NO | Free Liquids | NO | Particulates | NO |
| Corrosive | NO | Hazardous | NO | Pyrophorics | NO |

Comments
balance parts bagout filter#318

### Assay Information

| Isotope | MT | SNM (g) | Uncert (g) | Mcode | Limit | SNM (g)/unit | Date | By |
|---|---|---|---|---|---|---|---|---|
| PU-239 | 52 | 0.635000 | 0.329000 | N02 | 3.31 | 0.137 | DEC 1 1998 | |

### Justification Memos

| Memo ID |
|---|
| NONE |

### Hazardous Materials

| EPA Code | Material | Wt (g) |
|---|---|---|
| NONE | | |

### History

| Date | Name | Event | Comments |
|---|---|---|---|
| NOV 23 1998 | | CERTIFIED | |
| DEC 2 1998 | | PACKED | LA00000057745 |
| DEC 2 1998 | | CERTIFIED | added bagout filter # |

Controlled
Copy



Figure 6. Example Generator Container Specific Documentation (Continued)

## TRU Waste Origination & Disposition Information

| Itemid | Matrix | | | | Date |
|---|---|---|---|---|---|
| [redacted] | Metal (Non-Pu Scrap) | | | | NOV 17 1998 |
| 20.59 | Tare Wt | Net Wt (kg) 20.59 | Volume (l) | | Process Status TIGR |
| Generator | | | [redacted] | Room 114 | Phone 5-6161 |
| Waste Process Solid Waste Processing | Assay NDA Laboratory | | Combined into | Drumid LA00000057745 | |

| | | | | | |
|---|---|---|---|---|---|
| Beryllium | NO | Explosives | NO | PCB's | NO |
| Compressed Gases | NO | Free Liquids | NO | Particulates | NO |
| Corrosive | NO | Hazardous | NO | Pyrophorics | NO |

Comments
copper tubing and furnace parts filter 230,234

### Assay Information

| Isotope | MT | SNM (g) | Uncert (g) | Mcode | Limit | SNM (g)/unit | Date | By |
|---|---|---|---|---|---|---|---|---|
| PU-239 | 52 | 1.035000 | 0.290000 | N02 | 3.31 | 0.050 | NOV 23 1998 | |

### Justification Memos

| Memo ID |
|---|
| NONE |

### Hazardous Materials

| EPA Code | Material | Wt (g) |
|---|---|---|
| NONE | | |

### History

| Date | Name | Event | Comments |
|---|---|---|---|
| NOV 17 1998 | | CERTIFIED | |
| NOV 23 1998 | | PACKED | LA00000057745 |
| NOV 23 1998 | | CERTIFIED | add filter |

Printed FEB 12 00 11:04:04 by BUSTAMANTE LM

Controlled
Copy



Figure 6. Example Generator Container Specific Documentation (Continued)

# TRU Waste Origination & Disposition Information

| | | | | | |
|---|---|---|---|---|---|
| Tremid [redacted] | Matrix Metal (Non-Pu Scrap) | | | | Date NOV 17 1998 |
| Quantity | Gross Wt (kg) 20.04 | Tare Wt | Net Wt (kg) 20.04 | Volume (l) | Process Status XO |
| Generator | | | Znumber [redacted] | Room 401 | Phone 7-2572 |
| Waste Process Solid Waste Processing | | Assay NDA Laboratory | Combined into | | Drumid LA00000057745 |

| | | |
|---|---|---|
| Beryllium NO | Explosives NO | PCB's NO |
| Compressed Gases NO | Free Liquids NO | Particulates NO |
| Corrosive NO | Hazardous NO | Pyrophorics NO |

Comments
parts from furnaces, motors, pumps bagout filter #90,167

## Assay Information

| Isotope | MT | SNM (g) | Uncert (g) | Mcode | Limit | SNM (g)/unit | Date | By |
|---|---|---|---|---|---|---|---|---|
| PU-239 | 52 | 21.226000 | 0.725000 | N02 | 3.31 | 1.059 | NOV 30 1998 | |

## Justification Memos

| Memo ID |
|---|
| NONE |

## Hazardous Materials

| EPA Code | Material | Wt (g) |
|---|---|---|
| NONE | | |

## History

| Date | Name | Event | | Comments |
|---|---|---|---|---|
| NOV 18 1998 | | CERTIFIED | | |
| DEC 2 1998 | | PACKED | LA00000057745 | |
| DEC 2 1998 | | CERTIFIED | | |
| DEC 2 1998 | | CERTIFIED | updated gross wt | |

Controlled
Copy



Figure 6. Example Generator Container Specific Documentation (Continued)

## TRU Waste Origination & Disposition Information

| | | | | | |
|---|---|---|---|---|---|
| Itemid [redacted] | Matrix MgO Crucible (Chloride) | | | | Date JUN 3 1998 |
| Quantity | Gross Wt (kg) 0.39 | Tare Wt 0.07 | Net Wt (kg) 0.32 | Volume (l) | Process Status SS |
| Generator | | | Znumber [redacted] | Room 429 | Phone 7-2577 |
| Waste Process Solid Waste Processing | | Assay NDA Laboratory | Combined into | | Drumid LA00000057745 |

| | | |
|---|---|---|
| Beryllium NO | Explosives NO | PCB's NO |
| Compressed Gases NO | Free Liquids NO | Particulates NO |
| Corrosive NO | Hazardous NO | Pyrophorics NO |

Comments
changed Id. to be able to discard, caxbl1035 No filter #s legacy item

### Assay Information

| Isotope | MT | SNM (g) | Uncert (g) | Mcode | Limit | SNM (g)/unit | Date | By |
|---|---|---|---|---|---|---|---|---|
| PU-239 | 52 | 1.901000 | 0.026000 | PAN1 | 8.30 | 5.941 | JUN 9 1998 | |

### Justification Memos

| Memo ID |
|---|
| NONE |

### Hazardous Materials

| EPA Code | Material | Wt (g) |
|---|---|---|
| NONE | | |

### History

| Date | Name | Event | | Comments |
|---|---|---|---|---|
| JUN 9 1998 | | CERTIFIED | | |
| JUN 9 1998 | | PACKED | LA00000056889 | |
| JUN 9 1998 | | CERTIFIED | | |
| SEP 29 1998 | | UNPACKED | LA00000056889 | |
| SEP 29 1998 | | CERTIFIED | | |
| SEP 29 1998 | | PACKED | LA00000056889 | |
| SEP 29 1998 | | CERTIFIED | cert | |
| NOV 24 1998 | | UNPACKED | LA00000056889 | |
| NOV 24 1998 | | PACKED | LA00000057745 | |

Controlled
Copy



Figure 6. Example Generator Container Specific Documentation (Continued)

## TRU Waste Origination & Disposition Information

| | | | | | | |
|---|---|---|---|---|---|---|
| Tremid [redacted] | Matrix MgO Crucible (Chloride) | | | | | Date JUN 3 1998 |
| Quantity | Gross Wt (kg) 0.55 | Tare Wt 0.05 | Net Wt (kg) 0.50 | Volume (l) | | Process Status SS |
| Generator | | | | Znumber [redacted] | Room 429 | Phone 7-2577 |
| Waste Process Solid Waste Processing | | Assay NDA Laboratory | | Combined into | | Drumid LA00000057745 |

| | | |
|---|---|---|
| Beryllium NO | Explosives NO | PCB's NO |
| Compressed Gases NO | Free Liquids NO | Particulates NO |
| Corrosive NO | Hazardous NO | Pyrophorics NO |

Comments
changed id to be able to discard, caxbl17-98 No filter #s legacy item

### Assay Information

| Isotope | MT | SNM (g) | Uncert (g) | Mcode | Limit | SNM (g)/unit | Date | By |
|---|---|---|---|---|---|---|---|---|
| PU-239 | 52 | 3.366000 | 0.033000 | PAN1 | 8.30 | 6.732 | JUN 1 1998 | |

### Justification Memos

| Memo ID |
|---|
| NONE |

### Hazardous Materials

| EPA Code | Material | Wt (g) |
|---|---|---|
| NONE | | |

### History

| Date | Name | Event | | Comments |
|---|---|---|---|---|
| JUN 9 1998 | | CERTIFIED | | |
| JUN 9 1998 | | PACKED | LA00000056889 | |
| JUN 9 1998 | | CERTIFIED | | |
| SEP 29 1998 | | UNPACKED | LA00000056889 | |
| SEP 29 1998 | | PACKED | LA00000056889 | |
| SEP 29 1998 | | UNPACKED | LA00000056889 | |
| SEP 29 1998 | | CERTIFIED | | |
| SEP 29 1998 | | PACKED | LA00000056889 | |
| SEP 29 1998 | | CERTIFIED | cert | |
| NOV 24 1998 | | UNPACKED | LA00000056889 | |
| NOV 24 1998 | | PACKED | LA00000057745 | |

Printed FEB 12 99 11:04:06 by RUSTAMANTE LM

Figure 6. Example Generator Container Specific Documentation (Continued)

Figure 6. Example Generator Container Specific Documentation (Continued)



Figure 6. Example Generator Container Specific Documentation (Continued)



Figure 6. Example Generator Container Specific Documentation (Continued)



Figure 6. Example Generator Container Specific Documentation (Continued)



Figure 6. Example Generator Container Specific Documentation (Continued)



Figure 6. Example Generator Container Specific Documentation (Continued)



Controlled
Copy



Figure 6. Example Generator Container Specific Documentation (Continued)

HEALTH-SAFETY-ENVIRONMENT FORM

LOS ALAMOS SCIENTIFIC LABORATORY

DATE

CHEMICAL WASTE DISPOSAL REQUEST

REQUESTED BY _____ PHONE _____

GROUP _____ LOCATION: TA-_____ BLDG. _____ AREA/WING _____ ROOM _____

WASTE VOLUME ($ft^3$) _____

NUMBER OF CONTAINERS (SIZE/TYPE) _____

WASTE FORM (check as appropriate):

☐ SOLID ☐ LIQUID ☐ GAS

COMMON NAMES OF CHEMICALS: _____

POTENTIAL HAZARDS (check as appropriate):

CORROSIVES ☐ Acids ____strong ____mild ____weak
☐ Bases ____strong ____mild ____weak

☐ FLAMMABLE ☐ TOXIC ☐ OTHER:
☐ EXPLOSIVE ☐ CARCINOGEN _____
☐ PYROPHORIC ☐ INFECTIOUS _____
☐ OIL ☐ UNKNOWN _____

CAN MATERIALS REACT VIOLENTLY WHEN EXPOSED TO:

AIR _____ WATER _____ OTHER CHEMICALS _____

If yes, give details: _____

OTHER USEFUL INFORMATION: _____

(TO BE COMPLETED BY H-7)

DISPOSAL RECORD

AREA _____ PIT/SHAFT _____ DATE _____ BY _____

MAIL THIS FORM TO WASTE MANAGEMENT, H-7, MS-~~[illegible]~~ 516

6/80 HS&E 7-5A

Figure 7. Process Flow Diagram for Nitrate Operations (Legacy)



Figure 8. Process Flow Diagram for Nitrate Operations (Newly Generated)




Nitrate Processing Flow Diagram

Figure 9. Simplified Process Flow Diagram for Miscellaneous Operations (Legacy)



Figure 10. Simplified Process Flow Diagram for Miscellaneous Operations (Newly Generated)




Miscellaneous Operations Flow Diagram

Controlled
Copy



Figure 11. Simplified Process Flow Diagram for Special Processing (Legacy)



Figure 12. Simplified Process Flow Diagram for Special Operations (Newly Generated)




Special Operations Flow Diagram

Figure 13. Simplified Process Flow Diagram for Metal Operations (Legacy)




**NOTE:** All of these P/S codes may obtain feed material from or send product output to the vault.

Figure 13. Simplified Process Flow Diagram for Metal Operations (Legacy) (Continued)




**NOTE:** All of these P/S codes may obtain feed material from or send product output to the vault.

**NOTE:** P/S code UA tracks uranium compounds from Pit Disassembly. Activities under this P/S code would be similar to those under P/S codes IN, MW, and WE.

Figure 13. Simplified Process Flow Diagram for Metal Operations (Legacy) (Continued)




In 1988, P/S codes CO, GI, ID, OB, and RS were combined into P/S code FF. P/S codes CT, ID, and OM are status codes only, and probably do not generate TRU waste.




**NOTE:** All of these P/S codes may obtain feed material from or send product output to the vault.

Figure 14. Simplified Process Flow Diagram for Metal Operations (Newly Generated)



Controlled
Copy



Figure 15. Simplified Process Flow Diagram for Pyrochemical Operations (Legacy)

**SIMPLIFIED PROCESS FLOW DIAGRAM
FOR PYROCHEMICAL PROCESSES
(LEGACY)**



Figure 16. Simplified Process Flow Diagram for Chloride Operations (Legacy)




NOTE: Many of the P/S Codes for chloride operations involve more than one step or activity in the flow diagram. Thus, the same P/S Code can appear in more than one box on the flow diagram.

Figure 17. Simplified Process Flow Diagram for Pyrochemical and Chloride Operations (Newly Generated)




Pyrochemical/Chloride Processing Flow Diagram

Controlled
Copy



Figure 18. Simplified Process Flow Diagram for Pu-238 Operations (Legacy)



Controlled
Copy



Figure 18. Simplified Process Flow Diagram for Pu-238 Operations (Legacy) (Continued)



Figure 18. Simplified Process Flow Diagram for Pu-238 Operations (Legacy) (Continued)



Controlled
Copy



Figure 19. Simplified Process Flow Diagram for Pu-238 Operations (Newly Generated)




Pu-238 Operations Flow Diagram

Controlled
Copy



Figure 20. Waste Repackaging and Prohibited Item Disposition Flow Diagram



Figure 21. Below-Grade Drum Retrieval Flow Diagram



Figure 22. Below-Grade Crate Retrieval Flow Diagram



**Attachment 3**

LANL-Carlsbad Office Difficult Waste Team (DWT)

Amount of Zeolite Required to Meet the Constraints Established by the EMRTC Report RF 10-13: Application to LANL Evaporator Nitrate Salts, May 8, 2012

LA-UR-14-26860

# Amount of Zeolite Required to Meet the Constraints Established by the EMRTC Report RF 10-13: Application to LANL Evaporator Nitrate Salts

**5/8/2012**

LANL-Carlsbad Office Difficult Waste Team

Purpose:

The following document was developed in support of the Los Alamos National Laboratory Transuranic Program (LTP) by the LANL-Carlsbad Office, Difficult Waste Team. The document is divided into five sections, with the section on conclusions provided first, followed by background, assumptions, discussion, and recommendation.

## Conclusions:

1. Nitrate salts not yet remediated having no free liquid should be mixed with at least 1.2 volumes of Kitty Litter/Zeolite clay per volume of nitrate salts. For operational efficiency at WCRRF (rule-of-thumb) for every gallon of nitrate salt present the addition of two (2) gallons of zeolite/kitty litter may be added to help ensure the final mixture meets or exceeds EMRTC testing constraints.
2. Nitrate salts not yet remediated but having free liquids should be mixed with at least 1.2 volumes of Kitty Litter/Zeolite clay per composite volume of nitrate salt and liquid.[1] Ensure that no free liquid remains. For operational efficiency at WCRRF (rule-of-thumb) for every gallon of nitrate salt present the addition of two (2) gallons of zeolite/kitty litter may be added to help ensure the final mixture meets or exceeds EMRTC testing constraints.
3. Nitrate Salts previously remediated with Waste Lock 770® should be mixed with at least 1.2 volumes of Kitty Litter/Zeolite clay per composite volume of nitrate salt, absorbed liquid and Waste Lock 770®. For operational efficiency at WCRRF (rule-of-thumb) for every gallon of nitrate salt present the addition of two (2) gallons of zeolite/kitty litter may be added to help ensure the final mixture meets or exceeds EMRTC testing constraints.

## Background:

Nitrates salts from evaporator operations at TA55 were packaged (up to around 1991) primarily in plastic bags and ranged in moisture content up to saturation (generator knowledge states the salts were "cursorily drained of liquid").[2] Visual review by WCRRF operators of nitrate salts brought to WCRRF for remediation showed that almost all of

[1] When free liquids are readily apparent, the use of a "fired zeolite clay" product may be more efficient in holding free liquids than non-fired (e.g., ordinary kitty litter). The following are examples only of some fired zeolites and no endorsement is made for any of the examples given: Oil-Dry QuickSorb1™, ZeoFill™, or Zeolit™.
[2] Email Gerald W. Veazey to Randy Fitzgerald, August 9, 2011, subject: *"RE: Information on 47 Drums of Suspect Nitrate Evaporator Salts (from TA-55)".*

evaporator salt drums had free liquids (as much as 12 gallons) or the salt itself appeared quite wet. As a result, the LANL TRU Program (LTP) added Waste Lock 770[3] ® as an absorbent to the free liquids and wet salt. In some cases several 50-pound bags of Waste Lock 770® were used to absorb the volume of free liquid present in a drum.[4] Neither the volume nor weight of Waste Lock 770® added to drums or POCs was recorded for the remedial nitrate salt actions taken at WCRRF.

Nitrate salts brought into WCRRF for remediation were not weighed nor were their volumes estimated. Salts that did not have free liquids were not mixed with Waste Lock 770®. A surface dose rate was taken directly on these nitrate salts and if the reading was >180 mrem/hr the salts were packaged into a 12" Pipe Overpack Container (POC). Nitrate salts having free liquids with surface dose rates > 180 mrem/hr were packaged into 12" POCs with Waste Lock 770®.

Currently, there are four (4) basic categories of evaporator nitrate salts identified by LTP in Solution Package - SP 72:

1. Non-remediated salts without free liquids, that may or may not have lead shielding
2. Non-remediated salts with free liquids, that may or may not have lead shielding
3. Salts repackaged into drums or POCs that did not have free liquids (no Waste Lock 770® added)
4. Remediated salts repackaged into drums or POCs that did have free liquids (Waste Lock 770® has been added)

The Energetic Materials Research and Testing Center (EMRTC)[5] operating in conjunction with LANL-Carlsbad Office and Washington TRU Solutions previously tested the most oxidizing mixture of sodium and potassium nitrate salts mixed with zeolite or grout. The results of EMRTC[6] testing established the concentration at which the most reactive mixture of sodium and potassium nitrate becomes a non-oxidizer when mixed with either zeolite or grout. The results apply to LANL non-cemented nitrate salts. Accordingly, the application of the constraints established by EMRTC to the LANL evaporator nitrate salts, with certain bounding assumptions, provides sufficient information for the WIPP to affirm

[3] http://www.m2polymer.com/html/waste_lock_770.html. "[A] solid, granular superabsorbent polymer [that is] cross-linked polyacrylate material [that] swells and absorbs many times its weight in aqueous solutions…suited for the absorption and solidification of low level radioactive waste (LLRW)." Waste Lock 770®has a bulk density of 5.4 – 6.0 lbs/gal., for use in solutions with pH>4 (pH adjustment is recommended for pH4 or less).

[4] Oral communication with Energy Solutions WCRRF operations manager regarding the amount of Waste Lock 770® needed to absorb free liquids in some of the evaporator nitrate salts drums remediated at WCRRF.

[5] EMRTC is an approved examining agency (DOT/UN Testing and Classifications) for explosives and other hazardous materials.

[6] Graham Walsh, Research Scientist, Energetic Materials Research and Testing Center, New Mexico Institute for Mining and Technology, Socorro, New Mexico (Certified DOT Testing Laboratory), "*Results of Oxidizing Solids Testing, EMRTC Report RF 10-13*" prepared for Washington TRU Solutions, LLC, March 12, 2010.

that the LANL nitrate salts, when mixed with zeolite/kitty litter, will be considered a non-oxidizing solid.

**Assumptions:**

1. Bulk density of $KNO_3$ is approximately 0.8 g/cc and the crystal density about 2 g/cc; accordingly, the assumed density for the nitrate salt is 1 g/cc.[7]
2. Bulk density of kitty litter is about 0.4 g/cc to 0.5 g/cc.[8] Kitty litter is assumed to be ½ the bulk density of the nitrate salt.
3. Nitrate salts were loaded into POCs if the surface dose rate of the bare salt was >180 mrem/hr.
4. Density of the Waste Lock 770® plus water is assumed to be 1 g/cc (Waste Lock 770® is around 0.71 g/cc but the addition of water increases the density closer to 1)[9]
5. Cellulose used in the testing is more readily oxidized than Waste Lock 770®
6. The nitrate salts themselves cannot be readily removed from the salt/Waste Lock mixture
7. Weighing the mass of previously remediated nitrate salts in the WCRRF glovebox is impractical but the volume of the remediated salts can be estimated visually or by simple measurement (measurement of depth). Therefore, at least 10% excess of zeolite will be added to account for measurement error of the volume.

**Discussion:**

The bounding ratios for zeolite from the EMRTC report are:

50 wt.% cellulose
33 wt.% of nitrate salts
18 wt.% of zeolite/kitty litter

Using the assumptions stated above these values correspond to the following bounding volume ratios:
For nitrate salts not mixed with Waste Lock 770®:

48 vol.% of nitrate salts
52 vol% of zeolite/kitty litter

[7] See Merck http://www.merckmillipore.com/is-bin/INTERSHOP.enfinity/WFS/Merck-International-Site/en_US/-/USD/ViewPDFPrint.pdf?RenderPageType=ProductDetail&CatalogCategoryID=&ProductUUID=vdab.s1OzvUAAAEWevAW4z8b&PortalCatalogUUID=6dCb.s1Lbk0AAAEWf9cfVhTl, crystal density is listed at 2.109 in the Chemical Rubber Handbook for potassium nitrate.
[8] http://www.alibaba.com/showroom/cat-litter-bulk.html
[9] See footnote 2. The density of Waste Lock 770® is around 0.71 g/cc but the absorption of water increase the final density closer to 1 g/cc.

Therefore, for every liter of nitrate salt present at least 1.2 liters of zeolite/kitty litter must be added. For operational efficiency at WCRRF (rule-of-thumb) for every gallon of nitrate salt present the addition of two (2) gallons of zeolite/kitty litter may be added to help ensure the final mixture meets or exceeds EMRTC testing constraints

For nitrate salts mixed with Waste Lock 770® there is a certain ratio of Waste Lock 770® to nitrate where less zeolite than the pure nitrate case would be necessary to result in a non-oxidizing mixture. However the ratio of Waste Lock 770® to nitrate is not known so no credit can be taken for the dilution of nitrate. Therefore, for every liter of composite nitrate salt, absorbed liquid and Waste Lock 770® present at least 1.2 liters of zeolite/kitty litter must be added. For operational efficiency at WCRRF (rule-of-thumb) for every gallon of nitrate salt present the addition of two (2) gallons of zeolite/kitty litter may be added to help ensure the final mixture meets or exceeds EMRTC testing constraints.

## Recommendation:

Actual tests at WCRRF have demonstrated a 10X reduction in dose when the salts are loaded into 55-gallon drums; therefore, some of the salts previously packaged into POCs at WCRRF were done under an overly conservative constraint and could be re-packaged into 55-gallon drums and still meet the <200 mrem/hr surface dose rate on the outside of the 55-gallon drum.