

F A X**MONTGOMERY WATSON**1475 Pine Grove Rd Suite 109
PO Box 774018
Steamboat Springs, Colorado 80477Tel: 970 879 6260
Fax: 970 879 9048**Date:** June 27, 1998**To:** Cornelius Amindyas - NMED**Reference:** 602**From:** Patrick Corser - MW**Charged Amt:** NA**Fax No:** 505-827-1544**No. of Pages:** 1
(including cover)**Subject:** Monitoring Frequency for Vadose Zone Sumps

Cornelius,

On Friday you called to confirm the monitoring frequency that would be used for the vadose zone sumps. In our response to comments, we indicated that the vadose zone sumps would be monitored whenever the primary or secondary sumps were monitored (Volume 1 - Page 3-31R). In Volume 1, Section 5, Page 5-3, it states that "During the active life of the landfill, the leachate collection and removal system (LCRS) and leak detection system (LDS) will be checked daily for the presence of liquid." Therefore, the vadose zone sump will be checked for the presence of liquid on a daily basis during active operations. *during inspection*

We hope this adequately answers your question. If you need any additional information, please contact us.

Regards,

A handwritten signature of Patrick Corser in black ink.
Patrick Corsercc: Dale Gandy 505-396-6887
Larry Gandy 505-398-6887

If you do not receive all pages, or if there are any problems with this transmission, please call 970-879-6260