

REFERENCE COPY

C.2

SANDIA REPORT

SAND91-2247 • UC-721

Unlimited Release

Printed January 1992

SAND91-2247
0002
UNCLASSIFIED

01/92
22P STAC

WIPP Small Scale Seal Performance Tests – Status and Impacts

R. E. Finley, J. R. Tillerson

Prepared by
Sandia National Laboratories
Albuquerque, New Mexico 87185 and Livermore, California 94550
for the United States Department of Energy
under Contract DE-AC04-76DP00789

920602



Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from
Office of Scientific and Technical Information
PO Box 62
Oak Ridge, TN 37831

Prices available from (615) 576-8401, FTS 626-8401

Available to the public from
National Technical Information Service
US Department of Commerce
5285 Port Royal Rd
Springfield, VA 22161

NTIS price codes
Printed copy: A03
Microfiche copy: A01

SAND91-2247
Unlimited Release
Printed January 1992

Distribution
Category UC-721

WIPP Small Scale Seal Performance
Tests - Status and Impacts

by

R. E. Finley
J. R. Tillerson
Repository Isolation Systems Division 6346
Sandia National Laboratories
Albuquerque, New Mexico

Accepted for Presentation at the
Solution Mining Research Institute (SMRI) Conference
October 28-29, 1991
Las Vegas, Nevada

* This paper has been accepted for publication in the designated conference proceedings or journal, but may differ from its present form when it is published therein.

WIPP SMALL SCALE SEAL PERFORMANCE TESTS - STATUS AND IMPACTS

by

Ray E. Finley
Joe R. Tillerson
Repository Isolation Systems Division
Sandia National Laboratories
Albuquerque, NM 87185

Abstract

Numerous small-scale in situ seal experiments have been emplaced in boreholes up to 38 in. in diameter at the WIPP. Seal materials include expansive salt concrete, bentonite, and crushed salt. Emplacement techniques stressed conventional technology and the use of available site personnel. Preliminary evaluation of the performance of these seals has been completed by using structural data from embedded instrumentation and fluid flow data from gas and brine flow measurements. Preliminary results suggest that submicrodarcy permeabilities can be obtained using these materials and that structural performance is satisfactory.

1.0 Introduction


1.1 Background

The U.S. Department of Energy is developing the Waste Isolation Pilot Plant (WIPP) facility in southeastern New Mexico to demonstrate the safe disposal of Transuranic (TRU) radioactive wastes arising from the defense activities of the United States. The WIPP waste disposal horizon lies in a bedded salt formation approximately 2150 ft (656 m) below the ground surface. The salt is interspersed with thin clay and anhydrite layers. Figure 1 is a schematic of the WIPP facility, including the locations of major underground and surface features.

1.2 Sealing Program at WIPP

The sealing program at the WIPP is intended to develop and demonstrate technology such that seals can be designed to limit the release of radionuclides to the accessible environment. Current plans call for placement of seals in panel-access drifts for the TRU waste storage areas and in the four shafts accessing the WIPP (see Figure 1). Seal materials under consideration for use at the WIPP include concrete, crushed salt for long-term seals, and swelling clays for short-term seals. Information regarding the seal designs currently planned for the WIPP is given in Nowak et al. (1990). SNL is currently planning and performing major experiments intended to provide information that can be used to support actual WIPP facility seal designs. These experiments include Thermal-Structural Interaction (TSI) Tests, Large-Scale Seal Tests, Small Scale Seal Performance Tests (SSSPT), Disturbed Rock Zone (DRZ) characterization, and brine inflow tests. This paper discusses only the SSSPT program.

The SSSPTs are in situ experiments that are intermediate in scale between full-scale in situ seal tests and laboratory tests. The SSSPTs utilize materials and geometries similar to those currently planned for



2

Legend

- Planned Surface Caps and Plugs
- Seals

TRI-6346-59-12

Figure 1. Sectional View of WIPP Facility.

large-scale seal tests and seal emplacements; however, direct comparisons between the SSSPT and full-scale seals must be carefully evaluated because many of the measurements are scale dependent. These geometries, especially those intended to simulate sealing in shafts, provide demonstrations of technologies and confirmation of in situ processes that influence seal performance. This information may be useful for sealing other openings such as boreholes accessing solution mined caverns. The primary objectives (Stormont, 1985) of the Small-Scale Seal Performance Tests are as follows:

- 1) to determine in situ fluid flow performance for various seal systems, including evaluating flow paths, the difference between gas and brine permeabilities, and size effects,
- 2) to determine in situ mechanical performance of the host rock and seal materials, including material interfaces and size effects,
- 3) to assess seal emplacement techniques, and
- 4) to support the development of numerical predictive capabilities

A considerable body of work has been completed to date. This paper summarizes selected results. Many references will cite the original work.

2.0 SSSPT Test Description


The plans for the SSSPTs were developed in 1985 and are described in detail in Stormont (1985). The SSSPTs are a series of in situ experiments designed to evaluate the performance of various candidate seal materials emplaced in boreholes from 6 in. (15.2 cm) to 38 in. (96.5 cm) in diameter. The emplacement holes are oriented both vertically into the floor and horizontally into the ribs. The seal system is comprised of the seal, seal/rock interface, and the rock adjacent to the seal. Table 1 briefly describes the SSSPTs conducted to date, including a description of the primary seal material, orientation, and types of measurements made. In addition, all of the various test series utilize a similar test configuration. Figure 2 shows generalized configurations for the test series conducted to date (see Table 1). In general, an emplacement hole and an access hole (if used) are drilled either in the rib or floor of the opening. The seal material, in some cases containing instrumentation, is emplaced over a predetermined interval in the emplacement hole. A four packer fracture flow tool (FPFFT) capable of using brine or gas can be placed in the access hole (where used), and the interval beneath the seal can be pressurized for fluid flow measurements.

The emplacement techniques employed in the SSSPT test program emphasized conventional technology and the use of available personnel at the WIPP site. The seal materials used in the SSSPTs include expansive salt-based concrete, and blocks compressed from 100% crushed salt, 50/50% crushed salt/bentonite, and 100% bentonite. The blocks were pressed into workable sizes using a modified adobe block making machine (Sandia block machine) (Stormont and Howard, 1987). The manufacture and emplacement of the seal materials for each of the test series were accomplished without major difficulty, although placement of the expansive salt based concrete (SSSPT-A, SSSPT-B) required the use of chilled water and retarding admixture (sodium citrate) to maintain workability during transport underground. In addition, optimization studies to determine the most durable blocks were performed prior to the manufacture of crushed salt blocks (SSSPT-C Phase 1, SSSPT-D Phase 1), 50/50% salt bentonite blocks (SSSPT-C Phase 1), and 100% bentonite blocks (SSSPT-C Phase 2, SSSPT-D Phase 2).

3.0 Test Results

Test results for the SSSPT program are discussed in terms of the material used in the seal. The SSSPT program provides both operational information (relating to construction and materials) and performance information (relating to system response). The operational information is of a qualitative nature, whereas the performance information is obtained from direct measurements such as hole closure or gas and brine flow.

The emplacement of seals with embedded instrumentation added complexity to relatively simple seal designs. For instance, embedded instrumentation requires cabling to the surface for data acquisition. The cabling presents a potential pathway through the seal during gas and brine testing. Many of the seals tested in test series A and B showed obvious leakage along the instrumentation cable bundle when



TRI-6346-205-0

Figure 2. Generalized Test Configurations.

TABLE 1. TEST SERIES CURRENTLY PLANNED FOR SSSPT				
Test Series	Seal Material	Seal Emplacement Orientation	Emplacement Date	Measurements*
A	Salt-Based Concrete	Vertical	7/85	Seal Pressure; Displacement and Temperature; Gas and Brine Flow
B	Salt-Based Concrete	Horizontal	2/86	Seal Pressure; Gas and Brine Flow
C Phase 1	Salt and 50/50% Salt/Bentonite Block	Horizontal	9/86	Seal Pressure; Brine Flow
C Phase 2	Bentonite Block	Horizontal	12/90	Seal Pressure; Brine flow
D Phase 1	Salt Block	Vertical	1/88	Seal Pressure; Hole Closure; Floor Heave; Gas Flow
D Phase 2	Bentonite Block (short-term)	Vertical	9/89	Seal Pressure; Brine Flow

* Note: Instruments include strain gages, stress meters, thermocouples, pressure cells, borehole displacement gages, Multiple Point Borehole Extensometers (MPBX), and the Four Packer Fracture Flow Tool (FPFFT) for fluid flow measurements.

permeability testing was performed (Peterson et al., 1987). As a result, later test series included uninstrumented seals to evaluate the influence of instrumentation on seal performance.

EXPANSIVE SALT CONCRETE SEALS


SSSPT Series A and B utilized nine emplacement holes located in the floor of the D Room Alcove and in the west rib of Room M. The seal material, an expansive salt concrete developed for SNL by Waterways Experiment Station (WES) (Wakeley and Walley, 1986), was underlain by crushed salt. The aspect ratio of the seal ranged between 2:1 to 1:1. Key results from the expansive salt concrete seal tests are as follows:

EMPLACEMENT

- Emplacement of expansive salt concrete seals was successfully demonstrated as evidenced by the emplacement of nine seals in vertical and horizontal orientations using standard equipment and personnel (Stormont, 1986; Stormont and Howard, 1987)
- Standard commercial equipment and techniques were used successfully for vertical and horizontal emplacements (Stormont, 1986; Stormont and Howard, 1986)
- Concrete met emplacement criteria for slump, limited bleed, segregation, limited air entrapment, self-leveling behavior, and workability (Stormont, 1986; Stormont and Howard, 1986)

PERFORMANCE

- Submicrodarcy initial permeability was measured during brine flow testing (Peterson et al., 1987)
- A reduction in flow path size was observed by a decrease in tracer arrival times measured within a year of seal emplacement (Peterson et al., 1987)
- Brine flow rates of about 200 ml/day (Figure 3) corresponding to submicrodarcy permeabilities were measured for 91-cm-diameter seals (Peterson et al., 1987)



TRI-6346-204-0

Figure 3. Comparison of Typical Brine Flow Data from SSSPT Seals.

- Structural performance of the expansive salt concrete seals was satisfactory as evidenced by the seals withstanding 1.8 MPa back pressure during brine flow testing (Stormont, 1987; Van Sambeek and Stormont, 1987; Labreche and Van Sambeek, 1988)
- The expansivity of the concrete (0.12% in the lab) provided a sufficient interface between the seal and the rock to limit fluid flow at early times (Wakeley and Walley, 1986; Peterson et al., 1987; Stormont, 1987)
- There was little evidence of thermal cracking of the concrete during cooling (Stormont, 1987)
- Thermomechanical data during early times agreed well with numerical modeling predictions, however, questions remain as our ability to predict mechanical behavior and the interactions with the surrounding salt at later times (Labreche and Van Sambeek, 1988)

100% BENTONITE BLOCKS

SSSPT-C Phase 2 and SSSPT-D Phase 2 utilize four seals constructed using blocks of 100% bentonite pressed in the Sandia block machine (Stormont and Howard, 1987). The blocks were arranged in the seals in a manner that would minimize the potential for flow along a continuous interface. Key results from the 100% compressed bentonite block seal tests are as follows:

EMPLACEMENT

- Emplacement of 100% bentonite blocks in vertical and horizontal boreholes was successfully demonstrated by the completion of four seals in a confined space although construction was very labor intensive (Torres, 1987; Torres and Howard, 1989; Torres et al., in prep)
- High density (80% of intact bentonite) durable blocks could be consistently fabricated using modified available technology (Torres and Howard, 1990)
- Seal density of >75% of intact bentonite density can be achieved in a 3-ft bentonite core (Torres and Howard, 1990)

PERFORMANCE

- Microdarcy permeability was measured after about two months of brine testing
- The only 100% bentonite seal tested showed a marked decrease in brine flow due to bentonite swelling from about 1800 cc/day to about 20 cc/day after 150 days of testing (see Figure 3) (Torres and Howard, 1990)
- Pressure measurements show a roughly twofold increase in seal pressure after about 300 days of brine testing up to values near 0.7 MPa (Torres and Howard, 1989)

50/50% SALT/BENTONITE SEALS

SSSPT-C Phase 1 utilized blocks comprised of a mixture of 50% crushed salt and 50% bentonite. The blocks were laid so as to minimize the potential for flow along a continuous joint. Key results from the 50/50% salt bentonite block seals are as follows:

EMPLACEMENT

- Emplacement of 50/50% crushed salt/bentonite block seals in horizontal boreholes was successfully demonstrated by the completion of five seals in a confined space although construction was very labor intensive (Stormont and Howard, 1987)
- High density (>77% of salt/bentonite intact density) durable blocks of 50/50% crushed salt/bentonite could be consistently fabricated using modified available technology (Stormont and Howard, 1987)

PERFORMANCE

- Millidarcy permeability was measured after about 6 months of brine testing (Torres and Howard, 1989)
- The brine flow results for the two 50/50 salt/bentonite seals indicate a flow of about 250 ml/day after about 250 days (see Figure 3) (Torres and Howard, 1989)

- Structural measurements (Stormont and Howard, 1987) suggest that the salt/bentonite block seals do not behave significantly differently than do 100% salt block seals over the time periods discussed
- Long-term permeability of the seal can possibly be tailored using different proportions of materials

An additional emplacement-related observation is that one of the 50/50% salt/bentonite seals emplaced for SSSPT-C Phase 1 failed by piping as a result of adding brine too rapidly. The rapid brine input did not allow the bentonite adequate time to take up water and swell to effectively seal potential flow paths. This seal failure was not related to instrumentation cabling. The seal was dismantled, inspected, and replaced. Subsequent slow input brine testing did not result in a piping failure (Stormont and Howard, 1987).

100% CRUSHED SALT BLOCK SEALS

SSSPT Series C Phase 1 and Series D Phase 1 utilized seven seals: four horizontally emplaced and three vertically emplaced. The seals were constructed using blocks of 100% crushed salt pressed in the Sandia block machine. The blocks were arranged in the seals to minimize the potential for flow along a continuous joint. Key results of the 100% salt block seals are as follows:

EMPLACEMENT

- Emplacement of 100% crushed salt block seals in vertical and horizontal boreholes was successfully demonstrated in seven seals in a confined space although construction is very labor intensive (Torres et al., in prep; Torres, 1987; Stormont and Howard, 1987)
- High density (>82% intact salt) durable blocks of 100% crushed salt could be consistently fabricated using modified available technology (Stormont and Howard, 1987)
- Tamped-in-place crushed salt can be emplaced to >75% of host rock density, suggesting a possible alternative to block seals (Howard, 1988)

PERFORMANCE OF 100% CRUSHED BLOCK SEALS

- Gas flowrate within a few months after seal emplacement exceeded the measuring capability of the equipment (Torres et al., in prep).
- Structural measurements including seal pressure and borehole displacements agree with laboratory and modeling predictions that the crushed salt seals will provide little resistance to closure and little resistance to flow until the crushed salt has achieved 90 - 95% of the intact salt density (Holcomb and Shields, 1987; Sjaardema and Krieg, 1987)

4.0 Discussion

The Small Scale Seal Performance Tests have provided preliminary information on the performance of expansive salt concretes, crushed salt, crushed salt/bentonite mixtures, and 100% bentonite as seal materials for the Waste Isolation Pilot Plant. Seals using these materials have been successfully constructed and emplaced with conventional technology and available personnel at the WIPP. The preliminary results suggest that expansive salt concretes and bentonite seals can provide seals against brine flow during early time periods, with permeabilities in the microdarcy range. The performance of 50/50% crushed salt/bentonite mixtures is inconclusive at this time; however permeabilities in the millidarcy range have been achieved. Crushed salt seals have been successfully emplaced and are currently being monitored to evaluate the long-term behavior of such seal materials for the WIPP. Information obtained to date does not contradict laboratory and modeling predictions that crushed salt must reconsolidate to 90 - 95% of the in situ density before significant reduction in fluid flow and resistance to closure occur.

The impacts of the SSSPTs on the sealing program at the WIPP are significant. The SSSPTs have provided critical information on seal materials and performance that has been used in the development of preliminary designs for the WIPP seals. The SSSPTs have also identified limitations of our knowledge of seal material performance. For instance, it is not clear from the SSSPTs whether thermal strains from cooling will induce fractures in larger expansive salt concrete seals that may be used in the WIPP. Also,

test durations for the SSSPTs are so short that longer term behavior of the seal materials is unknown. Future goals for the SSSPT program will be to address these issues. It is clear that the existing SSSPT seals should be retested to evaluate time dependence on the seal performance.

5.0 References

- Holcomb, D.J., and Shields, M., 1987, "Hydrostatic Creep Consolidation of Crushed Salt with Added Water," SAND87-1990, Sandia National Laboratories, Albuquerque, NM.
- Howard, C.L., 1988, "Laboratory Compaction Tests of WIPP Site Crushed Salt," Memo to Distribution, July 15, 1988.
- Labreche, D.A., and Van Sambeek, L.L., 1988, "Analysis Of Data from Expansive Salt-Water Concrete Seals in Series B Small-Scale Seal Performance Tests, SAND87-7155, Sandia National Laboratories, Albuquerque, NM, April 1988.
- Nowak, E.J., Tillerson, J.R., and Torres, T.M., 1990, "Initial Reference Seal System Design: Waste Isolation Pilot Plant," SAND90-0355, Sandia National Laboratories, Albuquerque, NM, May 1990.
- Peterson, E.W., Lagus, P.L., and Lie, K., 1987, "Fluid Flow Measurements of Test Series A and B for the Small Scale Seal Performance Tests," SAND87-7041, Sandia National Laboratories, Albuquerque, NM, Dec. 1987.
- Sjaardema, G.D., and Krieg, R.D., 1987, "A Constitutive Model for the Consolidation of WIPP Crushed Salt and Its Use in Analyses of Backfilled Shaft and Drift Configurations," SAND87-1977, Sandia National Laboratories, Albuquerque, NM.
- Stormont, J.C., 1985, "Test Plan: Small-Scale Seal Performance Tests," Sandia National Laboratories, Albuquerque, NM, March 1985.
- Stormont, J.C., Tech Ed., 1986, "Development and Implementation: Test Series A of the Small-Scale Seal Performance Tests," SAND85-2602, Sandia National Laboratories, Albuquerque, NM, May 1986.
- Stormont, J.C., 1987, "Small-Scale Seal Performance Test Series 'A' Thermal/Structural Data Through the 180th Day," SAND87-0178, Sandia National Laboratories, Albuquerque, NM, May, 1987.
- Stormont, J.C., and Howard, C.L., 1986, "Development and Implementation: Test Series B of the Small-Scale Seal Performance Tests," SAND86-1329, Sandia National Laboratories, Albuquerque, NM, December 1986.
- Stormont, J.C., and Howard, C.L., 1987, "Development, Implementation and Early Results: Test Series C of the Small-Scale Seal Performance Tests," SAND87-2203, Sandia National Laboratories, Albuquerque, NM, Dec 1987.
- Torres, T.M., 1987, "Operations Plan for Test Series D of the Small-Scale Seal Performance Tests," Sandia National Laboratories, Albuquerque, NM.
- Torres, T.M., and Howard, C.L., 1989, "Addendum C2: Brine Flow - Permeability Performance and Additional Activities Required for Small-Scale Seal Performance Tests - Test Series C (Salt/Bentonite Block Seal Emplacements)," Memo to Distribution, Sandia National Laboratories, Albuquerque, NM, January 31, 1989.
- Torres, T.M., and Howard, C.L., 1990, "SSSPT-D, Phase 2: Implementation and Status of Brine Inflow Testing on Bentonite Seal L1DE5," Memo to Distribution, Sandia National Laboratories, Albuquerque, NM, August 27, 1990.
- Torres, T.M., Howard, C.L., and Finley, R.E., in prep, "Development, Implementation, and Early Results: Test Series D, Phase 1 of the Small-Scale Seal Performance Tests," SAND91-2001, Sandia National Laboratories, Albuquerque, NM.

Van Sambeek, L.L., and Stormont, J.C., 1987, "Thermal/Structural Modeling of Test Series A of the Small Scale Seal Performance Tests," SAND87-7037, Sandia National Laboratories, Albuquerque, NM, August, 1987.

Wakeley, L.D., and Walley, D.M., 1986, "Development and Field Placement of an Expansive Salt-Saturated Concrete (ESC) for the Waste Isolation Pilot Plant (WIPP)," Technical Report SL-86-36, Waterways Experiment Station, Army Corps of Engineers, Vicksburg, Mississippi, September 1986.

DISTRIBUTION

Federal Agencies

US Department of Energy, (5)
Office of Civilian Radioactive Waste
Management

Attn: Deputy Director, RW-2
Associate Director, RW-10
Office of Program
Administration and
Resources Management
Associate Director, RW-20
Office of Facilities
Siting and Development
Associate Director, RW-30
Office of Systems
Integration and
Regulations
Associate Director, RW-40
Office of External
Relations and Policy

Forrestal Building
Washington, DC 20585

US Department of Energy (4)
WIPP Project Integration Office

Attn: W.J. Arthur III
L.W. Gage
P.J. Higgins
D.A. Olona

PO Box 5400
Albuquerque, NM 87115-5400

US Department of Energy
Attn: National Atomic Museum Library
Albuquerque Operations Office
PO Box 5400
Albuquerque, NM 87185-5400

US Department of Energy (4)
WIPP Project Site Office (Carlsbad)

Attn: R. Becker
V. Daub
J. Lippis
J.A. Mewhinney

PO Box 3090
Carlsbad, NM 88221

US Department of Energy
Research & Waste Management Division

Attn: Director
PO Box E
Oak Ridge, TN 37831

US Department of Energy
Attn: E. Young
Room E-178
GAO/RCED/GTN
Washington, DC 20545

US Department of Energy
Office of Environmental Restoration
and Waste Management

Attn: J. Lytle, EM-30 (Trevion II)
Washington, DC 20585-0002

US Department of Energy (3)
Office of Environmental Restoration
and Waste Management

Attn: M. Frei, EM-34 (Trevion II)
Washington, DC 20585-0002

US Department of Energy
Office of Environmental Restoration
and Waste Management

Attn: S. Schneider, EM-342
(Trevion II)

Washington, DC 20585-0002

US Department of Energy (3)
Office of Environment, Safety
and Health

Attn: C. Borgstrom, EH-25
R. Pelletier, EH-231

Washington, DC 20585

US Department of Energy (2)

Idaho Operations Office
Fuel Processing and Waste
Management Division

785 DOE Place
Idaho Falls, ID 83402

US Environmental Protection
Agency (2)

Radiation Programs (ANR-460)

Attn: R. Guimond
Washington, DC 20460

US Geological Survey (2)
Water Resources Division

Attn: K. Peters
Suite 200
4501 Indian School, NE
Albuquerque, NM 87110

US Nuclear Regulatory Commission
Attn: H. Marson
Mail Stop 623SS
Washington, DC 20555

Boards

Defense Nuclear Facilities Safety
Board
Attn: D. Winters
Suite 700
625 Indiana Ave., NW
Washington, DC 20004

Nuclear Waste Technical Review
Board (2)
Attn: D.A. Deere
S.J.S. Parry
Suite 910
1100 Wilson Blvd.
Arlington, VA 22209-2297

Advisory Committee on Nuclear Waste
Nuclear Regulatory Commission
Attn: R. Major
7920 Norfolk Avenue
Bethesda, MD 20814

State Agencies

Environmental Evaluation Group (3)
Attn: Library
Suite F-2
7007 Wyoming, NE
Albuquerque, NM 87109

NM Bureau of Mines and Mineral
Resources
Socorro, NM 87801

NM Energy, Minerals, and Natural
Resources Department
Attn: Library
2040 S. Pacheco
Santa Fe, NM 87505

NM Environment Department (3)
Secretary of the Environment
Attn: J. Espinosa
1190 St. Francis Drive
Santa Fe, NM 87503-0968

NM Environment Department (1)
WIPP Project Site
Attn: P. McCausland
PO Box 3090
Carlsbad, NM 88221

Laboratories/Corporations

Battelle Pacific Northwest
Laboratories (2)
Attn: H.C. Burkholder, P7-41
R.E. Westerman, P8-37
Battelle Boulevard
Richland, WA 99352

Savannah River Laboratory (3)
Attn: N. Bibler
M.J. Plodinec
G.G. Wicks
Aiken, SC 29801

INTERA Inc.
Attn: J.F. Pickens
Suite 300
6850 Austin Center Blvd.
Austin, TX 78731

INTERA Inc.
Attn: W. Stensrud
PO Box 2123
Carlsbad, NM 88221

IT Corporation (2)
Attn: P. Drez
R.F. McKinney
Regional Office - Suite 700
5301 Central, NE
Albuquerque, NM 87108

Los Alamos National Laboratory
Attn: B. Erdal, CNC-11
PO Box 1663
Los Alamos, NM 87544

RE/SPEC, Inc.
Attn: W. Coons
Suite 300
4775 Indian School, NE
Albuquerque, NM 87110-3927

RE/SPEC, Inc.
Attn: J.L. Ratigan
PO Box 725
Rapid City, SD 57709

Southwest Research Institute (2)
Center for Nuclear Waste
Regulatory Analysis
Attn: P.K. Nair
6220 Culebra Road
San Antonio, TX 78228-0510

SAIC
Attn: G. Dymmel
101 Convention Center Dr.
Las Vegas, NV 89109

SAIC
Attn: H.R. Pratt,
10260 Campus Point Drive
San Diego, CA 92121

Tech Repts Inc. (3)
Attn: J. Chapman
R. Jones
E. Lorusso
5000 Marble, NE
Albuquerque, NM 87110

Westinghouse Electric Corporation (5)
Attn: Library
C. Cox
L. Fitch
R. Kehrman
L. Trego
PO Box 2078
Carlsbad, NM 88221

Universities

University of New Mexico
Geology Department
Attn: Library
Albuquerque, NM 87131

University of Washington
Attn: G.R. Heath
College of Ocean
and Fishery Sciences
583 Henderson Hall
Seattle, WA 98195

Individuals

D.W. Powers
Star Route Box 87
Anthony, TX 79821

Libraries

Thomas Brannigan Library
Attn: D. Dresp
106 W. Hadley St.
Las Cruces, NM 88001

Hobbs Public Library
Attn: M. Lewis
509 N. Ship Street
Hobbs, NM 88248

New Mexico State Library
Attn: N. McCallan
325 Don Gaspar
Santa Fe, NM 87503

New Mexico Tech
Martin Speere Memorial Library
Campus Street
Socorro, NM 87810

New Mexico Junior College
Pannell Library
Attn: R. Hill
Lovington Highway
Hobbs, NM 88240

WIPP Public Reading Room
Carlsbad Public Library
Attn: Director
101 S. Halagueno St.
Carlsbad, NM 88220

Government Publications Department
General Library
University of New Mexico
Albuquerque, NM 87131

National Academy of Sciences, WIPP Panel

Charles Fairhurst, Chairman
Department of Civil and
Mineral Engineering
University of Minnesota
500 Pillsbury Dr., SE
Minneapolis, MN 55455-0220

Howard Adler
Oak Ridge Associated Universities
Medical Sciences Division
PO Box 117
Oak Ridge, TN 37831-0117

John D. Bredehoeft
Western Region Hydrologist
Water Resources Division
US Geological Survey (M/S 439)
345 Middlefield Road
Menlo Park, CA 94025

Fred M. Ernsberger
250 Old Mill Road
Pittsburgh, PA 15238

Rodney C. Ewing
Department of Geology
University of New Mexico
Albuquerque, NM 87131

B. John Garrick
Pickard, Lowe & Garrick, Inc.
Suite 400
4590 MacArthur Blvd.
Newport Beach, CA 92660-2027

Leonard F. Konikow
US Geological Survey
431 National Center
Reston, VA 22092

Jeremiah O'Driscoll
Jody Incorporated
505 Valley Hill Drive
Atlanta, GA 30350

Christopher G. Whipple
Clement International
Suite 1380
160 Spear Street
San Francisco, CA 94105

Peter B. Myers
National Academy of Sciences
Board on Radioactive
Waste Management
2101 Constitution Avenue
Washington, DC 20418

Ina Alterman
Board on Radioactive
Waste Management
GF456
2101 Constitution Avenue
Washington, DC 20418

Foreign Addresses

Studiecentrum Voor Kernenergie
Centre D'Energie Nucleaire
Attn: A. Bonne
SCK/CEN
Boeretang 200
B-2400 Mol, BELGIUM

Atomic Energy of Canada, Ltd. (3)
Whiteshell Research Estab.
Attn: B. Goodwin
M. Stevens
D. Wushke
Pinewa, Manitoba, CANADA ROE 1L0

Francois Chenevier, Director (2)
ANDRA
Route du Panorama Robert Schumann
B.P.38
92266 Fontenay-aux-Roses Cedex
FRANCE

Jean-Pierre Olivier
OECD Nuclear Energy Agency
Division of Radiation Protection
and Waste Management
38, Boulevard Suchet
75016 Paris, FRANCE

Claude Sombret
Centre D'Etudes Nucleaires
De La Vallee Rhone
CEN/VALRHO
S.D.H.A. BP 171
30205 Bagnols-Sur-Ceze, FRANCE

Bundesministerium fur Forschung und
Technologie
Postfach 200 706
5300 Bonn 2, GERMANY

Gesellschaft fur Reaktorsicherheit
(GRS) (2)
Attn: B. Baltés
W. Muller
Schwertnergasse 1
D-5000 Cologne, GERMANY

Bundesanstalt fur Geowissenschaften
und Rohstoffe
Attn: M. Langer
Postfach 510 153
3000 Hanover 51, GERMANY

Hahn-Meitner-Institut fur
Kernforschung
Attn: W. Lutze
Glienicker Strasse 100
100 Berlin 39, GERMANY

Institut fur Tieflagerung (2)
Attn: K. Kuhn
Theodor-Heuss-Strasse 4
D-3300 Braunschweig, GERMANY

Physikalisch-Technische Bundesanstalt
Attn: P. Brenneke
Postfach 3345
D-3300 Braunschweig, GERMANY

D.R. Knowles
British Nuclear Fuels, plc
Risley, Warrington, Cheshire WA3 6AS
1002607 UNITED KINGDOM

AEA Technology
Attn: J.H. Rees
D5W/29 Culham Laboratory
Abington, Oxfordshire OX14 3DB
UNITED KINGDOM

AEA Technology
Attn: W.R. Rodwell
O44/A31 Winfrith Technical Centre
Dorchester, Dorset DT2 8DH
UNITED KINGDOM

AEA Technology
Attn: J.E. Tinson
B4244 Harwell Laboratory
Didcot, Oxfordshire OX11 0RA
UNITED KINGDOM

Nationale Genossenschaft fur die
Lagerung Radioaktiver Abfalle
(NAGRA) (2)
Attn: S. Vomvoris
P. Zuidema
Hardstrasse 73
CH-5430 Wettingen, SWITZERLAND

Shingo Tashiro
Japan Atomic Energy Research
Institute
Tokai-Mura, Ibaraki-Ken
319-11 JAPAN

Netherlands Energy Research
Foundation ECN
Attn: L.H. Vons
3 Westerduinweg
PO Box 1
1755 ZG Petten, THE NETHERLANDS

Svensk Karnbransleforsorjning AB
Attn: F. Karlsson
Project KBS
Karnbranslesakerhet
Box 5864
10248 Stockholm, SWEDEN

Sandia Internal

1502	J.C. Cummings
3141	S.A. Landenberger (5)
3145	Document Control (8) for DOE/OSTI
3151	G.C. Claycomb (3)
6000	D.L. Hartley
6119	E.D. Gorham
6119	Staff (10)
6121	J.R. Tillerson
6121	R.E. Finley (5)
6121	Staff (7)
6300	D.E. Miller
6302	T.E. Blejwas, Acting
6303	W.D. Weart
6303	S.Y. Pickering
6341	A.L. Stevens
6341	Staff (6)
6341	Sandia WIPP Central Files (10)
6342	D.R. Anderson
6342	Staff (20)
6343	T.M. Schultheis
6343	Staff (2)
6345	R.C. Lincoln
6345	Staff (9)
6347	D.R. Schafer
8523-2	Central Technical Files
9300	J.E. Powell
9305	M.J. Navratil